

Chapter NR 250

HOSPITAL

NR 250.01 Purpose.
 NR 250.02 Applicability.
 NR 250.03 Definitions.
 NR 250.04 Compliance with effluent limitations and standards.

NR 250.06 Application of effluent limitations and standards.
 NR 250.10 Effluent limitations, best practicable treatment.
 NR 250.13 Pretreatment standards.

NR 250.01 Purpose. The purpose of this chapter is to establish effluent limitations, standards of performance, and pretreatment standards for discharges of process wastes from the hospital category of point sources and subcategories thereof.

Note: The authority for promulgation of this chapter is set forth in ch. NR 205.
History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 250.02 Applicability. The effluent limitations, standards of performance, pretreatment standards, and other provisions in this chapter are applicable to pollutants or pollutant properties in discharges of process waste resulting from hospital activities.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 250.03 Definitions. Definitions of terms and meanings of abbreviations used in this chapter are set forth in ch. NR 205.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 250.04 Compliance with effluent limitations and standards. Discharge of pollutants from facilities subject to the provisions of this chapter may not exceed, as appropriate:

c1d By July 1, 1977 effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available;

c2d By July 1, 1983 effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable;

c3d Pretreatment standards for discharges to publicly owned treatment works;

c4d Standards of performance for new sources.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77; r. and recr. Register, August, 1983, No. 332, eff. 9-1-83.

NR 250.06 Application of effluent limitations and standards. The effluent limitations and standards set forth in this chapter shall be used in accordance with this section to establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this chapter, except as:

c1d They may be modified in accordance with subch. IV of ch. NR 220,

c2d They may be superseded by more stringent limitations and standards necessary to achieve water quality standards or meet other legal requirements, or

c3d They may be supplemented or superseded by standards or prohibitions for toxic pollutants or by additional limitations for other pollutants required to achieve water quality.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77; correction made under s. 13.93 c2md cbd 1., Stats., Register, July, 1997, No. 499; correction in c1d cad made under s. 13.92 c4d cbd 7, Stats., Register April 2018 No. 748.

NR 250.10 Effluent limitations, best practicable treatment. The following effluent limitations for all or specific subcategories establish, except as provided in subch. IV of ch. NR 220, the quantity or quality of pollutants or pollutant properties which may be discharged by a facility subject to the provisions of this chapter after application to process wastes of the best practicable control technology currently available cBPTd.

c1d The pH of all discharges shall be within the range of 6.0 to 9.0.

c2d The 30-day average and daily maximum limitations for BOD₅, suspended solids, are the BPT limitations set forth in table 1 in lbs or kg per 1000 occupied beds.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77; correction in cintro. made under s. 13.92 c4d cbd 7, Stats., Register April 2018 No. 748.

NR 250.13 Pretreatment standards. The pretreatment standards for discharges to publicly owned treatment works from sources subject to the provisions of this chapter shall be as set forth in ch. NR 211.

History: Cr. Register, August, 1983, No. 332, eff. 9-1-83.

Table 1
Effluent Limitations

	Parameter	BPT Limitations	
		lbs	kg
BOD ₅	- 30-day average	74.0	33.6
	- daily maximum	90.4	41.0
TSS	- 30-day average	74.5	33.8
	- daily maximum	122.4	55.6