

Chapter NR 512

FEASIBILITY REPORTS FOR LANDFILLS

NR 512.01	Purpose.	NR 512.10	Subsurface data analysis.
NR 512.02	Applicability.	NR 512.11	Data presentation.
NR 512.03	Definitions.	NR 512.12	Waste and leachate characterization.
NR 512.04	Initial site report.	NR 512.13	Constraints on landfill development.
NR 512.05	General submittal requirements.	NR 512.14	Proposed preliminary design.
NR 512.06	Procedural requirements.	NR 512.15	Identification of soil borrow sources.
NR 512.07	General facility information.	NR 512.16	Environmental review.
NR 512.08	Land use information.	NR 512.17	Need and design capacity.
NR 512.085	Alternative geotechnical investigation program.	NR 512.18	Evaluation of alternatives to land disposal.
NR 512.09	Site-specific geotechnical information.	NR 512.19	Noncompliance with plans or orders.

Note: Corrections made under s. 13.93 c2md cbd 7., Stats., [Register, August, 1997, No. 500.](#)

NR 512.01 Purpose. The purpose of this chapter is to help ensure that efficient, nuisance-free and environmentally acceptable solid waste management procedures are practiced in this state and to outline the requirements regarding feasibility reports for new landfills or expansions of existing landfills. The purpose of the feasibility report is to determine whether a proposed property has potential for use as a landfill and to identify any conditions which the applicant shall address in the plan of operation. This chapter is adopted under ch. 289, Stats., and s. 227.11, Stats.

History: Cr. [Register, January, 1988, No. 385](#), eff. 2-6-88; am., [Register, June, 1996, No. 486](#), eff. 7-1-96.

NR 512.02 Applicability. c1d cad Except as provided in par. **cbd** and except as otherwise provided, this chapter governs all landfills as defined under s. 289.01 c20d, Stats., including all CCR landfills and expansions.

cbd This chapter does not govern any of the following:

1. Landfills regulated under ch. [NR 503](#).
2. Hazardous waste facilities as defined under s. 291.01 c8d, Stats., and regulated under chs. [NR 660](#) to [679](#).
3. Metallic mining operations for nonferrous minerals as defined under s. 293.01 c9d, Stats., and regulated under ch. [NR 182](#).
4. Metallic mining operations for ferrous minerals as defined under s. 295.41 c26d, Stats., including mining wastes and mining waste sites as defined under s. 295.41 c30d and c31d, Stats., and regulated under subch. [III](#) of ch. 295, Stats.

c2d This chapter does not apply to the design, construction or operation of industrial wastewater facilities, sewerage systems and waterworks treating liquid wastes approved under s. 281.41, Stats., or permitted under ch. 283, Stats., nor to facilities used solely for the disposal of liquid municipal or industrial wastes which have been approved under s. 281.41, Stats., or permitted under ch. 283, Stats., except for facilities used for the disposal of solid waste.

History: Cr. [Register, January, 1988, No. 385](#), eff. 2-6-88; correction in c1d made under s. 13.93 c2md cbd 7., Stats., [Register, May, 1994, No. 461](#); am. c1d, [Register, June, 1996, No. 486](#), eff. 7-1-96; correction in c1d made under s. 13.93 c2md cbd 7., Stats., [Register December 2006 No. 612](#); CR 13-057: am. c1d [Register July 2015 No. 715](#), eff. 8-1-15; CR 21-076: renum. c1d to c1d cad and cbd 1. to 4. and am., cr. c1d cbd cintro.d [Register July 2022 No. 799](#), eff. 8-1-22.

NR 512.03 Definitions. The terms used in this chapter are defined in s. [NR 500.03](#).

History: Cr. [Register, January, 1988, No. 385](#), eff. 2-6-88.

NR 512.04 Initial site report. Any applicant intending to establish a new landfill or expand an existing landfill shall ob-

tain an initial site report opinion from the department prior to submitting a feasibility report.

History: Cr. [Register, January, 1988, No. 385](#), eff. 2-6-88; am., [Register, June, 1996, No. 486](#), eff. 7-1-96.

NR 512.05 General submittal requirements. An applicant proposing to construct a new landfill or expand an existing landfill shall submit a feasibility report and related materials in accordance with s. [NR 500.05](#) and this chapter. The feasibility report shall address all department review comments on the initial site report and any applicable pre-feasibility report. If the applicant requests any exemptions to the locational criteria and performance standards listed in s. [NR 504.04](#), justification for the request shall be provided in the narrative section of the feasibility report. Applicants proposing an alternative design to the requirements contained in ss. [NR 504.05](#), [504.06](#), [504.07](#), [504.08](#) and [504.09](#) shall include an analysis that predicts whether the proposed landfill will meet or exceed the performance standards of s. [NR 504.04 c4d cdd](#) regarding groundwater quality.

History: Cr. [Register, January, 1988, No. 385](#), eff. 2-6-88; am. [Register, June, 1996, No. 486](#), eff. 7-1-96.

NR 512.06 Procedural requirements. An applicant shall comply with all applicable procedural requirements of ss. [289.21](#) to [289.32](#), Stats.

c1d LOCAL APPROVALS. An applicant shall submit a written request including the standard notice developed under s. [289.22 c2d](#), Stats., to each affected municipality for the specification of all applicable local approval requirements under s. [289.22 c1md](#), Stats. An applicant subject to s. [289.33](#), Stats., shall apply for all applicable local approvals specified by a municipality under s. [289.22 c1md](#), Stats., at least 120 days prior to submitting the feasibility report to the department. If the municipality either fails to respond within 15 days after the receipt of the written request from the applicant or indicates that there are no applicable local approval requirements, the applicant may submit the feasibility report 135 days after receipt by the municipality of the written request from the applicant or 120 days after receipt of the response from the municipality indicating that there are no local approval requirements, whichever occurs first. The feasibility report shall contain a copy of all requests for the specification of applicable local approvals, responses from affected municipalities regarding any applicable local approvals, the standard notice, and follow up applications for any applicable local approvals to document that this requirement has been met.

c2d SUBMISSION OF REPORTS. An applicant shall submit a feasibility report to the department in accordance with ss. [289.21](#) to [289.29](#), Stats. At the same time, the applicant shall submit a copy of the initial site report, the department[s] initial site report

opinion, any applicable pre-feasibility report and the feasibility report to each participating municipality under s. 289.33 c6d cbd, Stats. The applicant shall notify the department of when and to whom the specified copies were submitted.

c3d COMPLETENESS. Within 60 days after a feasibility report is submitted, the department shall determine whether or not the feasibility report is complete. The department shall determine the completeness of the feasibility report by determining whether or not the items specified in the department[s] initial site report opinion letter and the minimum requirements of this chapter have been met. If the report is incomplete, the department shall notify the applicant in writing and specify the information which shall be submitted in an addendum before the feasibility report can be deemed complete. If the report is complete, the department shall publish a class I public notice in accordance with s. 289.25 c3d, Stats., and issue a preliminary determination stating whether or not an environmental impact statement is required. The department may require the applicant to submit additional information after determining that the feasibility report is complete if the department establishes that the feasibility of the proposed landfill cannot be determined without the additional information.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; am. c1d, c2d, c3d, Register, June, 1996, No. 486, eff. 7-1-96.

NR 512.07 General facility information. The feasibility report shall identify the project title; name, address and phone number of the primary contacts including the proposed landfill[s] owner, operator and any consultants; present property owner; proposed landfill location by quarter-quarter section; total acreage of the property and proposed limits of filling; proposed landfill life, design capacity and date of closure; municipalities and industries to be served; anticipated waste types and characteristics; anticipated volumes of each major waste stream and any seasonal fluctuations taking into account waste reduction, reuse, recycling, composting and the recovery of energy from solid waste; anticipated cover frequency; mode of operation; proposed sub-base, base and final grades; preliminary design concepts; need for the landfill; the alternatives to land disposal, including any proposed waste reduction and recovery services; and how the proposed facility relates to any applicable solid waste management plan approved under s. 289.10, Stats.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.08 and am., Register, June, 1996, No. 486, eff. 7-1-96; am., Register, August, 1997, No. 500, eff. 9-1-97; am. Register, September, 1998, No. 513, eff. 10-1-98.

NR 512.08 Land use information. The feasibility report shall include a discussion of land uses at the proposed landfill location and surrounding area. Relevant land use information contained in the initial site report may be referenced in the feasibility report. However, a thorough discussion of any changes in land uses since the submittal of the initial site report which may have an impact on the suitability of the property for waste disposal or on groundwater quality shall be included. The report shall address all areas where land use may affect or be affected by the proposed landfill. At a minimum, this will be the area within one mile of the proposed limits of filling. If the landfill owner proposes to accept municipal solid waste or other putrescible waste, the report shall include any information or bird study requested by the federal aviation administration or by the department concerning any airport whose runway end is within 5 miles of the proposed limits of filling.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.09 and am., r. c1d to c4d, Register, June, 1996, No. 486, eff. 7-1-96.

NR 512.085 Alternative geotechnical investigation program. The applicant may propose an alternative geotechnical investigation program to the department prior to initiating the

geotechnical investigations required for a feasibility report that are identified in ss. NR 512.09 and 512.10. A proposal shall include a detailed description of the proposed alternative program, detailed explanations of the rationale for the proposed differences between the code requirements in s. NR 512.09 or 512.10 and the proposed alternative program, and the anticipated benefits of the proposed alternative program. The department shall respond in writing and may accept the program as submitted, identify deficiencies in the proposed alternative program that must be addressed, or may reject the program. The program may not be implemented prior to receipt of written review by the department. The feasibility report shall include documentation of any alternative geotechnical investigation accepted by the department and justification for any reductions to the requirements in ss. NR 512.09 and 512.10. Formal approval of an accepted alternative geotechnical program shall be made in the department[s] feasibility determination.

History: CR 05-020: cr. Register January 2006 No. 601, eff. 2-1-06.

NR 512.09 Site-specific geotechnical information.

The applicant shall perform laboratory and field investigations to define the physical characteristics of the proposed landfill[s] location. At a minimum these investigations shall include the following specified requirements unless an alternative geotechnical investigation program under s. NR 512.085 specifically addressing these requirements, or a portion thereof, was accepted in writing by the department before the geotechnical investigation program for the feasibility report was initiated. Should the applicant identify minor discrepancies between the following specified requirements and the content of the feasibility report prior to its submittal to the department, the applicant may choose to identify those minor discrepancies in a separate letter to the department, including an explanation for them, and either propose a time table for providing that information or justify why it is not necessary to submit that specific information and request the necessary exemptions. The department shall respond to a letter in writing either accepting the explanation and requested approach or indicating that the discrepancies need to be addressed prior to issuing feasibility completeness.

c1d BORINGS. As specified in Table 1, borings sufficient to define sub-surface conditions shall be drilled both inside and outside the proposed limits of filling.

cad At a minimum, borings shall be drilled in 10 separate locations for the first 5 or less acres of the proposed fill area. Two borings shall be drilled for each additional 5 or less acres of proposed fill area. The borings shall be located on a grid pattern. All borings shall be located in or within 300 feet of the proposed limits of filling.

cbd Borings shall extend a minimum of 25 feet below the anticipated sub-base grade. If the boring is located outside the proposed limits of filling, the applicable sub-base grade is the elevation of the bottom of the proposed base liner nearest to the borehole.

ccd If regional information suggests that bedrock is within 50 feet of the lowest elevation of the proposed sub-base grades, one boring shall be extended at least 5 feet into bedrock. Every attempt shall be made to locate this boring outside the proposed limits of filling. Bedrock drilling shall be performed in accordance with ch. NR 141 and s. NR 507.05.

Note: Bedrock is defined in s. NR 500.03 c18d.

cdd Samples shall be collected and retained and boring logs shall be prepared in accordance with ss. NR 507.05 and 507.14.

ced Borings not converted to wells shall be abandoned in accordance with ss. NR 507.08 and 141.25.

c2d WELLS. As specified in Table 1, wells sufficient to de-

fine the hydrogeologic and groundwater quality conditions shall be installed. At a minimum, this includes:

cad Installing observation wells to adequately define the water table surface and horizontal hydraulic gradients. At a minimum, 5 water table observation wells shall be installed for the first 5 or less acres of disposal area and one additional observation well for each additional 5 or less acres of disposal area. The observation wells shall be constructed so that the water table intersects the well screens at all times during the year.

cbd A piezometer shall be installed adjacent to a water table observation well at 2 separate locations to create well nests for the first 5 or less acres of disposal area. One additional piezometer for each additional 10 or less acres of disposal area shall be installed to create additional well nests. For every 20 acres of disposal area at least one well nest shall be placed within the proposed limits of filling.

ccd For proposed limits of filling located in a fine-grained soil environment, each well nest required in par. cbd shall consist of 3 wells: a water table observation well, a piezometer installed at or just below the proposed subbase grades and a deeper piezometer installed at least 15 feet below the bottom of the upper piezometer[s] well screen.

cdd All wells shall be located no more than 300 feet from the proposed limits of filling and at least half of the wells shall be located no more than 150 feet from the proposed limits of filling.

ced All wells shall be designed, installed, developed, documented and sampled in accordance with ch. NR 141 and ss. NR 507.06, 507.07, 507.14 and 507.17. Alternative methods of well design and installation which achieve comparable results shall be approved by the department prior to well construction.

Note: Fine-grained soil environment is defined in s. NR 500.03 c86d.

Table 1

Coarse-Grained Soil Environments			
Piezometers	Water Table Observation Wells	Borings	Area
2	5	10	First 5 or less acres
-	1	2	Each additional 5 or less acres
1	-	-	Each additional 10 or less acres
Fine-Grained Soil Environments			
Piezometers	Water Table Observation Wells	Borings	Area
4	5	10	First 5 or less acres
-	1	2	Each additional 5 or less acres
2	-	-	Each additional 10 or less acres

c3d FIELD DIRECTION. A professional geologist or qualified technician who is directly supervised by a professional geologist shall observe and direct the drilling of all borings and the installation, development and abandonment of all wells. A professional geologist or qualified technician who is directly supervised by a professional geologist shall also conduct all in-field hydraulic conductivity tests and visually describe and classify all of the geologic samples.

c4d LABORATORY AND FIELD ANALYSIS. Laboratory and field analyses shall be conducted to identify the specific geologic, hydrogeologic and groundwater quality conditions at the proposed facility as outlined below:

cad For each major soil unit encountered, at least 5 representative samples shall be analyzed for grain size distribution using mechanical and hydrometer methods and Atterberg limits as appropriate for the particular type of material. Each representative sample shall be classified according to the unified soil classification system.

Note: Major soil unit is defined in s. NR 500.03 c138d.

cbd Laboratory hydraulic conductivity tests shall be conducted on at least 2 representative samples from each major fine-grained soil unit. Tests shall be run on undisturbed samples when conditions allow.

ccd The department may require that other tests be conducted as appropriate for the particular type of material.

cdd An in-field test shall be conducted on each well to determine the in-situ hydraulic conductivity. The test shall be of long enough duration and include a sufficient amount of data to provide a representative estimate of the actual hydraulic conductivity.

ced After each well has been properly developed, successive water level measurements shall be taken until stabilized readings

are obtained. Stabilized water level measurements shall be obtained on a monthly basis for a minimum of 6 months prior to submittal of the feasibility report. After this period, quarterly water level measurements shall be obtained for at least 4 quarters.

cfđ Stabilized water level measurements shall be obtained on a monthly basis for a minimum of 6 months prior to submittal of the feasibility report from surface water bodies including streams, lakes, ponds, drainage ditches and wetlands located within 1,000 feet of the proposed limits of filling. After this period, quarterly water level monitoring shall be performed for at least 4 quarters.

cgđ At least 4 rounds of baseline groundwater monitoring shall be performed on all observation wells and piezometers located outside the proposed limits of filling which were installed to evaluate the proposed property in accordance with s. NR 507.18 and submitted along with the feasibility report.

chđ The department may require other work such as groundwater modeling, pump tests, geophysical investigations, isopach maps or a fence diagram to assess the hydrogeologic conditions at the proposed facility.

c5d SAMPLE RETENTION. All soil and bedrock samples collected from the proposed property shall be retained in accordance with s. NR 507.05.

c6d ADDITIONAL REQUIREMENTS FOR LANDFILLS WITH EXTENDED COLLECTION LINES. cad Landfills shall meet the requirements of pars. cbd and ccd where they will accept municipal solid waste and contain leachate collection lines that exceed 1,200 feet from the end of each cleanout to the toe of the opposite slope. Where the requirements of this subsection differ from other requirements of this chapter, these requirements shall take precedence.

cbd A minimum of one boring in the area of each proposed

cell shall be drilled to physically characterize subbase conditions for landfill foundation assessment of stability and settlement. Borings shall be extended to a minimum of 50 feet below proposed subbase grades or to competent bedrock, whichever is shallower. Borings shall include standard penetration testing. Samples shall be taken at each significant soil layer. A minimum of one sample from each fine grained layer and from each soft or compressible coarse grained layer shall be subjected to geotechnical testing to define parameters used in assessments of stability and settlement of the liner.

ccd Consolidation testing data shall be included with the data summarized by major soil unit in the table required by s. [NR 512.10 c2d cdd](#).

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.11 and am. cintro.d, c1d cintro.d, cad, cbd, c2d cintro.d, cad, c3d, c4d cad, cbd, ced, cgd, chd, c5d, r. c1d ccd to ced, Register, June, 1996, No. 486, eff. 7-1-96; r. c2d camd, am. c2d ced Table 1 and c5d, Register, August, 1997, No. 500, eff. 9-1-97; am. Table 1, Register, September, 1998, No. 513, eff. 10-1-98; CR 04-077: cr. c6d Register November 2005 No. 599, eff. 12-1-05; CR 05-020: am. cintro.d Register January 2006 No. 601, eff. 2-1-06; correction in c6d ccd made under s. 13.93 c2md cbd 7., Stats., Register January 2006 No. 601; CR 06-026: am. c6d cad, Register December 2006 No. 612, eff. 1-1-07.

NR 512.10 Subsurface data analysis. c1d At a minimum, the data on subsurface investigations shall be presented in the narrative section of the report and shall include the following specified requirements unless an alternative geotechnical investigation program under s. [NR 512.085](#) specifically addressing these requirements, or a portion thereof, was accepted in writing by the department before the geotechnical investigation program for the feasibility report was initiated. Should the applicant identify minor discrepancies between the following specified requirements and the content of the feasibility report prior to its submittal to the department, the applicant may choose to identify those minor discrepancies in a separate letter to the department, including an explanation for them, and either propose a time table for providing that information or justify why it is not necessary to submit that specific information and request the necessary exemptions. The department shall respond to a letter in writing either accepting the explanation and requested approach or indicating that the discrepancies need to be addressed prior to issuing feasibility completeness.

c2d SOIL AND BEDROCK DESCRIPTIONS. Each major soil unit and bedrock formation shall be described using data from both subsurface investigations and regional information. The descriptions shall include:

cad Grain size distribution, geologic origin and classification of materials using the USCS system.

cbd The lateral and vertical extent of each major soil unit including description of lenses or other heterogeneities and, if bedrock is encountered by borings, the strike and dip of any rock formations. Strike and dip may be determined from regional or site-specific information.

ccd The presence and frequency of joints, fractures, voids, solution openings, faults or other structural features.

cdd Testing data shall be summarized by major soil unit in a table in the report. The table shall contain the following information: geologic origin, sample ID number, percentages of gravel, sand, silt and clay-sized materials, P200 content, liquid limit, plasticity index, and lab and field hydraulic conductivity. If average values are calculated for any of these test results, a range and standard deviation shall also be presented.

c3d HYDROGEOLOGIC PROPERTIES. The properties of each saturated soil unit or rock formation and its function in the groundwater flow system shall be described including the following:

cad Hydraulic conductivity.

cbd Role as a confining unit.

ccd Hydraulic connection to other units.

cdd Actual or potential use as a water supply.

ced Depth to groundwater and seasonal variations in groundwater elevation.

cfid Location and extent of perched groundwater.

cgd Local and regional flow directions including the location of groundwater divides.

chd Horizontal and vertical hydraulic gradients, particularly between soil units of differing hydraulic conductivity and between unconsolidated deposits and bedrock.

c4d APPENDIX. All raw data including boring logs, soil tests, hydraulic conductivity tests, water level measurements, baseline water quality laboratory reports, and department well construction, well development, and well information forms shall be included in the appendices of the report.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.12 and am. c1d cad, cbd, c2d chd, c3d, r. c2d cid, Register, June, 1996, No. 486, eff. 7-1-96; am. c3d, Register, August, 1997, No. 500, eff. 9-1-97; CR 05-020: renum. cintro.d to c3d to be c1d to c4d and am. c1d Register January 2006 No. 601, eff. 2-1-06.

NR 512.11 Data presentation. The results from the subsurface investigations shall be presented on 24 inch x 36 inch plan sheets, unless an alternative size is approved by the department in writing, as follows:

c1d EXISTING CONDITIONS. A detailed topographic survey of the proposed landfill and all areas within a distance of 1,500 feet from the proposed limits of filling. The minimum scale shall be 1" = 200 feet with a maximum 2 foot contour interval. The contour interval selected shall be sufficiently small to clearly show surface water flow patterns within and around the proposed landfill. This plan sheet shall show the following features:

cad 100-year floodplain area.

cbd Surface waters, including intermittent and ephemeral streams and wetlands.

ccd Residences, buildings, utility lines and other cultural features.

cdd Surrounding land uses, such as residential, commercial, agricultural and recreational.

ced Property and proposed limits of filling, including any previous fill areas.

cfid Access control, such as fences and gates.

cgd Water supply wells including any irrigation and stock wells.

chd Boring, test pit and well locations for the proposed landfill.

cid Other structures including storm water control systems, agricultural drain tile systems, access and internal roads, and storm and sanitary sewerage systems.

c2d GEOLOGIC CROSS-SECTIONS. Cross-sections shall be constructed through all borings, both perpendicular and parallel to the proposed landfill[s] baseline. For a proposed contiguous, horizontal or vertical expansion of an existing landfill, the cross-sections shall be expanded to include all the previous borings for the existing landfill. At least one cross-section shall be constructed parallel to groundwater flow. Where more than one interpretation can be reasonably made when evaluating heterogeneities within unconsolidated deposits, assume that the heterogeneities are continuous. The following information and where applicable, the information required by s. [NR 512.14 c2d cbd](#), shall be presented on the geologic cross-sections:

cad Inferred or questionable lithostatigraphic boundaries shall be shown with a dashed line or question mark.

cbd For clarity, a number or symbol shall be used to label major soil units instead of extensive shading. A key shall be provided which contains a description of each major soil unit including geologic description and origin, USCS classification and color.

ccd Boring logs showing the USCS classification and geologic origin of each major soil unit, the results of grain size analyses, Atterberg limits and field hydraulic conductivity tests. The data shall be correlated to the sample location.

cdd Well construction details shown to scale including the well screen and filter pack length, the location of the upper and any lower seals and stabilized water level elevations measured on the same day. Where 2 or more observation wells are presented on a cross-section, a line representing the water table shall be drawn. The date the measurements were taken shall be specified in the key.

c3d WATER TABLE MAPS. At least 2 water table contour maps shall be submitted. One map shall be based on the highest set of monthly water table elevations measured in the observation wells installed at the proposed landfill[s] location and the other map shall be based on the lowest set of monthly water table elevations measured in the observation wells installed at the proposed landfill[s] location. For each sampling round, all water level elevations shall be measured on the same day. The water table maps shall show all observation wells and the measured water level elevation at each observation well. Any observed variations in flow direction shall be discussed in the narrative of the report. For a contiguous, horizontal or vertical expansion of an existing landfill, the water table contour maps shall be expanded to include the observation wells and measured water table elevations at each observation well for the existing landfill. Inferred contours made beyond the extent of the observation well field shall be shown with dashed lines. If 3 or more bedrock wells are installed, a bedrock piezometric map shall be prepared.

c4d BEDROCK MAP. If at least 3 borings have been extended into bedrock, a bedrock contour map shall be prepared from specific and regional data.

c5d FLOW NET. A flow net shall be constructed parallel to the direction of groundwater flow to show the distribution of recharge and discharge.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; correction in c1d ccd made under s. 13.93 c2md cbd 5., Stats., Register, May, 1994, No. 461; renum. from NR 512.13 and am. c1d cintro.d ccd, ccd, cgd, chd cid, c2d cintro.d, ccd, cdd, c3d, c4d, Register, June, 1996, No. 486, eff. 7-1-96.

NR 512.12 Waste and leachate characterization.

c1d INDUSTRIAL WASTES. Unless otherwise approved, the physical and chemical characteristics of any high volume industrial waste such as a foundry process waste, papermill sludge, utility coal-ash waste, and other non-municipal waste that is anticipated to individually constitute more than 5% of the total proposed design capacity and leachates shall be analyzed and described. When more than one waste is generated, testing shall be performed on each waste stream. All leaching tests shall be done in accordance with published test procedures. Physical tests shall be done in accordance with ASTM standards or published test procedures. All testing procedures shall be documented. The proposed testing program including the leaching test method, the leaching media, the parameters to be analyzed for and the detection limits for each parameter specified should be discussed with the department prior to initiation of the work. Actual field leachate data may be substituted for chemical characterization data of an industrial waste if the data are from an existing monofill that contains waste similar to that which is to be placed into the proposed landfill and if approved in writing by the department.

c2d MUNICIPAL WASTES. Actual field leachate data from existing landfills of similar size, design and waste type or an estimate of the anticipated leachate strength and quality available from department files shall be included for all landfills for the disposal of municipal solid waste.

c3d LEACHATE GENERATION. The estimated daily volume of leachate that will be collected during operations and after closure shall be calculated. Unless otherwise approved by the department, the following rates shall be used to calculate the leachate volumes:

cad A minimum of 6 inches per year shall be used for all unclosed areas of the proposed limits of filling for landfills that will have a composite liner and a minimum of 4 inches per year shall be used for all unclosed areas of the proposed limits of filling for landfills that will not have a composite liner.

cbd One inch per year shall be used for all closed areas of the proposed limits of filling for landfills that will have a composite cap and a minimum of 3 inches per year shall be used for all closed areas of the proposed limits of filling for landfills that will not have a composite cap.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.15 and am. c1d, c2d, cr. c3d, c4d, Register, June, 1996, No. 486, eff. 7-1-96; r. c4d, Register, August, 1997, No. 500, eff. 9-1-97.

NR 512.13 Constraints on landfill development.

The feasibility report shall contain a discussion of constraints for the development of the proposed landfill. This shall include:

c1d LOCATIONAL CRITERIA AND PERFORMANCE STANDARDS. A demonstration that the proposed landfill will meet the locational criteria and performance standards under s. NR 504.04. For a new CCR landfill or an expansion of a CCR landfill, all of the following also apply:

cad The demonstration shall address all of the following factors, at a minimum, when determining whether an area is unstable:

1. On-site or local soil conditions that may result in significant differential settling.
2. On-site or local geologic or geomorphologic features.
3. On-site or local human-made features or events both surface and subsurface.

cbd A facility or practice near a floodplain may not restrict the flow of the regional flood, reduce the temporary water storage capacity of the flood plain, or result in washout of solid waste, so as to pose a hazard to human life, wildlife, or land or water resources.

ccd A facility or practice may not result in the destruction or adverse modification of the critical habitat of endangered or threatened species as identified under s. NR 27.03 c1d.

c2d GEOTECHNICAL INFORMATION. An analysis of the geologic, hydrogeologic, topographic and hydrologic features of the facility that may be favorable or unfavorable for landfill development.

c3d CONSTRUCTION AND OPERATION. A discussion of materials and support services required for landfill construction and operation. These shall include leachate treatment alternatives, identification of and a detailed evaluation of the capability of any proposed wastewater treatment plants to treat the anticipated quality and quantity of leachate, quality and quantity of acceptable materials available for landfill liner and final cap, and any specialized engineering structures to support landfilling activities.

c4d EXISTING FACILITY PERFORMANCE. For a proposed contiguous, horizontal or vertical expansion of an existing landfill,

the compliance status and performance of the existing landfill shall be evaluated.

cad The discussion in any applicable pre-feasibility report on the compliance status and performance of the existing landfill shall be referenced in the feasibility report and any changes in the compliance status and performance of the existing landfill since the submittal of any applicable pre-feasibility report shall be addressed.

cbd If a preventive action limit or enforcement standard adopted under ss. NR 140.10 and 140.12 has been attained or exceeded at the proposed landfill location, an exemption request under s. NR 140.28 and in accordance with s. NR 507.29 shall be contained in the feasibility report.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.16, am. cintro.d, c1d, c3d, r. and recr. c4d, Register, June, 1996, No. 486, eff. 7-1-96; am. c1d, c4d cintro.d and cad, Register, August, 1997, No. 500, eff. 9-1-97; CR 21-076: renum. c1d to c1d cintro.d and am., cr. c1d cad to ccd Register July 2022 No. 799, eff. 8-1-22; correction in c1d ccd made under s. 35.17, Stats., Register July 2022 No. 799.

NR 512.14 Proposed preliminary design. The feasibility report shall contain a proposed preliminary design based on conclusions outlined in the design constraints section of the feasibility report and in accordance with ch. NR 504.

c1d PRELIMINARY DESIGN REPORT. At a minimum, this portion of the narrative section of the feasibility report shall include the following information:

cad Preliminary materials balance calculations for the necessary volume of clay to construct the liner and final cap of the first phase of the landfill.

cbd Proposed methods for leachate and gas control including collection, containment and treatment.

ccd Proposed operating procedures including the general sequence of filling.

cdd A description of the proposed groundwater, leachate, surface water, gas, air, unsaturated zone and other monitoring programs to be implemented to meet the requirements of chs. NR 140 and 507 and a sampling plan for all monitoring devices in accordance with s. NR 507.16.

ced Proposed methods for storm water control in accordance with ch. NR 216 and visual screening.

cfid Proposed final use.

c2d PRELIMINARY ENGINEERING PLANS. The preliminary engineering design shall be presented on 24 inch x 36 inch plan sheets. A maximum 5 foot contour interval shall be used for required drawings, unless an alternate size or interval is approved by the department in writing. Plan sheets shall be prepared as follows:

cad The existing conditions map shall be used to show the proposed access, limits of filling, internal roads, load-out and scale facilities, associated buildings, storm water diversions, sedimentation basins, phases of facility development, sub-base and base grades, slopes and the leachate collection system including the location of any proposed leachate storage tank, lift station or sewer hook up.

cbd The present topography, proposed sub-base, base and final grades, and the liner and final cap configurations shall be displayed on all geologic cross-sections intersecting the proposed limits of filling.

ccd A plan sheet showing the proposed closure sequence and final grades.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.17 and am. cintro.d, c1d cad, cbd, ccd, c2d cintro.d, cad, cbd, r. c1d ccd, cfd, c2d ccd to ced, cr. c1d ccd, cfd, c2d ccd, Register, June, 1996, No. 486, eff. 7-1-96; am. c1d ced, Register, August, 1997, No. 500, eff. 9-1-97.

NR 512.15 Identification of soil borrow sources.

c1d The feasibility report shall include a copy of the department[s] initial site inspection evaluation for the proposed soil borrow sources designated to be used in the construction, operation or closure of the first phase of the landfill.

c2d The feasibility report shall include the documentation for soil borrow sources as described in s. NR 504.075 for the proposed soil borrow sources designated to be used in the construction, operation or closure of the first phase of the landfill.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.18 and am. c1d, c2d cintro.d, cad, cbd, ccd, cdd, c3d cintro.d, cad, cbd, ccd, cdd, ced, cr. c3d cfd, cgd, c4d, r. c2d ced, c3d cfd, Register, June, 1996, No. 486, eff. 7-1-96; CR 05-020: r. and recr. Register January 2006 No. 601, eff. 2-1-06.

NR 512.16 Environmental review. To aid the department in complying with ch. NR 150, and in determining the need for an environmental impact report, the feasibility report shall include an environmental analysis section. This analysis shall include the following items:

c1d PROJECT SUMMARY. The department[s] initial site report opinion letter, a brief overview of the project and a listing of the statutory authority and other relevant local, state and federal permits or approvals required as well as the need for exemptions, zoning changes and any other special permits or approvals.

c2d PROPOSED PHYSICAL CHANGES. A brief description of the proposed physical changes including:

cad The changes in terrestrial resources. This discussion shall include the quantity of soil to be excavated and the lateral extent of soil removal; the quantity and source of soils designated to be used in the construction, operation or closure of the landfill. All earthen modifications such as clearing and grubbing, excavation, soil placement necessary to reach the proposed sub-base grades, construction of access roads, stockpiles, and storm water controls shall also be described.

cbd The changes in aquatic resources including the potential impacts to streams, wetlands, ponds, lakes and flowages. This discussion shall include the discharge rates and volumes, in relevant quantities for groundwater control structures, leachate collection systems and storm water control structures under existing conditions as well as that anticipated during active operations and following closure. Information or any reports on how the proposed landfill and soil borrow sources designated to be used in the construction, operation or closure of the first phase of the proposed landfill comply with s. 30.19, Stats., and ch. NR 103 shall also be included.

ccd Buildings, treatment units, roads and other structures such as sedimentation basins and fences to be constructed in conjunction with the facility. This discussion shall include the size of the facilities and the number of miles of road to be constructed.

cdd Emissions and discharges such as dust, engine exhaust, odors, noise, gases, leachate, storm water and collected groundwater associated with landfill preparation, construction, operation, closure and post-closure of the landfill.

ced Other changes anticipated with landfill development.

cfid Maps, plans and other descriptive material to clarify the discussion such as a county map showing the general area of the project, a map of the proposed service area, a USGS topographic map, a plat map, zoning map, county wetlands map, soils map and a landfill development plan.

c3d EXISTING ENVIRONMENT. A brief description of the existing environment that may be affected shall be included. At a minimum this shall contain:

cad A description of the physical environment including the regional and local topography, geology, surface waters and asso-

ciated drainage features, hydrogeologic conditions, air, wetlands and designated soil borrow sources.

cbd The dominant aquatic and terrestrial plant and animal species and habitats found in the area including any threatened or endangered species and amount, type and hydraulic value of wetlands.

ccd Land use including dominant features and zoning in the area.

cdd Social and economic conditions including any ethnic or cultural groups.

ced Other special resources such as archaeological, historical, state or local natural areas, and prime agricultural lands.

c4d ENVIRONMENTAL CONSEQUENCES. A brief discussion of the probable adverse and beneficial impacts including primary, indirect and secondary impacts shall include:

cad The physical impacts which would be associated with landfill design, construction and operation, including air quality, windblown paper and dust and visual impacts.

cbd The biological impacts including destruction and creation of habitat, alteration of the physical environment and any impacts to endangered or threatened species.

ccd The impacts on land use.

cdd The social and economic impacts to local residents and cultural groups and the communities and industries served by the landfill such as effects on taxes, traffic and roads, noise, consistency with local planning and zoning.

ced Other special resources such as archaeological, historical, state or local natural areas and prime agricultural lands.

efd Probable adverse impacts that cannot be avoided including groundwater and surface water impacts, modifications of topography and any soil borrow source limitations on development around the landfill, any loss of agricultural or forest land, displacement of wildlife and adverse aesthetic impacts for people in and around the landfill.

c5d ALTERNATIVES. Identify, describe and discuss feasible alternatives including taking no action; enlargement, reduction or modification of the project; other landfills, locations or methods to the proposed action and their impacts. Particular attention shall be given to alternatives which might avoid some or all adverse environmental impacts, including planned and existing waste reduction and recycling, incineration, solid waste disposal, and transfer facilities that may serve to handle the waste expected to be disposed of at the proposed landfill, taking into account the economics of waste collection, transportation and disposal.

Note: Information provided in previous sections of the initial site report, any pre-feasibility report or feasibility report may be referenced to satisfy this section.

History: Cr. Register, January, 1988, No. 385, eff. 2-6-88; renum. from NR 512.19 and am. cintro.d, c2d cad to cfd, c3d cad, cbd, ced, c4d cad, cdd to cfd, c5d, r. c1d, cr. c1d, Register, June, 1996, No. 486, eff. 7-1-96; CR 13-022: am. cintro.d Register March 2014 No. 699, eff. 4-1-14.

NR 512.17 Need and design capacity. Unless the landfill is exempt under s. 289.28 c2d, Stats., the feasibility report shall contain an evaluation to justify the need for the proposed landfill in accordance with s. 289.28 c1d, Stats., and the design capacity for the proposed landfill under s. 289.29 c1d cdd,

Stats. In addition to the information specified in s. 289.28 c1d, Stats., the feasibility report shall contain information identifying the existing waste reduction activities, recycling activities and solid waste facilities used to manage solid wastes generated within the anticipated service area of the proposed landfill, and the remaining design capacity of each facility. The feasibility report shall also contain information for these listed activities and facilities for which a significant commitment or implementation or development has been made. In determining the design capacity of the proposed landfill under s. 289.29 c1d cdd, Stats., the department shall consider the effect of planned and existing waste reduction and recycling activities and other existing or proposed competing solid waste facilities, regardless of whether or not the other facilities are located within the service area, as defined under s. 289.28 c1d, Stats., of the proposed landfill.

History: Cr. Register, June, 1996, No. 486, eff. 7-1-96; correction made under s. 13.93 c2md cbd 7., Stats., Register March 2003 No. 567.

NR 512.18 Evaluation of alternatives to land disposal. The feasibility report shall include an analysis of the alternatives to the land disposal of waste, including potential and existing waste reduction, reuse, recycling, composting and energy recovery initiatives and services.

c1d ANALYSIS OF ALTERNATIVES TO LAND DISPOSAL. The analysis shall include a discussion of the trends affecting the waste stream, an estimate of the cost per ton of each alternative, when available and an evaluation of the feasibility of implementing each potential alternative.

c2d EVALUATION OF IMPLEMENTING ALTERNATIVES TO LAND DISPOSAL. The feasibility report shall evaluate the feasibility of implementing waste reduction initiatives and recycling services in connection with the proposed landfill and describe any waste reduction incentives and recycling services to be provided at the proposed landfill.

History: Cr. Register, June, 1996, No. 486, eff. 7-1-96.

NR 512.19 Noncompliance with plans or orders. The feasibility report shall identify all persons owning a 10% or greater legal or equitable interest in the applicant or in the assets of the applicant, including shareholders of a corporation which is an applicant and partners of a partnership which is an applicant. The feasibility report shall also identify all other Wisconsin solid or hazardous waste facilities for which the applicant or any identified person is named in, or subject to an order or plan approval issued by the department. In addition, the feasibility report shall identify all other Wisconsin solid or hazardous waste facilities which are owned by persons, including corporations and partnerships, in which the applicant or any identified person owns or previously owned a 10% or greater legal or equitable interest or a 10% or greater interest in the assets and include a statement indicating whether or not all plan approvals and orders relating to all identified facilities are being complied with.

Note: If noncompliance with an order or plan approval occurs while the applicant has or had a 10% or greater legal or equitable interest in the facility and is continuing, the department is prohibited from licensing the new or expanded solid waste disposal facility, unless the applicant provides proof of financial responsibility under s. 289.34 c3d, Stats., to assure that compliance is achieved.

History: Cr. Register, September, 1998, No. 513, eff. 10-1-98.