

Chapter NR 528

MANAGEMENT OF ACCUMULATED SEDIMENT FROM
STORM WATER MANAGEMENT STRUCTURES

NR 528.01	Purpose.	NR 528.06	Sediment evaluation, certification requirements and end use determination.
NR 528.02	Applicability.	NR 528.07	End uses of accumulated sediment.
NR 528.03	Definitions.	NR 528.08	Record retention.
NR 528.04	Locational criteria, performance standards, erosion control measures and ceiling levels.	NR 528.09	Department assistance.
NR 528.05	Management decisions.	NR 528.10	Sediment management program evaluation and compliance.

NR 528.01 Purpose. The purpose of this chapter is to provide a streamlined process for the management of accumulated sediment removed from storm water management structures in a manner that protects public health, safety and the environment and reduces the need to dispose of accumulated sediment in landfills. This chapter is adopted under authority of s. 227.11, Stats., and ch. 289, Stats.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09.

NR 528.02 Applicability. c1d Except as otherwise provided, this chapter governs the management of accumulated sediment from storm water management structures.

c2d This chapter applies to a sediment manager who is required or authorized to undertake the removal and subsequent management of the accumulated sediment derived from the operation and maintenance of storm water management structures.

c3d This chapter does not apply to any of the following materials:

cad Sediment removed from underground structures such as catch basin sumps or other proprietary flow-through storm water sedimentation devices.

cbd Sediment removed from waste water treatment devices regulated under s. SPS 382.34.

ccd Material collected through street sweepings.

cdd Sediment managed subject to the permit requirements of s. 30.20, Stats., for removal of material from beds of navigable waters or s. 30.30 or 30.31, Stats., for harbor improvements.

ced Hazardous waste regulated under chs. NR 660 to 679.

Note: The sediment manager or environmental professional may use knowledge or testing in accordance with NR 662.011 to determine if the accumulated sediment is subject to chs. NR 660 to 679. In general, accumulated sediment is not subject to regulation under chs. NR 660 to 679.

cfđ Solid waste regulated under chs. NR 518 and 538.

cgđ Sediment removed from temporary sediment control practices during the construction phase of a project.

chđ Contaminated soils regulated under chs. NR 700 to 722.

cid Metallic mining operations for nonferrous minerals as defined in s. 293.01 c9d, Stats., and regulated under ch. NR 182.

cjd Materials associated with metallic mining operations for ferrous minerals as defined in s. 295.41 c26d, Stats., including mining wastes as defined in s. 295.41 c30d and sediment from stormwater management structures, as regulated under subch. III of ch. 295, Stats.

Note: Use of this code does not release the sediment manager from the requirement to obtain other permits as appropriate. Permits may include ch. NR 216, for land disturbance of one or more acres; ch. 30, Stats., for waterway and wetland activities such as dredging of ponds or culvert cleaning; and ch. 283, Stats., for general wastewater discharges such as Pit/Trench Dewatering and Carriage and Interstitial Water from Dredging Operations.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09; correc-

tion in c3d cbd made under s. 13.92 c4d cbd 7., Stats., Register February 2012 No. 674; CR 13-057: cr. c3d cid, cjd Register July 2015 No. 715, eff. 8-1-15.

NR 528.03 Definitions. The following definitions as well as the definitions in ch. 289, Stats., and s. NR 500.03 are applicable to the terms used in this chapter.

c1d XAccumulated sedimentY means settleable solid material contained in storm water runoff that is collected, retained and subsequently removed from storm water management structures.

c2d XCommercialY means those buildings for which the primary function involves the sale of goods or services.

c3d XConfined geotechnical fillY has the meaning specified in s. NR 538.03 c2d.

Note: Section NR 538.03 c2d defines confined geotechnical fill to mean Xa fill that is covered by an impervious surface such as concrete or asphalt.Y

c4d XDedicated sediment management sitesY means sites designed and operated for multiple applications of accumulated sediment from one or more storm water management structures where the accumulated sediment is landspread or treated.

c5d XDrainage areaY means the land area from which the storm water management structure receives runoff.

c6d XEnd useY or Xend use of accumulated sedimentY means use in agriculture, landscaping, site stabilization, construction, transportation projects, fill, backfill, reclamation of disturbed sites including mine reclamation, the placement of accumulated sediment and similar uses.

c7d XEnvironmental professionalY means a professional engineer registered pursuant to s. 443.04, Stats., or a professional soil scientist, geologist or hydrologist licensed under ch. 470, Stats.

c8d XForebayY means a pond-like structure that receives storm water prior to its entrance into the main portion of the pond with the purpose of removing coarse-grained sediment.

c9d XGeneral fillY means a location where accumulated sediment is used as fill in a natural topographic depression, an excavation such as an existing borrow area or an intentional excavation or to build up or shape the local landscape.

c10d XIndustrialY means those buildings used for the manufacture, storage or distribution of goods.

c11d XInstitutionalY means any public or private schools or colleges, churches, hospitals, or other government facilities not covered under commercial.

c12d XLandspreading of accumulated sedimentY means the application of accumulated sediment in thin layers to the surface of the land or incorporation into subsurface soils.

c13d XLicensed landfillY means a solid waste disposal facility with a license obtained pursuant to ch. 289, Stats.

c14d XMulti-family residentialY means housing for three or more attached dwelling units in a single building.

c15d XSediment managerY means any person with responsibility for the management of the accumulated sediment and may include those holding fee title, an easement or other interest in a property, or their agent including contractors or subcontractors and others required or authorized to undertake removal and subsequent management of accumulated sediment, including data gathering, reporting and recordkeeping.

c16d XStorm water management structureY means a device that detains, retains and treats storm water runoff resulting in the accumulation of sediment, and pollutants carried in the runoff. Such structures are characterized by having an outlet that discharges to waters of the state but only in response to storm events and includes wet and dry detention ponds and infiltration basins but not landscape ponds on private property with no designed inlet or outlet.

c17d XWaters of the stateY means those portions of Lake Michigan and Lake Superior within the boundaries of Wisconsin, all lakes, bays, rivers, streams, springs, ponds, wells, impounding reservoirs, marshes, water courses, drainage systems and other surface water or groundwater, natural or artificial, public or private within the state or under its jurisdiction, except those waters which are entirely confined and retained completely upon the property of a person.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09.

NR 528.04 Locational criteria, performance standards, erosion control measures and ceiling levels. The sediment manager shall ensure that the management option selected for the accumulated sediment is implemented in accordance with all of the following applicable criteria:

c1d LOCALATIONAL CRITERIA. cad Except as provided in par. cbd, a site where accumulated sediment is used or deposited shall meet the locational criteria in Table 1.

cbd The locational criteria in Table 1 do not apply to sediment from a drainage area that meets all the criteria in s. NR 528.06

c2d or to sediment used in an end use in accordance with s. NR 528.07 c3d or to sediment managed under s. NR 528.07 c7d.

c2d PERFORMANCE STANDARDS. cad No person may use or dispose of accumulated sediment at a site if there is a reasonable probability that the sediment end use will cause any of the following:

1. A significant adverse impact on wetlands as defined in ch. NR 103.
2. A take of an endangered or threatened species prohibited by s. 29.604, Stats.
3. A detrimental effect on any surface water.
4. A detrimental effect on groundwater quality that will cause or exacerbate an exceedance of any preventive action limit or enforcement standard at a point of standards application as defined in ch. NR 140. The point of standards application is defined by s. NR 140.22 c1d.

cbd The accumulated sediment end use shall comply with all applicable department approvals, federal, state and local requirements and be conducted in accordance with this subsection.

Note: Compliance with this section does not release the sediment manager from the requirement to obtain other permits as appropriate. Permits may include ch. NR 216, for land disturbance of one or more acres; ch. 30, Stats., for waterway and wetland activities such as dredging of ponds or culvert cleaning; and ch. 283, Stats., for general wastewater discharges such as Pit/Trench Dewatering and Carriage and Interstitial Water from Dredging Operations.

c3d EROSION CONTROL MEASURES. The sediment manager shall ensure that measures are taken to control run-on and runoff, minimize the area disturbed by the project, minimize loss of fugitive dust and retain sediment on the site during and after the placement of the accumulated sediment. Runoff control measures shall be effectively inspected and maintained. Any area where topsoil is exposed shall be seeded and mulched or otherwise stabilized within 48 hours of placement. Where applicable, the requirements in ch. NR 216 shall be followed.

c4d CEILING LEVELS. If the sample results obtained in accordance with s. NR 528.06 c3d cbd exceed any of the ceiling levels listed in Table 2, the sediment manager shall ensure that the accumulated sediment is disposed of in a licensed landfill.

**Table 1
Locational Criteria for Management of Accumulated Sediment**

	Bedrock or Groundwater Table	Public Water Supply Well	Private Water Supply Well	Lake, Wetland, Pond or Any Navigable Waterway or Sinkhole	Residence	School, Health care Facility
Separation Distance in Feet	3	1,200	250	200	250	1,000 ¹ surface spread 500 incorporated

¹ The 1,000 foot separation applies when the pathogen or indicator organism level exceeds the criteria specified in s. NR 204.07 c6d and application to the surface of the land is the desired management option; if incorporated into the soil, then 500 feet is appropriate. However, if the pathogen or indicator organism level is below the criteria, the setback distance for a residence may be used.

**Table 2
Ceiling Levels Governing Management of Accumulated Sediment**

Parameter	Ceiling Level ppm or mg{kg on a dry weight basis unless otherwise specified
Total Arsenic	8
Total Cadmium	10
Total Chromium	100
Total Lead	250
pH	Less than 5 or greater than 10 standard units
Electrical conductivity	8 deciSiemens{meter cdS {md ¹ at 25°C

¹ deciSiemens{meter cdS {md and mmhos per centimeter are equivalent; dS{m is the modern nomenclature.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09.

NR 528.05 Management decisions. c1d The sediment manager shall determine from the options listed in s. [NR 528.07](#) an appropriate end use for the accumulated sediment based on consideration of all of the following factors:

- cad Evaluation of sediment sample data in s. [NR 528.06 c4d](#).
- cbd Completion and evaluation of the appropriate portions of the certification form supplied by the department.
- ccd Factors specific to the site where sediment is generated as identified in s. [NR 528.06 c3d cbd 5](#).

cdd Factors specific to the site proposed for end use of the accumulated sediment.

ced Any other factors relevant to the minimization of risk to public health, safety or the environment.

c2d No sediment may be used in a manner which is likely to cause any significant risk to public health, safety or the environment.

History: CR 08-111: cr. [Register November 2009 No. 647](#), eff. 12-1-09.

NR 528.06 Sediment evaluation, certification requirements and end use determination. Except in cases where the accumulated sediment will be disposed of in a licensed landfill, the sediment manager shall evaluate the characteristics of the drainage area from which the accumulated sediment is removed, sample the accumulated sediment, where applicable, evaluate the sample results, choose an end use and create and maintain a record by completing the required certification form as set out in this section.

c1d CERTIFICATION FORM. The sediment manager shall ensure that the applicable portions of the certification form supplied by the department are accurately and completely filled out and certified.

Note: Copies of the certification form may be obtained from the department of natural resources, bureau of waste and materials management, 101 South Webster Street, Natural Resources Building, P.O. Box 7921, Madison, Wisconsin 53707-7921, c608d 266-2111, DNRwastematerials@Wisconsin.gov.

c2d DRAINAGE AREA EVALUATION. The sediment manager shall certify in accordance with sub. **c1d** whether or not the drainage area meets all of the following criteria:

cad Has less than 15% commercial, multi-family residential, institutional and industrial land uses combined, excluding green space such as parks, cemeteries, golf courses and lawns.

cbd Has no areas of suspected contamination that may adversely affect sediment management.

ccd Has no other existing conditions or known historical events that may adversely affect sediment management.

cdd Has no reported hazardous substance spills regulated under s. **292.11**, Stats., since construction or since accumulated sediment was last removed.

c3d SAMPLING. If the drainage area does not meet the criteria in sub. **c2d**, the sediment manager shall ensure that the sediment is properly sampled and analyzed, each time, prior to its removal from the storm water management structure. Routine sediment sampling and handling shall be performed in accordance with par. **cad**. Sediment sample analysis shall be performed in accordance with par. **cbd**. All sediment sampling, handling and analysis shall be performed under the supervision of an environmental professional in accordance with par. **ccd**. The sediment manager may elect to use previous sampling results in lieu of new sediment sampling and analysis if the drainage area has not changed significantly since the sediment was last tested.

cad Sample collection. Representative accumulated sediment samples shall be obtained by meeting all of the following criteria:

1. Samples shall be obtained using proper handling, storage and delivery procedures required by the laboratory where the samples will be analyzed.

2. Samples shall be obtained that are representative of the entire volume of sediment to be removed and managed using all of the following:

a. One sample shall be obtained in each surface acre or portion of a surface acre in storm water management structures that are 4 acres or less. This sample may consist of multiple samples composited together to obtain a representative sample.

b. At least one sample per quadrant shall be obtained when the storm water management structure is greater than 4 acres.

c. A greater number of samples shall be obtained when necessary to represent the variability in the sediment due to factors such as sediment transport within the structure, changes in land use in the drainage area and the duration of time during which the sediment has been accumulating.

d. Samples shall be taken to the depth of the anticipated sediment removal.

3. Samples shall be obtained to provide a volume of 3

ment adequate to meet the analytical requirements based on the parameters to be analyzed for and the methods of analysis to be performed by the laboratory where the samples will be analyzed.

Note: Additional information on how to perform sediment sampling can be found in existing USEPA Guidance for its Biosolids Rule, CFR Part 503. Please see Methods and Manner of Sampling. http://www.epa.gov/owm/mtb/biosolids/503pe/503pe_6.pdf

cbd Sample analysis. Samples collected in par. **cad** shall be analyzed for all of the constituents in this paragraph. Constituents listed in subds. **3** and **5** shall be analyzed at a laboratory certified or registered in accordance with ch. **NR 149**:

1. Percent solids, percent organic matter, electrical conductivity as a saturated paste and pH to provide information on physical characteristics.

2. Total Kjeldahl nitrogen, total nitrate nitrogen, total phosphorus and total potassium to provide information on nutrient content. Nutrient content shall be expressed as mg/kg on a dry weight basis.

3. Total arsenic, cadmium, copper, chromium, lead, nickel and zinc to ensure these are not present at elevated levels and as indicator parameters showing the potential presence of other heavy metals and possible need for additional sampling. Results shall be calculated on a dry weight basis.

4. Pathogen or indicator organism, as referenced in ss. **NR 204.06 c2d cbd 4**, or **204.07 c6d**, showing the potential presence of other pathogens and possible need for additional pathogen sampling and analysis.

Note: Effective with the incorporation of this rule, the current pathogen indicator organism is fecal coliform. The maximum allowable density is 1,000 expressed as MPN/gTS (most probable number per gram of total solids on a dry weight basis).

5. Additional parameters beyond those required under subds. **1** to **4**, if deemed necessary by the sediment manager based on all of the following factors:

a. The present and past land uses in the drainage area served by the storm water management structure such as commercial, multi-family residential, institutional and industrial.

b. Any other known or suspected sources of contamination.

c. Existing conditions or known historical events that may affect the likelihood of safe sediment management.

d. Reported hazardous substance spills under s. **292.11**, Stats., in the drainage area since construction or since accumulated sediment was last removed.

e. Sample data indicating significantly elevated levels of contaminants above background concentrations for indicator parameters in subds. **3** and **4**, that may affect management in s. **NR 528.05**.

f. Any other applicable administrative code requirements.

Note: Additional parameters may include priority pollutants or TCLP constituents.

ccd Oversight. Sample collection and evaluation pursuant to this subsection shall be performed by or under the supervision of an environmental professional.

c4d SEDIMENT SAMPLE DATA EVALUATION. The sediment manager shall ensure that the sediment sample data collected in accordance with sub. **c3d cbd 1** to **4**, are evaluated by an environmental professional in accordance with sub. **c3d ccd** and compared with the ceiling levels in s. **NR 528.04 c4d** Table 2 and, based on the results of the evaluation, that all of the following applicable steps are taken:

cad If any of the ceiling levels in s. **NR 528.04 c4d** Table 2 are exceeded, the accumulated sediment shall be disposed of in a licensed landfill.

cbd If the indicator parameter levels do not exceed the ceiling levels in s. **NR 528.04 c4d** Table 2, but show elevated levels of contaminants, follow-up sampling shall be performed in accor-

dance with sub. [c3d cbd 5.](#), results evaluated, an appropriate end use determined in accordance with sub. [c5d](#) and the certification form supplied by the department completed.

ccd If the indicator parameter levels do not indicate elevated levels of contaminants, the sediment manager shall ensure that an appropriate end use is determined in accordance with sub. [c5d](#) and the certification form supplied by the department is completed.

Note: Technical support resources provided by the department may be referred to for assistance in evaluating the data when addressing elevated levels of contaminants.

c5d END USE DETERMINATION. The sediment manager shall ensure that the appropriate end use of accumulated sediment is determined using all of the following applicable steps:

cad The sediment manager shall complete the appropriate sections of the certification form provided by the department and certify whether or not the drainage area from which the sediment is removed meets the criteria in sub. [c2d](#).

cbd If all the criteria in sub. [c2d](#) are met, the sediment is not required to be sampled and the locational criteria in s. [NR 528.04 c1d](#) are not required to be met.

ccd If the criterion in sub. [c2d cad](#) is not met, but the criteria in sub. [c2d cbd](#) to [cdd](#) are met, the sediment shall be sampled pursuant to sub. [c3d](#) and the appropriate sections of the certification form provided by the department shall be completed. If the sample data indicates elevated levels of contaminants, additional parameters shall be sampled for in accordance with sub. [c3d cbd 5.](#) and the appropriate sections of the certification form provided by the department shall be completed.

cdd If the criteria in sub. [c2d cbd](#), [ccd](#) or [cdd](#) are not met, sources of contamination in the drainage area shall be further evaluated, additional sampling shall be considered in accordance with sub. [c3d cbd 5.](#) and the appropriate sections of the certification form provided by the department shall be completed.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09.

NR 528.07 End uses of accumulated sediment. The sediment manager shall ensure that an end use is chosen for the accumulated sediment in accordance with this section.

c1d LICENSED LANDFILL DISPOSAL. **cad** If the sediment manager determines that the accumulated sediment will be disposed of in a licensed landfill, the sediment does not need to be evaluated or sampled under s. [NR 528.06](#).

Note: The landfill operator should be contacted to determine whether the landfill requires the sediment be sampled before it is accepted at the landfill. The sediment may be appropriate for use as daily or final cover in accordance with the landfill's approved plan of operation.

cbd If any of the ceiling levels in s. [NR 528.04 c4d](#) Table 2 are exceeded, the accumulated sediment shall be disposed of in a licensed landfill.

c2d GENERAL FILL. **cad** The accumulated sediment may be used as general fill in a designed excavation or to improve a site by restoring original contours, filling depressions, improving or stabilizing borrow areas or other disturbed sites.

Note: Examples of uses may include reclamation of abandoned mines, fill in a topographic depression, or other uses that build up or shape the local landscape, mitigate safety or erosion hazards or otherwise improve disturbed sites.

cbd All of the following steps shall be taken to stabilize the site:

1. Complete placement and preparation of the sediment and any needed topsoil, substitute soil or cover material within 6 months or less of initiating placement in the project year.

2. Stabilize the cover, topsoil, substitute soil or sediment to prevent erosion due to wind and water, perform all revegetation, mulching or other equivalent stabilization activities prior to the end of the growing season and minimize the exposure of the sediment to the environment by employing one or more of the following measures:

- a. Place an impermeable cover.

- b. Place a topsoil layer of no less than 6 inches.

- c. Use the accumulated sediment in lieu of or in combination with topsoil, provided it is capable of supporting a vegetative cover.

3. Revegetate, mulch or otherwise stabilize the sediment within 48 hours of completing the sediment disposal.

ccd Control erosion during and after the placement of sediment in accordance with s. [NR 528.04 c3d](#).

c3d CONFINED GEOTECHNICAL FILL. The accumulated sediment may be used as confined geotechnical fill for a variety of uses such as subbase under paved lots and subbase or subgrade for building construction.

Note: Examples of confined geotechnical fill uses may include construction and maintenance of non-department of transportation projects, bridge abutment backfill or other similar uses in which the sediment is covered by an impervious surface such as concrete, asphalt, a building or similar material and thus not exposed to the environment.

c4d LANDSPREADING. The sediment manager shall ensure that the appropriate sections of the certification form provided by the department are completed and the other requirements in s. [NR 528.06](#) are complied with. When landspreading the accumulated sediment, all of the following shall apply:

cad *Site evaluation.* The site where the accumulated sediment is proposed to be landspread shall be evaluated to ensure that the site is suitable. The site evaluation shall include the soil factors in Table 3 and may include assessment of organic matter content, cation exchange capacity, soil permeability and any other characteristics or factors that would affect the mobility and attenuation of pollutants present in the sediment. The site shall meet the locational criteria in s. [NR 528.04 c1d](#) Table 1.

cbd *Application rate and depth.* The application rate of accumulated sediment may not exceed 5 dry tons per acre per year and may not exceed 15 dry tons per acre total loading during the life of the landspreading site. The depth of the application may not exceed 18 inches.

1. Neither the 5 dry tons per acre per year application rate limitation or the 15 dry tons per acre landspreading site life limit apply when accumulated sediment is used as a component of a marketable soil amendment product pursuant to a contract or used to facilitate nonmetallic mine reclamation as part of an approved reclamation plan.

2. The 5 dry tons per acre annual limit and the total loading limit of 15 dry tons per acre landspreading life may be adjusted based on soil sampling results, plant tissue monitoring data, landspreading site records or other data. All data necessary to justify the exceedances and extended use shall be collected and evaluated and all data and records shall be maintained in accordance with s. [NR 528.08](#).

Table 3
Soil Factors for Site Evaluation

Soil Factor ¹	Acceptability for Landspreading Accumulated Sediment			
	Unacceptable	Poor	Adequate	Preferred
pH standard units	Less than 5.3 or greater than 8.0	5.3 to 5.6 or 7.7 to 7.9	5.7 to 5.9 7.3 to 7.6	6.0 to 7.2
Texture		Silty clay ² , clay ² , sand ³ , loamy sand ³	Sandy loam, silty clay loam, sandy clay	Loam, silt loam, silt, clay loam, sandy clay loam

¹ Obtain from soil survey, not in-field test

² Acceptable only when incorporated

³ Acceptable only with increased site management determined by the sediment manager

ccd Nutrient content. The nitrogen and phosphorous content shall be provided to the receiver of the accumulated sediment if the receiver has a nutrient management plan for the acreage where the accumulated sediment will be landspread.

Note: Farmers required to follow a nutrient management plan need information on nutrient content in order to comply with NRCS Standard 590 available at: <http://efotg.nrcs.usda.gov/references/public/WI590.pdf>.

cdd Uniform application. The application of accumulated sediment to the land surface shall be uniform when surface applied, as well as during injection or incorporation.

ced Application limitations. Accumulated sediment may not be applied under any of the following situations:

1. On frozen or saturated ground.
2. When precipitation capable of producing runoff is forecast within 24 hours of the time of planned application, during or immediately after a precipitation event.
3. On slopes greater than 6%.

cfđ Pathogens. In all cases where a pathogen risk exists due to the presence of pathogens, as indicated by evidence of the pathogen or indicator organism and level per s. NR 528.06 c3d cbd 4., the following management practices shall be implemented:

1. At a minimum, accumulated sediment shall be incorporated into the surface soil to a depth of at least 6 inches by disking or an equivalent process and may include other measures such as signage, restriction on site access or other appropriate measures.
2. The following waiting periods and access restrictions shall apply beginning on the date when the landspreading activity is completed:
 - a. When lands are used for the production of forage crops, landspreading shall occur only after harvest has occurred and before any new growth reaches 6 inches.
 - b. When lands are used for food crops intended for human consumption, a period of at least 14 months shall elapse prior to emergence of the food crop.
 - c. When lands are used for grazing, at least 30 days shall elapse prior to allowing access to non-dairy animals and at least 60 days shall elapse before allowing access to dairy animals.
 - d. When lands are subject to public access or used for the harvest of crops grown for fiber or any other forage or crop production, not covered in this subd. 2. a. to c., a period of at least 30 days shall elapse before the site may be accessed or used.

c5d DEDICATED SEDIMENT MANAGEMENT SITE. The end use of landspreading or sediment treatment at a dedicated management site may be chosen if the sites are owned or leased by a municipality or other responsible unit of government. The sediment manager shall assume any additional site management, site monitoring and recordkeeping responsibilities that are necessary to minimize risk to public health, safety and the environment.

cad When sediment is used at a dedicated site, the sediment

manager shall ensure that the appropriate portions of the certification form provided by the department are completed. Based on the information obtained in accordance with s. NR 528.06, the sediment manager may choose to use the accumulated sediment for productive purposes including the growth of herbaceous or woody plants for harvest or for treatment to reduce contaminants in the accumulated sediment in accordance with this subsection.

cbd All of the following restrictions shall apply to dedicated sediment management sites:

1. The locational criteria in s. NR 528.04 c1d shall be met.
2. The sediment shall be applied to a depth of 18 inches or less below ground surface.
3. When the dedicated site is used for sediment treatment so as to attenuate or reduce contaminants in the accumulated sediment, only non-food chain crops or woody plants for harvest or phyto-remediation purposes may be grown.
4. In cases where the annual application rate or lifetime loading limit in sub. c4d cbd are not exceeded, the provisions of sub. c4d cbd 2. do not apply. In cases where the 5 dry tons per acre annual application rate limitation or the 15 dry tons per acre site life limit are exceeded, the sediment manager shall ensure that sub. c4d cbd 2. is followed as well as take any additional measures or practices that may be necessary to ensure safe long-term site use. These may include practices such as the collection and evaluation of contaminants in soils, plant tissue, other environmental receptors or monitoring devices. The sediment manager shall track the sediment application rates and cumulative site loading totals for contaminants in soil or other receptors as appropriate. The sediment manager shall ensure that any additional measures are implemented that may be necessary such as enhanced site management practices to control run-on and runoff and erosion control practices. At a minimum, the erosion control requirements of s. NR 528.04 c3d shall be met.
5. Accumulated sediment may be applied on frozen ground and on slopes greater than 6% or more provided the sediment management is performed in compliance with s. NR 528.04 c3d and adequate and permanent run-on and runoff controls are in place and maintained.
6. Sediment may not be applied when precipitation capable of producing runoff is forecast within 24 hours of the time of planned application, or during or immediately after a precipitation event.
7. In all cases where a pathogen risk exists due to the presence of pathogens, as indicated by evidence of the pathogen or indicator organism and level per s. NR 528.06 c3d cbd 4., then the waiting periods in sub. c4d cfd apply.
8. In all cases where a pathogen risk exists due to the presence of pathogens, no grazing is allowed and no human food chain crops may be grown where the sediment has been applied.
9. In all cases where a pathogen risk exists, permanent public

access controls shall be put in place and access restricted during any year when the sediment application occurs.

ccd The sediment manager shall ensure that an affidavit is filed indicating that the site was used for a dedicated sediment management site in the registrar of deeds office in the county where the site is located.

cdd The sediment manager shall ensure that all appropriate completed certification forms, all sediment sampling results and all monitoring data and site use and sediment loading records are retained in accordance with s. NR 528.08.

c6d SMALL QUANTITY, COARSE GRAINED SEDIMENT MANAGEMENT. The sediment manager may choose to manage certain kinds of coarse grained sediment as provided under this subsection.

cad If the annual volume of accumulated sediment to be managed is 100 cubic yards or less and comprised primarily of coarse-grained material such as that found in the forebay, the sediment manager shall complete the appropriate sections of the certification form provided by the department and indicate the following criteria are met:

1. The volume of accumulated sediment to be managed is 100 cubic yards or less.
2. No more than 15% of the material, as a percentage by weight, passes a No. 200 sieve.

cbd If the criteria in par. cad are met, no chemical testing is required and the sediment shall be managed in accordance with s. NR 528.04 c1d and c2d. If either par. cad 1. or 2. are not met, the accumulated sediment may not be used in accordance with this subsection and shall be managed in accordance with this section and ss. NR 528.04 to 528.06 and 528.08.

ccd The sediment manager shall maintain responsibility for managing the accumulated sediment.

cdd The sediment manager shall retain records in accordance with s. NR 528.08.

c7d END USE UNDER OTHER CONTROL. Accumulated sediment may be used under the control of another program in accordance with this subsection. End use of accumulated sediment pursuant to this subsection is not subject to the other provisions of this chapter provided equivalent protectiveness is afforded, including the provisions of ss. NR 528.04 c2d to c4d.

cad Accumulated sediment may be used in accordance with a department of transportation facility construction and maintenance project contract of specific duration that requires compliance with department of transportation standard specifications for site restoration and stabilization. Sampling in accordance with s. NR 528.06 c3d is not required when there is another requirement such as a contract or permit that requires sampling encompassing the s. NR 528.06 c3d requirements. Sampling pursuant to s. NR 528.06 c3d shall be performed if the contract or permit does not require sampling encompassing these requirements.

Note: The requirements of the WDOT concerning the restoration of disturbed sites are found in sections of the standard specifications including those addressing erosion control, seeding, final clean-up and may be found in: WDOT Standard Specifications, see <http://roadwaystandards.dot.wi.gov/standards/stdnspec/index.htm>.

cbd Accumulated sediment may be used in accordance with a ch. NR 135 nonmetallic mine reclamation permit issued pursuant to an applicable nonmetallic mining reclamation ordinance. Sampling in accordance with s. NR 528.06 c3d is not required when there is another document such as a contract or permit that requires sampling encompassing the s. NR 528.06 c3d requirements. Sampling pursuant to s. NR 528.06 c3d shall be performed if the contract or permit does not require sampling encompassing these requirements.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09.

NR 528.08 Record retention. All completed certification forms, all sediment sampling results, other site monitoring results and site management records shall be retained by the sediment manager in accordance with this section.

c1d ON-LINE SYSTEM. The department may develop an on-line system to receive and store the records.

cad If an on-line voluntary system is established, a sediment manager who chooses to use the on-line system no longer needs to retain the records.

cbd If the department requires the use of the on-line system, the records no longer need to be retained by the sediment manager.

c2d RETENTION TIME. If an on-line system is not established, or if a voluntary on-line system is established and the sediment manager chooses not to use it, the records shall be retained for 20 years. These records shall be provided to the department upon request.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09.

NR 528.09 Department assistance. To assist sediment managers in making the determinations required in this chapter, the department may provide outreach, training, certification forms, written and on-line technical assistance documents or other resources deemed appropriate.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09.

NR 528.10 Sediment management program evaluation and compliance. The department may consult and work with those who implement accumulated sediment uses and are interested in substantiating the effectiveness, safety and environmental protectiveness of the chosen sediment management practice. Sediment managers shall provide data documenting their operation to assist with the evaluation upon request by the department. The department may also request information necessary to determine compliance with this chapter. Sediment managers shall provide site access to department staff upon request.

History: CR 08-111: cr. Register November 2009 No. 647, eff. 12-1-09.