

Chapter NR 665

INTERIM LICENSE HAZARDOUS WASTE TREATMENT, STORAGE AND DISPOSAL FACILITY STANDARDS

Subchapter A — General

- NR 665.0001 Purpose, scope and applicability.
NR 665.0004 Imminent danger action.

Subchapter B — General Facility Standards

- NR 665.0010 Applicability.
NR 665.0011 Identification number.
NR 665.0012 Required notices.
NR 665.0013 General waste analysis.
NR 665.0014 Security.
NR 665.0015 General inspection requirements.
NR 665.0016 Personnel training.
NR 665.0017 General requirements for ignitable, reactive or incompatible wastes.
NR 665.0018 Location standards.
NR 665.0019 Construction quality assurance program.
NR 665.0020 Schedule of compliance for corrective action.

Subchapter C — Preparedness and Prevention

- NR 665.0030 Applicability.
NR 665.0031 Maintenance and operation of facility.
NR 665.0032 Required equipment.
NR 665.0033 Testing and maintenance of equipment.
NR 665.0034 Access to communications or alarm system.
NR 665.0035 Required aisle space.
NR 665.0037 Arrangements with local authorities.

Subchapter D — Contingency Plan and Emergency Procedures

- NR 665.0050 Applicability.
NR 665.0051 Purpose and implementation of contingency plan.
NR 665.0052 Content of contingency plan.
NR 665.0053 Copies of contingency plan.
NR 665.0054 Amendment of contingency plan.
NR 665.0055 Emergency coordinator.
NR 665.0056 Emergency procedures.

Subchapter E — Manifest System, Recordkeeping and Reporting

- NR 665.0070 Applicability.
NR 665.0071 Use of manifest system.
NR 665.0072 Manifest discrepancies.
NR 665.0073 Operating record.
NR 665.0074 Availability, retention and disposition of records.
NR 665.0075 Annual report.
NR 665.0076 Unmanifested waste report.
NR 665.0077 Additional reports.

Subchapter F — Groundwater Monitoring

- NR 665.0090 Applicability.
NR 665.0091 Groundwater monitoring system.
NR 665.0092 Sampling and analysis.
NR 665.0093 Preparation, evaluation and response.
NR 665.0094 Recordkeeping and reporting.

Subchapter G — Closure and Long-Term Care

- NR 665.0110 Applicability.
NR 665.0111 Closure performance standard.
NR 665.0112 Closure plan; amendment of plan.
NR 665.0113 Closure; time allowed for closure.
NR 665.0114 Disposal or decontamination of equipment, structures and soils.
NR 665.0115 Certification of closure.
NR 665.0116 Survey plat.
NR 665.0117 Long-term care and use of property.
NR 665.0118 Long-term care plan; amendment of plan.
NR 665.0119 Long-term care notices.
NR 665.0120 Certification of completion of long-term care.
NR 665.0121 Long-term care requirements for facilities that obtain enforceable documents in lieu of long-term care licenses.

Subchapter H — Financial Requirements

- NR 665.0140 Applicability.
NR 665.0141 Definitions.
NR 665.0142 Cost estimate for closure.
NR 665.0143 Financial assurance for closure.
NR 665.0144 Cost estimate for long-term care.
NR 665.0145 Financial assurance for long-term care.

- NR 665.0146 Use of a mechanism for financial assurance of both closure and long-term care.

- NR 665.0147 Liability requirements.

- NR 665.0148 Incapacity of owners or operators, guarantors or financial institutions.

Subchapter I — Containers

- NR 665.0170 Applicability.
NR 665.0171 Condition of containers.
NR 665.0172 Compatibility of waste with container.
NR 665.0173 Management of containers.
NR 665.0174 Inspections.
NR 665.0176 Special requirements for ignitable or reactive waste.
NR 665.0177 Special requirements for incompatible wastes.
NR 665.0178 Air emission standards.

Subchapter J — Tank Systems

- NR 665.0190 Applicability.
NR 665.0191 Assessment of existing tank system[s] integrity.
NR 665.0192 Design and installation of new tank systems or components.
NR 665.0193 Containment and detection of releases.
NR 665.0194 General operating requirements.
NR 665.0195 Inspections.
NR 665.0196 Response to leaks or spills and disposition of leaking or unfit-for-use tank systems.
NR 665.0197 Closure and long-term care.
NR 665.0198 Special requirements for ignitable or reactive wastes.
NR 665.0199 Special requirements for incompatible wastes.
NR 665.0200 Waste analysis and trial tests.
NR 665.0202 Air emission standards.

Subchapter K — Surface Impoundments

- NR 665.0220 Applicability.
NR 665.0221 Design and operating requirements.
NR 665.0222 Action leakage rate.
NR 665.0223 Containment system.
NR 665.0224 Response actions.
NR 665.0225 Waste analysis and trial tests.
NR 665.0226 Monitoring and inspection.
NR 665.0228 Closure and long-term care.
NR 665.0229 Special requirements for ignitable or reactive waste.
NR 665.0230 Special requirements for incompatible wastes.
NR 665.0231 Air emission standards.

Subchapter L — Waste Piles

- NR 665.0250 Applicability.
NR 665.0251 Protection from wind.
NR 665.0252 Waste analysis.
NR 665.0253 Containment.
NR 665.0254 Design and operating requirements.
NR 665.0255 Action leakage rates.
NR 665.0256 Special requirements for ignitable or reactive waste.
NR 665.0257 Special requirements for incompatible wastes.
NR 665.0258 Closure and long-term care.
NR 665.0259 Response actions.
NR 665.0260 Monitoring and inspection.

Subchapter M — Land Treatment

- NR 665.0270 Applicability.

Subchapter N — Landfills

- NR 665.0300 Applicability.
NR 665.0301 Design and operating requirements.
NR 665.0302 Action leakage rate.
NR 665.0303 Response actions.
NR 665.0304 Monitoring and inspection.
NR 665.0309 Surveying and recordkeeping.
NR 665.0310 Closure and long-term care.
NR 665.0312 Special requirements for ignitable or reactive waste.
NR 665.0313 Special requirements for incompatible wastes.
NR 665.0314 Special requirements for bulk and containerized liquids.
NR 665.0315 Special requirements for containers.
NR 665.0316 Disposal of small containers of hazardous waste in overpacked drums clab packs.

Subchapter O — Incinerators

- NR 665.0340 Applicability.
- NR 665.0341 Waste analysis.
- NR 665.0345 General operating requirements.
- NR 665.0347 Monitoring and inspections.
- NR 665.0351 Closure.
- NR 665.0352 Interim licensed incinerators burning particular hazardous wastes.

Subchapter P — Thermal Treatment

- NR 665.0370 Other thermal treatment.
- NR 665.0373 General operating requirements.
- NR 665.0375 Waste analysis.
- NR 665.0377 Monitoring and inspections.
- NR 665.0381 Closure.
- NR 665.0382 Open burning; waste explosives.
- NR 665.0383 Interim license thermal treatment devices burning particular hazardous waste.

Subchapter Q — Chemical, Physical and Biological Treatment

- NR 665.0400 Applicability.
- NR 665.0401 General operating requirements.
- NR 665.0402 Waste analysis and trial tests.
- NR 665.0403 Inspections.
- NR 665.0404 Closure.
- NR 665.0405 Special requirements for ignitable or reactive waste.
- NR 665.0406 Special requirements for incompatible wastes.

Subchapter R — Underground Injection

- NR 665.0430 Applicability.

Subchapter W — Drip Pads

- NR 665.0440 Applicability.
- NR 665.0441 Assessment of existing drip pad integrity.
- NR 665.0442 Design and installation of new drip pads.
- NR 665.0443 Design and operating requirements.
- NR 665.0444 Inspections.
- NR 665.0445 Closure.

Subchapter AA — Air Emission Standards for Process Vents

- NR 665.1030 Applicability.
- NR 665.1031 Definitions.
- NR 665.1032 Standards: process vents.
- NR 665.1033 Standards: closed-vent systems and control devices.
- NR 665.1034 Test methods and procedures.
- NR 665.1035 Recordkeeping requirements.

Subchapter BB — Air Emission Standards for Equipment Leaks

- NR 665.1050 Applicability.
- NR 665.1051 Definitions.
- NR 665.1052 Standards: pumps in light liquid service.
- NR 665.1053 Standards: compressors.
- NR 665.1054 Standards: pressure relief devices in gas or vapor service.
- NR 665.1055 Standards: sampling connection systems.
- NR 665.1056 Standards: open-ended valves or lines.
- NR 665.1057 Standards: valves in gas or vapor service or in light liquid service.
- NR 665.1058 Standards: pumps and valves in heavy liquid service, pressure relief devices in light liquid or heavy liquid service and flanges and other connectors.
- NR 665.1059 Standards: delay of repair.
- NR 665.1060 Standards: closed-vent systems and control devices.
- NR 665.1061 Alternative standards for valves in gas or vapor service or in light liquid service: percentage of valves allowed to leak.
- NR 665.1062 Alternative standards for valves in gas or vapor service or in light liquid service: skip period leak detection and repair.
- NR 665.1063 Test methods and procedures.
- NR 665.1064 Recordkeeping requirements.

Subchapter CC — Air Emission Standards for Tanks, Surface Impoundments and Containers

- NR 665.1080 Applicability.
- NR 665.1081 Definitions.
- NR 665.1082 Schedule for implementation of air emission standards.
- NR 665.1083 Standards: general.
- NR 665.1084 Waste determination procedures.
- NR 665.1085 Standards: tanks.
- NR 665.1086 Standards: surface impoundments.
- NR 665.1087 Standards: containers.
- NR 665.1088 Standards: closed-vent systems and control devices.
- NR 665.1089 Inspection and monitoring requirements.
- NR 665.1090 Recordkeeping requirements.

Subchapter DD — Containment Buildings

- NR 665.1100 Applicability.
- NR 665.1101 Design and operating standards.
- NR 665.1102 Closure and long-term care.

Subchapter EE — Hazardous Waste Munitions and Explosives Storage

- NR 665.1200 Applicability.
- NR 665.1201 Design and operating standards.
- NR 665.1202 Closure and long-term care.

Subchapter A — General

Note: After the effective date of ch. NR 670, the treatment, storage and disposal of hazardous waste is prohibited except according to a license. Section 291.25c4d, Stats., provides for the continued operation of an existing facility under an interim license, until final administrative disposition of the owner[s] and operator[s] operating license application is made.

NR 665.0001 Purpose, scope and applicability.

c1d The purpose of this chapter is to establish minimum state standards that define the acceptable management of hazardous waste during the period of the interim license and until certification of final closure or, if the facility is subject to long-term care requirements, until long-term care responsibilities are fulfilled.

c2d Except as provided in s. NR 665.1080 c2d, the standards of this chapter, and of ss. NR 664.0552, 664.0553 and 664.0554, apply to owners and operators of facilities that treat, store or dispose of hazardous waste who have fully complied with the interim license requirements of s. 291.25 c4d, Stats., and s. NR 670.010 until either an operating license is issued under s. 291.25, Stats., or until applicable closure and long-term care responsibilities under this chapter are fulfilled, and to those owners and operators of facilities in existence on November 19, 1980 who have failed to provide timely notification as required by s. 291.05 c1d, Stats., and s. NR 660.07 or failed to file part A of the EPA hazardous waste permit application as required by s. NR 670.010 c5d and c7d. These standards apply to all treatment, storage and disposal of hazardous waste at these facilities after August 1, 2006, except as specifically provided otherwise in this chapter or ch. NR 661.

c3d The requirements of this chapter do not apply to any of the following:

cad A person disposing of hazardous waste by means of ocean disposal subject to a permit issued under 33 USC 1401 to 1445.

Note: This chapter does apply to the treatment or storage of hazardous waste before it is loaded onto an ocean vessel for incineration or disposal at sea, as provided in sub. c2d. Title 33 USC 1401 to 1445 is also known as the ocean dumping portion of the federal marine protection, research and sanctuaries act.

ccd The owner or operator of a POTW which treats, stores or disposes of hazardous waste according to the requirements in s. NR 670.001 c3d cbd 9.

ced The owner or operator of a facility licensed or registered by the department to dispose of either of the following:

1. Municipal or industrial solid waste, if the only hazardous waste the facility disposes of is from very small quantity generators and the facility has been approved by the department to accept hazardous waste from very small quantity generators.

2. Household and very small quantity generator waste, if the facility complies with the requirements of ch. NR 666 subch. HH.

Note: The specific requirements for solid waste landfills accepting hazardous waste from very small quantity generators are contained in s. NR 506.155. Very small quantity generators have the option of ensuring delivery of their hazardous waste to certain solid waste disposal facilities under s. NR 662.014.

cfd The owner or operator of a facility managing recyclable materials described in s. NR 661.0006 c1d cbd, ccd and cdd except to the extent they are referred to in subch. C, F, G or H of ch. NR 666, or ch. NR 679d.

cgd A generator accumulating waste on-site in compliance with the applicable conditions for exemption specified in ss.

NR 662.014 to 662.017 and subchs. K and L of ch. NR 662, except to the extent the requirements are included in ss. NR 662.014 to 662.017 and subchs. K and L of ch. NR 662, or treating waste in containers or tanks, provided the requirements of ss. NR 662.014 to 662.017 are met.

chd A farmer disposing of waste pesticides from the farmer[s own use in compliance with s. NR 662.070.

cid The owner or operator of a totally enclosed treatment facility, as defined in s. NR 660.10.

cjd The owner or operator of an elementary neutralization unit or a wastewater treatment unit as defined in s. NR 660.10, provided that if the owner or operator is diluting hazardous ignitable cD001d wastes other than the D001 high TOC subcategory defined in s. NR 668.40, the table XTreatment Standards for Hazardous WastesYd, or reactive cD003d waste, to remove the characteristic before land disposal, the owner or operator shall comply with s. NR 665.0017 c2d.

ckd 1. Except as provided in subd. 2., a person engaged in treatment or containment activities during immediate response to any of the following situations:

- a. A discharge of a hazardous waste.
- b. An imminent and substantial threat of a discharge of a hazardous waste.
- c. A discharge of a material which, when discharged, becomes a hazardous waste.
- d. An immediate threat to human health, public safety, property or the environment, from the known or suspected presence of military munitions, other explosive material or an explosive device, as determined by an explosive or munitions emergency response specialist as defined in s. NR 660.10.

2. An owner or operator of a facility otherwise regulated by this chapter shall comply with all applicable requirements of subchs. C and D.

3. Any person who is covered by subd. 1. and who continues or initiates hazardous waste treatment or containment activities after the immediate response is over is subject to all applicable requirements of this chapter and chs. NR 200 to 210, 212 to 214 and 216 for those activities.

4. In the case of an explosives or munitions emergency response, if a federal, state, tribal or local official acting within the scope of that person[s responsibilities, or an explosives or munitions emergency response specialist, determines that immediate removal of the material or waste is necessary to protect human health or the environment, that official or specialist may authorize the removal of the material or waste by transporters who do not have EPA identification numbers or hazardous waste transportation licenses and without the preparation of a manifest. In the case of emergencies involving military munitions, the responding military emergency response specialist[s organizational unit shall retain records for 3 years identifying the dates of the response, the responsible persons responding, the type and description of material addressed and its disposition.

cLd A transporter storing manifested shipments of hazardous waste in containers meeting the requirements of s. NR 662.030 at a transfer facility for a period of 10 days or less.

cmd The addition of absorbent material to waste in a container as defined in s. NR 660.10d or the addition of waste to the absorbent material in a container provided that these actions occur at the time waste is first placed in the containers; and ss. NR 665.0017 c2d, 665.0171 and 665.0172 are complied with.

cnd Universal waste handlers and universal waste transporters as defined in s. NR 660.10d handling any of the following

wastes. These handlers are regulated under ch. NR 673, when handling any of the following universal wastes:

1. Batteries as described in s. NR 673.02.
2. Pesticides as described in s. NR 673.03.
3. Thermostats and mercury-containing equipment as described in s. NR 673.04.
4. Lamps as described in s. NR 673.05.

cpd Reverse distributors accumulating potentially creditable hazardous waste pharmaceuticals and evaluated hazardous waste pharmaceuticals, as defined in s. NR 666.500. Reverse distributors are subject to regulation under subch. P of ch. NR 666 in lieu of this chapter for the accumulation of potentially creditable hazardous waste pharmaceuticals and evaluated hazardous waste pharmaceuticals.

c4d EPA hazardous waste numbers F020, F021, F022, F023, F026 and F027 may not be managed at facilities regulated under this chapter unless any of the following apply:

cad The wastewater treatment sludge is generated in a surface impoundment as part of the plant[s wastewater treatment system.

cbd The waste is stored in tanks or containers.

ccd The waste is stored or treated in waste piles that meet the requirements of s. NR 664.0250 c3d as well as all other applicable requirements of subch. L.

cdd The waste is burned in incinerators that are certified pursuant to the standards and procedures in s. NR 665.0352.

ced The waste is burned in facilities that thermally treat the waste in a device other than an incinerator and that are certified pursuant to the standards and procedures in s. NR 665.0383.

c5d The requirements of this chapter apply to owners or operators of all facilities which treat, store or dispose of hazardous waste referred to in ch. NR 668, and the ch. NR 668 standards are considered material conditions or requirements of the interim license standards in this chapter.

c6d Section NR 666.205 identifies when the requirements of this chapter apply to the storage of military munitions classified as solid waste under s. NR 666.202. The treatment and disposal of hazardous waste military munitions are subject to the applicable licensing, procedural and technical standards in chs. NR 660 to 670.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c3d cnd 3. Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c3d cgd, cr. c3d cpd Register July 2020 No 775, eff. 8-1-20; correction in c2d, c3d cfd made under s. 13.92 c4d cbd 7., Stats., Register April 2021 No. 784.

NR 665.0004 Imminent danger action. Notwithstanding any other provisions of this chapter, enforcement actions may be brought pursuant to s. 291.85, Stats.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter B — General Facility Standards

NR 665.0010 Applicability. This subchapter applies to owners and operators of all hazardous waste facilities, except as s. NR 665.0001 provides otherwise.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0011 Identification number. Every facility owner or operator shall apply to the department for an EPA identification number according to the procedures in s. NR 660.07.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0012 Required notices. c1d The owner or operator of a facility that is arranging or has arranged to receive hazardous waste subject to subch. H of ch. NR 662 from a foreign source shall submit all of the following required notices:

cad In accordance with s. NR 662.084 c2d, for imports where

the competent authority of the country of export does not require the foreign exporter to submit to it a notification proposing export and obtain consent from EPA and the competent authorities for the countries of transit, the owner or operator of the facility, if acting as the importer, shall provide notification of the proposed transboundary movement in English to EPA using the allowable methods listed in s. NR 662.084 c2d cad at least 60 days before the first shipment is expected to depart the country of export. The notification may cover up to one year of shipments of wastes having similar physical and chemical characteristics, the same United Nations classification, the same hazardous waste codes and OECD waste codes, and being sent from the same foreign exporter.

cbd In accordance with s. NR 662.084 c4d cbd 15., a copy of the movement document bearing all required signatures within 3 working days of receipt of the shipment to the foreign exporter; to the competent authorities of the countries of export and transit that control the shipment as an export and transit shipment of hazardous waste respectively; and on or after the electronic import-export reporting compliance date, to EPA electronically using EPA[s waste import export tracking system, or its successor system. The original of the signed movement document shall be maintained at the facility for at least 3 years. The owner or operator of a facility may satisfy this recordkeeping requirement by retaining electronically submitted documents in the facility[s account on EPA[s waste import export tracking system, or its successor system, provided that copies are readily available for viewing and production if requested by EPA or the department. No owner or operator of a facility shall be held liable for the inability to produce the documents for inspection under this section if the owner or operator of a facility can demonstrate that the inability to produce the document is due exclusively to technical difficulty with EPA[s waste import export tracking system, or its successor system, for which the owner or operator of a facility bears no responsibility.

ccd In accordance with s. NR 662.084 c6d cdd, if the facility has physical control of the waste and the waste will be sent to an alternate facility or returned to the country of export, the owner or operator of the facility shall inform EPA of the need to return or arrange alternate management of the shipment using the allowable methods listed in s. NR 662.084 c2d cad.

cdd As specified in s. NR 662.084 c7d, the owner or operator shall do all of the following:

1. Send copies of the signed and dated confirmation of recovery or disposal, as soon as possible, but no later than 30 days after completing recovery or disposal on the waste in the shipment and no later than one calendar year following receipt of the waste, to the foreign exporter, to the competent authority of the country of export that controls the shipment as an export of hazardous waste, and on or after the electronic import-export reporting compliance date, to EPA electronically using EPA[s waste import export tracking system, or its successor system.

2. If the facility performed any of recovery operations R12, R13, or RC16, or disposal operations D13 through D15, or DC17, promptly send copies of the confirmation of recovery or disposal that it receives from the final recovery or disposal facility within one year of shipment delivery to the final recovery or disposal facility that performed one of recovery operations R1 through R11, or RC16, or one of disposal operations D1 through D12, or DC15 to DC16. Copies of the confirmation shall also be sent to the competent authority of the country of export that controls the shipment as an export of hazardous waste, and on or after the electronic import-export reporting compliance date, to EPA electronically using EPA[s waste import export tracking system,

or its successor system. The recovery and disposal operations in this subdivision are defined in s. NR 662.081.

c2d Before transferring ownership or operation of a facility during its operating life, or of a disposal facility during the long-term care period, the owner or operator shall notify the new owner or operator in writing of the requirements of this chapter and ch. NR 670. cAlso see s. NR 670.072.d

Note: An owner[s or operator[s failure to notify the new owner or operator of the requirements of this chapter in no way relieves the new owner or operator of that person[s obligation to comply with all applicable requirements.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: r. and recr. c1d Register August 2020 No. 776, eff. 9-1-20; correction in c1d cdd 2. made under s. 35.17, Stats., Register August 2020 No. 776.

NR 665.0013 General waste analysis. c1d cad Before an owner or operator treats, stores or disposes of any hazardous wastes, or nonhazardous wastes if applicable under s. NR 665.0113 c4d, the owner or operator shall obtain a detailed chemical and physical analysis of a representative sample of the wastes. At a minimum, the analysis shall contain all the information which must be known to treat, store or dispose of the waste according to this chapter and ch. NR 668.

1. Chemical and physical samples shall be analyzed by a laboratory certified or registered under ch. NR 149, except for field analyses for pH, specific conductance and temperature.

cbd The analysis may include data developed under ch. NR 661, and existing published or documented data on the hazardous waste or on waste generated from similar processes.

Note: For example, the facility[s records of analyses performed on the waste before August 1, 2006, or studies conducted on hazardous waste generated from processes similar to that which generated the waste to be managed at the facility, may be included in the data base required to comply with par. cad. The owner or operator of an off-site facility may arrange for the generator of the hazardous waste to supply part of the information required by par. cad, except as otherwise specified in s. NR 668.07c2d and c3d. If the generator does not supply the information, and the owner or operator chooses to accept a hazardous waste, the owner or operator is responsible for obtaining the information required to comply with this section.

ccd The analysis shall be repeated as necessary to ensure that it is accurate and up to date. At a minimum, the analysis shall be repeated when any of the following occurs:

1. The owner or operator is notified, or has reason to believe, that the process or operation generating the hazardous wastes or non-hazardous wastes, if applicable, under s. NR 665.0113 c4d has changed.

2. For off-site facilities, the results of the inspection required in par. cdd indicate that the hazardous waste received at the facility does not match the waste designated on the accompanying manifest or shipping paper.

cdd The owner or operator of an off-site facility shall inspect and, if necessary, analyze each hazardous waste movement received at the facility to determine whether it matches the identity of the waste specified on the accompanying manifest or shipping paper.

c2d The owner or operator shall develop and follow a written waste analysis plan which describes the procedures which the owner or operator will carry out to comply with sub. c1d. The owner or operator shall keep this plan at the facility. At a minimum, the plan shall specify all of the following:

cad The parameters for which each hazardous waste, or non-hazardous waste if applicable under s. NR 665.0113 c4d, will be analyzed and the rationale for the selection of these parameters i.e., how analysis for these parameters will provide sufficient information on the waste[s properties to comply with sub. c1dd.

cbd The test methods which will be used to test for these parameters.

ccd The sampling method which will be used to obtain a rep-

representative sample of the waste to be analyzed. A representative sample may be obtained using any of the following:

1. One of the sampling methods described in ch. NR 661 Appendix I.

2. An equivalent sampling method.

Note: See s. NR 660.21 for related discussion.

cdd The frequency with which the initial analysis of the waste will be reviewed or repeated to ensure that the analysis is accurate and up to date.

ced For off-site facilities, the waste analyses that hazardous waste generators have agreed to supply.

cfid Where applicable, the methods that will be used to meet the additional waste analysis requirements for specific waste management methods specified in ss. NR 665.0200, 665.0225, 665.0252, 665.0314, 665.0341, 665.0375, 665.0402, 665.1034 c4d, 665.1063 c4d, 665.1084 and 668.07.

cgd For surface impoundments exempted from land disposal restrictions under s. NR 668.04 c1d, the procedures and schedule for all of the following:

1. The sampling of impoundment contents.
2. The analysis of test data.
3. The annual removal of residues which are not delisted under s. NR 660.22 or which exhibit a characteristic of hazardous waste and meet any of the following criteria:

a. The residues do not meet applicable treatment standards of subch. D of ch. NR 668.

b. Where no treatment standards have been established, any of the following applies:

1d The residues are prohibited from land disposal under s. NR 668.32 or 42 USC 6924cdd.

2d The residues are prohibited from land disposal under s. NR 668.33.

chd For owners and operators seeking an exemption to the air emission standards of subch. CC according to s. NR 665.1083, any of the following:

1. If direct measurement is used for the waste determination, the procedures and schedules for waste sampling and analysis, and the results of the analysis of test data to verify the exemption.

2. If knowledge of the waste is used for the waste determination, any information prepared by the facility owner or operator or by the generator of the hazardous waste, if the waste is received from off-site, that is used as the basis for knowledge of the waste.

c3d For off-site facilities, the waste analysis plan required in sub. c2d shall also specify the procedures which will be used to inspect and, if necessary, analyze each movement of hazardous waste received at the facility to ensure that it matches the identity of the waste designated on the accompanying manifest or shipping paper. At a minimum, the plan shall describe all of the following:

cad The procedures which will be used to determine the identity of each movement of waste managed at the facility.

cbd The sampling method which will be used to obtain a representative sample of the waste to be identified, if the identification method includes sampling.

ccd The procedures that the owner or operator of an off-site landfill receiving containerized hazardous waste will use to determine whether a hazardous waste generator or treater has added a biodegradable sorbent to the waste in the container.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c2d ccd 1. made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; correction in c1d cbd made under s. 13.92 c4d cbd 7., Stats., Register April 2021 No. 784.

NR 665.0014 Security. c1d The owner or operator shall prevent the unknowing entry, and minimize the possibility for the unauthorized entry, of persons or livestock onto the active portion of the facility, unless all of the following conditions are met:

cad Physical contact with the waste, structures or equipment with the active portion of the facility will not injure unknowing or unauthorized persons or livestock which may enter the active portion of a facility.

cbd Disturbance of the waste or equipment, by the unknowing or unauthorized entry of persons or livestock onto the active portion of a facility, will not cause a violation of the requirements of this chapter.

c2d Unless exempt under sub. c1d cad and cbd, a facility shall have any of the following:

cad A 24-hour surveillance system ce.g., television monitoring or surveillance by guards or facility personnel which continuously monitors and controls entry onto the active portion of the facility.

cbd All of the following:

1. An artificial or natural barrier ce.g., a fence in good repair or a fence combined with a cliffd, which completely surrounds the active portion of the facility.

2. A means to control entry, at all times, through the gates or other entrances to the active portion of the facility ce.g., an attendant, television monitors, locked entrance or controlled roadway access to the facilityd.

Note: The requirements of this subsection are satisfied if the facility or plant within which the active portion is located itself has a surveillance system, or a barrier and a means to control entry, which complies with the requirements of par. cad or cbd.

c3d Unless exempt under sub. c1d cad and cbd, a sign with the legend, XDanger—Unauthorized Personnel Keep Out,Y shall be posted at each entrance to the active portion of a facility, and at other locations, in sufficient numbers to be seen from any approach to this active portion. The legend shall be written in English and in any other language predominant in the area surrounding the facility, and shall be legible from a distance of at least 25 feet. Existing signs with a legend other than XDanger—Unauthorized Personnel Keep OutY may be used if the legend on the sign indicates that only authorized personnel are allowed to enter the active portion, and that entry onto the active portion can be dangerous.

Note: See s. NR 665.0117c2d for discussion of security requirements at disposal facilities during the long-term care period.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0015 General inspection requirements.

c1d The owner or operator shall inspect the facility for malfunctions and deterioration, operator errors and discharges which may be causing, or may lead to, release of hazardous waste constituents to the environment or a threat to human health. The owner or operator shall conduct these inspections often enough to identify problems in time to correct them before they harm human health or the environment.

c2d cad The owner or operator shall develop and follow a written schedule for inspecting all monitoring equipment, safety and emergency equipment, security devices and operating and structural equipment csuch as dikes and sump pumpsd that are important to preventing, detecting or responding to environmental or human health hazards.

cbd The owner or operator shall keep this schedule at the facility.

ccd The schedule shall identify the types of problems ce.g., malfunctions or deteriorationd which are to be looked for during

the inspection ce.g., inoperative sump pump, leaking fitting, eroding dike, etc.d.

cdd The frequency of inspection may vary for the items on the schedule. However, the frequency should be based on the rate of deterioration of the equipment and the probability of an environmental or human health incident if the deterioration, malfunction or any operator error goes undetected between inspections. Areas subject to spills, such as loading and unloading areas, shall be inspected daily when in use. At a minimum, the inspection schedule shall include the items and frequencies called for in ss. NR 665.0174, 665.0193, 665.0195, 665.0226, 665.0260, 665.0304, 665.0347, 665.0377, 665.0403, 665.1033, 665.1052, 665.1053, 665.1058 and 665.1084 to 665.1090, where applicable.

c3d The owner or operator shall remedy any deterioration or malfunction of equipment or structures which the inspection reveals on a schedule which ensures that the problem does not lead to an environmental or human health hazard. Where a hazard is imminent or has already occurred, remedial action shall be taken immediately.

c4d The owner or operator shall record inspections in an inspection log or summary and shall keep these records for at least 3 years from the date of inspection. At a minimum, these records shall include the date and time of the inspection, the name of the inspector, a notation of the observations made and the date and nature of any repairs or other remedial actions.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0016 Personnel training. c1d cad Facility personnel shall successfully complete a program of classroom instruction or on-the-job training that teaches them to perform their duties in a way that ensures the facility[s compliance with the requirements of this chapter. The owner or operator shall ensure that this program includes all the elements described in the document required under sub. c4d ccd.

cbd This program shall be directed by a person trained in hazardous waste management procedures, and shall include instruction which teaches facility personnel hazardous waste management procedures including contingency plan implementation and relevant to the positions in which they are employed.

ccd At a minimum, the training program shall be designed to ensure that facility personnel are able to respond effectively to emergencies by familiarizing them with emergency procedures, emergency equipment and emergency systems, including, where applicable, all of the following:

1. Procedures for using, inspecting, repairing and replacing facility emergency and monitoring equipment.
2. Key parameters for automatic waste feed cut-off systems.
3. Communications or alarm systems.
4. Response to fires or explosions.
5. Response to groundwater contamination incidents.
6. Shutdown of operations.

cdd For facility personnel that receive emergency response training pursuant to occupational safety and health administration cOSHA regulations 29 CFR 1910.120 cpd c8d and cq, the facility is not required to provide separate emergency response training pursuant to this section, provided that the overall facility training meets all the requirements of this section.

c2d Facility personnel shall successfully complete the program required in sub. c1d within 6 months after August 1, 2006 or 6 months after the date of their employment or assignment to a facility, or to a new position at a facility, whichever is later. Employees hired after August 1, 2006 may not work in unsupervised positions until they have completed the training requirements of sub. c1d.

c3d Facility personnel shall take part in an annual review of the initial training required in sub. c1d.

c4d The owner or operator shall maintain all of the following documents and records at the facility:

cad The job title for each position at the facility related to hazardous waste management, and the name of the employee filling each job.

cbd A written job description for each position listed under par. cad. This description may be consistent in its degree of specificity with descriptions for other similar positions in the same company location or bargaining unit, but shall include the requisite skill, education or other qualifications, and duties of facility personnel assigned to each position.

ccd A written description of the type and amount of both introductory and continuing training that will be given to each person filling a position listed under par. cad.

cdd Records that document that the training or job experience required under subs. c1d, c2d and c3d has been given to, and completed by, facility personnel.

c5d Training records on current personnel shall be kept until closure of the facility. Training records on former employees shall be kept for at least 3 years from the date the employee last worked at the facility. Personnel training records may accompany personnel transferred within the same company.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: cr. c1d cdd Register July 2017 No. 739, eff. 8-1-17.

NR 665.0017 General requirements for ignitable, reactive or incompatible wastes. c1d The owner or operator shall take precautions to prevent accidental ignition or reaction of ignitable or reactive waste. This waste shall be separated and protected from sources of ignition or reaction including, but not limited to, open flames, smoking, cutting and welding, hot surfaces, frictional heat, sparks static, electrical or mechanical, spontaneous ignition ce.g., from heat-producing chemical reactions and radiant heat. While ignitable or reactive waste is being handled, the owner or operator shall confine smoking and open flame to specially designated locations. XNo SmokingY signs shall be conspicuously placed wherever there is a hazard from ignitable or reactive waste.

c2d Where specifically required by other sections of this chapter, the treatment, storage or disposal of ignitable or reactive waste, and the mixture or commingling of incompatible wastes, or incompatible wastes and materials, shall be conducted so that it does not do any of the following:

cad Generate extreme heat or pressure, fire or explosion or violent reaction.

cbd Produce uncontrolled toxic mists, fumes, dusts or gases in sufficient quantities to threaten human health.

ccd Produce uncontrolled flammable fumes or gases in sufficient quantities to pose a risk of fire or explosions.

cdd Damage the structural integrity of the device or facility containing the waste.

ced Through other like means threaten human health or the environment.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0018 Location standards. The placement of any hazardous waste in a salt dome, salt bed formation, underground mine or cave, wetland, or critical habitat is prohibited.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0019 Construction quality assurance program. c1d CQA PROGRAM. cad A construction quality assurance cCQAd program is required for all surface impoundment,

waste pile and landfill units that are required to comply with ss. NR 665.0221 c1d, 665.0254 and 665.0301 c1d. The program shall ensure that the constructed unit meets or exceeds all design criteria and specifications in the interim license. The program shall be developed and implemented under the direction of a CQA officer who is a registered professional engineer.

cbd The CQA program shall address all of the following physical components, where applicable:

1. Foundations.
2. Dikes.
3. Low-permeability soil liners.
4. Geomembranes cflexible membrane linersd.
5. Leachate collection and removal systems and leak detection systems.
6. Final cover systems.

c2d WRITTEN CQA PLAN. Before construction begins on a unit subject to the CQA program under sub. c1d, the owner or operator shall develop a written CQA plan. The plan shall identify steps that will be used to monitor and document the quality of materials and the condition and manner of their installation. The CQA plan shall include all of the following:

cad Identification of applicable units, and a description of how they will be constructed.

cbd Identification of key personnel in the development and implementation of the CQA plan, and CQA officer qualifications.

ccd A description of inspection and sampling activities for all unit components identified in sub. c1d cbd, including observations and tests that will be used before, during and after construction to ensure that the construction materials and the installed unit components meet the design specifications. The description shall cover sampling size and locations, frequency of testing, data evaluation procedures, acceptance and rejection criteria for construction materials, plans for implementing corrective measures and data or other information to be recorded and retained in the operating record under s. NR 665.0073.

c3d CONTENTS OF PROGRAM. cad The CQA program shall include observations, inspections, tests and measurements sufficient to ensure all of the following:

1. Structural stability and integrity of all components of the unit identified in sub. c1d cbd.
2. Proper construction of all components of the liners, leachate collection and removal system, leak detection system and final cover system, according to interim license specifications and good engineering practices, and proper installation of all components ce.g., pipesd according to design specifications.
3. Conformity of all materials used with design and other material specifications under ss. NR 664.0221, 664.0251 and 664.0301.

cbd The CQA program shall include test fills for compacted soil liners, using the same compaction methods as in the full-scale unit, to ensure that the liners are constructed to meet the hydraulic conductivity requirements of ss. NR 664.0221 c3d cad, 664.0251 c3d cad and 664.0301 c3d cad in the field. Compliance with the hydraulic conductivity requirements shall be verified by using in-situ testing on the constructed test fill. The test fill requirement is waived where data are sufficient to show that a constructed soil liner meets the hydraulic conductivity requirements of ss. NR 664.0221 c3d cad, 664.0251 c3d cad and 664.0301 c3d cad in the field.

c4d CERTIFICATION. The owner or operator of units subject to s. NR 665.0019 shall submit to the department by certified mail or hand delivery, at least 30 days prior to receiving waste, a

certification signed by the CQA officer that the CQA plan has been successfully carried out and that the unit meets the requirements of s. NR 665.0221 c1d, 665.0254 or 665.0301 c1d. The owner or operator may receive waste in the unit after 30 days from the department[s receipt of the CQA certification unless the department determines in writing that the construction is not acceptable, extends the review period for a maximum of 30 more days or seeks additional information from the owner or operator during this period. Documentation supporting the CQA officer[s certification shall be furnished to the department upon request.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0020 Schedule of compliance for corrective action. The license issued under s. 291.25 c4d, Stats., shall contain schedules of compliance for the corrective action and assurances of financial responsibility for completing the corrective action. Corrective action requirements shall be consistent with s. 291.37, Stats. Financial assurance requirements regarding corrective action requirements shall be consistent with s. 289.41 c2d to c12d, Stats.

History: CR 19-082: cr. Register August 2020 No. 776, eff. 9-1-20; correction made under s. 35.17, Stats., Register August 2020 No. 776; correction made under s. 13.92 c4d cbd 7., Stats., Register April 2021 No. 784.

Subchapter C — Preparedness and Prevention

NR 665.0030 Applicability. This subchapter applies to owners and operators of all hazardous waste facilities, except as s. NR 665.0001 provides otherwise.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0031 Maintenance and operation of facility. Facilities shall be maintained and operated to minimize the possibility of a fire, explosion or any unplanned sudden or non-sudden release of hazardous waste or hazardous waste constituents to air, soil or surface water which could threaten human health or the environment.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0032 Required equipment. All facilities shall be equipped with all of the following, unless none of the hazards posed by waste handled at the facility could require any of the following particular kinds of equipment:

c1d An internal communications or alarm system capable of providing immediate emergency instruction cvoice or signald to facility personnel.

c2d A device, such as a telephone cimmediately available at the scene of operationsd or a hand-held 2-way radio, capable of summoning emergency assistance from local police departments, fire departments or state or local emergency response teams.

c3d Portable fire extinguishers, fire control equipment including special extinguishing equipment, such as that using foam, inert gas or dry chemicalsd, spill control equipment and decontamination equipment.

c4d Water at adequate volume and pressure to supply water hose streams, foam producing equipment, automatic sprinklers or water spray systems.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0033 Testing and maintenance of equipment. All facility communications or alarm systems, fire protection equipment, spill control equipment and decontamination equipment, where required, shall be tested and maintained as necessary to assure its proper operation in time of emergency.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0034 Access to communications or alarm

system. c1d Whenever hazardous waste is being poured, mixed, spread or otherwise handled, all personnel involved in the operation shall have immediate access to an internal alarm or emergency communication device, either directly or through visual or voice contact with another employee, unless such a device is not required under s. [NR 665.0032](#).

c2d If there is ever just one employee on the premises while the facility is operating, that employee shall have immediate access to a device, such as a telephone immediately available at the scene of operation or a hand-held 2-way radio, capable of summoning external emergency assistance, unless such a device is not required under s. [NR 665.0032](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0035 Required aisle space. The owner or operator shall maintain aisle space to allow the unobstructed movement of personnel, fire protection equipment, spill control equipment and decontamination equipment to any area of facility operation in an emergency, unless aisle space is not needed for any of these purposes.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0037 Arrangements with local authorities.

c1d The owner or operator shall attempt to make all of the following arrangements, as appropriate for the type of waste handled at the facility and the potential need for the services of these organizations:

cad Arrangements to familiarize police, fire departments and emergency response teams with the layout of the facility, properties of hazardous waste handled at the facility and associated hazards, places where facility personnel would normally be working, entrances to roads inside the facility and possible evacuation routes.

cbd Where more than one police and fire department might respond to an emergency, agreements designating primary emergency authority to a specific police and a specific fire department, and agreements with any others to provide support to the primary emergency authority.

ccd Agreements with state emergency response teams, emergency response contractors and equipment suppliers.

cdd Arrangements to familiarize local hospitals with the properties of hazardous waste handled at the facility and the types of injuries or illnesses which could result from fires, explosions or releases at the facility.

c2d Where state or local authorities decline to enter into these arrangements, the owner or operator shall document the refusal in the operating record.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter D — Contingency Plan and Emergency Procedures

NR 665.0050 Applicability. This subchapter applies to owners and operators of all hazardous waste facilities, except as s. [NR 665.0001](#) provides otherwise.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0051 Purpose and implementation of contingency plan. c1d The owner or operator shall have a contingency plan for the facility. The contingency plan shall be designed to minimize hazards to human health or the environment from fires, explosions or any unplanned sudden or non-sudden release of hazardous waste or hazardous waste constituents to air, soil or surface water.

c2d The provisions of the plan shall be carried out immediately whenever there is a fire, explosion or release of hazardous

waste or hazardous waste constituents which could threaten human health or the environment.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0052 Content of contingency plan. c1d

The contingency plan shall describe the actions facility personnel must take to comply with ss. [NR 665.0051](#) and [665.0056](#) in response to fires, explosions or any unplanned sudden or non-sudden release of hazardous waste or hazardous waste constituents to air, soil or surface water at the facility.

c2d If the owner or operator has already prepared a spill prevention, control and countermeasures cSPCCd plan according to [40 CFR part 112](#), or some other emergency or contingency plan, the owner or operator need only amend that plan to incorporate hazardous waste management provisions that are sufficient to comply with the requirements of this chapter. The owner or operator may develop one contingency plan which meets all regulatory requirements. The department recommends that the plan be based on the national response team[s] cNRTd integrated contingency plan guidance. When modifications are made to non-hazardous waste provisions in an integrated contingency plan, the changes do not trigger the need for a hazardous waste license modification.

c3d The plan shall describe arrangements agreed to by local police departments, fire departments, hospitals, contractors and state and local emergency response teams to coordinate emergency services, pursuant to s. [NR 665.0037](#).

c4d The plan shall list names, addresses and phone numbers of all persons qualified to act as emergency coordinator csee s. [NR 665.0055d](#), and this list shall be kept up to date. Where more than one person is listed, one shall be named as primary emergency coordinator and others shall be listed in the order in which they will assume responsibility as alternates.

c5d The plan shall include a list of all emergency equipment at the facility csuch as fire extinguishing systems, spill control equipment, communications and alarm systems cinternal and externald and decontamination equipmentd, where this equipment is required. This list shall be kept up to date. In addition, the plan shall include the location and a physical description of each item on the list, and a brief outline of its capabilities.

c6d The plan shall include an evacuation plan for facility personnel where there is a possibility that evacuation could be necessary. This plan shall describe the signal or signals to be used to begin evacuation, evacuation routes and alternate evacuation routes cin cases where the primary routes could be blocked by releases of hazardous waste or firesd.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c2d Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c2d Register August 2020 No. 776, eff. 9-1-20.

NR 665.0053 Copies of contingency plan. A copy of the contingency plan and all revisions to the plan shall be:

c1d Maintained at the facility.

c2d Submitted to all local police departments, fire departments, hospitals and state and local emergency response teams that may be called upon to provide emergency services.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0054 Amendment of contingency plan. The contingency plan shall be reviewed, and immediately amended, if necessary, whenever any of the following occurs:

c1d Applicable rules or the facility interim license are revised.

c2d The plan fails in an emergency.

c3d The facility changes—in its design, construction, opera-

tion, maintenance or other circumstances—in a way that materially increases the potential for fires, explosions or releases of hazardous waste or hazardous waste constituents, or changes the response necessary in an emergency.

c4d The list of emergency coordinators changes.

c5d The list of emergency equipment changes.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0055 Emergency coordinator. At all times, there shall be at least one employee either on the facility premises or on call *ci.e.*, available to respond to an emergency by reaching the facility within a short period of time with the responsibility for coordinating all emergency response measures. This emergency coordinator shall be thoroughly familiar with all aspects of the facility's contingency plan, all operations and activities at the facility, the location and characteristics of waste handled, the location of all records within the facility and the facility layout. In addition, this person shall have the authority to commit the resources needed to carry out the contingency plan.

Note: The emergency coordinator's responsibilities are more fully spelled out in s. NR 665.0056. Applicable responsibilities for the emergency coordinator vary, depending on factors such as type and variety of wastes handled by the facility, and type and complexity of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0056 Emergency procedures. c1d Whenever there is an imminent or actual emergency situation, the emergency coordinator or a designee when the emergency coordinator is on call shall immediately do all of the following:

cad Activate internal facility alarms or communication systems, where applicable, to notify all facility personnel.

cbd Notify appropriate state or local agencies with designated response roles if their help is needed.

c2d Whenever there is a release, fire or explosion, the emergency coordinator shall immediately identify the character, exact source, amount and areal extent of any released materials. The emergency coordinator may do this by observation or review of facility records or manifests and, if necessary, by chemical analysis.

c3d Concurrently, the emergency coordinator shall assess possible hazards to human health or the environment that may result from the release, fire or explosion. This assessment shall consider both direct and indirect effects of the release, fire or explosion *ce.g.*, the effects of any toxic, irritating or asphyxiating gases that are generated, or the effects of any hazardous surface water run-off from water or chemical agents used to control fire and heat-induced explosions.

c4d If the emergency coordinator determines that the facility has had a release, fire or explosion which could threaten human health, or the environment, outside the facility, that person shall report the findings according to all of the following:

cad If the emergency coordinator's assessment indicates that evacuation of local areas may be advisable, the emergency coordinator shall immediately notify appropriate local authorities. The emergency coordinator shall be available to help appropriate officials decide whether local areas should be evacuated.

cbd The emergency coordinator shall immediately notify either the government official designated as the on-scene coordinator for that geographical area in the applicable regional contingency plan under 40 CFR part 300d, or the national response center using its 24-hour toll free number 800{424-8802d and the division of emergency government using its 24-hour toll free number 800{943-0003d. The report shall include all of the following:

1. Name and telephone number of reporter.
2. Name and address of facility.

3. Time and type of incident *ce.g.*, release, fire.

4. Name and quantity of materials involved, to the extent known.

5. The extent of injuries, if any.

6. The possible hazards to human health or the environment, outside the facility.

c5d During an emergency, the emergency coordinator shall take all reasonable measures necessary to ensure that fires, explosions and releases do not occur, recur or spread to other hazardous waste at the facility. These measures shall include, where applicable, stopping processes and operations, collecting and containing released waste and removing or isolating containers.

c6d If the facility stops operations in response to a fire, explosion or release, the emergency coordinator shall monitor for leaks, pressure buildup, gas generation or ruptures in valves, pipes or other equipment, wherever this is appropriate.

c7d Immediately after an emergency, the emergency coordinator shall provide for treating, storing or disposing of recovered waste, contaminated soil or surface water or any other material that results from a release, fire or explosion at the facility.

Note: Unless the owner or operator can demonstrate, according to s. NR 661.0003 c3d or c4d, that the recovered material is not a hazardous waste, the owner or operator becomes a generator of hazardous waste and shall manage it according to all applicable requirements of chs. NR 662 and 663 and this chapter.

c8d The emergency coordinator shall ensure all of the following, in the affected areas of the facility:

cad No waste that may be incompatible with the released material is treated, stored or disposed of until cleanup procedures are completed.

cbd All emergency equipment listed in the contingency plan is cleaned and fit for its intended use before operations are resumed.

c9d The owner or operator shall note in the operating record the time, date and details of any incident that requires implementing the contingency plan. Within 15 days after the incident, the owner or operator shall submit a written report on the incident to the department. The report shall include all of the following:

cad Name, address and telephone number of the owner or operator.

cbd Name, address and telephone number of the facility.

ccd Date, time and type of incident *ce.g.*, fire, explosion.

cdd Name and quantity of materials involved.

ced The extent of injuries, if any.

cfid An assessment of actual or potential hazards to human health or the environment, where this is applicable.

cgd Estimated quantity and disposition of recovered material that resulted from the incident.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: r. c9d, renum. c10d to c9d Register July 2017 No. 739, eff. 8-1-17.

Subchapter E — Manifest System, Recordkeeping and Reporting

NR 665.0070 Applicability. This subchapter applies to owners and operators of both on-site and off-site facilities, except as s. NR 665.0001 provides otherwise. Sections NR 665.0071, 665.0072 and 665.0076 do not apply to owners and operators of on-site facilities that do not receive any hazardous waste from off-site sources, and to owners and operators of off-site facilities with respect to waste military munitions exempted from manifest requirements under s. NR 666.203 c1d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0071 Use of manifest system. c1d cad If a

facility receives hazardous waste accompanied by a manifest, the owner or operator, or an agent, shall sign and date each copy of the manifest as indicated in par. [cbd](#) to certify that the hazardous waste covered by the manifest was received, that the hazardous waste was received except as noted in the discrepancy space of the manifest, or that the hazardous waste was rejected as noted in the manifest discrepancy space.

[cbd](#) If a facility receives a hazardous waste shipment accompanied by a manifest, the owner, operator or an agent shall do all of the following:

1. Sign and date each copy of the manifest.
2. Note any discrepancies, as defined in s. [NR 665.0072 c1d](#), on each copy of the manifest.
3. Immediately give the transporter at least one copy of the manifest.
4. Within 30 days of delivery, send a copy of page 2 of the manifest to the generator.
5. Submit paper manifests according to all the following requirements:
 - a. Beginning on June 30, 2018, send page 1 of any paper manifest and any paper continuation sheet to the e-manifest system for purposes of data entry and processing, or in lieu of submitting the paper copy to EPA, the owner or operator may transmit to the EPA system an image file of page 1 of the manifest and any continuation sheet, or both a data file and image file corresponding to page 1 of the manifest and any continuation sheet, within 30 days of the date of delivery. Submissions of copies to the e-manifest system shall be made at the mailing address or electronic mail submission address specified at the e-manifest program website[s] directory of services. Beginning on June 30, 2021, EPA will not accept mailed paper manifests from facilities for processing in e-manifest.
 - b. Beginning on June 30, 2021, the requirement to submit page 1 of the paper manifest and any paper continuation sheet to the e-manifest system for purposes of data entry and processing may be met by the owner or operator only by transmitting to the EPA system an image file of page 1 of the manifest and any continuation sheet, or by transmitting to the EPA system both a data file and the image file corresponding to page 1 of the manifest and any continuation sheet, within 30 days of the date of delivery. Submissions of copies to the e-manifest system shall be made to the electronic mail submission address specified at the e-manifest program website[s] directory of services.
6. Retain at the facility a copy of each manifest for at least 3 years from the date of delivery.

[ccd](#) The owner or operator of a facility that receives hazardous waste subject to subch. [H of ch. NR 662](#) from a foreign source shall do all of the following:

1. Additionally list the relevant consent number from consent documentation supplied by EPA to the facility for each waste listed on the manifest, matched to the relevant list number for the waste from block 9b. If additional space is needed, the owner or operator should use a continuation sheet, EPA Form 8700-22A.
2. Send a copy of the manifest within 30 days of delivery to EPA using the addresses listed in s. [NR 662.082 c5d](#) until the facility can submit such a copy to the e-manifest system under par. [cbd 5](#).

[c2d](#) If a facility receives, from a rail or water bulk shipment transporter, hazardous waste which is accompanied by a shipping paper containing all the information required on the manifest excluding the EPA identification numbers, generator[s] certification and signature[s], the owner or operator, or an agent, shall do all of the following:

[cad](#) Sign and date each copy of the manifest or shipping paper if the manifest has not been received to certify that the hazardous waste covered by the manifest or shipping paper was received.

[cbd](#) Note any significant discrepancies as defined in s. [NR 665.0072 c1d](#) in the manifest or shipping paper if the manifest has not been received on each copy of the manifest or shipping paper.

Note: The department does not intend that the owner or operator of a facility whose procedures under s. [NR 665.0013c3d](#) include waste analysis shall perform that analysis before signing the shipping paper and giving it to the transporter. Section [NR 665.0072c2d](#), however, requires reporting an unreconciled discrepancy discovered during later analysis.

[ccd](#) Immediately give the rail or water bulk shipment transporter at least one copy of the manifest or shipping paper if the manifest has not been received.

[cdd](#) Within 30 days after the delivery, send a copy of the signed and dated manifest or a signed and dated copy of the shipping paper if the manifest has not been received within 30 days after delivery to the generator and, within 45 days, send one copy of the manifest to the department in an electronic format specified by the department.

Note: Section [NR 662.023 c3d](#) requires the generator to send 3 copies of the manifest to the facility when hazardous waste is sent by rail or water bulk shipment.

[ced](#) Retain at the facility a copy of the manifest and shipping paper if signed in lieu of the manifest at the time of delivery for at least 3 years from the date of delivery.

[cfd](#) Pay a manifest fee for each manifest submitted, as designated in ch. [NR 670 Appendix II](#). The department will bill each facility annually for accumulated manifest review fees.

[c3d](#) Whenever a shipment of hazardous waste is initiated from a facility, the owner or operator of that facility shall comply with the requirements under ch. [NR 662](#). The provisions under ss. [NR 662.015](#), [662.016](#), and [662.017](#) are applicable to the on-site accumulation of hazardous wastes by generators. Therefore, the provisions under ss. [NR 662.015](#), [662.016](#), and [662.017](#) only apply to owners or operators who are shipping hazardous waste which they generated at that facility or operating as a large quantity generator consolidating hazardous waste from very small quantity generators under s. [NR 662.017 c6d](#).

[c4d](#) In accordance with s. [NR 662.084 c4d cbd 15.](#), within 3 working days of the receipt of a shipment subject to subch. [H of ch. NR 662](#), the owner or operator of a facility shall provide a copy of the movement document bearing all required signatures to the foreign exporter; to the competent authorities of the countries of export and transit that control the shipment as an export and transit of hazardous waste respectively; and on or after the electronic import-export reporting compliance date, to EPA electronically using EPA[s] waste import export tracking system, or its successor system. The original copy of the movement document shall be maintained at the facility for at least 3 years from the date of signature. The owner or operator of a facility may satisfy this recordkeeping requirement by retaining electronically submitted documents in the facility[s] account on EPA[s] waste import export tracking system, or its successor system, provided that copies are readily available for viewing and production if requested by any EPA or department. No owner or operator of a facility shall be held liable for the inability to produce the documents for inspection under this section if the owner or operator of a facility can demonstrate that the inability to produce the document is due exclusively to technical difficulty with EPA[s] waste import export tracking system, or its successor system, for which the owner or operator of a facility bears no responsibility.

[c5d](#) The owner or operator of a facility shall determine whether the consignment state for a shipment regulates any addi-

tional wastes beyond those regulated federally as hazardous wastes under its state hazardous waste program. The owner or operator of a facility shall also determine whether the consignee state or generator state requires the facility to submit any copies of the manifest to these states.

c6d An electronic manifest that is obtained, completed, and transmitted in accordance with s. NR 662.020 c1d ccd, and used in accordance with this paragraph in lieu of the paper manifest form is the legal equivalent of paper manifest forms bearing handwritten signatures, and satisfies for all purposes any requirement in these regulations to obtain, complete, sign, provide, use, or retain a manifest. Legal equivalence to paper manifests include the following:

cad Any requirement for the owner or operator of a facility to sign a manifest or manifest certification by hand, or to obtain a handwritten signature, is satisfied by signing with or obtaining a valid and enforceable electronic signature within the meaning specified in 40 CFR 262.25 cad and s. NR 662.025 c1d.

cbd Any requirement to give, provide, send, forward, or to return to another person a copy of the manifest is satisfied when a copy of an electronic manifest is transmitted to the other person.

ccd Any requirement for a manifest to accompany a hazardous waste shipment is satisfied when a copy of an electronic manifest is accessible during transportation and forwarded to the person or persons who are scheduled to receive delivery of the waste shipment.

cdd Any requirement for an owner or operator to keep or retain a copy of each manifest is satisfied by the retention of the facility's electronic manifest copies in its account on the e-manifest system, provided that the copies are readily available for viewing and production if requested by the department.

ced No owner or operator may be held liable for the inability to produce an electronic manifest for inspection under this section if the owner or operator can demonstrate that the inability to produce the electronic manifest is due exclusively to a technical difficulty with EPA's electronic manifest system for which the owner or operator bears no responsibility.

c7d An owner or operator may participate in the electronic manifest system either by accessing the electronic manifest system from the owner's or operator's electronic equipment, or by accessing the electronic manifest system from portable equipment brought to the owner's or operator's site by the transporter who delivers the waste shipment to the facility.

c8d If a facility receives hazardous waste that is accompanied by a paper replacement manifest for a manifest that was originated electronically, all of the following procedures apply to the delivery of the hazardous waste by the final transporter:

cad Upon delivery of the hazardous waste to the designated facility, the owner or operator shall sign and date each copy of the paper replacement manifest by hand in Item 20, designated facility certification of receipt, and note any discrepancies in Item 18, discrepancy indication space, of the paper replacement manifest.

cbd The owner or operator of the facility shall return one copy of the paper replacement manifest to the final transporter.

ccd Within 30 days of delivery of the waste to the designated facility, the owner or operator of the facility shall send one signed and dated copy of the paper replacement manifest to the generator, and send an additional signed and dated copy of the paper replacement manifest to the electronic manifest system.

cdd The owner or operator of the facility shall retain at the facility one copy of the paper replacement manifest for at least 3 years from the date of delivery.

c9d If an owner or operator using an electronic manifest

signs the manifest electronically using an electronic signature method which is undergoing pilot or demonstration tests aimed at demonstrating the practicality or legal dependability of the signature method, then the owner or operator shall also sign with an ink signature the facility's certification of receipt or discrepancies on the printed copy of the manifest provided by the transporter. Upon executing its ink signature on the printed copy, the owner or operator shall retain the original copy among its records for at least 3 years from the date of delivery of the waste.

c10d cad As prescribed in 40 CFR 265.1311, and determined in 40 CFR 265.1312, an owner or operator who is a user of the electronic manifest system shall be assessed a user fee by EPA for the submission and processing of each electronic and paper manifest. EPA shall update the schedule of user fees and publish them to the user community, as provided in 40 CFR 265.1313.

cbd An owner or operator subject to user fees under this section shall make user fee payments in accordance with the requirements of 40 CFR 265.1314, subject to the informal fee dispute resolution process of 40 CFR 265.1316, and subject to the sanctions for delinquent payments under 40 CFR 265.1315.

c11d Electronic manifest signatures shall meet the criteria described in 40 CFR 262.25 and s. NR 662.025.

c12d After facilities have certified to the receipt of hazardous wastes by signing Item 20 of the manifest, any post-receipt data corrections may be submitted at any time by any interested person, for example the waste handler, shown on the manifest. The person submitting the corrections shall do all of the following:

cad Interested persons must make all corrections to manifest data by electronic submission, either by directly entering corrected data to the web-based service provided in e-manifest for the corrections, or by an upload of a data file containing data corrections relating to one or more previously submitted manifests.

cbd Each correction submission shall include all of the following information:

1. The Manifest Tracking Number and date of receipt by the facility of the original manifest for which data are being corrected.
2. The item numbers of the original manifest that is the subject of the submitted corrections.
3. For each item number with corrected data, the data previously entered and the corresponding data as corrected by the correction submission.

ccd Each correction submission shall include a statement that the person submitting the corrections certifies that to the best of his or her knowledge or belief, the corrections that are included in the submission will cause the information reported about the previously received hazardous wastes to be true, accurate, and complete in accordance with all of the following:

1. The certification statement must be executed with a valid electronic signature.
2. A batch upload of data corrections may be submitted under one certification statement.

cdd Upon receipt by the system of any correction submission, other interested persons shown on the manifest will be provided electronic notice of the submitter's corrections.

ced Other interested persons shown on the manifest may respond to the submitter's corrections with comments to the submitter, or by submitting another correction to the system, certified by the respondent as specified in par. ccd, and with notice of the corrections to other interested persons shown on the manifest.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 06-102: am. Register March 2007 No. 615, eff. 4-1-07; corrections in c1d cbd 6., c2d cfd made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; CR 19-082: am. c1d

cbd 1., 4., r. and recr. c1d cbd 5., 6., ced, c3d and c4d, cr. c6d to c12d Register August 2020 No. 776, eff. 9-1-20; correction in c1d cbd 6., c3d, c6d cintro.d, c9d, c12d cbd 1. made under s. 35.17, Stats., Register August 2020 No. 776.

NR 665.0072 Manifest discrepancies. c1d Manifest discrepancies are:

cad Significant differences, as defined by sub. c2d, between the quantity or type of hazardous waste designated on the manifest or shipping paper, and the quantity or type of hazardous waste a facility actually receives.

cbd Rejected wastes, which may be a full or partial shipment of hazardous waste that the treatment, storage or disposal facility cannot accept.

ccd Container residues, which are residues that exceed the quantity limits for empty containers set forth in s. NR 661.0007 c2d.

c2d Significant discrepancies in quantity are, for bulk waste, variations greater than 10% in weight, and for batch waste, any variation in piece count, such as a discrepancy of one drum in a truckload. Significant discrepancies in type are obvious differences which can be discovered by inspection or waste analysis, such as waste solvent substituted for waste acid or toxic constituents not reported on the manifest or shipping paper.

c3d Upon discovering a significant discrepancy, the owner or operator shall attempt to reconcile the discrepancy with the waste generator or transporter ce.g., with telephone conversationsd. If the discrepancy is not resolved within 15 days after receiving the waste, the owner or operator shall immediately submit to the department a letter describing the discrepancy and attempts to reconcile it, and a copy of the manifest or shipping paper at issue.

c4d cad Upon rejecting waste or identifying a container residue that exceeds the quantity limits for empty containers set forth in s. NR 661.0007 c2d, the facility owner or operator shall consult with the generator prior to forwarding the waste to another facility that can manage the waste. If it is impossible to locate an alternative facility that can receive the waste, the facility owner or operator may return the rejected waste or residue to the generator. The facility owner or operator shall send the waste to the alternative facility or to the generator within 60 days of the rejection or the container residue identification.

cbd While the facility owner or operator is making arrangements for forwarding rejected wastes or residues to another facility under this section, it shall ensure that either the delivering transporter retains custody of the waste, or the facility owner or operator shall provide for secure, temporary custody of the waste, pending delivery of the waste to the first transporter designated on the manifest prepared under sub. c5d or c6d.

c5d Except as provided in par. cgd, for full or partial load rejections and residues that are to be sent off-site to an alternate facility, the facility owner or operator shall prepare a new manifest in accordance with s. NR 662.020 c1d and the following instructions:

cad Write the generator[s] EPA ID number in Item 1 of the new manifest. Write the generator[s] name and mailing address in Item 5 of the new manifest. If the mailing address is different from the generator[s] site address, then write the generator[s] site address in the designated space for Item 5.

cbd Write the name of the alternate designated facility and the facility[s] EPA ID number in the designated facility block cItem 8d of the new manifest.

ccd Copy the manifest tracking number found in Item 4 of the old manifest to the special handling and additional information block of the new manifest, and indicate that the shipment is a residue or rejected waste from the previous shipment.

cdd Copy the manifest tracking number found in Item 4 of the new manifest to the manifest reference number line in the discrepancy block of the old manifest cItem 18ad.

ced Write the DOT description for the rejected load or the residue in Item 9 cU.S. DOT descriptiond of the new manifest and write the container types, quantity and volume of waste.

cfđ Sign the generator[s] or offeror[s] certification to certify, as the offeror of the shipment, that the waste has been properly packaged, marked and labeled and is in proper condition for transportation, and mail a signed copy of the manifest to the generator identified in Item 5 of the new manifest.

cgd For full load rejections that are made while the transporter remains present at the facility, the facility owner or operator may forward the rejected shipment to the alternate facility by completing Item 18b of the original manifest and supplying the information on the next destination facility in the alternate facility space. The facility owner or operator shall retain a copy of this manifest for its records, and then give the remaining copies of the manifest to the transporter to accompany the shipment. If the original manifest is not used, then the facility owner or operator shall use a new manifest and comply with pars. cad to cfd.

c6d Except as provided in par. cgd, for rejected wastes and residues that must be sent back to the generator, the facility owner or operator shall prepare a new manifest in accordance with s. NR 662.020 c1d and the following instructions:

cad Write the facility[s] EPA ID number in Item 1 of the new manifest. Write the facility[s] name and mailing address in Item 5 of the new manifest. If the mailing address is different from the facility[s] site address, then write the facility[s] site address in the designated space for Item 5 of the new manifest.

cbd Write the name of the initial generator and the generator[s] EPA ID number in the designated facility block cItem 8d of the new manifest.

ccd Copy the manifest tracking number found in Item 4 of the old manifest to the special handling and additional information block of the new manifest, and indicate that the shipment is a residue or rejected waste from the previous shipment.

cdd Copy the manifest tracking number found in Item 4 of the new manifest to the manifest reference number line in the discrepancy block of the old manifest cItem 18ad.

ced Write the DOT description for the rejected load or the residue in Item 9 cU.S. DOT Descriptiond of the new manifest and write the container types, quantity and volume of waste.

cfđ Sign the generator[s] or offeror[s] certification to certify, as offeror of the shipment, that the waste has been properly packaged, marked and labeled and is in proper condition for transportation.

cgd For full load rejections that are made while the transporter remains at the facility, the facility owner or operator may return the shipment to the generator with the original manifest by completing Item 18a and 18b of the manifest and supplying the generator[s] information in the alternate facility space. The facility owner or operator shall retain a copy for its records and then give the remaining copies of the manifest to the transporter to accompany the shipment. If the original manifest is not used, then the facility owner or operator shall use a new manifest and comply with pars. cad to cfd and chđ.

chđ For full or partial load rejections and container residues contained in non-empty containers that are returned to the generator, the facility shall also comply with the exception reporting requirements specified in s. NR 662.042 c1d.

c7d If a facility owner or operator rejects a waste or identifies a container residue that exceeds the quantity limits for empty

containers set forth in s. NR 661.0007 c2d after it has signed, dated and returned a copy of the manifest to the delivering transporter or to the generator, the facility owner or operator shall amend its copy of the manifest to indicate the rejected wastes or residues in the discrepancy space of the amended manifest. The facility owner or operator shall also copy the manifest tracking number from Item 4 of the new manifest to the discrepancy space of the amended manifest, and shall re-sign and date the manifest to certify to the information as amended. The facility owner or operator shall retain the amended manifest for at least 3 years from the date of amendment and shall, within 30 days, send a copy of the amended manifest to the transporter and generator that received copies prior to their being amended. Within 45 days, the facility owner or operator shall also send one copy of the amended manifest to the department in an electronic format specified by the department.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 06-102: am. Register March 2007 No. 615, eff. 4-1-07; CR 16-007: am. c6d cad Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c1d ccd, c4d cad, c5d cfd, c6d cad, cgd, cr. c6d chd, am. c7d Register August 2020 No. 776, eff. 9-1-20; correction in c6d chd made under s. 13.92 c4d cbd 7., Stats., Register April 2021 No. 784.

NR 665.0073 Operating record. c1d The owner or operator shall keep a written operating record at the facility.

c2d All of the following information shall be recorded, as it becomes available, and maintained in the operating record for 3 years unless noted as follows:

cad A description and the quantity of each hazardous waste received, and the methods and dates of its treatment, storage, or disposal at the facility as required by ch. NR 665 Appendix I. This information shall be maintained in the operating record until closure of the facility.

cbd The location of each hazardous waste within the facility and the quantity at each location. For disposal facilities, the location and quantity of each hazardous waste shall be recorded on a map or diagram of each cell or disposal area. For all facilities, this information shall include cross-references to specific manifest document numbers, if the waste was accompanied by a manifest. This information shall be maintained in the operating record until closure of the facility.

Note: See s. NR 665.0119 for related requirements.

ccd Records and results of waste analysis, waste determinations and trial tests performed as specified in ss. NR 665.0013, 665.0200, 665.0225, 665.0252, 665.0314, 665.0341, 665.0375, 665.0402, 665.1034, 665.1063, 665.1084, 668.04 c1d and 668.07.

cdd Summary reports and details of all incidents that require implementing the contingency plan as specified in s. NR 665.0056 c9d.

ced Records and results of inspections as required by s. NR 665.0015 c4d cexcept these data need be kept only 3 yearsd.

cfid Maintain in the operating record for 3 years the monitoring, testing or analytical data, and corrective actions where required by subch. F and by ss. NR 665.0019, 665.0094, 665.0191, 665.0193, 665.0195, 665.0224, 665.0226, 665.0255, 665.0260, 665.0302, 665.0304, 665.0347, 665.0377, 665.1034 c3d to c6d, 665.1035, 665.1063 c4d to c9d, 665.1064, and 665.1083 to 665.1090. Records and results pertaining to groundwater monitoring and cleanup shall be maintained in the operating record until closure of the facility.

Note: As required by s. NR 665.0094, monitoring data at disposal facilities shall be kept throughout the long-term care period.

cgd All closure cost estimates under s. NR 665.0142 and, for disposal facilities, all long-term care cost estimates under s. NR 665.0144 shall be maintained in the operating record until closure of the facility.

chd Records of the quantities and date of placement for each shipment of hazardous waste placed in land disposal units under an extension to the effective date of any land disposal restriction granted pursuant to s. NR 668.05, monitoring data required pursuant to a petition under s. NR 668.06 and the applicable notice required by a generator under s. NR 668.07 c1d. All of this information shall be maintained in the operating record until closure of the facility.

cid For an off-site treatment facility, a copy of the notice required by the generator or the owner or operator under s. NR 668.07.

cjd For an on-site treatment facility, the information contained in the notice cexcept the manifest numberd required by the generator or the owner or operator under s. NR 668.07.

ckd For an off-site land disposal facility, a copy of the notice required by the generator or the owner or operator of a treatment facility under s. NR 668.07.

cLd For an on-site land disposal facility, the information contained in the notice cexcept the manifest numberd required by the generator or the owner or operator of a treatment facility under s. NR 668.07.

cmd For an off-site storage facility, a copy of the notice required by the generator or the owner or operator under s. NR 668.07.

cnd For an on-site storage facility, the information contained in the notice cexcept the manifest numberd required by the generator or the owner or operator of a treatment facility under s. NR 668.07.

cod Monitoring, testing, or analytical data, and corrective action where required by ss. NR 665.0090 and 665.0093 c4d cbd and ced, and the certification as required by s. NR 665.0196 c6d shall be maintained in the operating record until closure of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c2d cad made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; CR 16-007: am. c2d cintro.d, cad, cbd, cfd to chd, cr. c2d cod Register July 2017 No. 739, eff. 8-1-17; correction in c2d cdd, cfd made under s. 13.92 c4d cbd 7., Stats., Register July 2017 No. 739.

NR 665.0074 Availability, retention and disposition of records. c1d All records, including plans, required under this chapter shall be furnished upon request, and made available at all reasonable times for inspection, by any officer, employee or representative of the department.

c2d The retention period for all records required under this chapter is extended automatically during the course of any unresolved enforcement action regarding the facility or as requested by the department.

c3d A copy of records of waste disposal locations and quantities under s. NR 665.0073 c2d cbd shall be submitted to the department and local land authority upon closure of the facility csee s. NR 665.0119d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0075 Annual report. The owner or operator shall prepare and submit a single copy of an annual report to the department by March 1 of each year. The annual report shall be submitted on department forms, shall cover facility activities during the previous calendar year and shall, at a minimum, include all of the following information:

c1d The EPA identification number, name and address of the facility.

c2d The calendar year covered by the report.

c3d For off-site facilities, the EPA identification number of each hazardous waste generator from which the facility received a

hazardous waste during the year. For imported shipments, the report shall give the name and address of the foreign generator.

c4d A description and the quantity of each hazardous waste the facility received during the year. For off-site facilities, this information shall be listed by EPA identification number of each generator.

c5d The method of treatment, storage or disposal for each hazardous waste.

c6d Monitoring data under s. NR 665.0094 c1d cbd 2. and 3. and c2d cbd, where required.

c7d The most recent closure cost estimate under s. NR 665.0142, and, for disposal facilities, the most recent long-term care cost estimate under s. NR 665.0144.

c8d For generators who treat, store or dispose of hazardous waste on-site, a description of the efforts undertaken during the year to reduce the volume and toxicity of waste generated.

c9d For generators who treat, store or dispose of hazardous waste on-site, a description of the changes in volume and toxicity of waste actually achieved during the year in comparison to previous years to the extent the information is available for the years prior to 1984.

c10d The certification signed by the owner or operator of the facility or an authorized representative.

Note: Information on annual reporting is available at: <http://dnr.wi.gov/topic/Waste/AnnualReport.html>.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0076 Unmanifested waste report. c1d If a facility accepts for treatment, storage or disposal any hazardous waste from an off-site source without an accompanying manifest, or without an accompanying shipping paper as described in s. NR 663.20 c5d, and if the waste is not excluded from the manifest requirement by chs. NR 660 to 679, then the owner or operator shall prepare and submit a report to the department within 15 days after receiving the waste. The unmanifested waste report shall contain all of the following information:

cad The EPA identification number, name and address of the facility.

cbd The date the facility received the waste.

ccd The EPA identification number, name and address of the generator and the transporter, if available.

cdd A description and the quantity of each unmanifested hazardous waste the facility received.

ced The method of treatment, storage or disposal for each hazardous waste.

cfid The certification signed by the owner or operator of the facility or an authorized representative.

cgd A brief explanation of why the waste was unmanifested, if known.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 06-102: am. Register March 2007 No. 615, eff. 4-1-07; corrections in c1d cintro.d made under s. 13.93 c2md cbd 7., Stats., Register March 2007 No. 615.

NR 665.0077 Additional reports. In addition to submitting the annual and unmanifested waste reports described in ss. NR 665.0075 and 665.0076, the owner or operator shall also report all of the following to the department:

c1d Releases, fires and explosions as specified in s. NR 665.0056 c9d.

c2d Groundwater contamination and monitoring data as specified in ss. NR 665.0093 and 665.0094.

c3d Facility closure as specified in s. NR 665.0115.

c4d Other information as required by subchs. AA, BB and CC.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c1d made under s. 13.92 c4d cbd 7., Stats., Register July 2017 No 739.

Subchapter F — Groundwater Monitoring

NR 665.0090 Applicability. c1d By August 1, 1982, the owner or operator of a surface impoundment or landfill facility which is used to manage hazardous waste shall implement a groundwater monitoring program capable of determining the facility[s impact on the quality of groundwater in the uppermost aquifer underlying the facility, except as s. NR 665.0001 and sub. c3d provide otherwise.

c2d Except as subs. c3d and c4d provide otherwise, the owner or operator shall install, operate and maintain a groundwater monitoring system which meets the requirements of s. NR 665.0091 and chs. NR 140 and 141, and shall comply with ss. NR 665.0092 to 665.0094. This groundwater monitoring program shall be carried out during the active life of the facility, and for disposal facilities, during the long-term care period as well.

c3d All or part of the groundwater monitoring requirements of this subchapter may be waived if the owner or operator can demonstrate that there is a low potential for migration of hazardous waste or hazardous waste constituents from the facility via the uppermost aquifer to water supply wells cdomestic, industrial or agriculturald or to surface water. This demonstration shall be in writing, and shall be kept at the facility. This demonstration shall be certified by a qualified geologist or geotechnical engineer and shall establish all of the following:

cad The potential for migration of hazardous waste or hazardous waste constituents from the facility to the uppermost aquifer, by an evaluation of all of the following:

1. A water balance of precipitation, evapotranspiration, runoff and infiltration.

2. Unsaturated zone characteristics c.i.e., geologic materials, physical properties and depth to groundwater.

cbd The potential for hazardous waste or hazardous waste constituents which enter the uppermost aquifer to migrate to a water supply well or surface water, by an evaluation of all of the following:

1. Saturated zone characteristics c.i.e., geologic materials, physical properties and rate of groundwater flow.

2. The proximity of the facility to water supply wells or surface water.

c4d If an owner or operator assumes cor knowsd that groundwater monitoring of indicator parameters in accordance with ss. NR 665.0091 and 665.0092 would show statistically significant increases cor decreases in the case of pHd when evaluated under s. NR 665.0093 c2d, the owner or operator may install, operate and maintain an alternate groundwater monitoring system cother than the one described in ss. NR 665.0091 and 665.0092d. If the owner or operator decides to use an alternate groundwater monitoring system, the owner or operator shall do all of the following:

cad Within one year after August 1, 2017, submit to the department a specific plan, certified by a qualified geologist or geotechnical engineer, which satisfies the requirements of s. NR 665.0093 c4d ccd, for an alternate groundwater monitoring system. This plan shall be placed in the facility[s operating record and be maintained until closure of the facility.

cbd By August 1, 1982, initiate the determinations specified in s. NR 665.0093 c4d cdd.

ccd Prepare and submit a written report in accordance with s.

NR 665.0093 c4d ced, and place it in the facility[s] operating record and maintain it until closure of the facility.

cdd Continue to make the determinations specified in s. NR 665.0093 c4d cdd on a quarterly basis until final closure of the facility.

ced Comply with the recordkeeping and reporting requirements in s. NR 665.0094 c2d.

c5d The groundwater monitoring requirements of this subchapter may be waived with respect to any surface impoundment that is used to neutralize wastes which are hazardous solely because they exhibit the corrosivity characteristic under s. NR 661.0022 or are listed as hazardous wastes in subch. D of ch. NR 661 only for this reason, and contains no other hazardous wastes, if the owner or operator can demonstrate that there is no potential for migration of hazardous wastes from the impoundment. The demonstration shall establish, based upon consideration of the characteristics of the wastes and the impoundment, that the corrosive wastes will be neutralized to the extent that they no longer meet the corrosivity characteristic before they can migrate out of the impoundment. The demonstration shall be in writing and shall be certified by a qualified professional.

c6d The department may replace all or part of the requirements of this subchapter applying to a regulated unit as defined in s. NR 664.0090d, with alternative requirements developed for groundwater monitoring set out in an approved closure or long-term care plan or in an enforceable document as defined in s. NR 670.001 c3d cgd, where the department determines that all of the following apply:

cad A regulated unit is situated among solid waste management units or areas of concern, a release has occurred and both the regulated unit and one or more solid waste management units or areas of concern are likely to have contributed to the release.

cbd It is not necessary to apply the requirements of this subchapter because the alternative requirements will protect human health and the environment. The alternative standards for the regulated unit shall meet the requirements of s. NR 664.0101 c1d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c4d cad, ccd Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c5d Register August 2020 No. 776, eff. 9-1-20.

NR 665.0091 Groundwater monitoring system. c1d

A groundwater monitoring system shall be capable of yielding groundwater samples for analysis and shall consist of all of the following:

cad Monitoring wells at least one installed hydraulically upgradient c.i.e., in the direction of increasing static head from the limit of the waste management area. Their number, locations and depths shall be sufficient to yield groundwater samples that are all of the following:

1. Representative of background groundwater quality in the uppermost aquifer near the facility.
2. Not affected by the facility.

cbd Monitoring wells at least three installed hydraulically downgradient c.i.e., in the direction of decreasing static head at the limit of the waste management area. Their number, locations and depths shall ensure that they immediately detect any statistically significant amounts of hazardous waste or hazardous waste constituents that migrate from the waste management area to the uppermost aquifer.

ccd The facility owner or operator may demonstrate that an alternate hydraulically downgradient monitoring well location will meet all of the following criteria. The demonstration shall be in writing and kept at the facility. The demonstration shall be certified by a qualified groundwater scientist and establish that all of the following apply:

1. An existing physical obstacle prevents monitoring well installation at the hydraulically downgradient limit of the waste management area.

2. The selected alternate downgradient location is as close to the limit of the waste management area as practical.

3. The location ensures detection that, given the alternate location, is as early as possible of any statistically significant amounts of hazardous waste or hazardous waste constituents that migrate from the waste management area to the uppermost aquifer.

4. Lateral expansion, new or replacement units are not eligible for an alternate downgradient location under this paragraph.

c2d Separate monitoring systems for each waste management component of a facility are not required provided that provisions for sampling upgradient and downgradient water quality will detect any discharge from the waste management area.

cad In the case of a facility consisting of only one surface impoundment or landfill, the waste boundary perimeter describes the waste management area.

cbd In the case of a facility consisting of more than one surface impoundment or landfill, an imaginary boundary line which circumscribes the several waste management components describes the waste management area.

c3d All monitoring wells shall be cased in a manner that maintains the integrity of the monitoring well bore hole. This casing shall be screened or perforated, and packed with gravel or sand where necessary, to enable sample collection at depths where appropriate aquifer flow zones exist. The annular space c.i.e., the space between the bore hole and well casing above the sampling depth shall be sealed with a suitable material c.e.g., cement grout or bentonite slurry to prevent contamination of samples and the groundwater.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0092 Sampling and analysis. c1d

The owner or operator shall obtain and analyze samples from the installed groundwater monitoring system. The owner or operator shall develop and follow a groundwater sampling and analysis plan. Chemical and physical samples shall be analyzed by a laboratory certified or registered under ch. NR 149, except for field analyses for pH, specific conductance and temperature. The owner or operator shall keep this plan at the facility. The plan shall include procedures and techniques for all of the following:

cad Sample collection.

cbd Sample preservation and shipment.

ccd Analytical procedures.

cdd Chain of custody control.

Note: See XProcedures Manual For Ground-water Monitoring At Solid Waste Disposal Facilities, Y EPA-530{SW-611, and XMethods for Chemical Analysis of Water and Wastes, Y EPA-600{4-79-020, for discussions of sampling and analysis procedures.

c2d The owner or operator shall determine the concentration or value of all of the following parameters in groundwater samples in accordance with subs. c3d and c4d:

cad Parameters characterizing the suitability of the groundwater as a drinking water supply, as specified in ch. NR 665 Appendix III.

cbd All of the following parameters establishing groundwater quality:

1. Chloride.
2. Iron.
3. Manganese.
4. Phenols.
5. Sodium.

6. Sulfate.

Note: These parameters are to be used as a basis for comparison in the event a groundwater quality assessment is required under s. NR 665.0093c4d.

ccd All of the following parameters used as indicators of groundwater contamination:

1. pH.
2. Specific conductance.
3. Total organic carbon.
4. Total organic halogen.

c3d cad For all monitoring wells, the owner or operator shall establish initial background concentrations or values of all parameters specified in sub. c2d. The owner or operator shall do this quarterly for one year.

cbd For each of the indicator parameters specified in sub. c2d ccd, at least 4 replicate measurements shall be obtained for each sample and the initial background arithmetic mean and variance shall be determined by pooling the replicate measurements for the respective parameter concentrations or values in samples obtained from upgradient wells during the first year.

c4d After the first year, all monitoring wells shall be sampled and the samples analyzed with the following frequencies:

cad Samples collected to establish groundwater quality shall be obtained and analyzed for the parameters specified in sub. c2d cbd at least annually.

cbd Samples collected to indicate groundwater contamination shall be obtained and analyzed for the parameters specified in sub. c2d ccd at least semi-annually.

c5d Elevation of the groundwater surface at each monitoring well shall be determined each time a sample is obtained.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c2d cad made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

NR 665.0093 Preparation, evaluation and response. c1d By August 1, 1982, the owner or operator shall prepare an outline of a groundwater quality assessment program. The outline shall describe a more comprehensive groundwater monitoring program than that described in ss. NR 665.0091 and 665.0092d capable of determining all of the following:

cad Whether hazardous waste or hazardous waste constituents have entered the groundwater.

cbd The rate and extent of migration of hazardous waste or hazardous waste constituents in the groundwater.

ccd The concentrations of hazardous waste or hazardous waste constituents in the groundwater.

c2d For each indicator parameter specified in s. NR 665.0092 c2d ccd, the owner or operator shall calculate the arithmetic mean and variance, based on at least 4 replicate measurements on each sample, for each well monitored in accordance with s. NR 665.0092 c4d cbd, and compare these results with its initial background arithmetic mean. The comparison shall consider individually each of the wells in the monitoring system, and shall use the Student[t]-test at the 0.01 level of significance csee ch. NR 665 Appendix IVd to determine statistically significant increases and decreases, in the case of pHd over initial background.

c3d cad If the comparisons for the upgradient wells made under sub. c2d show a significant increase or pH decreased, the owner or operator shall submit this information in accordance with s. NR 665.0094 c1d cbd 2.

cbd If the comparisons for downgradient wells made under sub. c2d show a significant increase or pH decreased, the owner or operator shall then immediately obtain additional groundwater samples from those downgradient wells where a significant difference was detected, split the samples in 2 and obtain analyses of

all additional samples to determine whether the significant difference was a result of laboratory error.

c4d cad If the analyses performed under sub. c3d cbd confirm the significant increase or pH decreased, the owner or operator shall provide written notice to the department—within 7 days of the date of the confirmation—that the facility may be affecting groundwater quality.

cbd Within 15 days after the notification under par. cad, the owner or operator shall develop and submit to the department a specific plan, based on the outline required under sub. c1d and certified by a qualified geologist or geotechnical engineer, for a groundwater quality assessment program at the facility. This plan shall be placed in the facility[s] operating record and be maintained until closure of the facility.

ccd The plan to be submitted under s. NR 665.0090 c4d cad or cbd shall specify all of the following:

1. The number, location and depth of wells.
2. Sampling and analytical methods for those hazardous wastes or hazardous waste constituents in the facility.
3. Evaluation procedures, including any use of previously-gathered groundwater quality information.
4. A schedule of implementation.

cdd The owner or operator shall implement the groundwater quality assessment plan which satisfies the requirements of par. ccd, and, at a minimum, determine all of the following:

1. The rate and extent of migration of the hazardous waste or hazardous waste constituents in the groundwater.
2. The concentrations of the hazardous waste or hazardous waste constituents in the groundwater.

ced The owner or operator shall make the first determination under par. cdd as soon as technically feasible, and, within 15 days after that determination, submit to the department a written report containing an assessment of the groundwater quality. This report shall be placed in the facility[s] operating record and be maintained until closure of the facility.

cbd If the owner or operator determines, based on the results of the first determination under par. cdd, that no hazardous waste or hazardous waste constituents from the facility have entered the groundwater, then the owner or operator may reinstate the indicator evaluation program described in s. NR 665.0092 and sub. c2d. If the owner or operator reinstates the indicator evaluation program, the owner or operator shall so notify the department in the report submitted under par. ced.

cgd If the owner or operator determines, based on the first determination under par. cdd, that hazardous waste or hazardous waste constituents from the facility have entered the groundwater, then the owner or operator:

1. Shall continue to make the determinations required under par. cdd on a quarterly basis until final closure of the facility, if the groundwater quality assessment plan was implemented prior to final closure of the facility.
2. May cease to make the determinations required under par. cdd, if the groundwater quality assessment plan was implemented during the long-term care period.

c5d Notwithstanding any other provision of this subchapter, any groundwater quality assessment to satisfy the requirements of sub. c4d cdd which is initiated prior to final closure of the facility shall be completed and reported in accordance with sub. c4d ced.

c6d Unless the groundwater is monitored to satisfy the requirements of sub. c4d cdd, at least annually the owner or operator shall evaluate the data on groundwater surface elevations obtained under s. NR 665.0092 c5d to determine whether the re-

quirements under s. NR 665.0091 c1d for locating the monitoring wells continues to be satisfied. If the evaluation shows that s. NR 665.0091 c1d is no longer satisfied, the owner or operator shall immediately modify the number, location or depth of the monitoring wells to bring the groundwater monitoring system into compliance with s. NR 665.0091 c1d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c2d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; CR 16-007: am. c4d cbd, ced Register July 2017 No. 739, eff. 8-1-17.

NR 665.0094 Recordkeeping and reporting. c1d

Unless the groundwater is monitored to satisfy the requirements of s. NR 665.0093 c4d cdd, the owner or operator shall do all of the following:

cad Keep records of the analyses required in s. NR 665.0092 c3d and c4d, the associated groundwater surface elevations required in s. NR 665.0092 c5d and the evaluations required in s. NR 665.0093 c2d throughout the active life of the facility, and, for disposal facilities, throughout the long-term care period as well.

cbd Report all of the following groundwater monitoring information to the department:

1. During the first year when initial background concentrations are being established for the facility: Concentrations or values of the parameters listed in s. NR 665.0092 c2d cad for each groundwater monitoring well within 15 days after completing each quarterly analysis. The owner or operator shall separately identify for each monitoring well any parameters whose concentration or value has been found to exceed the maximum contaminant levels listed in ch. NR 665 Appendix III.

2. Annually: Concentrations or values of the parameters listed in s. NR 665.0092 c2d ccd for each groundwater monitoring well, along with the required evaluations for these parameters under s. NR 665.0093 c2d. The owner or operator shall separately identify any significant differences from initial background found in the upgradient wells, in accordance with s. NR 665.0093 c3d cad. During the active life of the facility, this information shall be submitted no later than March 1 following each calendar year.

3. No later than March 1 following each calendar year: Results of the evaluations of groundwater surface elevations under s. NR 665.0093 c6d, and a description of the response to that evaluation, where applicable.

c2d If the groundwater is monitored to satisfy the requirements of s. NR 665.0093 c4d cdd, the owner or operator shall do all of the following:

cad Keep records of the analyses and evaluations specified in the plan, which satisfies the requirements of s. NR 665.0093 c4d ccd, throughout the active life of the facility, and, for disposal facilities, throughout the long-term care period as well.

cbd Annually, until final closure of the facility, submit to the department a report containing the results of the groundwater quality assessment program which includes, but is not limited to, the calculated cor measured rate of migration of hazardous waste or hazardous waste constituents in the groundwater during the reporting period. This information shall be submitted no later than March 1 following each calendar year.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c1d cbd 1. made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

Subchapter G — Closure and Long-Term Care

NR 665.0110 Applicability. Except as s. NR 665.0001 provides otherwise:

c1d Sections NR 665.0111 to 665.0115 cwhich concern clo-

sured apply to the owners and operators of all hazardous waste management facilities.

c2d Sections NR 665.0116 to 665.0120 cwhich concern long-term cared apply to the owners and operators of all of the following:

cad All hazardous waste disposal facilities.

cbd Waste piles and surface impoundments for which the owner or operator intends to remove the wastes at closure to the extent that these sections are made applicable to the facilities in s. NR 665.0228 or 665.0258.

ccd Tank systems that are required under s. NR 665.0197 to meet requirements for landfills.

cdd Containment building that are required under s. NR 665.1102 to meet the requirements for landfills.

c3d Section NR 665.0121 applies to owners and operators of units that are subject to the requirements of s. NR 670.001 c3d cgd and are regulated under an enforceable document cas defined in s. NR 670.001 c3d cgdd.

c4d The department may replace all or part of the requirements of this subchapter cand the unit-specific standards in s. NR 665.0111 c3dd applying to a regulated unit cas defined in s. NR 664.0090d, with alternative requirements for closure set out in an approved closure or long-term care plan, or in an enforceable document cas defined in s. NR 670.001 c3d cgdd, where the department determines both of the following conditions are met:

cad A regulated unit is situated among solid waste management units cor areas of concern, a release has occurred and both the regulated unit and one or more solid waste management units cor areas of concern are likely to have contributed to the release.

cbd It is not necessary to apply the closure requirements of this subchapter cor those referenced in this subchapter because the alternative requirements will protect human health and the environment, and will satisfy the closure performance standard of s. NR 665.0111 c1d and c2d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0111 Closure performance standard. The owner or operator shall close the facility in a manner that does all of the following:

c1d Minimizes the need for further maintenance.

c2d Controls, minimizes or eliminates, to the extent necessary to protect human health and the environment, post-closure escape of hazardous waste, hazardous constituents, leachate, contaminated run-off or hazardous waste decomposition products to the ground or surface waters or to the atmosphere.

c3d Complies with the closure requirements of this subchapter, including, but not limited to, the requirements of ss. NR 665.0197, 665.0228, 665.0258, 665.0310, 665.0351, 665.0381, 665.0404 and 665.1102.

c4d Meets, in the case of a landfill or surface impoundment, applicable requirements in ch. NR 140 and applicable soil cleanup standards in ch. NR 720 or meets the applicable closure requirements of sub. c2d or c3d, whichever are more stringent.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0112 Closure plan; amendment of plan.

c1d WRITTEN PLAN. By February 1, 1982, or by 6 months after the effective date of the rule that first subjects a facility to provisions of this section, the owner or operator of a hazardous waste management facility shall have a written closure plan. Until final closure is completed and certified in accordance with s. NR 665.0115, a copy of the most current plan shall be furnished to the department upon request, including request by mail. In addition, for facilities without approved plans, it shall also be pro-

vided during site inspections, on the day of inspection, to any officer, employee or representative of the department.

c2d CONTENT OF PLAN. The plan shall identify steps necessary to perform partial or final closure of the facility, or both, at any point during its active life. The closure plan shall include, at least all of the following:

cad A description of how each hazardous waste management unit at the facility will be closed in accordance with s. NR 665.0111.

cbd A description of how final closure of the facility will be conducted in accordance with s. NR 665.0111. The description shall identify the maximum extent of the operation which will be unclosed during the active life of the facility.

ccd An estimate of the maximum inventory of hazardous wastes ever on-site over the active life of the facility and a detailed description of the methods to be used during partial and final closure, including, but not limited to methods for removing, transporting, treating, storing or disposing of all hazardous waste, identification of and the types of off-site hazardous waste management units to be used, if applicable.

cdd A detailed description of the steps needed to remove or decontaminate all hazardous waste residues and contaminated containment system components, equipment, structures and soils during partial and final closure including, but not limited to, procedures for cleaning equipment and removing contaminated soils, methods for sampling and testing surrounding soils and criteria for determining the extent of decontamination necessary to satisfy the closure performance standard.

ced A detailed description of other activities necessary during the partial and final closure period to ensure that all partial closures and final closure satisfy the closure performance standards, including, but not limited to, groundwater monitoring, leachate collection and run-on and run-off control.

cf A schedule for closure of each hazardous waste management unit and for final closure of the facility. The schedule shall include, at a minimum, the total time required to close each hazardous waste management unit and the time required for intervening closure activities which will allow tracking of the progress of partial and final closure. **cfd** For example, in the case of a landfill unit, estimates of the time required to treat or dispose of all hazardous waste inventory and of the time required to place a final cover shall be included.

cg An estimate of the expected year of final closure for facilities that use trust funds to demonstrate financial assurance under s. NR 665.0143 or 665.0145 and whose remaining operating life is less than 20 years, and for facilities without approved closure plans.

ch For facilities where the department has applied alternative requirements at a regulated unit under s. NR 665.0090 **cd**, 665.0110 **cd** or 665.0140 **cd**, either the alternative requirements applying to the regulated unit, or a reference to the enforceable document containing those alternative requirements.

c3d AMENDMENT OF PLAN. The owner or operator may amend the closure plan at any time prior to the notification of partial or final closure of the facility. An owner or operator with an approved closure plan shall submit a written request to the department to authorize a change to the approved closure plan. The written request shall include a copy of the amended closure plan for approval by the department.

cad The owner or operator shall amend the closure plan under any of the following circumstances:

1. Changes in operating plans or facility design affect the closure plan.

2. There is a change in the expected year of closure, if applicable.

3. In conducting partial or final closure activities, unexpected events require a modification of the closure plan.

4. The owner or operator requests the department to apply alternative requirements to a regulated unit under s. NR 665.0090 **cd**, 665.0110 **cd** or 665.0140 **cd**.

cbd The owner or operator shall amend the closure plan at least 60 days prior to the proposed change in facility design or operation, or no later than 60 days after an unexpected event has occurred which has affected the closure plan. If an unexpected event occurs during the partial or final closure period, the owner or operator shall amend the closure plan no later than 30 days after the unexpected event. This paragraph also applies to owners or operators of surface impoundments and waste piles who intended to remove all hazardous wastes at closure, but are required to close as landfills in accordance with s. NR 665.0310.

ccd An owner or operator with an approved closure plan shall submit the modified plan to the department at least 60 days prior to the proposed change in facility design or operation, or no more than 60 days after an unexpected event has occurred which has affected the closure plan. If an unexpected event has occurred during the partial or final closure period, the owner or operator shall submit the modified plan no more than 30 days after the unexpected event. This paragraph also applies to owners or operators of surface impoundments and waste piles who intended to remove all hazardous wastes at closure but are required to close as landfills in accordance with s. NR 665.0310. If the amendment to the plan is a class 2 or 3 modification according to the criteria in s. NR 670.042, the modification to the plan will be approved according to the procedures in sub. **cd**.

cdd The department may request modifications to the plan under the conditions described in par. **cad**. An owner or operator with an approved closure plan shall submit the modified plan within 60 days of the request from the department, or within 30 days if the unexpected event occurs during partial or final closure. If the amendment is considered a class 2 or 3 modification according to the criteria in s. NR 670.042, the modification to the plan will be approved in accordance with the procedures in sub. **cd**.

c4d NOTIFICATION OF PARTIAL CLOSURE AND FINAL CLOSURE. **cad** The owner or operator shall notify the department in writing of the intent to close the facility at least 180 days prior to the partial or final closure of a hazardous waste facility. The owner or operator shall submit the closure plan to the department at least 180 days prior to the date on which the owner or operator expects to begin closure of the first surface impoundment, waste pile, or landfill unit, or final closure if it involves such a unit, whichever is earlier. The owner or operator shall submit the closure plan to the department at least 45 days prior to the date on which the owner or operator expects to begin partial or final closure of a boiler or industrial furnace. The owner or operator shall submit the closure plan to the department at least 45 days prior to the date on which the owner or operator expects to begin final closure of a facility with only tanks, container storage or incinerator units.

cbd The date when the owner or operator expects to begin closure shall be either of the following:

1. Within 30 days after the date on which any hazardous waste management unit receives the known final volume of hazardous wastes, or, if there is a reasonable possibility that the hazardous waste management unit will receive additional hazardous wastes, no later than one year after the date on which the unit received the most recent volume of hazardous waste. If the owner

or operator of a hazardous waste management unit can demonstrate to the department that the hazardous waste management unit or facility has the capacity to receive additional hazardous wastes and the owner or operator has taken, and will continue to take, all steps to prevent threats to human health and the environment, including compliance with all interim license requirements, the department may approve an extension to this one-year limit.

2. For units meeting the requirements of s. NR 665.0113 c4d, no later than 30 days after the date on which the hazardous waste management unit receives the known final volume of nonhazardous wastes, or if there is a reasonable possibility that the hazardous waste management unit will receive additional nonhazardous wastes, no later than one year after the date on which the unit received the most recent volume of nonhazardous wastes. If the owner or operator can demonstrate to the department that the hazardous waste management unit has the capacity to receive additional nonhazardous wastes and the owner or operator has taken, and will continue to take, all steps to prevent threats to human health and the environment, including compliance with all applicable interim license requirements, the department may approve an extension to this one-year limit.

ccd The owner or operator shall submit its closure plan to the department no later than 15 days after either of the following:

1. Denial, suspension or revocation of an interim license except when an operating license is issued simultaneously with revocation of an interim license.

2. Issuance of a judicial decree, department order, or final order pursuant to 42 USC 6928 chd to cease receiving waste or close.

cdd The department will provide the owner or operator and the public, through a newspaper notice, the opportunity to submit written comments on the plan and request modifications to the plan no later than 30 days from the date of the notice. The department will also, in response to a request or at its own discretion, hold a public hearing whenever such a hearing might clarify one or more issues concerning a closure plan. The department will give public notice of the hearing at least 30 days before it occurs. cPublic notice of the hearing may be given at the same time as notice of the opportunity for the public to submit written comments, and the 2 notices may be combined.d The department will approve, modify or disapprove the plan within 90 days of its receipt. If the department does not approve the plan, it shall provide the owner or operator with a detailed written statement of reasons for the refusal and the owner or operator shall modify the plan or submit a new plan for approval within 30 days after receiving the written statement. The department will approve or modify this plan in writing within 60 days. If the department modifies the plan, this modified plan becomes the approved closure plan. The department shall assure that the approved plan is consistent with ss. NR 665.0111, 665.0113 to 665.0115 and this section and the applicable requirements of subch. F and ss. NR 665.0197, 665.0228, 665.0258, 665.0310, 665.0351, 665.0381, 665.0404 and 664.1102. A copy of the modified plan with a detailed statement of reasons for the modifications shall be mailed to the owner or operator.

c5d REMOVAL OF WASTES AND DECONTAMINATION OR DISMANTLING OF EQUIPMENT. Nothing in this section shall preclude the owner or operator from removing hazardous wastes and decontaminating or dismantling equipment in accordance with the approved partial or final closure plan at any time before or after notification of partial or final closure.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c4d ccd 2. Register August 2020 No. 776, eff. 9-1-20.

NR 665.0113 Closure; time allowed for closure.

c1d Within 90 days after receiving the final volume of hazardous wastes, or the final volume of nonhazardous wastes if the owner or operator complies with all applicable requirements in subs. c4d and c5d, at a hazardous waste management unit or facility, or within 90 days after approval of the closure plan, whichever is later, the owner or operator shall treat, remove from the unit or facility or dispose of on-site, all hazardous wastes in accordance with the approved closure plan. The department may approve a longer period if the owner or operator demonstrates that the conditions in pars. cad and cbd are met:

cad Either of the following applies:

1. The activities required to comply with this subsection will, of necessity, take longer than 90 days to complete.

2. All of the following apply:

a. The hazardous waste management unit or facility has the capacity to receive additional hazardous wastes, or has the capacity to receive non-hazardous wastes if the facility owner or operator complies with subs. c4d and c5d.

b. There is a reasonable likelihood that the owner or operator or another person will recommence operation of the hazardous waste management unit or the facility within one year.

c. Closure of the hazardous waste management unit or facility would be incompatible with continued operation of the site.

cbd The owner or operator has taken and will continue to take all steps to prevent threats to human health and the environment, including compliance with all applicable interim license requirements.

c2d The owner or operator shall complete partial and final closure activities in accordance with the approved closure plan and within 180 days after receiving the final volume of hazardous wastes, or the final volume of nonhazardous wastes if the owner or operator complies with all applicable requirements in subs. c4d and c5d, at the hazardous waste management unit or facility, or 180 days after approval of the closure plan, if that is later. The department may approve an extension to the closure period if the owner or operator demonstrates that the conditions in pars. cad and cbd are met:

cad Either of the following applies:

1. The partial or final closure activities will, of necessity, take longer than 180 days to complete.

2. All of the following apply:

a. The hazardous waste management unit or facility has the capacity to receive additional hazardous wastes, or has the capacity to receive non-hazardous wastes if the facility owner or operator complies with subs. c4d and c5d.

b. There is reasonable likelihood that the owner or operator or another person will recommence operation of the hazardous waste management unit or the facility within one year.

c. Closure of the hazardous waste management unit or facility would be incompatible with continued operation of the site.

cbd The owner or operator has taken and will continue to take all steps to prevent threats to human health and the environment from the unclosed but not operating hazardous waste management unit or facility, including compliance with all applicable interim license requirements.

c3d The demonstrations referred to in subs. c1d cad and c2d cad shall be made as follows:

cad The demonstrations in sub. c1d cad shall be made at least 30 days prior to the expiration of the 90-day period in sub. c1d.

cbd The demonstration in sub. c2d cad shall be made at least 30 days prior to the expiration of the 180-day period in sub. c2d,

unless the owner or operator is otherwise subject to the deadlines in sub. **c4d**.

c4d The department may allow an owner or operator to receive non-hazardous wastes in a landfill, or surface impoundment unit after the final receipt of hazardous wastes at that unit if all the following conditions are met:

cad The owner or operator submits an amended feasibility and plan of operation report, or a feasibility and plan of operation report, if not previously required, and demonstrates that all the following criteria are met:

1. The unit has the existing design capacity as indicated on the part A application to receive non-hazardous wastes.
2. There is a reasonable likelihood that the owner or operator or another person will receive non-hazardous wastes in the unit within one year after the final receipt of hazardous wastes.
3. The non-hazardous wastes will not be incompatible with any remaining wastes in the unit or with the facility design and operating requirements of the unit or facility under this chapter.
4. Closure of the hazardous waste management unit would be incompatible with continued operation of the unit or facility.
5. The owner or operator is operating and will continue to operate in compliance with all applicable interim license requirements.

cbd The feasibility and plan of operation report includes an amended waste analysis plan, groundwater monitoring and response program, human exposure assessment required under **42 USC 6939a** and closure and long-term care plans, and updated cost estimates and demonstrations of financial assurance for closure and long-term care as necessary and appropriate to reflect any changes due to the presence of hazardous constituents in the non-hazardous wastes, and changes in closure activities, including the expected year of closure if applicable under s. **NR 665.0112 c2d cgd**, as a result of the receipt of non-hazardous wastes following the final receipt of hazardous wastes.

ccd The feasibility and plan of operation report is amended, as necessary and appropriate, to account for the receipt of non-hazardous wastes following receipt of the final volume of hazardous wastes.

cdd The feasibility and plan of operation report and the demonstrations referred to in pars. **cad** and **cbd** are submitted to the department no later than 180 days prior to the date on which the owner or operator of the facility receives the known final volume of hazardous wastes, or no later than 90 days after August 1, 2006, whichever is later.

c5d In addition to the requirements in sub. **c4d**, an owner or operator of a hazardous waste surface impoundment that is not in compliance with the liner and leachate collection system requirements in **42 USC 6924codc1d** and **6925cjdc1d** or **42 USC 6924codc2d** or **c3d** or **6925cjdc2d**, **c3d**, **c4d** or **c13d** shall do all of the following:

cad Submit with the feasibility and plan of operation report both of the following:

1. A contingent corrective measures plan.
2. A plan for removing hazardous wastes in compliance with par. **cbd**.

cbd Remove all hazardous wastes from the unit by removing all hazardous liquids and removing all hazardous sludges to the extent practicable without impairing the integrity of the liners, if any.

ccd Removal of hazardous wastes shall be completed no later than 90 days after the final receipt of hazardous wastes. The department may approve an extension to this deadline if the owner or operator demonstrates that the removal of hazardous wastes

will, of necessity, take longer than the allotted period to complete and that an extension will not pose a threat to human health and the environment.

cdd If a release that is a statistically significant increase or decrease in the case of pHd in hazardous constituents over background levels is detected in accordance with the requirements in subch. **F**, the owner or operator of the unit:

1. Shall implement corrective measures in accordance with the approved contingent corrective measures plan required by par. **cad** no later than one year after detection of the release, or approval of the contingent corrective measures plan, whichever is later.

2. May receive wastes at the unit following detection of the release only if the approved corrective measures plan includes a demonstration that continued receipt of wastes will not impede corrective action.

3. May be required by the department to implement corrective measures in less than one year or to cease receipt of wastes until corrective measures have been implemented if necessary to protect human health and the environment.

ced During the period of corrective action, the owner or operator shall provide annual reports to the department describing the progress of the corrective action program, compile all groundwater monitoring data, and evaluate the effect of the continued receipt of non-hazardous wastes on the effectiveness of the corrective action.

efd The department may require the owner or operator to commence closure of the unit if the owner or operator fails to implement corrective action measures in accordance with the approved contingent corrective measures plan within one year as required in par. **cdd**, or fails to make substantial progress in implementing corrective action and achieving the facility[s] background levels.

cgd If the owner or operator fails to implement corrective measures as required in par. **cdd**, or if the department determines that substantial progress has not been made pursuant to par. **efd**, the department shall:

1. Notify the owner or operator in writing that the owner or operator shall begin closure in accordance with the deadlines in subs. **c1d** and **c2d** and provide a detailed statement of reasons for this determination.

2. Provide the owner or operator and the public, through a newspaper notice, the opportunity to submit written comments on the decision no later than 20 days after the date of the notice.

3. If the department receives no written comments, the decision will become final 5 days after the close of the comment period. The department will notify the owner or operator that the decision is final, and that a revised closure plan, if necessary, shall be submitted within 15 days of the final notice and that closure shall begin in accordance with the deadlines in subs. **c1d** and **c2d**.

4. If the department receives written comments on the decision, it shall make a final decision within 30 days after the end of the comment period, and provide the owner or operator in writing and the public through a newspaper notice, a detailed statement of reasons for the final decision. If the department determines that substantial progress has not been made, closure shall be initiated in accordance with the deadlines in subs. **c1d** and **c2d**.

5. The final determinations made by the department under subs. **3**. and **4**. are not subject to administrative appeal.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c5d ced Register July 2017 No. 739, eff. 8-1-17.

NR 665.0114 Disposal or decontamination of

equipment, structures and soils. During the partial and final closure periods, all contaminated equipment, structures and soil shall be properly disposed of, or decontaminated unless specified otherwise in s. NR 665.0197, 665.0228, 665.0258 or 665.0310. By removing all hazardous wastes or hazardous constituents during partial and final closure, the owner or operator may become a generator of hazardous waste and shall handle that hazardous waste in accordance with all applicable requirements of ch. NR 662.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0115 Certification of closure. Within 60 days of completion of closure of each hazardous waste surface impoundment, waste pile and landfill unit, and within 60 days of completion of final closure, the owner or operator shall submit to the department, by registered mail, a certification that the hazardous waste management unit or facility, as applicable, has been closed in accordance with the specifications in the approved closure plan. The certification shall be signed by the owner or operator and by a qualified professional engineer. Documentation supporting the professional engineer[s] certification shall be furnished to the department upon request until the department releases the owner or operator from the financial assurance requirements for closure under s. NR 665.0143 c10d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. Register July 2017 No. 739, eff. 8-1-17.

NR 665.0116 Survey plat. No later than the submission of the certification of closure of each hazardous waste disposal unit, an owner or operator shall submit to the local zoning authority, or the authority with jurisdiction over local land use, and to the department, a survey plat indicating the location and dimensions of landfill cells or other hazardous waste disposal units with respect to permanently surveyed benchmarks. This plat shall be prepared and certified by a professional land surveyor. The plat filed with the local zoning authority, or the authority with jurisdiction over local land use shall contain a note, prominently displayed, which states the owner[s] or operator[s] obligation to restrict disturbance of the hazardous waste disposal unit according to the applicable rules of this subchapter.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0117 Long-term care and use of property. **c1d** cad Long-term care for each hazardous waste management unit subject to the requirements of this section and ss. NR 665.0118 to 665.0120 shall begin after completion of closure of the unit and continue for a minimum of 40 years after that date. It shall consist of at least both of the following:

1. Monitoring and reporting in accordance with the requirements of subchs. F, K, L and N.
2. Maintenance and monitoring of waste containment systems in accordance with the requirements of subchs. F, K, L and N.

cbd Any time preceding closure of a hazardous waste management unit subject to long-term care requirements or final closure, or any time during the long-term care period for a particular hazardous waste disposal unit, the department may extend the long-term care period applicable to the hazardous waste management unit or facility, if the department finds that the extended period is necessary to protect human health and the environment ce.g., leachate or groundwater monitoring results indicate a potential for migration of hazardous wastes at levels which may be harmful to human health and the environmentd.

c2d The department may require, at partial and final closure, continuation of any of the security requirements of s. NR

665.0014 during part or all of the long-term care period under either of the following circumstances:

cad Hazardous wastes may remain exposed after completion of partial or final closure.

cbd Access by the public or domestic livestock may pose a hazard to human health.

c3d Post-closure use of property on or in which hazardous wastes remain after partial or final closure may never be allowed to disturb the integrity of the final cover, liners or any other components of the containment system, or the function of the facility[s] monitoring systems, unless the department finds that either of the following applies:

cad The disturbance is necessary to the proposed use of the property, and will not increase the potential hazard to human health or the environment.

cbd The disturbance is necessary to reduce a threat to human health or the environment.

c4d All long-term care activities shall be in accordance with the provisions of the approved long-term care plan as specified in s. NR 665.0118.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0118 Long-term care plan; amendment of plan. **c1d** WRITTEN PLAN. By February 1, 1982, the owner or operator of a hazardous waste disposal unit shall have a written long-term care plan. An owner or operator of a surface impoundment or waste pile that intends to remove all hazardous wastes at closure shall prepare a long-term care plan and submit it to the department within 90 days of the date that the owner or operator or department determines that the hazardous waste management unit or facility must be closed as a landfill, subject to the requirements of s. NR 665.0117, this section, ss. NR 665.0119 and 665.0120.

c2d AVAILABILITY OF PLAN. Until final closure of the facility, a copy of the most current long-term care plan shall be furnished to the department upon request, including request by mail. In addition, for facilities without approved long-term care plans, it shall also be provided during site inspections, on the day of inspection, to any officer, employee or representative of the department. After final closure has been certified, the person or office specified in sub. c3d ccd shall keep the approved long-term care plan during the long-term care period.

c3d CONTENT OF PLAN. For each hazardous waste management unit subject to the requirements of this section, the long-term care plan shall identify the activities that will be carried on after closure of each disposal unit and the frequency of these activities, and include at least all of the following:

cad A description of the planned monitoring activities and frequencies at which they will be performed to comply with subchs. F, K, L and N during the long-term care period.

cbd A description of the planned maintenance activities, and frequencies at which they will be performed, to ensure both of the following:

1. The integrity of the cap and final cover or other containment systems in accordance with the requirements of subchs. K, L and N.

2. The function of the monitoring equipment in accordance with the requirements of subchs. F, K, L and N.

ccd The name, address and phone number of the person or office to contact about the hazardous waste disposal unit or facility during the long-term care period.

cdd For facilities subject to s. NR 665.0121, provisions that satisfy the requirements of s. NR 665.0121 c1d cad and ccd.

ced For facilities where the department has applied alternative requirements at a regulated unit under s. NR 665.0090 c6d, 665.0110 c4d or 665.0140 c4d, either the alternative requirements that apply to the regulated unit, or a reference to the enforceable document containing those requirements.

c4d AMENDMENT OF PLAN. The owner or operator may amend the long-term care plan any time during the active life of the facility or during the long-term care period. An owner or operator with an approved long-term care plan shall submit a written request to the department to authorize a change to the approved plan. The written request shall include a copy of the amended long-term care plan for approval by the department.

cad The owner or operator shall amend the long-term care plan whenever any of the following occurs:

1. Changes in operating plans or facility design affect the long-term care plan.
2. Events which occur during the active life of the facility, including partial and final closures, affect the long-term care plan.
3. The owner or operator requests the department to apply alternative requirements to a regulated unit under s. NR 665.0090 c6d, 665.0110 c4d or 665.0140 c4d.

cbd The owner or operator shall amend the long-term care plan at least 60 days prior to the proposed change in facility design or operation, or no later than 60 days after an unexpected event has occurred which has affected the long-term care plan.

ccd An owner or operator with an approved long-term care plan shall submit the modified plan to the department at least 60 days prior to the proposed change in facility design or operation, or no more than 60 days after an unexpected event has occurred which has affected the long-term care plan. If an owner or operator of a surface impoundment or a waste pile who intended to remove all hazardous wastes at closure in accordance with s. NR 665.0228 c1d or 665.0258 c1d is required to close as a landfill in accordance with s. NR 665.0310, the owner or operator shall submit a long-term care plan within 90 days of the determination by the owner or operator or department that the unit must be closed as a landfill. If the amendment to the long-term care plan is a class 2 or 3 modification according to the criteria in s. NR 670.042, the modification to the plan will be approved according to the procedures in sub. c6d.

cdd The department may request modifications to the plan under the conditions described in par. cad. An owner or operator with an approved long-term care plan shall submit the modified plan no later than 60 days of the request from the department. If the amendment to the plan is considered a class 2 or 3 modification according to the criteria in s. NR 670.042, the modifications to the long-term care plan will be approved in accordance with the procedures in sub. c6d. If the department determines that an owner or operator of a surface impoundment or waste pile who intended to remove all hazardous wastes at closure must close the facility as a landfill, the owner or operator shall submit a long-term care plan for approval to the department within 90 days of the determination.

c5d SUBMITTAL OF PLAN. The owner or operator of a facility with hazardous waste management units subject to these requirements shall submit its long-term care plan to the department at least 180 days before the date the owner or operator expects to begin partial or final closure of the first hazardous waste disposal unit. The date the owner or operator Xexpects to begin closureY of the first hazardous waste disposal unit shall be either within 30 days after the date on which the hazardous waste management unit receives the known final volume of hazardous waste or, if there is a reasonable possibility that the hazardous waste management unit will receive additional hazardous wastes, no later than

one year after the date on which the unit received the most recent volume of hazardous wastes. The owner or operator shall submit the long-term care plan to the department no later than 15 days after either of the following:

cad Denial, suspension or revocation of an interim license except when an operating license is issued to the facility simultaneously with revocation of an interim licensed.

cbd Issuance of a judicial decree, department order, or final order pursuant to 42 USC 6928 chd to cease receiving waste or close.

c6d REVIEW OF PLAN. The department will provide the owner or operator and the public, through a newspaper notice, the opportunity to submit written comments on the long-term care plan and request modifications to the plan no later than 30 days from the date of the notice. The department will also, in response to a request or at its own discretion, hold a public hearing whenever such a hearing might clarify one or more issues concerning a long-term care plan. The department will give public notice of the hearing at least 30 days before it occurs. cPublic notice of the hearing may be given at the same time as notice of the opportunity for the public to submit written comments, and the 2 notices may be combined.d The department shall approve, modify or disapprove the plan within 90 days of its receipt. If the department does not approve the plan, it shall provide the owner or operator with a detailed written statement of reasons for the refusal and the owner or operator shall modify the plan or submit a new plan for approval within 30 days after receiving the written statement. The department will approve or modify this plan in writing within 60 days. If the department modifies the plan, this modified plan becomes the approved long-term care plan. The department shall ensure that the approved long-term care plan is consistent with s. NR 665.0117, this section, ss. NR 665.0119 and 665.0120. A copy of the modified plan with a detailed statement of reasons for the modifications shall be mailed to the owner or operator.

c7d MODIFICATION OF PLAN. The long-term care plan and length of the long-term care period may be modified any time prior to the end of the long-term care period in either of the following 2 ways:

cad The owner or operator or any member of the public may petition the department to extend or reduce the long-term care period applicable to a hazardous waste management unit or facility based on cause, or alter the requirements of the long-term care period based on cause.

1. The petition shall include evidence demonstrating either of the following:

a. The secure nature of the hazardous waste management unit or facility makes the long-term care requirements unnecessary or supports reduction of the long-term care period specified in the current long-term care plan ce.g., leachate or groundwater monitoring results, characteristics of the wastes, application of advanced technology or alternative disposal, treatment or re-use techniques indicate that the facility is secured.

b. The requested extension in the long-term care period or alteration of long-term care requirements is necessary to prevent threats to human health and the environment ce.g., leachate or groundwater monitoring results indicate a potential for migration of hazardous wastes at levels which may be harmful to human health and the environmentd.

2. The department will consider these petitions only when they present new and relevant information not previously considered by the department. Whenever the department is considering a petition, it will provide the owner or operator and the public, through a newspaper notice, the opportunity to submit written

comments within 30 days of the date of the notice. The department will also, in response to a request or at its own discretion, hold a public hearing whenever a hearing might clarify one or more issues concerning the long-term care plan. The department will give the public notice of the hearing at least 30 days before it occurs. cPublic notice of the hearing may be given at the same time as notice of the opportunity for written public comments, and the 2 notices may be combined.d After considering the comments, the department will issue a final determination, based upon the criteria set forth in this paragraph.

3. If the department denies the petition, it will send the petitioner a brief written response giving a reason for the denial.

cbd The department may tentatively decide to modify the long-term care plan if it deems it necessary to prevent threats to human health and the environment. The department may propose to extend or reduce the long-term care period applicable to a hazardous waste management unit or facility based on cause or alter the requirements of the long-term care period based on cause.

1. The department will provide the owner or operator and the affected public, through a newspaper notice, the opportunity to submit written comments within 30 days of the date of the notice and the opportunity for a public hearing as in par. cad 2. After considering the comments, the department will issue a final determination.

2. The department will base its final determination upon the same criteria as required for petitions under par. cad 1. A modification of the long-term care plan may include, where appropriate, the temporary suspension rather than permanent deletion of one or more long-term care requirements. At the end of the specified period of suspension, the department would then determine whether the requirements should be permanently discontinued or reinstated to prevent threats to human health and the environment.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c5d cbd Register August 2020 No. 776, eff. 9-1-20.

NR 665.0119 Long-term care notices. c1d No later than 60 days after certification of closure of each hazardous waste disposal unit, the owner or operator shall submit to the local zoning authority, or the authority with jurisdiction over local land use, and to the department, a record of the type, location and quantity of hazardous wastes disposed of within each cell or other disposal unit of the facility. For hazardous wastes disposed of before July 1, 1985, the owner or operator shall identify the type, location and quantity of the hazardous wastes to the best of the owner or operator[s] knowledge and in accordance with any records the owner or operator has kept.

c2d Within 60 days of certification of closure of the first hazardous waste disposal unit and within 60 days of certification of closure of the last hazardous waste disposal unit, the owner or operator shall do both of the following:

cad Record, in accordance with ch. 706, Stats., a notation on the deed to the facility property, or on some other instrument which is normally examined during title search, that will in perpetuity notify any potential purchaser of the property of all of the following:

1. The land has been used to manage hazardous wastes.
2. Its use is restricted under the rules in this subchapter.
3. The survey plat and record of the type, location and quantity of hazardous wastes disposed of within each cell or other hazardous waste disposal unit of the facility required by s. NR 665.0116 and sub. c1d have been filed with the local zoning authority or the authority with jurisdiction over local land use and with the department.

cbd Submit a certification signed by the owner or operator that the owner or operator has recorded the notation specified in par. cad and a copy of the document in which the notation has been placed, to the department.

c3d If the owner or operator or any subsequent owner of the land upon which a hazardous waste disposal unit was located wishes to remove hazardous wastes and hazardous waste residues, the liner, if any, and all contaminated structures, equipment and soils, the owner or operator shall request a modification to the approved long-term care plan in accordance with the requirements of s. NR 665.0118 c7d. The owner or operator shall demonstrate that the removal of hazardous wastes will satisfy the criteria of s. NR 665.0117 c3d. By removing hazardous waste, the owner or operator may become a generator of hazardous waste and shall manage it in accordance with all applicable requirements of chs. NR 660 to 673. If the owner or operator is granted approval to conduct the removal activities, the owner or operator may request that the department approve either of the following:

cad The removal of the notation on the deed to the facility property or other instrument normally examined during title search.

cbd The addition of a notation to the deed or instrument indicating the removal of the hazardous waste.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0120 Certification of completion of long-term care. No later than 60 days after the completion of the established long-term care period for each hazardous waste disposal unit, the owner or operator shall submit to the department, by registered mail, a certification that the long-term care period for the hazardous waste disposal unit was performed in accordance with the specifications in the approved long-term care plan. The owner or operator and a qualified professional engineer shall sign the certification. Documentation supporting the professional engineer[s] certification shall be furnished to the department upon request until the department releases the owner or operator from the financial assurance requirements for long-term care under s. NR 665.0145 c10d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. Register July 2017 No. 739, eff. 8-1-17.

NR 665.0121 Long-term care requirements for facilities that obtain enforceable documents in lieu of long-term care licenses. c1d Owners and operators who are subject to the requirement to obtain a long-term care license under s. NR 670.001 c3d, but who obtain enforceable documents in lieu of long-term care licenses, as provided under s. NR 670.001 c3d cgd, shall comply with all of the following requirements:

cad The requirements to submit information about the facility in s. NR 670.028.

cbd The requirements for facility-wide corrective action in s. NR 664.0101.

ccd The requirements of ss. NR 664.0091 to 664.0100.

c2d cad The department, in issuing enforceable documents under this section in lieu of licenses, will assure a meaningful opportunity for public involvement which, at a minimum, includes public notice and opportunity for public comment as follows:

1. When the department becomes involved in a remediation at the facility as a regulatory or enforcement matter.
2. On the proposed preferred remedy and the assumptions upon which the remedy is based, in particular those related to land use and site characterization.
3. At the time of a proposed decision that remedial action is

complete at the facility. These requirements shall be met before the department may consider that the facility has met the requirements of s. NR 670.001 c3d cgd, unless the facility qualifies for a modification to these public involvement procedures under par. cbd or ccd.

cbd If the department determines that even a short delay in the implementation of a remedy would adversely affect human health or the environment, the department may delay compliance with the requirements of par. cad and implement the remedy immediately. However, the department shall assure involvement of the public at the earliest opportunity, and, in all cases, upon making the decision that additional remedial action is not needed at the facility.

ccd The department may allow a remediation initiated prior to August 1, 2006 to substitute for corrective action required under a long-term care license even if the public involvement requirements of par. cad have not been met so long as the department assures that notice and comment on the decision that no further remediation is necessary to protect human health and the environment takes place at the earliest reasonable opportunity after August 1, 2006.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter H — Financial Requirements

NR 665.0140 Applicability. c1d The requirements of ss. NR 665.0142, 665.0143, 665.0147 and 665.0148 apply to owners or operators of all hazardous waste facilities, except as provided otherwise in this section or in s. NR 665.0001.

c2d The requirements of ss. NR 665.0144 and 665.0146 apply only to owners and operators of one or more of the following:

cad Disposal facilities.

cbd Tank systems that are required under s. NR 664.0197 to meet the requirements for landfills.

ccd Containment buildings that are required under s. NR 665.1102 to meet the requirements for landfills.

c3d States and the federal government are exempt from the requirements of s. NR 665.0147.

c4d The department may replace all or part of the requirements of this subchapter applying to a regulated unit with alternative requirements for financial assurance set out in the license or in an enforceable document as defined in s. NR 670.001 c3d cgd, where the department does all of the following:

cad Prescribes alternative requirements for the regulated unit under s. NR 665.0090 c6d or 665.0110 c4d or both.

cbd Determines that it is not necessary to apply the requirements of this subchapter because the alternative financial assurance requirements will protect human health and the environment.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0141 Definitions. When used in this subchapter, the following terms have the meanings given below.

c1d XCaptive insurance companyY means a closely-held company owned by one or more organizations, parents, whose original purpose was and may continue to be, to insure some or all of the risks of shareholders or affiliated organizations.

c2d XClosure planY means the plan for closure prepared in accordance with the requirements of s. NR 665.0112.

c3d XCurrent closure cost estimateY means the most recent of the estimates prepared in accordance with s. NR 665.0142 c1d to c3d.

c4d XCurrent long-term care cost estimateY means the most

recent of the estimates prepared in accordance with s. NR 665.0144 c1d to c3d.

c5d XParent corporationY means a corporation which directly owns at least 50% of the voting stock of the corporation which is the facility owner or operator; the latter corporation is deemed a XsubsidiaryY of the parent corporation.

c6d XLong-term care planY means the plan for long-term care prepared in accordance with the requirements of ss. NR 665.0117 to 665.0120.

c7d The following terms are used in the specifications for the financial tests for liability coverage. The definitions are intended to assist in the understanding of this chapter and are not intended to limit the meanings of terms in a way that conflicts with generally accepted accounting practices.

cad XAssetsY means all existing and all probable future economic benefits obtained or controlled by a particular entity.

cbd XCurrent assetsY means cash or other assets or resources commonly identified as those which are reasonably expected to be realized in cash or sold or consumed during the normal operating cycle of the business.

ccd XCurrent liabilitiesY means obligations whose liquidation is reasonably expected to require the use of existing resources properly classifiable as current assets or the creation of other current liabilities.

cdd XCurrent plugging and abandonment cost estimateY means the most recent of the estimates prepared in accordance with ch. NR 815.

ced XIndependently auditedY refers to an audit performed by an independent certified public accountant in accordance with generally accepted auditing standards.

cfd XLiabilitiesY means probable future sacrifices of economic benefits arising from present obligations to transfer assets or provide services to other entities in the future as a result of past transactions or events.

cgd XNet working capitalY means current assets minus current liabilities.

chd XNet worthY has the meaning given in s. 289.41 c1d ccd, Stats.

cid XTangible net worthY means the tangible assets that remain after deducting liabilities. The assets would not include intangibles such as goodwill and rights to patents or royalties.

c8d In the liability insurance requirements, the terms Xbodily injuryY and Xproperty damageY shall have the meanings given these terms by applicable state law. However, these terms do not include those liabilities which, consistent with standard industry practice, are excluded from coverage in liability policies for bodily injury and property damage. The department intends the meanings of other terms used in the liability insurance requirements to be consistent with their common meanings within the insurance industry. The definitions given below of several of the terms are intended to assist in the understanding of this chapter and are not intended to limit their meanings in a way that conflicts with general insurance industry usage.

cad XAccidental occurrenceY means an accident, including continuous or repeated exposure to conditions, which results in bodily injury or property damage neither expected nor intended from the standpoint of the insured.

cbd XLegal defense costsY means any expenses that an insurer incurs in defending against claims of third parties brought under the terms and conditions of an insurance policy.

ccd XNonsudden accidental occurrenceY means an occurrence which takes place over time and involves continuous or repeated exposure.

cdd XSudden accidental occurrenceY means an occurrence which is not continuous or repeated in nature.

c9d XSubstantial business relationshipY means the extent of a business relationship necessary under applicable state law to make a guarantee contract issued incident to that relationship valid and enforceable. A substantial business relationship shall arise from a pattern of recent or ongoing business transactions, in addition to the guarantee itself, such that a currently existing business relationship between the guarantor and the owner or operator is demonstrated to the satisfaction of the department.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0142 Cost estimate for closure. c1d The owner or operator shall have a detailed written estimate, in current dollars, of the cost of closing the facility in accordance with the requirements in ss. NR 665.0111 to 665.0115 and applicable closure requirements in ss. NR 665.0197, 665.0228, 665.0258, 665.0310, 665.0351, 665.0381, 665.0404 and 665.1102.

cad The estimate shall equal the cost of final closure at the point in the facility[s active life when the extent and manner of its operation would make closure the most expensive, as indicated by its closure plan csee s. NR 665.0112 c2dd.

cbd The closure cost estimate shall be based on the costs to the owner or operator of hiring a third party to close the facility. A third party is a party who is neither a parent corporation nor a subsidiary of the owner or operator. The owner or operator may use costs for on-site disposal if the owner or operator can demonstrate that on-site disposal capacity will exist at all times over the life of the facility.

ccd The closure cost estimate may not incorporate any salvage value that may be realized with the sale of hazardous wastes, or non-hazardous wastes if applicable under s. NR 665.0113 c4d, facility structures or equipment, land or other assets associated with the facility at the time of partial or final closure.

cdd The owner or operator may not incorporate a zero cost for hazardous wastes, or non-hazardous wastes if applicable under s. NR 665.0113 c4d, that might have economic value.

c2d During the active life of the facility, the owner or operator shall adjust the closure cost estimate for inflation within 60 days prior to the anniversary date of the establishment of the financial instrumentcsd used to comply with s. NR 665.0143. For owners and operators of disposal facilities using the net worth test, the closure cost estimate shall be updated for inflation as required under s. 289.41 c5d cdd, Stats. The adjustment may be made by recalculating the closure cost estimate in current dollars, or by using an inflation factor derived from the most recent implicit price deflator for gross domestic product published by the U.S. department of commerce in its *Survey of Current Business*, as specified in pars. cad and cbd. The inflation factor is the result of dividing the latest published annual deflator by the deflator for the previous year.

cad The first adjustment shall be made by multiplying the closure cost estimate by the inflation factor. The result is the adjusted closure cost estimate.

cbd Subsequent adjustments shall be made by multiplying the latest adjusted closure cost estimate by the latest inflation factor.

c3d During the active life of the facility, the owner or operator shall revise the closure cost estimate no later than 30 days after a revision has been made to the closure plan which increases the cost of closure. If the owner or operator has an approved closure plan, the closure cost estimate shall be revised no later than 30 days after the department has approved the request to modify the closure plan, if the change in the closure plan increases the

cost of closure. The revised closure cost estimate shall be adjusted for inflation as specified in sub. c2d.

c4d The owner or operator shall keep the following at the facility during the operating life of the facility: The latest closure cost estimate prepared in accordance with subs. c1d to c3d and, when this estimate has been adjusted in accordance with sub. c2d, the latest adjusted closure cost estimate.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0143 Financial assurance for closure. By June 1, 1984, an owner or operator of each facility shall establish financial assurance for closure of the facility. The owner or operator shall choose from the options as specified in subs. c1d to c7d.

c1d CLOSURE TRUST FUND. cad An owner or operator may satisfy the requirements of this section by establishing a closure trust fund which conforms to the requirements of this subsection and submitting an originally signed duplicate of the trust agreement to the department. The trustee shall be an entity which has the authority to act as a trustee and whose trust operations are regulated and examined by a federal or state agency.

cbd The wording of the trust agreement shall be identical to the wording on the department form specified in s. NR 664.0151 c1d cad and the trust agreement shall be accompanied by a formal certification of acknowledgment as specified in s. NR 664.0151 c1d cbd. Schedule A of the trust agreement shall be updated within 60 days after a change in the amount of the current closure cost estimate covered by the agreement.

ccd Payments into the trust fund shall be made annually by the owner or operator over the 20 years beginning on June 1, 1984 or over the remaining operating life of the facility as estimated in the closure plan, whichever period is shorter. For the purposes of this section, this period is referred to as the Xpay-in period.Y The payments into the closure trust fund shall be made as follows:

1. The first payment shall be made by June 1, 1984, except as provided in par. ced. The first payment shall be at least equal to the current closure cost estimate, except as provided in sub. c8d, divided by the number of years in the pay-in period.

2. Subsequent payments shall be made no later than 30 days after each anniversary date of the first payment. The amount of each subsequent payment shall be determined by this formula:

$$\text{Next payment} = \frac{\text{CE} - \text{CV}}{\text{Y}}$$

where CE is the current closure cost estimate, CV is the current value of the trust fund and Y is the number of years remaining in the pay-in period.

cdd The owner or operator may accelerate payments into the trust fund or may deposit the full amount of the current closure cost estimate at the time the fund is established. However, the owner or operator shall maintain the value of the fund at no less than the value that the fund would have if annual payments were made as specified in par. ccd.

ced If the owner or operator establishes a closure trust fund after having used one or more alternate mechanisms specified in this section, the first payment shall be in at least the amount that the fund would contain if the trust fund were established initially and annual payments made as specified in par. ccd.

cfd After the pay-in period is completed, whenever the current closure cost estimate changes, the owner or operator shall compare the new estimate with the trustee[s most recent annual valuation of the trust fund. If the value of the fund is less than the amount of the new estimate, the owner or operator, within 60

days after the change in the cost estimate, shall either deposit an amount into the fund so that its value after this deposit at least equals the amount of the current closure cost estimate, or obtain other financial assurance as specified in this section to cover the difference.

cgd If the value of the trust fund is greater than the total amount of the current closure cost estimate, the owner or operator may submit a written request to the department for release of the amount in excess of the current closure cost estimate.

chd If an owner or operator substitutes other financial assurance as specified in this section for all or part of the trust fund, the owner or operator may submit a written request to the department for release of the amount in excess of the current closure cost estimate covered by the trust fund.

cid Within 60 days after receiving a request from the owner or operator for release of funds as specified in par. **cgd** or **chd**, the department will instruct the trustee to release to the owner or operator funds as the department specifies in writing.

cjd After beginning partial or final closure, an owner or operator or another person authorized to conduct partial or final closure may request reimbursements for partial or final closure expenditures by submitting itemized bills to the department. The owner or operator may request reimbursements for partial closure only if sufficient funds are remaining in the trust fund to cover the maximum costs of closing the facility over its remaining operating life. No later than 60 days after receiving bills for partial or final closure activities, the department will instruct the trustee to make reimbursements in those amounts as the department specifies in writing, if the department determines that the partial or final closure expenditures are in accordance with the approved closure plan, or otherwise justified. If the department has reason to believe that the maximum cost of closure over the remaining life of the facility will be significantly greater than the value of the trust fund, the department may withhold reimbursements of amounts as the department deems prudent until the department determines, in accordance with sub. **c10d** that the owner or operator is no longer required to maintain financial assurance for final closure of the facility. If the department does not instruct the trustee to make the reimbursements, the department will provide to the owner or operator a detailed written statement of reasons.

ckd The department will agree to termination of the trust when one of the following applies:

1. An owner or operator substitutes alternate financial assurance as specified in this section.
2. The department releases the owner or operator from the requirements of this section in accordance with sub. **c10d**.

c2d SURETY BOND GUARANTEEING PAYMENT INTO A CLOSURE TRUST FUND. **cad** An owner or operator may satisfy the requirements of this section by obtaining a surety bond which conforms to the requirements of this subsection and submitting the bond to the department. The surety company issuing the bond shall, at a minimum, be among those listed as acceptable sureties on federal bonds in Circular 570 of the U.S. department of the treasury.

cbd The wording of the surety bond shall be identical to the wording on the department form specified in s. **NR 664.0151 c2d**.

ccd The owner or operator who uses a surety bond to satisfy the requirements of this section shall also establish a standby trust fund. Under the terms of the bond, all payments made shall be deposited by the surety directly into the standby trust fund in accordance with instructions from the department. This standby trust fund must meet the requirements specified in sub. **c1d** except for all of the following:

1. An originally signed duplicate of the trust agreement must be submitted to the department with the surety bond.

2. Until the standby trust fund is funded pursuant to the requirements of this section, all of the following are not required:

- a. Payments into the trust fund as specified in sub. **c1d**.
- b. Updating of Schedule A of the trust agreement csee Form 4430-022d to show current closure cost estimates.
- c. Annual valuations as required by the trust agreement.
- d. Notices of nonpayment as required by the trust agreement.

cdd The bond must guarantee that the owner or operator shall do any of the following:

1. Fund the standby trust fund in an amount equal to the penal sum of the bond before the beginning of final closure of the facility.

2. Fund the standby trust fund in an amount equal to the penal sum within 15 days after an administrative order to begin final closure issued by the department becomes final, or within 15 days after an order to begin final closure is issued.

3. Provide alternate financial assurance as specified in this section, and obtain the department[s] written approval of the assurance provided, within 90 days after receipt by both the owner or operator and the department of a notice of cancellation of the bond from the surety.

ced Under the terms of the bond, the surety will become liable on the bond obligation when the owner or operator fails to perform as guaranteed by the bond.

cfid The penal sum of the bond shall be in an amount at least equal to the current closure cost estimate, except as provided in sub. **c8d**.

cgd Whenever the current closure cost estimate increases to an amount greater than the penal sum, the owner or operator, within 60 days after the increase, shall either cause the penal sum to be increased to an amount at least equal to the current closure cost estimate and submit evidence of the increase to the department, or obtain other financial assurance as specified in this section to cover the increase. Whenever the current closure cost estimate decreases, the penal sum may be reduced to the amount of the current closure cost estimate following written approval by the department.

chd Under the terms of the bond, the surety may cancel the bond by sending notice of cancellation by certified mail to the owner or operator and to the department. Cancellation may not occur, however, during the 120 days beginning on the date of receipt of the notice of cancellation by both the owner or operator and the department, as evidenced by the return receipts. Not less than 30 days prior to the expiration of the 120-day notice period, the owner shall deliver to the department a replacement bond or other proof of financial responsibility under this section, in the absence of which all storage, treatment or disposal operations shall immediately cease and the bond shall remain in effect as long as any obligation of the owner remains for closure.

cid The owner or operator may cancel the bond if the department has given prior written consent based on the receipt of evidence of alternate financial assurance as specified in this section.

c3d CLOSURE LETTER OF CREDIT. **cad** An owner or operator may satisfy the requirements of this section by obtaining an irrevocable letter of credit which conforms to the requirements of this subsection and submitting the letter to the department. The issuing institution shall be an entity which has the authority to issue letters of credit and whose letter-of-credit operations are regulated and examined by a federal or state agency.

cbd The wording of the letter of credit shall be identical to the

wording on the department form specified in s. NR 664.0151 c4d.

cdd The letter of credit shall be accompanied by a letter from the owner or operator referring to the letter of credit by number, issuing institution and date, and providing the following information: The EPA identification number, name and address of the facility, and the amount of funds assured for closure of the facility by the letter of credit.

ced The letter of credit shall be irrevocable and issued for a period of at least one year. The letter of credit shall provide that the expiration date will be automatically extended for a period of at least one year unless, at least 120 days before the current expiration date, the issuing institution notifies both the owner or operator and the department by certified mail of a decision not to extend the expiration date. Under the terms of the letter of credit, the 120 days will begin on the date when both the owner or operator and the department have received the notice, as evidenced by the return receipts.

cfid The letter of credit shall be issued in an amount at least equal to the current closure cost estimate, except as provided in sub. c8d.

cgd Whenever the current closure cost estimate increases to an amount greater than the amount of the credit, the owner or operator, within 60 days after the increase, shall either cause the amount of the credit to be increased so that it at least equals the current closure cost estimate and submit evidence of the increase to the department, or obtain other financial assurance as specified in this section to cover the increase. Whenever the current closure cost estimate decreases, the amount of the credit may be reduced to the amount of the current closure cost estimate following written approval by the department.

chd Following a final administrative determination by the department or EPA pursuant to 42 USC 6928 that the owner or operator has failed to perform final closure in accordance with the approved closure plan when required to do so, the department or EPA regional administrator may draw on the letter of credit.

cid If the owner or operator does not establish alternate financial assurance as specified in this section and obtain written approval of the alternate assurance from the department within 90 days after receipt by both the owner or operator and the department of a notice from the issuing institution that it has decided not to extend the letter of credit beyond the current expiration date, the department will draw on the letter of credit. The department may delay the drawing if the issuing institution grants an extension of the term of the credit. During the last 30 days of any extension the department will draw on the letter of credit if the owner or operator has failed to provide alternate financial assurance as specified in this section and obtain written approval of the assurance from the department.

cjd The department will authorize the release of the letter of credit when any of the following apply:

1. An owner or operator substitutes alternate financial assurance as specified in this section.
2. The department releases the owner or operator from the requirements of this section in accordance with sub. c10d.

c4d CLOSURE INSURANCE. cad An owner or operator may satisfy the requirements of this section by obtaining closure insurance which conforms to the requirements of this subsection and submitting a certificate of the insurance to the department. By June 1, 1984 the owner or operator shall submit to the department a letter from an insurer stating that the insurer is considering issuance of closure insurance conforming to the requirements of this subsection to the owner or operator. By August 30, 1984, the owner or operator shall submit the certificate of insurance to

the department or establish other financial assurance as specified in this section. At a minimum, the insurer shall be licensed to transact the business of insurance, or eligible to provide insurance as an excess or surplus lines insurer, in one or more states. The department, after conferring with the Wisconsin insurance commissioner, shall determine the acceptability of a surplus lines or captive insurance company to provide coverage for proof of financial responsibility. The department shall ask the insurance commissioner to provide a financial analysis of the insurer including a recommendation as to the insurer[s] ability to provide the required coverage. The department may require a periodic review of the acceptability of a surplus lines or captive insurance company.

cbd The wording of the certificate of insurance shall be identical to the wording on the department form specified in s. NR 664.0151 c5d.

ccd The closure insurance policy shall be issued for a face amount at least equal to the current closure cost estimate, except as provided in sub. c8d. The term Xface amountY means the total amount the insurer is obligated to pay under the policy. Actual payments by the insurer will not change the face amount, although the insurer[s] future liability will be lowered by the amount of the payments.

cdd The closure insurance policy shall guarantee that funds will be available to close the facility whenever final closure occurs. The policy shall also guarantee that once final closure begins, the insurer will be responsible for paying out funds, up to an amount equal to the face amount of the policy, upon the direction of the department, to the party or parties as the department specifies.

ced After beginning partial or final closure, an owner or operator or any other person authorized to conduct closure may request reimbursements for closure expenditures by submitting itemized bills to the department. The owner or operator may request reimbursements for partial closure only if the remaining value of the policy is sufficient to cover the maximum costs of closing the facility over its remaining operating life. Within 60 days after receiving bills for closure activities, the department will instruct the insurer to make reimbursements in the amounts as the department specifies in writing if the department determines that the partial or final closure expenditures are in accordance with the approved closure plan or otherwise justified. If the department has reason to believe that the maximum cost of closure over the remaining life of the facility will be significantly greater than the face amount of the policy, the department may withhold reimbursement of the amounts as the department deems prudent until the department determines, in accordance with sub. c10d, that the owner or operator is no longer required to maintain financial assurance for final closure of the particular facility. If the department does not instruct the insurer to make the reimbursements, the department will provide to the owner or operator a detailed written statement of reasons.

cfid The owner or operator shall maintain the policy in full force and effect until the department consents to termination of the policy by the owner or operator as specified in par. cjd. Failure to pay the premium, without substitution of alternate financial assurance as specified in this section, will constitute a significant violation of this chapter, warranting a remedy as the department deems necessary. The violation will be deemed to begin upon receipt by the department of a notice of future cancellation, termination or failure to renew due to nonpayment of the premium, rather than upon the date of expiration.

cgd Each policy shall contain a provision allowing assignment of the policy to a successor owner or operator. The assignment

may be conditional upon consent of the insurer, provided the consent is not unreasonably refused.

chd The policy shall provide that the insurer may not cancel, terminate or fail to renew the policy unless a replacement insurance policy or other proof of financial responsibility under this section is provided to the department by the owner or operator. The automatic renewal of the policy shall, at a minimum, provide the insured with the option of renewal at the face amount of the expiring policy. If the insurer elects to cancel, terminate or fail to renew the policy, the insurer shall provide notice by certified mail to the owner or operator and the department not less than 120 days prior to the proposed cancellation date. Cancellation, termination or failure to renew may not occur, however, during the 120 days beginning with the date of receipt of the notice by both the department and the owner or operator, as evidenced by the return receipts. Cancellation, termination or failure to renew may not occur and the policy will remain in full force and effect in the event that on or before the date of expiration any of the following apply:

1. The department deems the facility abandoned.
2. An interim license is denied, suspended or revoked.
3. Closure is ordered by the department or a U.S. district court or other court of competent jurisdiction.
4. The owner or operator is named as debtor in a voluntary or involuntary bankruptcy proceeding under 11 USC.
5. The premium due is paid.

cid Whenever the current closure cost estimate increases to an amount greater than the face amount of the policy, the owner or operator, within 60 days after the increase, shall either cause the face amount to be increased to an amount at least equal to the current closure cost estimate and submit evidence of the increase to the department, or obtain other financial assurance as specified in this section to cover the increase. Whenever the current closure cost estimate decreases, the face amount may be reduced to the amount of the current closure cost estimate following written approval by the department.

cjd The department will give written consent to the owner or operator that the owner or operator may terminate the insurance policy when any of the following apply:

1. An owner or operator substitutes alternate financial assurance as specified in this section.
2. The department releases the owner or operator from the requirements of this section in accordance with sub. **c10d**.

c5d NET WORTH TEST FOR CLOSURE. **cad** An owner or operator of a disposal facility may use the net worth test to provide financial responsibility if all of the following are met:

1. Only a company that meets the definition in s. **289.41 c1d cbd**, Stats., may use the net worth method of providing proof of financial responsibility.
2. The owner or operator shall comply with the net worth test requirements of s. **289.41 c4d, c6d, and c7d**, Stats., and the minimum security requirements of s. **289.41 c9d**, Stats., whichever are applicable. The updated net worth test information required under s. **289.41 c4d**, Stats., shall be submitted annually to the department within 90 days after the close of the company[s fiscal year.

cbd For companies with more than one facility, the total cost of compliance for all facilities shall be used to determine the net worth to closure and long-term care cost ratio.

c6d CLOSURE DEPOSIT WITH THE DEPARTMENT. An owner may deposit cash, certificates of deposit or U.S. government securities with the department. The deposit must be accompanied by a signed duplicate original of Form 4430-028 as specified in s.

NR 664.0151 c14d. The amount of the deposit shall be determined according to s. **NR 665.0142** and shall be submitted as part of the interim license application. Cash deposits placed with the department shall be segregated and invested in an interest bearing account. All interest payments shall be accumulated in the account. The department shall have the right to use part or all of the funds to carry out the closure requirements of the written closure plan or the applicable requirements in s. **NR 665.0112** if the owner fails to do so.

c7d CLOSURE ESCROW ACCOUNT. **cad** An owner or operator may satisfy the requirements of this section by establishing a closure escrow account which conforms to the requirements of this subsection and submitting an originally signed duplicate of the escrow agreement to the department. An owner or operator of a new facility shall submit the originally signed duplicate of the escrow agreement to the department at least 60 days before the date on which hazardous waste is first received for treatment, storage or disposal. The escrow agent shall be an entity which has the authority to act as an escrow agent, and the escrow account shall be established with a bank or financial institution which is examined and regulated by the state or a federal agency.

cbd The wording of the escrow agreement shall be identical to the wording on the department form specified in s. **NR 664.0151 c6d cad**, and the escrow agreement shall be accompanied by a formal certification of acknowledgment as specified in s. **NR 664.0151 c6d cbd**. Schedule A of the escrow agreement shall be updated within 60 days after a change in the amount of the current closure cost estimate covered by the agreement.

ccd Payments into the escrow account shall be made annually by the owner or operator over the term of the interim license and over the remaining operating life of the facility as estimated in the closure plan. For the purposes of this section, this period is referred to as the Xpay-in period.Y The payments into the closure escrow account shall be made as follows:

1. For a new facility, the first payment shall be made before the initial receipt of hazardous waste for treatment, storage or disposal. A receipt from the escrow agent for this payment shall be submitted by the owner or operator to the department before this initial receipt of hazardous waste. The first payment shall be at least equal to the current closure cost estimate, except as provided in sub. **c8d**, divided by the number of years in the pay-in period. Subsequent payments shall be made no later than 30 days after each anniversary date of the first payment. The amount of each subsequent payment shall be determined by this formula:

$$\text{Next payment} = \frac{\text{CE} - \text{CV}}{\text{Y}}$$

where CE is the current closure cost estimate, CV is the current value of the escrow account and Y is the number of years remaining in the pay-in period.

2. If an owner or operator establishes a escrow account as specified in this subsection, and the value of that escrow account is less than the current closure cost estimate when a license is awarded for the facility, the amount of the current closure cost estimate still to be paid into the escrow account shall be paid in over the pay-in period as defined in the introduction to this paragraph. Payments shall continue to be made no later than 30 days after each anniversary date of the first payment. The amount of each payment shall be determined by this formula:

$$\text{Next payment} = \frac{\text{CE} - \text{CV}}{\text{Y}}$$

where CE is the current closure cost estimate, CV is the cur-

rent value of the escrow account and Y is the number of years remaining in the pay-in period.

cdd The owner or operator may accelerate payments into the escrow account or may deposit the full amount of the current closure cost estimate at the time the account is established. However, the owner or operator shall maintain the value of the account at no less than the value that the account would have if annual payments were made as specified in par. **ccd**.

ced If the owner or operator establishes a closure escrow account after having used one or more alternate mechanisms specified in this section, the first payment shall be in at least the amount that the account would contain if the escrow account were established initially and annual payments were made as specified in par. **ccd**.

cfb After the pay-in period is completed, whenever the current closure cost estimate changes, the owner or operator shall compare the new estimate with the escrow agent[s most recent annual valuation of the escrow account. If the value of the account is less than the amount of the new estimate, the owner or operator, within 60 days after the change in the cost estimate, shall either deposit an amount into the account so that its value after this deposit at least equals the amount of the current closure cost estimate, or obtain other financial assurance as specified in this section to cover the difference.

cgd If the value of the escrow account is greater than the total amount of the current closure cost estimate, the owner or operator may submit a written request to the department for release of the amount in excess of the current closure cost estimate.

chd If an owner or operator substitutes other financial assurance as specified in this section for all or part of the escrow account, the owner or operator may submit a written request to the department for release of the amount in excess of the current closure cost estimate covered by the escrow account

cid Within 60 days after receiving a request from the owner or operator for release of funds as specified in par. **cgd** or **chd**, the department will instruct the escrow agent to release to the owner or operator funds as the department specifies in writing.

cjd After beginning partial or final closure, an owner or operator or another person authorized to conduct partial or final closure may request reimbursements for partial or final closure expenditures by submitting itemized bills to the department. The owner or operator may request reimbursements for partial closure only if sufficient funds are remaining in the escrow account to cover the maximum costs of closing the facility over its remaining operating life. Within 60 days after receiving bills for partial or final closure activities, the department will instruct the escrow agent to make reimbursements in those amounts as the department specifies in writing, if the department determines that the partial or final closure expenditures are in accordance with the approved closure plan, or otherwise justified. If the department has reason to believe that the maximum cost of closure over the remaining life of the facility will be significantly greater than the value of the escrow account, the department may withhold reimbursements of amounts as the department deems prudent until the department determines, in accordance with sub. **c10d** that the owner or operator is no longer required to maintain financial assurance for final closure of the facility. If the department does not instruct the escrow agent to make the reimbursements, the department will provide the owner or operator with a detailed written statement of reasons.

ckd The department will agree to termination of the escrow account when one of the following applies:

1. An owner or operator substitutes alternate financial assurance as specified in this section.

2. The department releases the owner or operator from the requirements of this section in accordance with sub. **c10d**.

c8d USE OF MULTIPLE FINANCIAL MECHANISMS. An owner or operator may satisfy the requirements of this section by establishing more than one financial mechanism per facility. These mechanisms are limited to trust funds, surety bonds guaranteeing payment, deposits with the department, escrow accounts, letters of credit and insurance. The mechanisms shall be as specified in subs. **c1d** to **c4d**, **c6d** and **c7d**, except that it is the combination of mechanisms, rather than the single mechanism, which shall provide financial assurance for an amount at least equal to the current closure cost estimate. The department may use any or all of the mechanisms to provide for closure of the facility.

c9d USE OF A FINANCIAL MECHANISM FOR MULTIPLE FACILITIES. An owner or operator may use a financial assurance mechanism specified in this section to meet the requirements of this section for more than one facility. Evidence of financial assurance submitted to the department shall include a list showing, for each facility, the EPA identification number, name, address and the amount of funds for closure assured by the mechanism. If the facilities covered by the mechanism are in more than one state, identical evidence of financial assurance shall be submitted to and maintained with the state agency regulating hazardous waste or with the appropriate U.S. EPA regional administrator if the facility is located in unauthorized states. The amount of funds available through the mechanism shall be no less than the sum of funds that would be available if a separate mechanism had been established and maintained for each facility. In directing funds available through the mechanism for closure of any of the facilities covered by the mechanism, the department may direct only the amount of funds designated for that facility, unless the owner or operator agrees to the use of additional funds available under the mechanism.

c10d RELEASE OF THE OWNER OR OPERATOR FROM THE REQUIREMENTS OF THIS SECTION. Within 60 days after receiving certifications from the owner or operator and a qualified professional engineer that final closure has been completed in accordance with the approved closure plan, the department will notify the owner or operator in writing that the owner or operator is no longer required by this section to maintain financial assurance for final closure of the facility, unless the department has reason to believe that final closure has not been in accordance with the approved closure plan. The department shall provide the owner or operator a detailed written statement of any reason to believe that closure has not been in accordance with the approved closure plan.

Note: The department may consider other financial commitments as allowed by s. 289.41 **c3d** *cad* 5., Stats.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. **c5d** *cad* 2., **c10d** Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. **c3d** *chd* Register August 2020 No. 776, eff. 9-1-20.

NR 665.0144 Cost estimate for long-term care. **c1d**

The owner or operator of a hazardous waste disposal unit shall have a detailed written estimate, in current dollars, of the annual cost of long-term care monitoring and maintenance of the facility according to the applicable long-term care rules in ss. **NR 665.0117** to **665.0120**, **665.0228**, **665.0258** and **665.0310**.

cad The long-term care cost estimate shall be based on the costs to the owner or operator of hiring a third party to conduct long-term care activities. A third party is a party who is neither a parent corporation nor subsidiary of the owner or operator.

cbd The long-term care cost estimate is calculated by multiplying the annual long-term care cost estimate by the number of years of long-term care required under s. **NR 665.0117**.

c2d During the active life of the facility, the owner or opera-

tor shall adjust the long-term care cost estimate for inflation within 60 days prior to the anniversary date of the establishment of the financial instrument or instruments used to comply with s. NR 665.0145. For owners or operators of disposal facilities using the net worth test, the long-term care cost estimate shall be updated for inflation as specified in s. 289.41 c5d cdd, Stats. The adjustment may be made by recalculating the long-term care cost estimate in current dollars or by using an inflation factor derived from the most recent implicit price deflator for gross domestic product published by the U.S. department of commerce in its *Survey of Current Business* as specified in s. NR 665.0145 c2d cad and cbd. The inflation factor is the result of dividing the latest published annual deflator by the deflator for the previous year.

cad The first adjustment is made by multiplying the long-term care cost estimate by the inflation factor. The result is the adjusted long-term care cost estimate.

cbd Subsequent adjustments are made by multiplying the latest adjusted long-term care cost estimate by the latest inflation factor.

c3d During the active life of the facility, the owner or operator shall revise the long-term care cost estimate no later than 30 days after a revision to the long-term care plan which increases the cost of long-term care. If the owner or operator has an approved long-term care plan, the long-term care cost estimate shall be revised no later than 30 days after the department has approved the request to modify the plan, if the change in the long-term care plan increases the cost of long-term care. The revised long-term care cost estimate shall be adjusted for inflation as specified in sub. c2d.

c4d The owner or operator shall keep the following at the facility during the operating life of the facility: the latest long-term care cost estimate prepared in accordance with subs. c1d and c3d and, when this estimate has been adjusted in accordance with sub. c2d, the latest adjusted long-term care cost estimate.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0145 Financial assurance for long-term care. By June 1, 1984, an owner or operator of a facility with a hazardous waste disposal unit shall establish financial assurance for long-term care of the disposal unit or units.

c1d LONG-TERM CARE TRUST FUND. cad An owner or operator may satisfy the requirements of this section by establishing a long-term care trust fund which conforms to the requirements of this subsection and submitting an originally signed duplicate of the trust agreement to the department. The trustee shall be an entity which has the authority to act as a trustee and whose trust operations are regulated and examined by a federal or state agency.

cbd The wording of the trust agreement shall be identical to the wording on the department form specified in s. NR 664.0151 c1d cad, and the trust agreement shall be accompanied by a formal certification of acknowledgment as specified in s. NR 664.0151 c1d cbd. Schedule A of the trust agreement shall be updated within 60 days after a change in the amount of the current long-term care cost estimate covered by the agreement.

ccd Payments into the trust fund shall be made annually by the owner or operator over the 20 years beginning on June 1, 1984 or over the remaining operating life of the facility as estimated in the closure plan, whichever period is shorter. For the purposes of this section, this period is referred to as the Xpay-in period.Y The payments into the long-term care trust fund shall be made as follows:

1. The first payment shall be made by June 1, 1984, except as provided in par. ced. The first payment shall be at least equal to

the current long-term care cost estimate, except as provided in sub. c8d, divided by the number of years in the pay-in period.

2. Subsequent payments shall be made no later than 30 days after each anniversary date of the first payment. The amount of each subsequent payment shall be determined by this formula:

$$\text{Next payment} = \frac{\text{CE} - \text{CV}}{\text{Y}}$$

where CE is the current long-term care cost estimate, CV is the current value of the trust fund and Y is the number of years remaining in the pay-in period.

cdd The owner or operator may accelerate payments into the trust fund or the owner or operator may deposit the full amount of the current long-term care cost estimate at the time the fund is established. However, the owner or operator shall maintain the value of the fund at no less than the value that the fund would have if annual payments were made as specified in par. ccd.

ced If the owner or operator establishes a long-term care trust fund after having used one or more alternate mechanisms specified in this section, the first payment shall be in at least the amount that the fund would contain if the trust fund were established initially and annual payments made as specified in par. ccd.

cfd After the pay-in period is completed, whenever the current long-term care cost estimate changes during the operating life of the facility, the owner or operator shall compare the new estimate with the trustee[s] most recent annual valuation of the trust fund. If the value of the fund is less than the amount of the new estimate, the owner or operator, within 60 days after the change in the cost estimate, shall either deposit an amount into the fund so that its value after this deposit at least equals the amount of the current long-term care cost estimate, or obtain other financial assurance as specified in this section to cover the difference.

cgd During the operating life of the facility, if the value of the trust fund is greater than the total amount of the current long-term care cost estimate, the owner or operator may submit a written request to the department for release of the amount in excess of the current long-term care cost estimate.

chd If an owner or operator substitutes other financial assurance as specified in this section for all or part of the trust fund, the owner or operator may submit a written request to the department for release of the amount in excess of the current long-term care cost estimate covered by the trust fund.

cid Within 60 days after receiving a request from the owner or operator for release of funds as specified in par. cgd or chd, the department will instruct the trustee to release to the owner or operator the funds as the department specifies in writing.

cjd During the period of long-term care, the department may approve a release of funds if the owner or operator demonstrates to the department that the value of the trust fund exceeds the remaining cost of long-term care.

ckd An owner or operator or any other person authorized to conduct long-term care may request reimbursements for long-term care expenditures by submitting itemized bills to the department. Within 60 days after receiving bills for long-term care activities, the department will instruct the trustee to make reimbursements in those amounts as the department specifies in writing, if the department determines that the long-term care expenditures are in accordance with the approved long-term care plan or otherwise justified. If the department does not instruct the trustee to make the reimbursements, the department will provide

the owner or operator with a detailed written statement of reasons.

cLd The department will agree to termination of the trust when one of the following applies:

1. An owner or operator substitutes alternate financial assurance as specified in this section.
2. The department releases the owner or operator from the requirements of this section in accordance with sub. c10d.

c2d SURETY BOND GUARANTEEING PAYMENT INTO A LONG TERM CARE TRUST FUND. cad An owner or operator may satisfy the requirements of this section by obtaining a surety bond which conforms to the requirements of this subsection and submitting the bond to the department. The surety company issuing the bond shall, at a minimum, be among those listed as acceptable sureties on federal bonds in Circular 570 of the U.S. department of the treasury.

cbd The wording of the surety bond shall be identical to the wording on the department form specified in s. NR 664.0151 c2d.

ccd The owner or operator who uses a surety bond to satisfy the requirements of this section shall also establish a standby trust fund. Under the terms of the bond, all payments made shall be deposited by the surety directly into the standby trust fund in accordance with instructions from the department. This standby trust fund must meet the requirements specified in sub. c1d except for all of the following:

1. An originally signed duplicate of the trust agreement must be submitted to the department with the surety bond.
2. Until the standby trust fund is funded pursuant to the requirements of this section, all of the following are not required:
 - a. Payments into the trust fund as specified in sub. c1d.
 - b. Updating of Schedule A of the trust agreement csee Form 4430-022d to show current closure cost estimates.
 - c. Annual valuations as required by the trust agreement.
 - d. Notices of nonpayment as required by the trust agreement.

cdd The bond must guarantee that the owner or operator will do any of the following:

1. Fund the standby trust fund in an amount equal to the penal sum of the bond before the beginning of final closure of the facility.
2. Fund the standby trust fund in an amount equal to the penal sum within 15 days after an administrative order to begin final closure issued by the department becomes final, or within 15 days after an order to begin final closure is issued.
3. Provide alternate financial assurance as specified in this section, and obtain the department[s written approval of the assurance provided, within 90 days after receipt by both the owner or operator and the department of a notice of cancellation of the bond from the surety.

ced Under the terms of the bond, the surety will become liable on the bond obligation when the owner or operator fails to perform as guaranteed by the bond.

cfid The penal sum of the bond shall be in an amount at least equal to the current long-term care cost estimate, except as provided in sub. c8d.

cgd Whenever the current long-term care cost estimate increases to an amount greater than the penal sum, the owner or operator, within 60 days after the increase, shall either cause the penal sum to be increased to an amount at least equal to the current long-term care cost estimate and submit evidence of the increase to the department, or obtain other financial assurance as specified in this section to cover the increase. Whenever the current long-term care cost estimate decreases, the penal sum may be re-

duced to the amount of the current long-term care cost estimate following written approval by the department.

chd Under the terms of the bond, the surety may cancel the bond by sending notice of cancellation by certified mail to the owner or operator and to the department. Cancellation may not occur, however, during the 120 days beginning on the date of receipt of the notice of cancellation by both the owner or operator and the department, as evidenced by the return receipts. Not less than 30 days prior to the expiration of the 120-day notice period, the owner shall deliver to the department a replacement bond or other proof of financial responsibility under this section, in the absence of which all storage, treatment or disposal operations shall immediately cease and the bond shall remain in effect as long as any obligation of the owner remains for long-term care

cid The owner or operator may cancel the bond if the department has given prior written consent based on the receipt of evidence of alternate financial assurance as specified in this section.

c3d LONG-TERM CARE LETTER OF CREDIT. cad An owner or operator may satisfy the requirements of this section by obtaining an irrevocable letter of credit which conforms to the requirements of this subsection and submitting the letter to the department. The issuing institution shall be an entity which has the authority to issue letters of credit and whose letter-of-credit operations are regulated and examined by a federal or state agency.

cbd The wording of the letter of credit shall be identical to the wording on the department form specified in s. NR 664.0151 c4d.

cdd The letter of credit shall be accompanied by a letter from the owner or operator referring to the letter of credit by number, issuing institution and date, and providing the following information: The EPA identification number, name and address of the facility, and the amount of funds assured for long-term care of the facility by the letter of credit.

ced The letter of credit shall be irrevocable and issued for a period of at least one year. The letter of credit shall provide that the expiration date will be automatically extended for a period of at least one year unless, at least 120 days before the current expiration date, the issuing institution notifies both the owner or operator and the department by certified mail of a decision not to extend the expiration date. Under the terms of the letter of credit, the 120 days will begin on the date when both the owner or operator and the department have received the notice, as evidenced by the return receipts.

cfid The letter of credit shall be issued in an amount at least equal to the current long-term care cost estimate, except as provided in sub. c8d.

cgd Whenever the current long-term care cost estimate increases to an amount greater than the amount of the credit during the operating life of the facility, the owner or operator, within 60 days after the increase, shall either cause the amount of the credit to be increased so that it at least equals the current long-term care cost estimate and submit evidence of the increase to the department, or obtain other financial assurance as specified in this section to cover the increase. Whenever the current long-term care cost estimate decreases during the operating life of the facility, the amount of the credit may be reduced to the amount of the current long-term care cost estimate following written approval by the department.

chd During the period of long-term care, the department may approve a decrease in the amount of the letter of credit if the owner or operator demonstrates to the department that the amount exceeds the remaining cost of long-term care.

cid Following a determination by the department that the owner or operator has failed to perform long-term care in accor-

dance with the approved long-term care plan and other license requirements, the department may draw on the letter of credit.

cjd If the owner or operator does not establish alternate financial assurance as specified in this section and obtain written approval of the alternate assurance from the department within 90 days after receipt by both the owner or operator and the department of a notice from the issuing institution that it has decided not to extend the letter of credit beyond the current expiration date, the department will draw on the letter of credit. The department may delay the drawing if the issuing institution grants an extension of the term of the credit. During the last 30 days of any extension the department will draw on the letter of credit if the owner or operator has failed to provide alternate financial assurance as specified in this section and obtain written approval of the assurance from the department.

cLd The department will authorize the release of the letter of credit when any of the following apply:

1. An owner or operator substitutes alternate financial assurance as specified in this section.
2. The department releases the owner or operator from the requirements of this section in accordance with sub. c10d.

c4d LONG-TERM CARE INSURANCE. cad An owner or operator may satisfy the requirements of this section by obtaining long-term care insurance which conforms to the requirements of this subsection and submitting a certificate of the insurance to the department. By June 1, 1984 the owner or operator shall submit to the department a letter from an insurer stating that the insurer is considering issuance of long-term care insurance conforming to the requirements of this subsection to the owner or operator. By August 30, 1984, the owner or operator shall submit the certificate of insurance to the department or establish other financial assurance as specified in this section. At a minimum, the insurer shall be licensed to transact the business of insurance, or eligible to provide insurance as an excess or surplus lines insurer, in one or more States. The department, after conferring with the Wisconsin insurance commissioner, shall determine the acceptability of a surplus lines or captive insurance company to provide coverage for proof of financial responsibility. The department shall ask the insurance commissioner to provide a financial analysis of the insurer including a recommendation as to the insurer[s] ability to provide the required coverage. The department may require a periodic review of the acceptability of a surplus lines or captive insurance company.

cbd The wording of the certificate of insurance shall be identical to the wording on the department form specified in s. NR 664.0151 c5d.

ccd The long-term care insurance policy shall be issued for a face amount at least equal to the current long-term care cost estimate, except as provided in sub. c8d. The term Xface amountY means the total amount the insurer is obligated to pay under the policy. Actual payments by the insurer will not change the face amount, although the insurer[s] future liability will be lowered by the amount of the payments.

cdd The long-term care insurance policy shall guarantee that funds will be available to provide long-term care of the facility whenever the long-term care period begins. The policy shall also guarantee that once long-term care begins the insurer will be responsible for paying out funds, up to an amount equal to the face amount of the policy, upon the direction of the department, to the party or parties as the department specifies.

ced An owner or operator or any other person authorized to perform long-term care may request reimbursement for long-term care expenditures by submitting itemized bills to the department. Within 60 days after receiving bills for long-term care activities,

the department will instruct the insurer to make reimbursements in those amounts as the department specifies in writing, if the department determines that the long-term care expenditures are in accordance with the approved long-term care plan or otherwise justified. If the department does not instruct the insurer to make the reimbursements, the department will provide a detailed written statement of reasons.

cfD The owner or operator shall maintain the policy in full force and effect until the department consents to termination of the policy by the owner or operator as specified in par. ckd. Failure to pay the premium, without substitution of alternate financial assurance as specified in the section, will constitute a significant violation of this chapter, warranting a remedy as the department deems necessary. The violation will be deemed to begin upon receipt by the department of a notice of future cancellation, termination or failure to renew due to nonpayment of the premium, rather than upon the date of expiration.

cgd Each policy shall contain a provision allowing assignment of the policy to a successor owner or operator. The assignment may be conditional upon consent of the insurer, provided the consent is not unreasonably refused.

chd The policy shall provide that the insurer may not cancel, terminate or fail to renew the policy unless a replacement insurance policy or other proof of financial responsibility under this section is provided to the department by the owner or operator. The automatic renewal of the policy shall, at a minimum, provide the insured with the option of renewal at the face amount of the expiring policy. If the insurer elects to cancel, terminate or fail to renew the policy, the insurer shall provide notice by certified mail to the owner or operator and the department not less than 120 days prior to the proposed cancellation date. Cancellation, termination or failure to renew may not occur, however, during the 120 days beginning with the date of receipt of the notice by both the department and the owner or operator, as evidenced by the return receipts. Cancellation, termination or failure to renew may not occur and the policy will remain in full force and effect in the event that on or before the date of expiration any of the following apply:

1. The department deems the facility abandoned.
2. Interim license is denied, suspended or revoked.
3. Closure is ordered by the department or a U.S. district court or other court of competent jurisdiction.
4. The owner or operator is named as debtor in a voluntary or involuntary bankruptcy proceeding under 11 USC.
5. The premium due is paid.

cid Whenever the current long-term care cost estimate increases to an amount greater than the face amount of the policy during the operating life of the facility, the owner or operator, within 60 days after the increase, shall either cause the face amount to be increased to an amount at least equal to the current long-term care cost estimate and submit evidence of the increase to the department, or obtain other financial assurance as specified in this section to cover the increase. Whenever the current long-term care cost estimate decreases during the operating life of the facility, the face amount may be reduced to the amount of the current long-term care cost estimate following written approval by the department.

cjd Commencing on the date that liability to make payments pursuant to the policy accrues, the insurer will thereafter annually increase the face amount of the policy. The increase shall be equivalent to the face amounts of the policy, less any payments made, multiplied by an amount equivalent to 85 percent of the most recent investment rate or of the equivalent coupon-issue

yield announced by the U.S. treasury for 26-week treasury securities.

ckd The department will give written consent to the owner or operator that the department may terminate the insurance policy when any of the following apply:

1. An owner or operator substitutes alternate financial assurance as specified in this section.
2. The department releases the owner or operator from the requirements of this section in accordance with sub. c10d.

c5d NET WORTH TEST FOR LONG-TERM CARE. cad An owner or operator of a disposal facility may use the net worth test to provide financial responsibility if all of the following are met:

1. Only a company that meets the definition in s. 289.41 c1d cbd, Stats., may use the net worth method of providing proof of financial responsibility.
2. The owner shall comply with the net worth test requirements of s. 289.41 c4d, c6d, and c7d, Stats., and the minimum security requirements of s. 289.41 c9d, Stats., whichever are applicable. The updated net worth test information required under s. 289.41 c4d, Stats., shall be submitted annually to the department within 90 days after the close of the company[s] fiscal year.

cbd For companies with more than one facility, the total cost of compliance for all facilities shall be used to determine the net worth to closure and long-term care cost ratio.

c6d LONG TERM CARE DEPOSIT WITH THE DEPARTMENT. An owner may deposit cash, certificates of deposit or U.S. government securities with the department. The deposit must be accompanied by a signed duplicate original of Form 4430-028 as specified in s. NR 664.0151 c14d. The amount of the deposit shall be determined according to s. NR 665.0144 and shall be submitted as part of an interim license application. Cash deposits placed with the department shall be segregated and invested in an interest bearing account. All interest payments shall be accumulated in the account. The department shall have the right to use part or all of the funds to carry out the long-term care requirements of the written long-term care plan or the applicable requirements in s. NR 665.0118 if the owner fails to do so.

c7d ESCROW ACCOUNT. cad An owner or operator may satisfy the requirements of this section by establishing a long-term care escrow account which conforms to the requirements of this subsection and submitting an originally signed duplicate of the escrow agreement to the department. An owner or operator of a new facility shall submit the originally signed duplicate of the escrow agreement to the department at least 60 days before the date on which hazardous waste is first received for disposal. The escrow agent shall be an entity which has the authority to act as an escrow agent and the escrow account shall be established with a bank or financial institution which is regulated and examined by a federal or state agency.

cbd The wording of the escrow agreement shall be identical to the wording on the department form specified in s. NR 664.0151 c6d cad, and the escrow agreement shall be accompanied by a formal certification of acknowledgment as specified in s. NR 664.0151 c6d cbd. Schedule A of the escrow agreement shall be updated within 60 days after a change in the amount of the current long-term care cost estimate covered by the agreement.

ccd Payments into the escrow account shall be made annually by the owner or operator over the term of the interim license and over the remaining operating life of the facility as estimated in the closure plan. For the purposes of this section, this period is referred to as the Xpay-in period.Y The payments into the long-term care escrow account shall be made as follows:

1. For a new facility, the first payment shall be made before

the initial receipt of hazardous waste for disposal. A receipt from the escrow agent for this payment shall be submitted by the owner or operator to the department before this initial receipt of hazardous waste. The first payment shall be at least equal to the current long-term care cost estimate, except as provided in sub. c8d, divided by the number of years in the pay-in period. Subsequent payments shall be made no later than 30 days after each anniversary date of the first payment. The amount of each subsequent payment shall be determined by this formula:

$$\text{Next payment} = \frac{\text{CE} - \text{CV}}{\text{Y}}$$

where CE is the current long-term care cost estimate, CV is the current value of the escrow account and Y is the number of years remaining in the pay-in period.

2. If an owner or operator establishes a escrow account as specified in this subsection, and the value of that escrow account is less than the current long-term care cost estimate when an interim license is awarded for the facility, the amount of the current long-term care cost estimate still to be paid into the account shall be paid in over the pay-in period as defined in the introduction to this paragraph. Payments shall continue to be made no later than 30 days after each anniversary date of the first payment. The amount of each payment shall be determined by this formula:

$$\text{Next payment} = \frac{\text{CE} - \text{CV}}{\text{Y}}$$

where CE is the current long-term care cost estimate, CV is the current value of the escrow account and Y is the number of years remaining in the pay-in period.

cdd The owner or operator may accelerate payments into the escrow account or may deposit the full amount of the current long-term care cost estimate at the time the account is established. However, the owner or operator shall maintain the value of the account at no less than the value that the account would have if annual payments were made as specified in par. ccd.

ced If the owner or operator establishes a long-term care escrow account after having used one or more alternate mechanisms specified in this section, the first payment shall be in at least the amount that the account would contain if the escrow account were established initially and annual payments made as specified in par. ccd.

cfđ After the pay-in period is completed, whenever the current long-term care cost estimate changes during the operating life of the facility, the owner or operator shall compare the new estimate with the escrow agent[s] most recent annual valuation of the escrow account. If the value of the account is less than the amount of the new estimate, the owner or operator, within 60 days after the change in the cost estimate, shall either deposit an amount into the account so that its value after this deposit at least equals the amount of the current long-term care cost estimate, or obtain other financial assurance as specified in this section to cover the difference.

cgd During the operating life of the facility, if the value of the escrow account is greater than the total amount of the current long-term care cost estimate, the owner or operator may submit a written request to the department for release of the amount in excess of the current long-term care cost estimate.

chđ If an owner or operator substitutes other financial assurance as specified in this section for all or part of the escrow account, the owner or operator may submit a written request to the department for release of the amount in excess of the current long-term care cost estimate covered by the escrow account.

cid Within 60 days after receiving a request from the owner or operator for release of funds as specified in par. [cgd](#) or [chd](#), the department will instruct the escrow agent to release to the owner or operator funds as the department specifies in writing.

cjd During the period of long-term care, the department may approve a release of funds if the owner or operator demonstrates to the department that the value of the escrow account exceeds the remaining cost of long-term care.

ckd An owner or operator or any other person authorized to conduct long-term care may request reimbursements for long-term care expenditures by submitting itemized bills to the department. Within 60 days after receiving bills for long-term care activities, the department will instruct the escrow agent to make reimbursements in those amounts as the department specifies in writing, if the department determines that the long-term care expenditures are in accordance with the approved long-term care plan or otherwise justified. If the department does not instruct the escrow agent to make the reimbursements, the department will provide the owner or operator with a detailed written statement of reasons.

cLd The department will agree to termination of the escrow account when one of the following applies:

1. An owner or operator substitutes alternate financial assurance as specified in this section.
2. The department releases the owner or operator from the requirements of this section in accordance with sub. [c10d](#).

c8d USE OF MULTIPLE FINANCIAL MECHANISMS. An owner or operator may satisfy the requirements of this section by establishing more than one financial mechanism per facility. These mechanisms are limited to trust funds, surety bonds guaranteeing payment, deposits with the department, escrow accounts, letters of credit and insurance. The mechanisms shall be as specified in subs. [c1d](#) to [c4d](#), [c6d](#) and [c7d](#) except that it is the combination of mechanisms, rather than the single mechanism, which shall provide financial assurance for an amount at least equal to the current long-term care cost estimate. The department may use any or all of the mechanisms to provide for long-term care of the facility.

c9d USE OF A FINANCIAL MECHANISM FOR MULTIPLE FACILITIES. An owner or operator may use a financial assurance mechanism specified in this section to meet the requirements of this section for more than one facility. Evidence of financial assurance submitted to the department shall include a list showing, for each facility, the EPA identification number, name, address and the amount of funds for long-term care assured by the mechanism. If the facilities covered by the mechanism are in more than one state, identical evidence of financial assurance shall be submitted to and maintained with the state agency regulating hazardous waste or with the appropriate EPA regional administrator if the facilities are located in unauthorized states. The amount of funds available through the mechanism shall be no less than the sum of funds that would be available if a separate mechanism had been established and maintained for each facility. In directing funds available through the mechanism for long-term care of any of the facilities covered by the mechanism, the department may direct only the amount of funds designated for that facility, unless the owner or operator agrees to the use of additional funds available under the mechanism.

c10d RELEASE OF THE OWNER OR OPERATOR FROM THE REQUIREMENTS OF THIS SECTION. Within 60 days after receiving certifications from the owner or operator and a qualified professional engineer that the long-term care period has been completed in accordance with the approved long-term care plan, the department will notify the owner or operator in writing that the

owner or operator is no longer required by this section to maintain financial assurance for long-term care of that unit, unless the department has reason to believe that long-term care has not been in accordance with the approved long-term care plan. The department will provide the owner or operator a detailed written statement of any reason to believe that long-term care has not been in accordance with the approved long-term care plan.

Note: The department may consider other financial commitments as allowed by s. [289.41 c3d cad 5.](#), Stats.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c5d cad 2., c10d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0146 Use of a mechanism for financial assurance of both closure and long-term care. An owner or operator may satisfy the requirements for financial assurance for both closure and long-term care for one or more facilities by using a trust fund, surety payment bond, deposit with the department, escrow account, letter of credit, insurance or net worth test that meets the specifications for the mechanism in both ss. [NR 665.0143](#) and [665.0145](#). The amount of funds available through the mechanism shall be no less than the sum of funds that would be available if a separate mechanism had been established and maintained for financial assurance of closure and of long-term care.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0147 Liability requirements. c1d COVERAGE FOR SUDDEN ACCIDENTAL OCCURRENCES. An owner or operator of a hazardous waste treatment, storage or disposal facility, or a group of facilities, shall demonstrate financial responsibility for bodily injury and property damage to third parties caused by sudden accidental occurrences arising from operations of the facility or group of facilities. The owner or operator shall have and maintain liability coverage for sudden accidental occurrences in the amount of at least \$1 million per occurrence with an annual aggregate of at least \$2 million, exclusive of legal defense costs. This liability coverage may be demonstrated as specified in par. [cad](#), [cbd](#), [ccd](#), [cdd](#), [ced](#) or [cfd](#):

cad An owner or operator may demonstrate the required liability coverage by having liability insurance as specified in this subsection.

1. Each insurance policy shall be amended by attachment of the hazardous waste facility liability endorsement, or evidenced by a certificate of liability insurance. The wording of the endorsement shall be identical to the wording specified in s. [NR 664.0151 c9d](#). The wording of the certificate of insurance shall be identical to the wording specified in s. [NR 664.0151 c10d](#). The owner or operator shall submit a signed duplicate original of the endorsement or the certificate of insurance to the department. If the facilities are located in more than one state, identical evidence of financial assurance shall be submitted to and maintained with the state agency regulating hazardous waste or with the appropriate EPA regional administrator if the facilities are located in unauthorized states. If requested by a regional administrator or the department, the owner or operator shall provide a signed duplicate original of the insurance policy.

2. Each insurance policy shall be issued by an insurer which, at a minimum, is licensed to transact the business of insurance, or eligible to provide insurance as an excess or surplus lines insurer, in one or more States.

3. The department, after conferring with the Wisconsin insurance commissioner, shall determine the acceptability of a surplus lines or captive insurance company to provide coverage for proof of financial responsibility. The department shall ask the insurance commissioner to provide a financial analysis of the insurer including a recommendation as to the insurer[s] ability to

provide the required coverage. The department may require a periodic review of the acceptability of a surplus lines or captive insurance company.

cbd An owner or operator may meet the requirements of this section by passing a financial test or using the guarantee for liability coverage as specified in subs. **c6d** and **c7d**.

ccd An owner or operator may meet the requirements of this section by obtaining a letter of credit for liability coverage as specified in sub. **c8d**.

cdd An owner or operator may meet the requirements of this section by obtaining a surety bond for liability coverage as specified in sub. **c9d**.

ced An owner or operator may meet the requirements of this section by obtaining a trust fund for liability coverage as specified in sub. **c10d**.

cfb An owner or operator may demonstrate the required liability coverage through the use of combinations of insurance, financial test, guarantee, letter of credit, surety bond and trust fund, except that the owner or operator may not combine a financial test covering part of the liability coverage requirement with a guarantee unless the financial statement of the owner or operator is not consolidated with the financial statement of the guarantor. The amounts of coverage demonstrated shall total at least the minimum amounts required by this section. If the owner or operator demonstrates the required coverage through the use of a combination of financial assurances under this subsection, the owner or operator shall specify at least one assurance as XprimaryY coverage and shall specify other assurance as XexcessY coverage.

cgd An owner or operator shall notify the department in writing within 30 days whenever any of the following occur:

1. A claim results in a reduction in the amount of financial assurance for liability coverage provided by a financial instrument authorized in pars. **cad** to **cfb**.

2. A Certification of Valid Claim for bodily injury or property damages caused by a sudden or non-sudden accidental occurrence arising from the operation of a hazardous waste treatment, storage or disposal facility is entered between the owner or operator and third-party claimant for liability coverage under pars. **cad** to **cfb**.

3. A final court order establishing a judgment for bodily injury or property damage caused by a sudden or non-sudden accidental occurrence arising from the operation of a hazardous waste treatment, storage or disposal facility is issued against the owner or operator or an instrument that is providing financial assurance for liability coverage under pars. **cad** to **cfb**.

c2d COVERAGE FOR NONSUDDEN ACCIDENTAL OCCURRENCES. An owner or operator of a surface impoundment or landfill which is used to manage hazardous waste, or a group of facilities, shall demonstrate financial responsibility for bodily injury and property damage to third parties caused by nonsudden accidental occurrences arising from operations of the facility or group of facilities. The owner or operator shall have and maintain liability coverage for nonsudden accidental occurrences in the amount of at least \$3 million per occurrence with an annual aggregate of at least \$6 million, exclusive of legal defense costs. An owner or operator who shall meet the requirements of this section may combine the required per-occurrence coverage levels for sudden and nonsudden accidental occurrences into a single per-occurrence level, and combine the required annual aggregate coverage levels for sudden and nonsudden accidental occurrences into a single annual aggregate level. Owners or operators who combine coverage levels for sudden and nonsudden accidental occurrences shall maintain liability coverage in the amount of at least \$4 million per occurrence and \$8 million annual aggregate.

This liability coverage may be demonstrated as specified in par. **cad**, **cbd**, **ccd**, **cdd**, **ced** or **cfb**:

cad An owner or operator may demonstrate the required liability coverage by having liability insurance as specified in this subsection.

1. Each insurance policy shall be amended by attachment of the hazardous waste facility liability endorsement or evidenced by a certificate of liability insurance. The wording of the endorsement shall be identical to the wording specified in s. **NR 664.0151 c9d**. The wording of the certificate of insurance shall be identical to the wording specified in s. **NR 664.0151 c10d**. The owner or operator shall submit a signed duplicate original of the endorsement or the certificate of insurance to the department. If the facilities are located in more than one state, identical evidence of financial assurance shall be submitted to and maintained with the state agency regulating hazardous waste or with the appropriate EPA regional administrator if the facilities are located in an unauthorized state. If requested by the department, the owner or operator shall provide a signed duplicate original of the insurance policy.

2. Each insurance policy shall be issued by an insurer which, at a minimum, is licensed to transact the business of insurance, or eligible to provide insurance as an excess or surplus lines insurer, in one or more States.

3. The department, after conferring with the Wisconsin insurance commissioner, shall determine the acceptability of a surplus lines or captive insurance company to provide coverage for proof of financial responsibility. The department shall ask the insurance commissioner to provide a financial analysis of the insurer including a recommendation as to the insurer[s] ability to provide the required coverage. The department may require a periodic review of the acceptability of a surplus lines or captive insurance company.

cbd An owner or operator may meet the requirements of this section by passing a financial test or using the guarantee for liability coverage as specified in subs. **c6d** and **c7d**.

ccd An owner or operator may meet the requirements of this section by obtaining a letter of credit for liability coverage as specified in sub. **c8d**.

cdd An owner or operator may meet the requirements of this section by obtaining a surety bond for liability coverage as specified in sub. **c9d**.

ced An owner or operator may meet the requirements of this section by obtaining a trust fund for liability coverage as specified in sub. **c10d**.

cfb An owner or operator may demonstrate the required liability coverage through the use of combinations of insurance, financial test, guarantee, letter of credit, surety bond and trust fund, except that the owner or operator may not combine a financial test covering part of the liability coverage requirement with a guarantee unless the financial statement of the owner or operator is not consolidated with the financial statement of the guarantor. The amounts of coverage demonstrated shall total at least the minimum amounts required by this section. If the owner or operator demonstrates the required coverage through the use of a combination of financial assurances under this subsection, the owner or operator shall specify at least one assurance as XprimaryY coverage and shall specify other assurance as XexcessY coverage.

cgd An owner or operator shall notify the department in writing within 30 days whenever any of the following occur:

1. A claim results in a reduction in the amount of financial assurance for liability coverage provided by a financial instrument authorized in pars. **cad** to **cfb**.

2. A certification of valid claim for bodily injury or property

damages caused by a sudden or non-sudden accidental occurrence arising from the operation of a hazardous waste treatment, storage or disposal facility is entered between the owner or operator and third-party claimant for liability coverage under pars. [cad](#) to [cfd](#).

3. A final court order establishing a judgment for bodily injury or property damage caused by a sudden or non-sudden accidental occurrence arising from the operation of a hazardous waste treatment, storage or disposal facility is issued against the owner or operator or an instrument that is providing financial assurance for liability coverage under pars. [cad](#) to [cfd](#).

c3d REQUEST FOR VARIANCE. If an owner or operator can demonstrate to the satisfaction of the department that the levels of financial responsibility required by sub. [c1d](#) or [c2d](#) are not consistent with the degree and duration of risk associated with treatment, storage or disposal at the facility or group of facilities, the owner or operator may obtain a variance from the department. The request for a variance shall be submitted in writing to the department. If granted, the variance will take the form of an adjusted level of required liability coverage, the level to be based on the department[s] assessment of the degree and duration of risk associated with the ownership or operation of the facility or group of facilities. The department may require an owner or operator who requests a variance to provide the technical and engineering information as is deemed necessary by the department to determine a level of financial responsibility other than that required by sub. [c1d](#) or [c2d](#). The department will process a variance request as if it were a license modification request under s. [NR 670.041 c1d ced](#) and subject to the procedures of s. [NR 670.405](#). Notwithstanding any other provision, the department may hold a public hearing at the department[s] discretion or whenever the department finds, on the basis of requests for a public hearing, a significant degree of public interest in a tentative decision to grant a variance.

c4d ADJUSTMENTS BY THE DEPARTMENT. If the department determines that the levels of financial responsibility required by sub. [c1d](#) or [c2d](#) are not consistent with the degree and duration of risk associated with treatment, storage or disposal at the facility or group of facilities, the department may adjust the level of financial responsibility required under sub. [c1d](#) or [c2d](#) as may be necessary to protect human health and the environment. This adjusted level will be based on the department[s] assessment of the degree and duration of risk associated with the ownership or operation of the facility or group of facilities. In addition, if the department determines that there is a significant risk to human health and the environment from nonsudden accidental occurrences resulting from the operations of a facility that is not a surface impoundment, or landfill, the department may require that an owner or operator of the facility comply with sub. [c2d](#). An owner or operator shall furnish to the department, within a reasonable time, any information which the department requests to determine whether cause exists for adjustments of level or type of coverage. The department will process an adjustment of the level of required coverage as if it were a license modification under s. [NR 670.041 c1d ced](#) and subject to the procedures of s. [NR 670.405](#). Notwithstanding any other provision, the department may hold a public hearing at the department[s] discretion or whenever the department finds, on the basis of requests for a public hearing, a significant degree of public interest in a tentative decision to adjust the level or type of required coverage.

c5d PERIOD OF COVERAGE. Within 60 days after receiving certifications from the owner or operator and a qualified professional engineer that final closure has been completed in accordance with the approved closure plan, the department will notify the owner or operator in writing that the owner or operator is no

longer required to maintain liability coverage for that facility, unless the department has reason to believe that closure has not been in accordance with the approved closure plan.

c6d FINANCIAL TEST FOR LIABILITY COVERAGE. [cad](#) An owner or operator may satisfy the requirements of this section by demonstrating that the owner or operator passes a financial test as specified in this subsection. To pass this test the owner or operator shall meet the criteria of subd. [1.](#) or [2.](#):

1. The owner or operator shall have all of the following:
 - a. Net working capital and tangible net worth each at least 6 times the amount of liability coverage to be demonstrated by this test.
 - b. Tangible net worth of at least \$10 million.
 - c. Assets in the United States amounting to either: 1d At least 90 percent of the owner or operator[s] total assets. 2d At least 6 times the amount of liability coverage to be demonstrated by this test.
2. The owner or operator shall have all of the following:
 - a. A current rating for the owner or operator[s] most recent bond issuance of AAA, AA, A or BBB as issued by Standard and Poor[s], or Aaa, Aa, A or Baa as issued by Moody[s].
 - b. Tangible net worth of at least \$10 million.
 - c. Tangible net worth at least 6 times the amount of liability coverage to be demonstrated by this test.
 - d. Assets in the United States amounting to either: 1d At least 90 percent of the owner or operator[s] total assets. 2d At least 6 times the amount of liability coverage to be demonstrated by this test.

[cbd](#) The phrase Xamount of liability coverageY as used in par. [cad](#) refers to the annual aggregate amounts for which coverage is required under subs. [c1d](#) and [c2d](#).

[ccd](#) To demonstrate that the owner or operator meets this test, the owner or operator shall submit the following 3 items to the department:

1. A letter signed by the owner[s] or operator[s] chief financial officer and worded as specified in s. [NR 664.0151 c7d](#).
2. A copy of the independent certified public accountant[s] report on examination of the owner[s] or operator[s] financial statements for the latest completed fiscal year.
3. A special report from the owner[s] or operator[s] independent certified public accountant to the owner or operator stating all of the following:
 - a. The independent certified public accountant has compared the data which the letter from the chief financial officer specifies as having been derived from the independently audited, year-end financial statements for the latest fiscal year with the amounts in the financial statements.
 - b. In connection with that procedure, no matters came to the attention of the independent certified public accountant which would provide cause to believe that the specified data should be adjusted.

[ced](#) After the initial submission of items specified in par. [ccd](#), the owner or operator shall send updated information to the department within 90 days after the close of each succeeding fiscal year. This information shall consist of all 3 items specified in par. [ccd](#).

[cfd](#) If the owner or operator no longer meets the requirements of par. [cad](#), the owner or operator shall obtain insurance, a letter of credit, a surety bond, a trust fund or a guarantee for the entire amount of required liability coverage as specified in this section. Evidence of liability coverage shall be submitted to the department within 90 days after the end of the fiscal year for which the

year-end financial data show that the owner or operator no longer meets the test requirements.

cgd The department may disallow use of this test on the basis of qualifications in the opinion expressed by the independent certified public accountant in the accountant[s] report on examination of the owner[s] or operator[s] financial statements csee par. ccd 2.d. An adverse opinion or a disclaimer of opinion will be cause for disallowance. The department will evaluate other qualifications on an individual basis. The owner or operator shall provide evidence of insurance for the entire amount of required liability coverage as specified in this section within 30 days after notification of disallowance.

c7d GUARANTEE FOR LIABILITY COVERAGE. cad Subject to par. cbd, an owner or operator may meet the requirements of this section by obtaining a written guarantee, referred to as Xguarantee.Y The guarantor shall be the direct or higher-tier parent corporation of the owner or operator, a firm whose parent corporation is also the parent corporation of the owner or operator, or a firm with a substantial business relationship with the owner or operator. The guarantor shall meet the requirements for owners or operators in subs. c6d cad to cfd. The wording of the guarantee shall be identical to the wording specified in s. NR 664.0151 c8d. A certified copy of the guarantee shall accompany the items sent to the department as specified in sub. c6d ccd. One of these items shall be the letter from the guarantor[s] chief financial officer. If the guarantor[s] parent corporation is also the parent corporation of the owner or operator, this letter shall describe the value received in consideration of the guarantee. If the guarantor is a firm with a substantial business relationship with the owner or operator, this letter shall describe this substantial business relationship and the value received in consideration of the guarantee. The guarantee shall remain in force unless the guarantor sends notice of cancellation by certified mail to the owner or operator and to the department. This guarantee may not be terminated unless and until the department approves alternate liability coverage complying with this section. If the owner or operator fails to satisfy a judgment based on a determination of liability for bodily injury or property damage to third parties caused by sudden or nonsudden accidental occurrences cor both as the case may be, arising from the operation of facilities covered by this corporate guarantee, or fails to pay an amount agreed to in settlement of claims arising from or alleged to arise from the injury or damage, the guarantor will do so up to the limits of coverage.

cbd 1. In the case of corporations incorporated in the United States, a guarantee may be used to satisfy the requirements of this section only if the attorneys general or insurance commissioners of the following states have submitted a written statement to the department that a guarantee executed as described in this section and s. NR 664.0151 c8d, 40 CFR 264.151chdc2d or other state requirements that are equivalent to 40 CFR 264.151chdc2d is a legally valid and enforceable obligation in that state:

- a. The state in which the guarantor is incorporated.
- b. Each state in which a facility covered by the guarantee is located.

2. In the case of corporations incorporated outside the United States, a guarantee may be used to satisfy the requirements of this section only if all of the following conditions are met:

- a. The non-U.S. corporation has identified a registered agent for service of process in each state in which a facility covered by the guarantee is located and in the state in which it has its principal place of business.
- b. The attorney general or insurance commissioner of each

state in which a facility covered by the guarantee is located and the state in which the guarantor corporation has its principal place of business, has submitted a written statement to the department that a guarantee executed as described in this section and s. NR 664.0151 c8d, 40 CFR 264.151chdc2d or other state requirements that are equivalent to 40 CFR 264.151chdc2d is a legally valid and enforceable obligation in that state.

c8d LETTER OF CREDIT FOR LIABILITY COVERAGE. cad An owner or operator may satisfy the requirements of this section by obtaining an irrevocable letter of credit that conforms to the requirements of this subsection and submitting a copy of the letter of credit to the department.

cbd The financial institution issuing the letter of credit shall be an entity that has the authority to issue letters of credit and whose letter of credit operations are regulated and examined by a federal or state agency.

ccd The wording of the letter of credit shall be identical to the wording specified in s. NR 664.0151 c11d.

c9d SURETY BOND FOR LIABILITY COVERAGE. cad An owner or operator may satisfy the requirements of this section by obtaining a surety bond that conforms to the requirements of this subsection and submitting a copy of the bond to the department.

cbd The surety company issuing the bond shall be among those listed as acceptable sureties on federal bonds in the most recent circular 570 of the U.S. department of the treasury.

ccd The wording of the surety bond shall be identical to the wording specified in s. NR 664.0151 c12d.

cdd A surety bond may be used to satisfy the requirements of this section only if the attorneys general or insurance commissioners of the following states have submitted a written statement to the department that a surety bond executed as described in this section and s. NR 664.0151 c12d, 40 CFR 264.151cld or other state requirements that are equivalent to 40 CFR 264.151cld is a legally valid and enforceable obligation in that state:

1. The state in which the surety is incorporated.
2. Each state in which a facility covered by the surety bond is located.

c10d TRUST FUND FOR LIABILITY COVERAGE. cad An owner or operator may satisfy the requirements of this section by establishing a trust fund that conforms to the requirements of this subsection and submitting an originally signed duplicate of the trust agreement to the department.

cbd The trustee shall be an entity which has the authority to act as a trustee and whose trust operations are regulated and examined by a federal or state agency.

ccd The trust fund for liability coverage shall be funded for the full amount of the liability coverage to be provided by the trust fund before it may be relied upon to satisfy the requirements of this section. If at any time after the trust fund is created the amount of funds in the trust fund is reduced below the full amount of the liability coverage to be provided, the owner or operator, by the anniversary date of the establishment of the fund, shall either add sufficient funds to the trust fund to cause its value to equal the full amount of liability coverage to be provided, or obtain other financial assurance as specified in this section to cover the difference. For purposes of this subsection, Xthe full amount of the liability coverage to be providedY means the amount of coverage for sudden or nonsudden occurrences, or both, required to be provided by the owner or operator by this section, less the amount of financial assurance for liability coverage that is being provided by other financial assurance mechanisms being used to demonstrate financial assurance by the owner or operator.

cdd The wording of the trust fund shall be identical to the wording specified in s. [NR 664.0151 c13d](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c5d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0148 Incapacity of owners or operators, guarantors or financial institutions. c1d An owner or operator shall notify the department by certified mail of the commencement of a voluntary or involuntary bankruptcy proceeding under 11 USC, naming the owner or operator as debtor, within 10 days after commencement of the proceeding.

c2d An owner or operator who fulfills the requirements of s. [NR 665.0143](#), [665.0145](#) or [665.0147](#) by obtaining a trust fund, surety bond, letter of credit or insurance policy will be deemed to be without the required financial assurance or liability coverage in the event of bankruptcy of the trustee or issuing institution, or a suspension or revocation of the authority of the trustee institution to act as trustee or of the institution issuing the surety bond, letter of credit or insurance policy to issue the instruments. The owner or operator shall establish other financial assurance or liability coverage within 60 days after such an event.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter I — Containers

NR 665.0170 Applicability. This subchapter applies to owners and operators of all hazardous waste facilities that store containers of hazardous waste, except as s. [NR 665.0001](#) provides otherwise.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0171 Condition of containers. If a container holding hazardous waste is not in good condition, or if it begins to leak, the owner or operator shall transfer the hazardous waste from this container to a container that is in good condition, or manage the waste in some other way that complies with the requirements of this chapter.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0172 Compatibility of waste with container. The owner or operator shall use a container made of or lined with materials which will not react with, and are otherwise compatible with, the hazardous waste to be stored, so that the ability of the container to contain the waste is not impaired.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0173 Management of containers. c1d A container holding hazardous waste shall always be closed during storage, except when it is necessary to add or remove waste.

c2d A container holding hazardous waste may not be opened, handled or stored in a manner which may rupture the container or cause it to leak.

Note: Re-use of containers in transportation is governed by U.S. department of transportation regulations, including those set forth in [49 CFR 173.28](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0174 Inspections. At least weekly, the owner or operator shall inspect areas where containers are stored, looking for leaking containers and for deterioration of containers and the containment system caused by corrosion or other factors. The owner or operator shall comply with ss. [NR 664.0015 c3d](#) and [664.0171](#) for remedial action required if deterioration or leaks are detected.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. Register August 2020 No. 776, eff. 9-1-20; correction made under s. [13.92 c4d cbd 7.](#), Stats., Register April 2021 No. 784.

NR 665.0176 Special requirements for ignitable or reactive waste. Containers holding ignitable or reactive waste

shall be located at least 15 meters c50 feetd from the facility[s property line.

Note: See s. [NR 665.0017 c1d](#) for additional requirements.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0177 Special requirements for incompatible wastes. c1d Incompatible wastes, or incompatible wastes and materials, csee ch. [NR 665 Appendix V](#) for examplesd may not be placed in the same container, unless s. [NR 665.0017 c2d](#) is complied with.

c2d Hazardous waste may not be placed in an unwashed container that previously held an incompatible waste or material csee ch. [NR 665 Appendix V](#) for examplesd, unless s. [NR 665.0017 c2d](#) is complied with.

c3d A storage container holding a hazardous waste that is incompatible with any waste or other materials stored nearby in other containers, piles, open tanks or surface impoundments shall be separated from the other materials or protected from them by means of a dike, berm, wall or other device.

Note: The purpose of this section is to prevent fires, explosions, gaseous emissions, leaching or other discharge of hazardous waste or hazardous waste constituents which could result from the mixing of incompatible wastes or materials if containers break or leak.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c1d, c2d made under s. [13.92 c4d cbd 7.](#), Stats., Register March 2013 No. 687.

NR 665.0178 Air emission standards. The owner or operator shall manage all hazardous waste placed in a container in accordance with the applicable requirements of subchs. [AA](#), [BB](#) and [CC](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter J — Tank Systems

NR 665.0190 Applicability. The requirements of this subchapter apply to owners and operators of facilities that use tank systems for storing or treating hazardous waste except as otherwise provided in subs. [c1d](#) to [c3d](#) or in s. [NR 665.0001](#).

c1d Tank systems that are used to store or treat hazardous waste which contains no free liquids and are situated inside a building with an impermeable floor are exempted from the requirements in s. [NR 664.0193](#). To demonstrate the absence or presence of free liquids in the stored or treated waste, the following test shall be used: Method 9095B cpaint filter liquids testd as described in XTest Methods for Evaluating Solid Waste, Physical{Chemical Methods,Y EPA SW-846, incorporated by reference in s. [NR 660.11](#).

c2d Tank systems, including sumps, as defined in s. [NR 660.10](#), that serve as part of a secondary containment system to collect or contain releases of hazardous wastes are exempted from the requirements in s. [NR 665.0193 c1d](#).

c3d Tanks, sumps and other collection devices used in conjunction with drip pads, as defined in s. [NR 660.10](#) and regulated under subch. [W](#), shall meet the requirements of this subchapter.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0191 Assessment of existing tank system[s integrity. c1d For each existing tank system that does not have secondary containment meeting the requirements of s. [NR 665.0193](#), the owner or operator shall determine that the tank system is not leaking or is unfit for use. Except as provided in sub. [c3d](#), the owner or operator shall obtain and keep on file at the facility a written assessment reviewed and certified by a qualified professional engineer in accordance with s. [NR 670.011 c4d](#), that attests to the tank system[s integrity by January 12, 1988.

c2d This assessment shall determine that the tank system is

adequately designed and has sufficient structural strength and compatibility with the wastes to be stored or treated to ensure that it will not collapse, rupture or fail. At a minimum, this assessment shall consider all of the following:

cad Design standards, if available, according to which the tank and ancillary equipment were constructed.

cbd Hazardous characteristics of the wastes that have been or will be handled.

ccd Existing corrosion protection measures.

cdd Documented age of the tank system, if available, otherwise, an estimate of the aged.

ced Results of a leak test, internal inspection or other tank integrity examination such that:

1. For non-enterable underground tanks, this assessment shall consist of a leak test that is capable of taking into account the effects of temperature variations, tank end deflection, vapor pockets and high water table effects.

2. For other than non-enterable underground tanks and for ancillary equipment, this assessment shall be either a leak test, as described in subd. 1., or an internal inspection or other tank integrity examination certified by a qualified professional engineer in accordance with s. NR 670.011 c4d that addresses cracks, leaks, corrosion, and erosion.

Note: The practices described in the American Petroleum Institute cAPId Publication, Guide for Inspection of Refinery Equipment, Chapter XIII, XAtmospheric and Low-Pressure Storage TanksY, 4th edition, 1981, may be used, where applicable, as guidelines in conducting the integrity examination of an other than non-enterable underground tank system.

c3d Tank systems that store or treat materials that become hazardous wastes subsequent to March 1, 1991 shall conduct this assessment within 12 months after the date that the waste becomes a hazardous waste.

c4d If, as a result of the assessment conducted in accordance with sub. c1d, a tank system is found to be leaking or unfit for use, the owner or operator shall comply with the requirements of s. NR 665.0196.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d, c2d ced 2. Register July 2017 No. 739, eff. 8-1-17.

NR 665.0192 Design and installation of new tank systems or components. c1d Owners or operators of new tank systems or components shall ensure that the foundation, structural support, seams, connections and pressure controls if applicable are adequately designed and that the tank system has sufficient structural strength, compatibility with the wastes to be stored or treated and corrosion protection so that it will not collapse, rupture or fail. The owner or operator shall obtain a written assessment reviewed and certified by a qualified professional engineer in accordance with s. NR 670.011 c4d attesting that the system has sufficient structural integrity and is acceptable for the storing and treating of hazardous waste. This assessment shall include, at a minimum, all of the following information:

cad Design standards according to which the tanks and ancillary equipment are or will be constructed.

cbd Hazardous characteristics of the wastes to be handled.

ccd For new tank systems or components in which the external shell of a metal tank or any external metal component of the tank system is or will be in contact with the soil or with water, a determination by a corrosion expert of all of the following:

1. Factors affecting the potential for corrosion, including but not limited to, all of the following:

- a. Soil moisture content.
- b. Soil pH.
- c. Soil sulfides level.

d. Soil resistivity.

e. Structure to soil potential.

f. Influence of nearby underground metal structures ce.g., pipingd.

g. Stray electric current.

h. Existing corrosion-protection measures ce.g., coating, cathodic protectiond.

2. The type and degree of external corrosion protection that are needed to ensure the integrity of the tank system during the use of the tank system or component, consisting of one or more of the following:

a. Corrosion-resistant materials of construction such as special alloys or fiberglass-reinforced plastic.

b. Corrosion-resistant coating csuch as epoxy or fiberglassd with cathodic protection ce.g., impressed current or sacrificial anodesd.

c. Electrical isolation devices such as insulating joints and flanges.

Note: The practices described in the National Association of Corrosion Engineers cNACEd standard, XRecommended Practice cRP-02-85d—Control of External Corrosion on Metallic Buried, Partially Buried, or Submerged Liquid Storage SystemsY, and the American Petroleum Institute cAPId Publication 1632, Xcathodic Protection of Underground Petroleum Storage Tanks and Piping SystemsY, may be used, where applicable, as guidelines in providing corrosion protection for tank systems.

cdd For underground tank system components that are likely to be affected by vehicular traffic, a determination of design or operational measures that will protect the tank system against potential damage.

ced Design considerations to ensure all of the following:

1. Tank foundations will maintain the load of a full tank.

2. Tank systems will be anchored to prevent flotation or dislodgement where the tank system is placed in a saturated zone.

3. Tank systems will withstand the effects of frost heave.

c2d The owner or operator of a new tank system shall ensure that proper handling procedures are adhered to in order to prevent damage to the system during installation. Prior to covering, enclosing or placing a new tank system or component in use, an independent, qualified installation inspector or a qualified professional engineer, either of whom is trained and experienced in the proper installation of tank systems, shall inspect the system or component for the presence of any of the following items:

cad Weld breaks.

cbd Punctures.

ccd Scrapes of protective coatings.

cdd Cracks.

ced Corrosion.

cfid Other structural damage or inadequate construction or installation.

All discrepancies shall be remedied before the tank system is covered, enclosed or placed in use.

c3d New tank systems or components and piping that are placed underground and that are backfilled shall be provided with a backfill material that is a noncorrosive, porous, homogeneous substance and that is carefully installed so that the backfill is placed completely around the tank and compacted to ensure that the tank and piping are fully and uniformly supported.

c4d All new tanks and ancillary equipment shall be tested for tightness prior to being covered, enclosed or placed in use. If a tank system is found not to be tight, all repairs necessary to remedy the leaks in the system shall be performed prior to the tank system being covered, enclosed or placed in use.

c5d Ancillary equipment shall be supported and protected

against physical damage and excessive stress due to settlement, vibration, expansion or contraction.

Note: The piping system installation procedures described in American Petroleum Institute cAPId Publication 1615 cNovember 1979d, XInstallation of Underground Petroleum Storage SystemsY, or ANSI Standard B31.3, XPetroleum Refinery SystemY, may be used, where applicable, as guidelines for proper installation of piping systems.

c6d The owner or operator shall provide the type and degree of corrosion protection necessary, based on the information provided under sub. **c1d ccd**, to ensure the integrity of the tank system during use of the tank system. An independent corrosion expert shall supervise the installation of a corrosion protection system that is field fabricated, to ensure proper installation.

c7d The owner or operator shall obtain and keep on file at the facility written statements by those persons required to certify the design of the tank system and supervise the installation of the tank system in accordance with the requirements of subs. **c2d** to **c6d** to attest that the tank system was properly designed and installed and that repairs, pursuant to subs. **c2d** and **c4d** were performed. These written statements shall also include the certification statement as required in s. **NR 670.011 c4d**.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d cintro.d, c2d cintro.d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0193 Containment and detection of releases. c1d In order to prevent the release of hazardous waste or hazardous constituents to the environment, secondary containment that meets the requirements of this section shall be provided except as provided in subs. **c6d** and **c7dd**:

cad For all new and existing tank systems or components, prior to their being put into service.

cbd For tank systems that store or treat materials that become hazardous wastes, within 2 years of the hazardous waste listing, or when the tank system has reached 15 years of age, whichever comes later.

c2d Secondary containment systems shall be all of the following:

cad Designed, installed and operated to prevent any migration of wastes or accumulated liquid out of the system to the soil, groundwater or surface water at any time during the use of the tank system.

cbd Capable of detecting and collecting releases and accumulated liquids until the collected material is removed.

c3d To meet the requirements of sub. **c2d**, secondary containment systems shall be at a minimum all of the following:

cad Constructed of or lined with materials that are compatible with the wastes to be placed in the tank system and shall have sufficient strength and thickness to prevent failure due to pressure gradients including static head and external hydrological forcesd, physical contact with the waste to which they are exposed, climatic conditions, the stress of installation and the stress of daily operation including stresses from nearby vehicular traffidd.

cbd Placed on a foundation or base capable of providing support to the secondary containment system and resistance to pressure gradients above and below the system and capable of preventing failure due to settlement, compression or uplift.

ccd Provided with a leak detection system that is designed and operated so that it will detect the failure of either the primary and secondary containment structure or any release of hazardous waste or accumulated liquid in the secondary containment system within 24 hours, or at the earliest practicable time if the existing detection technology or site conditions will not allow detection of a release within 24 hours.

cdd Sloped or otherwise designed or operated to drain and re-

move liquids resulting from leaks, spills or precipitation. Spilled or leaked waste and accumulated precipitation shall be removed from the secondary containment system within 24 hours, or in as timely a manner as is possible to prevent harm to human health or the environment, if removal of the released waste or accumulated precipitation cannot be accomplished within 24 hours.

Note: If the collected material is a hazardous waste under ch. **NR 661**, it is subject to management as a hazardous waste according to all applicable requirements of chs. **NR 662** to **664** and this chapter. If the collected material is discharged through a point source to waters of the state, it is subject to ss. **283.31** and **283.33**, Stats. If discharged to a publicly owned treatment works cPOTWd, it is subject to s. **283.21c2d**, Stats. If the collected material is released to the environment, it may be subject to the reporting requirements of **40 CFR part 302** and the requirements of s. **292.11**, Stats., and chs. **NR 706** to **726**.

c4d Secondary containment for tanks shall include one or more of the following devices:

cad A liner cexternal to the tankd.

cbd A vault.

ccd A double-walled tank.

cdd An equivalent device as approved by the department.

c5d In addition to the requirements of subs. **c2d** to **c4d**, secondary containment systems shall satisfy the following requirements:

cad External liner systems shall be all of the following:

1. Designed or operated to contain 100 percent of the capacity of the largest tank within its boundary.

2. Designed or operated to prevent run-on or infiltration of precipitation into the secondary containment system unless the collection system has sufficient excess capacity to contain run-on or infiltration. The additional capacity shall be sufficient to contain precipitation from a 25-year, 24-hour rainfall event.

3. Free of cracks or gaps.

4. Designed and installed to completely surround the tank and to cover all surrounding earth likely to come into contact with the waste if released from the tank ci.e., capable of preventing lateral as well as vertical migration of the wasted.

5. Provided with an impermeable interior coating or lining that is compatible with the stored waste and that will prevent migration of waste into the concrete.

cbd Vault systems shall be all of the following:

1. Designed or operated to contain 100 percent of the capacity of the largest tank within its boundary.

2. Designed or operated to prevent run-on or infiltration of precipitation into the secondary containment system unless the collection system has sufficient excess capacity to contain run-on or infiltration. The additional capacity shall be sufficient to contain precipitation from a 25-year, 24-hour rainfall event.

3. Constructed with chemical-resistant water stops in place at all joints cif anyd.

4. Provided with an impermeable interior coating or lining that is compatible with the stored waste and that will prevent migration of waste into the concrete.

5. Provided with a means to protect against the formation of and ignition of vapors within the vault, if the waste being stored or treated meets any of the following:

a. The definition of ignitable waste under s. **NR 661.0021**.

b. The definition of reactive waste under s. **NR 661.0023** and may form an ignitable or explosive vapor.

6. Provided with an exterior moisture barrier or be otherwise designed or operated to prevent migration of moisture into the vault if the vault is subject to hydraulic pressure.

ccd Double-walled tanks shall be all of the following:

1. Designed as an integral structure ci.e., an inner tank

within an outer shell so that the outer shell contains any release from the inner tank.

2. Protected, if constructed of metal, from both corrosion of the primary tank interior and the external surface of the outer shell.

3. Provided with a built-in, continuous leak detection system capable of detecting a release within 24 hours or at the earliest practicable time, if the owner or operator can demonstrate to the department, and the department concurs, that the existing leak detection technology or site conditions will not allow detection of a release within 24 hours.

Note: The provisions outlined in the Steel Tank Institute's Standard for Dual Wall Underground Steel Storage Tanks may be used as guidelines for aspects of the design of underground steel double-walled tanks.

c6d Ancillary equipment shall be provided with full secondary containment e.g., trench, jacketing, double-walled piping that meets the requirements of subs. **c2d** and **c3d** except for all of the following:

cad Aboveground piping exclusive of flanges, joints, valves and connections that is visually inspected for leaks on a daily basis.

cbd Welded flanges, welded joints and welded connections that are visually inspected for leaks on a daily basis.

ccd Sealless or magnetic coupling pumps and sealless valves, that are visually inspected for leaks on a daily basis.

cdd Pressurized aboveground piping systems with automatic shut-off devices e.g., excess flow check valves, flow metering shutdown devices, loss of pressure actuated shut-off devices that are visually inspected for leaks on a daily basis.

c7d The owner or operator may obtain a variance from the requirements of this section if the department finds, as a result of a demonstration by the owner or operator that alternative design and operating practices, together with location characteristics, will prevent the migration of hazardous waste or hazardous constituents into the groundwater or surface water at least as effectively as secondary containment during the active life of the tank system; or, that in the event of a release that does migrate to groundwater or surface water, no substantial present or potential hazard will be posed to human health or the environment. New underground tank systems may not, per a demonstration in accordance with par. **cbd**, be exempted from the secondary containment requirements of this section. Application for a variance as allowed in this subsection does not waive compliance with the requirements of this subchapter for new tank systems.

cad In deciding whether to grant a variance based on a demonstration of equivalent protection of groundwater and surface water, the department will consider all of the following:

1. The nature and quantity of the waste.
2. The proposed alternate design and operation.
3. The hydrogeologic setting of the facility, including the thickness of soils between the tank system and groundwater.
4. All other factors that would influence the quality and mobility of the hazardous constituents and the potential for them to migrate to groundwater or surface water.

cbd In deciding whether to grant a variance, based on a demonstration of no substantial present or potential hazard, the department will consider all of the following:

1. The potential adverse effects on groundwater, surface water and land quality taking into account all of the following:
 - a. The physical and chemical characteristics of the waste in the tank system, including its potential for migration.
 - b. The hydrogeological characteristics of the facility and surrounding land.

c. The potential for health risks caused by human exposure to waste constituents.

d. The potential for damage to wildlife, crops, vegetation and physical structures caused by exposure to waste constituents.

e. The persistence and permanence of the potential adverse effects.

2. The potential adverse effects of a release on groundwater quality, taking into account all of the following:

a. The quantity and quality of groundwater and the direction of groundwater flow.

b. The proximity and withdrawal rates of groundwater in the area.

c. The current and future uses of groundwater in the area.

d. The existing quality of groundwater, including other sources of contamination and their cumulative impact on the groundwater quality.

3. The potential adverse effects of a release on surface water quality, taking into account all of the following:

a. The quantity and quality of groundwater and the direction of groundwater flow.

b. The patterns of rainfall in the region.

c. The proximity of the tank system to surface waters.

d. The current and future uses of surface waters in the area and any water quality standards established for those surface waters.

e. The existing quality of surface water, including other sources of contamination and the cumulative impact on surface-water quality.

4. The potential adverse effects of a release on the land surrounding the tank system, taking into account all of the following:

a. The patterns of rainfall in the region.

b. The current and future uses of the surrounding land.

ccd The owner or operator of a tank system, for which a variance from secondary containment had been granted in accordance with the requirements of par. **cad**, at which a release of hazardous waste has occurred from the primary tank system but has not migrated beyond the zone of engineering control as established in the variance, shall do all of the following:

1. Comply with the requirements of s. **NR 665.0196**, except sub. **c4d**.

2. Decontaminate or remove contaminated soil to the extent necessary to do all of the following:

a. Enable the tank system, for which the variance was granted, to resume operation with the capability for the detection of and response to releases at least equivalent to the capability it had prior to the release.

b. Prevent the migration of hazardous waste or hazardous constituents to groundwater or surface water.

3. If contaminated soil cannot be removed or decontaminated in accordance with subd. 2., comply with the requirements of s. **NR 665.0197 c2d**.

cdd The owner or operator of a tank system, for which a variance from secondary containment had been granted in accordance with the requirements of par. **cad**, at which a release of hazardous waste has occurred from the primary tank system and has migrated beyond the zone of engineering control as established in the variance, shall do all of the following:

1. Comply with the requirements of s. **NR 665.0196 c1d** to **c4d**.

2. Prevent the migration of hazardous waste or hazardous constituents to groundwater or surface water, if possible, and decontaminate or remove contaminated soil. If contaminated soil

cannot be decontaminated or removed, or if groundwater has been contaminated, the owner or operator shall comply with the requirements of s. NR 665.0197 c2d.

3. If repairing, replacing or reinstalling the tank system, provide secondary containment in accordance with the requirements of subs. c1d to c6d or reapply for a variance from secondary containment and meet the requirements for new tank systems in s. NR 665.0192 if the tank system is replaced. The owner or operator shall comply with these requirements even if contaminated soil can be decontaminated or removed, and groundwater or surface water has not been contaminated.

c8d All of the following procedures shall be followed in order to request a variance from secondary containment:

cad The department shall be notified in writing by the owner or operator that the owner or operator intends to conduct and submit a demonstration for a variance from secondary containment as allowed in sub. c7d according to the following schedule:

1. For existing tank systems, at least 24 months prior to the date that secondary containment must be provided in accordance with sub. c1d.

2. For new tank systems, at least 30 days prior to entering into a contract for installation of the tank system.

cbd As part of the notification, the owner or operator shall also submit to the department a description of the steps necessary to conduct the demonstration and a timetable for completing each of the steps. The demonstration shall address each of the factors listed in sub. c7d cad or cbd.

ccd The demonstration for a variance shall be completed and submitted to the department within 180 days after notifying the department of intent to conduct the demonstration.

cdd The department will inform the public, through a newspaper notice, of the availability of the demonstration for a variance. The notice shall be placed in a daily or weekly major local newspaper of general circulation and shall provide at least 30 days from the date of the notice for the public to review and comment on the demonstration for a variance. The department also will hold a public hearing, in response to a request or at its own discretion, whenever such a hearing might clarify one or more issues concerning the demonstration for a variance. Public notice of the hearing will be given at least 30 days prior to the date of the hearing and may be given at the same time as notice of the opportunity for the public to review and comment on the demonstration. These 2 notices may be combined.

ced The department will approve or disapprove the request for a variance within 90 days of receipt of the demonstration from the owner or operator and will notify in writing the owner or operator and each person who submitted written comments or requested notice of the variance decision. If the demonstration for a variance is incomplete or does not include sufficient information, the 90-day time period will begin when the department receives a complete demonstration, including all information necessary to make a final determination. If the public comment period in par. cdd is extended, the 90-day time period will be similarly extended.

c9d All tank systems, until the time that secondary containment meeting the requirements of this section is provided, shall comply with the following:

cad For non-enterable underground tanks, a leak test that meets the requirements of s. NR 665.0191 c2d ced shall be conducted at least annually.

cbd For other than non-enterable underground tanks and for all ancillary equipment, the owner or operator shall either conduct a leak test as in par. cad or develop a schedule and procedure

for an assessment of the overall condition of the tank system by a qualified professional engineer. The schedule and procedure shall be adequate to detect obvious cracks, leaks and corrosion or erosion that may lead to cracks and leaks. The owner or operator shall remove the stored waste from the tank, if necessary, to allow the condition of all internal tank surfaces to be assessed. The frequency of these assessments shall be based on the material of construction of the tank and its ancillary equipment, the age of the system, the type of corrosion or erosion protection used, the rate of corrosion or erosion observed during the previous inspection and the characteristics of the waste being stored or treated.

Note: The practices described in the American Petroleum Institute cAPId Publication Guide for Inspection of Refining Equipment, Chapter XIII, XAtmospheric and Low Pressure Storage TanksY, 4th edition, 1981, may be used, when applicable, as guidelines for assessing the overall condition of the tank system.

ccd The owner or operator shall maintain on file at the facility a record of the results of the assessments conducted in accordance with pars. cad and cbd.

cdd If a tank system or component is found to be leaking or unfit-for-use as a result of the leak test or assessment in pars. cad and cbd, the owner or operator shall comply with the requirements of s. NR 665.0196.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: r. and recr. c1d, am. c9d cbd Register July 2017 No. 739, eff. 8-1-17; CR 19-082: cr. c5d cad 5., am. c5d cbd 5. a., b. Register August 2020 No. 776, eff. 9-1-20; correction in c5d cad 5. made under s. 35.17, Stats., Register August 2020 No. 776.

NR 665.0194 General operating requirements. c1d Hazardous wastes or treatment reagents may not be placed in a tank system if they could cause the tank, its ancillary equipment or the secondary containment system to rupture, leak, corrode or otherwise fail.

c2d The owner or operator shall use appropriate controls and practices to prevent spills and overflows from tank or secondary containment systems. These include at a minimum all of the following:

cad Spill prevention controls ce.g., check valves, dry discount couplingsd.

cbd Overfill prevention controls ce.g., level sensing devices, high level alarms, automatic feed cutoff or bypass to a standby tankd.

ccd Maintenance of sufficient freeboard in uncovered tanks to prevent overtopping by wave or wind action or by precipitation.

c3d The owner or operator shall comply with the requirements of s. NR 665.0196 if a leak or spill occurs in the tank system.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0195 Inspections. c1d The owner or operator shall inspect, where present, at least once each operating day, data gathered from monitoring and leak detection equipment cfor example, pressure or temperature gauges, monitoring wellsd to ensure that the tank system is being operated according to its design.

Note: Section NR 665.0015 c3d requires the owner or operator to remedy any deterioration or malfunction found. Section NR 665.0196 requires the owner or operator to notify the department within 24 hours of confirming a release. Also, if a hazardous substance is released to the environment, 40 CFR part 302 may require the owner or operator to notify the national response center and s. 292.11, Stats, and ch. NR 706 may require the owner or operator to notify the department.

c2d Except as noted under the sub. c3d, the owner or operator shall inspect at least once each operating day:

cad Overfill and spill control equipment cfor example, waste-feed cutoff systems, bypass systems, and drainage systemsd to ensure that it is in good working order.

cbd Above ground portions of the tank system, if any, to detect corrosion or releases of waste.

ccd The construction materials and the area immediately sur-

rounding the externally accessible portion of the tank system, including the secondary containment system cfor example, diked to detect erosion or signs of releases of hazardous waste cfor example, wet spots, dead vegetationd.

c3d Owners or operators of tank systems that either use leak detection equipment to alert facility personnel to leaks, or implement established workplace practices to ensure leaks are promptly identified, shall inspect at least weekly those areas described in sub. **c2d cad** to **ccd**. Use of the alternate inspection schedule shall be documented in the facility[s operating record. This documentation shall include a description of the established workplace practices at the facility.

c5d Ancillary equipment that is not provided with secondary containment, as described in s. **NR 665.0193 c6d cad** to **cdd**, shall be inspected at least once each operating day.

c6d The owner or operator shall document in the operating record of the facility an inspection of those items in subs. **c1d** and **c2d**.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: r. and recr. Register July 2017 No. 739, eff. 8-1-17; CR 19-082: r. c4d, cr. c5d Register August 2020 No. 776, eff. 9-1-20.

NR 665.0196 Response to leaks or spills and disposition of leaking or unfit-for-use tank systems. A tank system or secondary containment system from which there has been a leak or spill, or which is unfit for use, shall be removed from service immediately, and the owner or operator shall satisfy the following requirements:

c1d CESSATION OF USE; PREVENT FLOW OR ADDITION OF WASTES. The owner or operator shall immediately stop the flow of hazardous waste into the tank system or secondary containment system and inspect the system to determine the cause of the release.

c2d REMOVAL OF WASTE FROM TANK SYSTEM OR SECONDARY CONTAINMENT SYSTEM. **cad** If the release was from the tank system, the owner or operator shall, within 24 hours after detection of the leak or, if the owner or operator demonstrates that that is not possible, at the earliest practicable time remove as much of the waste as is necessary to prevent further release of hazardous waste to the environment and to allow inspection and repair of the tank system to be performed.

cbd If the release was to a secondary containment system, all released materials shall be removed within 24 hours or in as timely a manner as is possible to prevent harm to human health and the environment.

c3d CONTAINMENT OF VISIBLE RELEASES TO THE ENVIRONMENT. The owner or operator shall immediately conduct a visual inspection of the release and, based upon that inspection do all of the following:

cad Prevent further migration of the leak or spill to soils or surface water.

cbd Remove, and properly dispose of, any visible contamination of the soil or surface water.

c4d NOTIFICATIONS, REPORTS. **cad** Any release to the environment, except as provided in par. **cbd**, shall be reported to the department within 24 hours of detection. If the release has been reported pursuant to ch. **NR 706**, that report will satisfy this requirement.

cbd A leak or spill of hazardous waste that is exempted from the requirements of this subsection if it is all of the following:

1. Less than or equal to a quantity of one pound.
2. Immediately contained and cleaned-up.

ccd Within 30 days of detection of a release to the environ-

ment, a report containing all of the following information shall be submitted to the department:

1. Likely route of migration of the release.

2. Characteristics of the surrounding soil csoil composition, geology, hydrogeology, climated.

3. Results of any monitoring or sampling conducted in connection with the release, cif availabled. If sampling or monitoring data relating to the release are not available within 30 days, these data shall be submitted to the department as soon as they become available.

4. Proximity to downgradient drinking water, surface water and population areas.

5. Description of response actions taken or planned.

c5d PROVISION OF SECONDARY CONTAINMENT, REPAIR OR CLOSURE. **cad** Unless the owner or operator satisfies the requirements of pars. **cbd** to **cdd**, the tank system shall be closed in accordance with s. **NR 665.0197**.

cbd If the cause of the release was a spill that has not damaged the integrity of the system, the owner or operator may return the system to service as soon as the released waste is removed and repairs, if necessary, are made.

ccd If the cause of the release was a leak from the primary tank system into the secondary containment system, the system shall be repaired prior to returning the tank system to service.

cdd If the source of the release was a leak to the environment from a component of a tank system without secondary containment, the owner or operator shall provide the component of the system from which the leak occurred with secondary containment that satisfies the requirements of s. **NR 665.0193** before it can be returned to service, unless the source of the leak is an aboveground portion of a tank system. If the source is an aboveground component that can be inspected visually, the component shall be repaired and may be returned to service without secondary containment as long as the requirements of sub. **c6d** are satisfied. If a component is replaced to comply with the requirements of this paragraph, that component shall satisfy the requirements for new tank systems or components in ss. **NR 665.0192** and **665.0193**. Additionally, if a leak has occurred in any portion of a tank system component that is not readily accessible for visual inspection ce.g., the bottom of an inground or onground tankd, the entire component shall be provided with secondary containment in accordance with s. **NR 665.0193** prior to being returned to use.

c6d CERTIFICATION OF MAJOR REPAIRS. If the owner or operator has repaired a tank system in accordance with sub. **c5d**, and the repair has been extensive cfor example, installation of an internal liner; repair of a ruptured primary containment or secondary containment vesseld, the tank system may not be returned to service unless the owner or operator has obtained a certification by a qualified professional engineer in accordance with s. **NR 670.011 c4d** that the repaired system is capable of handling hazardous wastes without release for the intended life of the system. This certification shall be placed in the operating record and maintained until closure of the facility.

Note: The department or EPA regional administrator may, on the basis of any information received that there is or has been a release of hazardous waste or hazardous constituents into the environment, issue an order under s. **291.37** or **291.85**, Stats., or **42 USC 6924 cvd**, **6928 chd**, or **6973 cad**, requiring corrective action or other response as deemed necessary to protect human health or the environment.

Note: See s. **NR 665.0015 c3d** for the requirements necessary to remedy a failure. Also, if a hazardous substance is released to the environment, **40 CFR part 302** may require the owner or operator to notify the national response center and s. **292.11**, Stats., and ch. **NR 706** may require the owner or operator to notify the department.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c6d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0197 Closure and long-term care. c1d At closure of a tank system, the owner or operator shall remove or decontaminate all waste residues, contaminated containment system components, liners, etc., contaminated soils, and structures and equipment contaminated with waste, and manage them as hazardous waste, unless s. NR 661.0003 c4d applies. The closure plan, closure activities, cost estimates for closure and financial responsibility for tank systems shall meet all of the requirements specified in subchs. G and H.

c2d If the owner or operator demonstrates that not all contaminated soils can be practicably removed or decontaminated as required in sub. c1d, then the owner or operator shall close the tank system and perform long-term care in accordance with the closure and long-term care requirements that apply to landfills c s. NR 665.0310d. In addition, for the purposes of closure, long-term care and financial responsibility, such a tank system is then considered to be a landfill, and the owner or operator shall meet all of the requirements for landfills specified in subchs. G and H.

c3d If an owner or operator has a tank system which does not have secondary containment that meets the requirements of s. NR 665.0193 c2d to c6d and which is not exempt from the secondary containment requirements in accordance with s. NR 665.0193 c7d, then:

cad The closure plan for the tank system shall include both a plan for complying with sub. c1d and a contingent plan for complying with sub. c2d.

cbd A contingent long-term care plan for complying with sub. c2d shall be prepared and submitted as part of the feasibility and plan of operation report.

ccd The cost estimates calculated for closure and long-term care shall reflect the costs of complying with the contingent closure plan and the contingent long-term care plan, if these costs are greater than the costs of complying with the closure plan prepared for the expected closure under sub. c1d.

cdd Financial assurance shall be based on the cost estimates in par. ccd.

ced For the purposes of the contingent closure and long-term care plans, such a tank system is considered to be a landfill, and the contingent plans shall meet all of the closure, long-term care and financial responsibility requirements for landfills under subchs. G and H.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d Register August 2020 No. 776, eff. 9-1-20.

NR 665.0198 Special requirements for ignitable or reactive wastes. c1d Ignitable or reactive waste may not be placed in a tank system, unless par. cad, cbd or ccd applies:

cad The waste is treated, rendered or mixed before or immediately after placement in the tank system so that all of the following apply:

1. The resulting waste, mixture or dissolved material no longer meets the definition of ignitable or reactive waste under s. NR 661.0021 or 661.0023.

2. Section NR 665.0017 c2d is complied with.

cbd The waste is stored or treated in such a way that it is protected from any material or conditions that may cause the waste to ignite or react.

ccd The tank system is used solely for emergencies.

c2d The owner or operator of a facility where ignitable or reactive waste is stored or treated in tanks shall comply with the requirements for the maintenance of protective distances between the waste management area and any public ways, streets, alleys or an adjoining property line that can be built upon as required in Tables 2-1 to 2-6 of the National Fire Protection Association's

XFlammable and Combustible Liquids Code Y c1977 or 1981d, incorporated by reference in s. NR 660.11.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d cad 1. Register August 2020 No. 776, eff. 9-1-20.

NR 665.0199 Special requirements for incompatible wastes. c1d Incompatible wastes, or incompatible waste and materials csee ch. NR 665 Appendix V for examplesd, may not be placed in the same tank system, unless s. NR 665.0017 c2d is complied with.

c2d Hazardous waste may not be placed in a tank system that has not been decontaminated and that previously held an incompatible waste or material, unless s. NR 665.0017 c2d is complied with.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c1d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

NR 665.0200 Waste analysis and trial tests. In addition to performing the waste analysis required by s. NR 665.0013, the owner or operator shall do any of the following, whenever a tank system is to be used to treat chemically or to store a hazardous waste that is substantially different from waste previously treated or stored in that tank system; or treat chemically a hazardous waste with a substantially different process than any previously used in that tank system:

c1d Conduct waste analyses and trial treatment or storage tests (e.g., bench-scale or pilot-plant scale tests).

c2d Obtain written, documented information on similar waste under similar operating conditions to show that the proposed treatment or storage will meet the requirements of s. NR 665.0194 c1d.

Note: Section NR 665.0013 requires the waste analysis plan to include analyses needed to comply with ss. NR 665.0198 and 665.0199. Section NR 665.0073 requires the owner or operator to place the results from each waste analysis and trial test, or the documented information, in the operating record of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0202 Air emission standards. The owner or operator shall manage all hazardous waste placed in a tank in accordance with the applicable requirements of subchs. AA, BB and CC.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter K — Surface Impoundments

NR 665.0220 Applicability. This subchapter applies to owners and operators of facilities that use surface impoundments to treat, store or dispose of hazardous waste, except as s. NR 665.0001 provides otherwise.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0221 Design and operating requirements. c1d The owner or operator of each new surface impoundment unit, each lateral expansion of a surface impoundment unit, and each replacement of an existing surface impoundment unit shall install 2 or more liners and a leachate collection and removal system between the liners, and operate the leachate collection and removal system in accordance with s. NR 664.0221 c3d, unless exempted under s. NR 664.0221 c4d, c5d, or c6d.

c2d The owner or operator of each unit referred to in sub. c1d shall notify the department at least 60 days prior to receiving waste. The owner or operator of each facility submitting notice shall file a feasibility and plan of operation report within 6 months of the receipt of the notice.

c3d The owner or operator of any replacement surface impoundment unit is exempt from sub. c1d if both of the following apply:

cad The existing unit was constructed in compliance with the design standards of [42 USC 6924](#) cod c1d cAd cid and c5d .

cbd There is no reason to believe that the liner is not functioning as designed.

c4d The double liner requirement in sub. [c1d](#) may be waived by the department for any monofill, if the requirements of pars. [cad](#) and [cbd 1.](#) or [2.](#) are met:

cad The monofill contains only hazardous wastes from foundry furnace emission controls or metal casting molding sand, and the wastes do not contain constituents which would render the wastes hazardous for reasons other than the toxicity characteristic in s. [NR 661.0024](#), with EPA hazardous waste numbers D004 to D017.

cbd 1. All of the following:

a. The monofill has at least one liner for which there is no evidence that the liner is leaking. For the purposes of this subsection the term XlinerY means a liner designed, constructed, installed and operated to prevent hazardous waste from passing into the liner at any time during the active life of the facility, or a liner designed, constructed, installed and operated to prevent hazardous waste from migrating beyond the liner to adjacent subsurface soil, groundwater or surface water at any time during the active life of the facility. In the case of any surface impoundment which has been exempted from the requirements of sub. [c1d](#) on the basis of a liner designed, constructed, installed and operated to prevent hazardous waste from passing beyond the liner, at the closure of the impoundment the owner or operator shall remove or decontaminate all waste residues, all contaminated liner material and contaminated soil to the extent practicable. If all contaminated soil is not removed or decontaminated, the owner of operator of the impoundment shall comply with appropriate long-term care requirements, including but not limited to groundwater monitoring and corrective action.

b. The monofill is located more than one-quarter mile from an underground source of drinking water cas that term is defined in [40 CFR 144.3d](#).

c. The monofill is in compliance with generally applicable groundwater monitoring requirements for facilities with operating licenses under s. [291.25](#), Stats.

2. The owner or operator demonstrates that the monofill is located, designed and operated so as to assure that there will be no migration of any hazardous constituent into groundwater or surface water at any future time.

c5d In the case of any unit in which the liner and leachate collection system has been installed pursuant to the requirements of sub. [c1d](#) and in good faith compliance with sub. [c1d](#) and with guidance documents governing liners and leachate collection systems under sub. [c1d](#), no liner or leachate collection system which is different from that which was so installed pursuant to sub. [c1d](#) will be required for the unit by the department when issuing the first operating license to the facility, except that the department will not be precluded from requiring installation of a new liner when the department has reason to believe that any liner installed pursuant to the requirements of sub. [c1d](#) is leaking.

c6d A surface impoundment shall maintain enough freeboard to prevent any overtopping of the dike by overfilling, wave action or a storm. Except as provided in sub. [c7d](#), there shall be at least 60 centimeters c2 feetd of freeboard.

c7d A freeboard level less than 60 centimeters c2 feetd may be maintained if the owner or operator obtains certification by a qualified engineer that alternate design features or operating plans will, to the best of that person[s] knowledge and opinion, prevent overtopping of the dike. The certification, along with a

written identification of alternate design features or operating plans preventing overtopping, shall be maintained at the facility.

c8d Surface impoundments that are newly subject to [42 USC 6925](#) cjd c1d due to the promulgation of additional listings or characteristics for the identification of hazardous waste shall be in compliance with subs. [c1d](#), [c3d](#) and [c4d](#) not later than 48 months after the promulgation of the additional listing or characteristic. This compliance period may not be cut short as the result of the promulgation of land disposal prohibitions under ch. [NR 668](#) or the granting of an extension to the effective date of a prohibition pursuant to s. [NR 668.05](#), within this 48-month period.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c4d cad Register August 2020 No. 776, eff. 9-1-20.

NR 665.0222 Action leakage rate. c1d The owner or operator of surface impoundment units subject to s. [NR 665.0221 c1d](#) shall submit a proposed action leakage rate to the department when submitting the notice required under s. [NR 665.0221 c2d](#). Within 60 days of receipt of the notification, the department shall establish an action leakage rate, either as proposed by the owner or operator or modified using the criteria in this section, or extend the review period for up to 30 days. If no action is taken by the department before the original 60 or extended 90 day review periods, the action leakage rate shall be approved as proposed by the owner or operator.

c2d The department shall approve an action leakage rate for surface impoundment units subject to s. [NR 665.0221 c1d](#). The action leakage rate is the maximum design flow rate that the leak detection system can remove without the fluid head on the bottom liner exceeding one foot. The action leakage rate shall include an adequate safety margin to allow for uncertainties in the design ce.g., slope, hydraulic conductivity, thickness of drainage materiald, construction, operation and location of the leak detection system, waste and leachate characteristics, likelihood and amounts of other sources of liquids in the leak detection system and proposed response actions ce.g., the action leakage rate shall consider decreases in the flow capacity of the system over time resulting from siltation and clogging, rib layover and creep of synthetic components of the system, overburden pressures, etc.d.

c3d To determine if the action leakage rate has been exceeded, the owner or operator shall convert the weekly or monthly flow rate from the monitoring data obtained under s. [NR 665.0226 c2d](#), to an average daily flow rate cgallons per acre per dayd for each sump. Unless the department approves a different calculation, the average daily flow rate for each sump shall be calculated weekly during the active life and closure period, and if the unit closes in accordance with s. [NR 665.0228 c1d cbd](#), monthly during the long-term care period when monthly monitoring is required under s. [NR 665.0226 c2d](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0223 Containment system. All earthen dikes shall have a protective cover, such as grass, shale or rock, to minimize wind and water erosion and to preserve their structural integrity.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0224 Response actions. c1d The owner or operator of surface impoundment units subject to s. [NR 665.0221 c1d](#) shall develop and keep on site until closure of the facility a response action plan. The response action plan shall set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan shall describe the actions specified in sub. [c2d](#).

c2d If the flow rate into the leak detection system exceeds the

action leakage rate for any sump, the owner or operator shall do all of the following:

cad Notify the department in writing of the exceedence within 7 days of the determination.

cbd Submit a preliminary written assessment to the department within 14 days of the determination, as to the amount of liquids, likely sources of liquids, possible location, size and cause of any leaks and short-term actions taken and planned.

ccd Determine to the extent practicable the location, size and cause of any leak.

cdd Determine whether waste receipt should cease or be curtailed, whether any waste should be removed from the unit for inspection, repairs or controls and whether or not the unit should be closed.

ced Determine any other short-term and longer-term actions to be taken to mitigate or stop any leaks.

cfid Within 30 days after the notification that the action leakage rate has been exceeded, submit to the department the results of the analyses specified in pars. [ccd](#), [cdd](#) and [ced](#), the results of actions taken and actions planned. Monthly thereafter, as long as the flow rate in the leak detection system exceeds the action leakage rate, the owner or operator shall submit to the department a report summarizing the results of any remedial actions taken and actions planned.

c3d To make the leak and remediation determinations in sub. [c2d ccd](#), [cdd](#) and [ced](#), the owner or operator shall comply with par. [cad](#) or [cbd](#):

cad Do all of the following:

1. Assess the source of liquids and amounts of liquids by source.
2. Conduct a fingerprint, hazardous constituent or other analyses of the liquids in the leak detection system to identify the source of liquids and possible location of any leaks, and the hazard and mobility of the liquid.
3. Assess the seriousness of any leaks in terms of potential for escaping into the environment.

cbd Document why the assessments are not needed.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0225 Waste analysis and trial tests. In addition to the waste analyses required by s. [NR 665.0013](#), whenever a surface impoundment is to be used to chemically treat a hazardous waste which is substantially different from waste previously treated in that impoundment or chemically treat hazardous waste with a substantially different process than any previously used in that impoundment, before treating the different waste or using the different process the owner or operator shall do either of the following:

c1d Conduct waste analyses and trial treatment tests ce.g., bench scale or pilot plant scale testsd.

c2d Obtain written, documented information on similar treatment of similar waste under similar operating conditions to show that this treatment will comply with s. [NR 665.0017 c2d](#).

Note: As required by s. [NR 665.0013](#), the waste analysis plan shall include analyses needed to comply with ss. [NR 665.0229](#) and [665.0230](#). As required by s. [NR 665.0073](#), the owner or operator shall place the results from each waste analysis and trial test, or the documented information, in the operating record of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0226 Monitoring and inspection. c1d The owner or operator shall inspect both of the following:

cad The freeboard level at least once each operating day to ensure compliance with s. [NR 665.0222](#).

cbd The surface impoundment, including dikes and vegeta-

tion surrounding the dike, at least once a week to detect any leaks, deterioration or failures in the impoundment.

c2d cad An owner or operator required to have a leak detection system under s. [NR 665.0221 c1d](#) shall record the amount of liquids removed from each leak detection system sump at least once each week during the active life and closure period.

cbd After the final cover is installed, the amount of liquids removed from each leak detection system sump shall be recorded at least monthly. If the liquid level in the sump stays below the pump operating level for 2 consecutive months, the amount of liquids in the sumps shall be recorded at least quarterly. If the liquid level in the sump stays below the pump operating level for 2 consecutive quarters, the amount of liquids in the sumps shall be recorded at least semi-annually. If at any time during the long-term care period the pump operating level is exceeded at units on quarterly or semi-annual recording schedules, the owner or operator shall return to monthly recording of amounts of liquids removed from each sump until the liquid level again stays below the pump operating level for 2 consecutive months.

ccd XPump operating levelY is a liquid level proposed by the owner or operator and approved by the department based on pump activation level, sump dimensions and level that avoids backup into the drainage layer and minimizes head in the sump. The timing for submission and approval of the proposed Xpump operating levelY will be in accordance with s. [NR 665.0222 c1d](#).

Note: As required by s. [NR 665.0015c3d](#), the owner or operator shall remedy any deterioration or malfunction the owner or operator finds.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0228 Closure and long-term care. c1d At closure, the owner or operator shall comply with either par. [cad](#) or [cbd](#):

cad Remove or decontaminate all waste residues, contaminated containment system components cliners, etc.d, contaminated subsoils and structures and equipment contaminated with waste and leachate, and manage them as hazardous waste unless s. [NR 661.0003 c4d](#) applies.

cbd Close the impoundment and provide long-term care for a landfill under subch. [G](#) and s. [NR 665.0310](#), including all of the following:

1. Eliminate free liquids by removing liquid wastes or solidifying the remaining wastes and waste residues.
2. Stabilize remaining wastes to a bearing capacity sufficient to support the final cover.
3. Cover the surface impoundment with a final cover designed and constructed to do all of the following:
 - a. Provide long-term minimization of the migration of liquids through the closed impoundment.
 - b. Function with minimum maintenance.
 - c. Promote drainage and minimize erosion or abrasion of the cover.
 - d. Accommodate settling and subsidence so that the cover[s] integrity is maintained.
 - e. Have a permeability less than or equal to the permeability of any bottom liner system or natural subsoils present.

c2d In addition to the requirements of subch. [G](#) and s. [NR 665.0310](#), during the long-term care period, the owner or operator of a surface impoundment in which wastes, waste residues or contaminated materials remain after closure in accordance with the provisions of sub. [c1d cbd](#), shall do all of the following:

cad Maintain the integrity and effectiveness of the final cover, including making repairs to the cover as necessary to correct the effects of settling, subsidence, erosion or other events.

cbd Maintain and monitor the leak detection system in accor-

dance with ss. [NR 664.0221 c3d cbd 4.](#) and [ccd](#) and [665.0226 c2d](#) and comply with all other applicable leak detection system requirements of this chapter.

ccd Maintain and monitor the groundwater monitoring system and comply with all other applicable requirements of subch. **F**.

cdd Prevent run-on and run-off from eroding or otherwise damaging the final cover.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d cad Register August 2020 No. 776, eff. 9-1-20.

NR 665.0229 Special requirements for ignitable or reactive waste. Ignitable or reactive waste may not be placed in a surface impoundment, unless the waste and impoundment satisfy all applicable requirements of ch. [NR 668](#), and sub. [c1d](#), [c2d](#) or [c3d](#):

c1d The waste is treated, rendered or mixed before or immediately after placement in the impoundment so that both of the following apply:

cad The resulting waste, mixture or dissolution of material no longer meets the definition of ignitable or reactive waste under s. [NR 661.0021](#) or [661.0023](#).

cbd Section [NR 665.0017 c2d](#) is complied with.

c2d All of the following conditions are met:

cad The waste is managed in such a way that it is protected from any material or conditions which may cause it to ignite or react.

ccd The owner or operator obtains a certification from a qualified chemist or engineer that, to the best of that person[s] knowledge and opinion, the design features or operating plans of the facility will prevent ignition or reaction.

cdd The certification and the basis for it are maintained at the facility.

c3d The surface impoundment is used solely for emergencies.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d cad Register August 2020 No. 776, eff. 9-1-20.

NR 665.0230 Special requirements for incompatible wastes. Incompatible wastes, or incompatible wastes and materials, csee ch. [NR 665 Appendix V](#) for examples may not be placed in the same surface impoundment, unless s. [NR 665.0017 c2d](#) is complied with.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

NR 665.0231 Air emission standards. The owner or operator shall manage all hazardous waste placed in a surface impoundment in accordance with the applicable requirements of subchs. **BB** and **CC**.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter L — Waste Piles

NR 665.0250 Applicability. This subchapter applies to owners and operators of facilities that treat or store hazardous waste in piles, except as s. [NR 665.0001](#) provides otherwise. Alternatively, a pile of hazardous waste may be managed as a land-fill under subchapter N.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0251 Protection from wind. The owner or operator of a pile containing hazardous waste which could be subject to dispersal by wind shall cover or otherwise manage the pile so that wind dispersal is controlled.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0252 Waste analysis. In addition to the waste

analyses required by s. [NR 665.0013](#), the owner or operator shall analyze a representative sample of waste from each incoming movement before adding the waste to any existing pile, unless the only wastes the facility receives which are amenable to piling are compatible with each other, or the waste received is compatible with the waste in the pile to which it is to be added. The analysis conducted shall be capable of differentiating between the types of hazardous waste the owner or operator places in piles, so that mixing of incompatible waste does not inadvertently occur. The analysis shall include a visual comparison of color and texture.

Note: As required by s. [NR 665.0013](#), the waste analysis plan shall include analyses needed to comply with ss. [NR 665.0256](#) and [665.0257](#). As required by s. [NR 665.0073](#), the owner or operator shall place the results of this analysis in the operating record of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0253 Containment. If leachate or run-off from a pile is a hazardous waste, the owner or operator shall comply with sub. [c1d](#) or [c2d](#):

c1d Do all of the following:

cad The pile shall be placed on an impermeable base that is compatible with the waste under the conditions of treatment or storage.

cbd The owner or operator shall design, construct, operate and maintain a run-on control system capable of preventing flow onto the active portion of the pile during peak discharge from at least a 25-year storm.

ccd The owner or operator shall design, construct, operate and maintain a run-off management system to collect and control at least the water volume resulting from a 24-hour, 25-year storm.

cdd Collection and holding facilities ce.g., tanks or basins associated with run-on and run-off control systems shall be emptied or otherwise managed expeditiously to maintain design capacity of the system.

c2d Do both of the following:

cad The pile shall be protected from precipitation and run-on by some other means.

cbd No liquids or wastes containing free liquids may be placed in the pile.

Note: If collected leachate or run-off is discharged through a point source to waters of the state, it is subject to the requirements of ss. [283.31](#) and [283.33](#), Stats.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0254 Design and operating requirements. The owner or operator of each new waste pile on which construction commences after June 1, 1995, each lateral expansion of a waste pile unit on which construction commences after June 1, 1995 and each replacement of an existing waste pile unit that is to commence reuse after June 1, 1995 shall install 2 or more liners and a leachate collection and removal system above and between the liners, and operate the leachate collection and removal systems in accordance with s. [NR 664.0251 c3d](#), unless exempted under s. [NR 664.0251 c4d](#), [c5d](#) or [c6d](#), and shall comply with the procedures of s. [NR 665.0221 c2d](#). XConstruction commences Y is as defined in s. [NR 660.10](#) under Xexisting facility Y.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0255 Action leakage rates. c1d The owner or operator of waste pile units subject to s. [NR 665.0254](#) shall submit a proposed action leakage rate to the department when submitting the notice required under s. [NR 665.0254](#). Within 60 days of receipt of the notification, the department shall establish an action leakage rate, either as proposed by the owner or operator or modified using the criteria in this section, or extend the review period for up to 30 days. If no action is taken by the department before the original 60 or extended 90 day review periods,

the action leakage rate shall be approved as proposed by the owner or operator.

c2d The department shall approve an action leakage rate for waste pile units subject to s. NR 665.0254. The action leakage rate is the maximum design flow rate that the leak detection system can remove without the fluid head on the bottom liner exceeding one foot. The action leakage rate shall include an adequate safety margin to allow for uncertainties in the design ce.g., slope, hydraulic conductivity, thickness of drainage material, construction, operation and location of the leak detection system, waste and leachate characteristics, likelihood and amounts of other sources of liquids in the leak detection system and proposed response actions ce.g., the action leakage rate shall consider decreases in the flow capacity of the system over time resulting from siltation and clogging, rib layover and creep of synthetic components of the system, overburden pressures, etc.d.

c3d To determine if the action leakage rate has been exceeded, the owner or operator shall convert the weekly flow rate from the monitoring data obtained under s. NR 665.0260, to an average daily flow rate cgallons per acre per dayd for each sump. Unless the department approves a different calculation, the average daily flow rate for each sump shall be calculated weekly during the active life and closure period.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0256 Special requirements for ignitable or reactive waste. Ignitable or reactive waste may not be placed in a pile unless the waste and pile satisfy all applicable requirements of ch. NR 668, and either of the following:

c1d Addition of the waste to an existing pile results in the waste or mixture no longer meeting the definition of ignitable or reactive waste under s. NR 661.0021 or 661.0023, and complies with s. NR 665.0017 c2d.

c2d The waste is managed in such a way that it is protected from any material or conditions which may cause it to ignite or react.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d Register August 2020 No. 776, eff. 9-1-20.

NR 665.0257 Special requirements for incompatible wastes. c1d Incompatible wastes, or incompatible wastes and materials, csee ch. NR 665 Appendix V for examplesd may not be placed in the same pile, unless s. NR 665.0017 c2d is complied with.

c2d A pile of hazardous waste that is incompatible with any waste or other material stored nearby in other containers, piles, open tanks or surface impoundments shall be separated from the other materials, or protected from them by means of a dike, berm, wall or other device.

Note: The purpose of this is to prevent fires, explosions, gaseous emissions, leaching or other discharge of hazardous waste or hazardous waste constituents which could result from the contact or mixing of incompatible wastes or materials.

c3d Hazardous waste may not be piled on the same area where incompatible wastes or materials were previously piled, unless that area has been decontaminated sufficiently to ensure compliance with s. NR 665.0017 c2d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c1d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

NR 665.0258 Closure and long-term care. c1d At closure, the owner or operator shall remove or decontaminate all waste residues, contaminated containment system components cliners, etc.d, contaminated subsoils and structures and equipment contaminated with waste and leachate, and manage them as hazardous waste unless s. NR 661.0003 c4d applies.

c2d If, after removing or decontaminating all residues and

making all reasonable efforts to effect removal or decontamination of contaminated components, subsoils, structures and equipment as required in sub. c1d, the owner or operator finds that not all contaminated subsoils can be practicably removed or decontaminated, the owner or operator shall close the facility and perform long-term care in accordance with the closure and long-term care requirements that apply to landfills cs. NR 665.0310d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d Register August 2020 No. 776, eff. 9-1-20.

NR 665.0259 Response actions. c1d The owner or operator of waste pile units subject to s. NR 665.0254 shall develop and keep on-site until closure of the facility a response action plan. The response action plan shall set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan shall describe the actions specified in sub. c2d.

c2d If the flow rate into the leak detection system exceeds the action leakage rate for any sump, the owner or operator shall do all of the following:

cad Notify the department in writing of the exceedence within 7 days of the determination.

cbd Submit a preliminary written assessment to the department within 14 days of the determination, as to the amount of liquids, likely sources of liquids, possible location, size and cause of any leaks and short-term actions taken and planned.

ccd Determine to the extent practicable the location, size and cause of any leak.

cdd Determine whether waste receipts should cease or be curtailed, whether any waste should be removed from the unit for inspection, repairs or controls and whether or not the unit should be closed.

ced Determine any other short-term and longer-term actions to be taken to mitigate or stop any leaks.

cfD Within 30 days after the notification that the action leakage rate has been exceeded, submit to the department the results of the analyses specified in pars. ccd, cdd and ced, the results of actions taken and actions planned. Monthly thereafter, as long as the flow rate in the leak detection system exceeds the action leakage rate, the owner or operator shall submit to the department a report summarizing the results of any remedial actions taken and actions planned.

c3d To make the leak and remediation determinations in sub. c2d ccd, cdd and ced, the owner or operator shall comply with par. cad or cbd:

cad Do all of the following:

1. Assess the source of liquids and amounts of liquids by source.

2. Conduct a fingerprint, hazardous constituent or other analyses of the liquids in the leak detection system to identify the source of liquids and possible location of any leaks, and the hazard and mobility of the liquid.

3. Assess the seriousness of any leaks in terms of potential for escaping into the environment.

cbd Document why the assessments are not needed.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0260 Monitoring and inspection. An owner or operator required to have a leak detection system under s. NR 665.0254 shall record the amount of liquids removed from each leak detection system sump at least once each week during the active life and closure period.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter M — Land Treatment

NR 665.0270 Applicability. Land treatment of any hazardous waste is prohibited. The Department may not grant a variance under s. 291.31, Stats., to allow land treatment of any hazardous waste, as identified or listed in ch. NR 661.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter N — Landfills

NR 665.0300 Applicability. This subchapter applies to owners and operators of facilities that dispose of hazardous waste in landfills, except as s. NR 665.0001 provides otherwise. A waste pile used as a disposal facility is a landfill and is governed by this subchapter.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0301 Design and operating requirements.

c1d The owner or operator of each new landfill unit, each lateral expansion of a landfill unit, and each replacement of an existing landfill unit shall install 2 or more liners and a leachate collection and removal system above and between the liners, and operate the leachate collection and removal systems in accordance with s. NR 664.0301 c3d, unless exempted under s. NR 664.0301 c4d, c5d, or c6d.

c2d The owner or operator of each unit referred to in sub. c1d shall notify the department at least 60 days prior to receiving waste. The owner or operator of each facility submitting notice shall file a feasibility and plan of operation report within 6 months after the department receives the notice.

c3d The owner or operator of any replacement landfill unit is exempt from sub. c1d if both of the following apply:

cad The existing unit was constructed in compliance with the design standards of 42 USC 6924 cod c1d cAd cid and c5d.

cbd There is no reason to believe that the liner is not functioning as designed.

c4d The double liner requirement in sub. c1d may be waived by the department for any monofill, if pars. cad and cbd 1. or 2. apply:

cad The monofill contains only hazardous wastes from foundry furnace emission controls or metal casting molding sand, and the wastes do not contain constituents which would render the wastes hazardous for reasons other than the toxicity characteristic in s. NR 661.0024, with EPA hazardous waste numbers D004 to D017.

cbd 1. All of the following conditions are met:

a. The monofill has at least one liner for which there is no evidence that the liner is leaking.

b. The monofill is located more than one-quarter mile from an underground source of drinking water cas that term is defined in 40 CFR 144.3d.

c. The monofill is in compliance with generally applicable groundwater monitoring requirements for facilities with operating licenses under s. 291.25, Stats.

2. The owner or operator demonstrates that the monofill is located, designed and operated so as to assure that there will be no migration of any hazardous constituent into groundwater or surface water at any future time.

c5d In the case of any unit in which the liner and leachate collection system has been installed pursuant to the requirements of sub. c1d and in good faith compliance with sub. c1d and with guidance documents governing liners and leachate collection systems under sub. c1d, no liner or leachate collection system which is different from that which was so installed pursuant to sub. c1d

will be required for the unit by the department when issuing the first operating license to the facility, except that the department will not be precluded from requiring installation of a new liner when the department has reason to believe that any liner installed pursuant to the requirements of sub. c1d is leaking.

c6d The owner or operator shall design, construct, operate and maintain a run-on control system capable of preventing flow onto the active portion of the landfill during peak discharge from at least a 25-year storm.

c7d The owner or operator shall design, construct, operate and maintain a run-off management system to collect and control at least the water volume resulting from a 24-hour, 25-year storm.

c8d Collection and holding facilities ce.g., tanks or basinsd associated with run-on and run-off control systems shall be emptied or otherwise managed expeditiously after storms to maintain design capacity of the system.

c9d The owner or operator of a landfill containing hazardous waste which is subject to dispersal by wind shall cover or otherwise manage the landfill so that wind dispersal of the hazardous waste is controlled.

Note: As required by s. NR 665.0013, the waste analysis plan shall include analyses needed to comply with ss. NR 665.0312, 665.0313 and 665.0314. As required by s. NR 665.0073, the owner or operator shall place the results of these analyses in the operating record of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c4d cad Register August 2020 No. 776, eff. 9-1-20.

NR 665.0302 Action leakage rate. c1d The owner or operator of landfill units subject to s. NR 665.0301 c1d shall submit a proposed action leakage rate to the department when submitting the notice required under s. NR 665.0301 c2d. Within 60 days of receipt of the notification, the department shall establish an action leakage rate, either as proposed by the owner or operator or modified using the criteria in this section, or extend the review period for up to 30 days. If no action is taken by the department before the original 60 or extended 90 day review periods, the action leakage rate shall be approved as proposed by the owner or operator.

c2d The department shall approve an action leakage rate for landfill units subject to s. NR 665.0301 c1d. The action leakage rate is the maximum design flow rate that the leak detection system can remove without the fluid head on the bottom liner exceeding one foot. The action leakage rate shall include an adequate safety margin to allow for uncertainties in the design ce.g., slope, hydraulic conductivity, thickness of drainage materiald, construction, operation and location of the leak detection system, waste and leachate characteristics, likelihood and amounts of other sources of liquids in the leak detection system and proposed response actions ce.g., the action leakage rate shall consider decreases in the flow capacity of the system over time resulting from siltation and clogging, rib layover and creep of synthetic components of the system, overburden pressures, etc.d.

c3d To determine if the action leakage rate has been exceeded, the owner or operator shall convert the weekly or monthly flow rate from the monitoring data obtained under s. NR 665.0304, to an average daily flow rate cgallons per acre per dayd for each sump. Unless the department approves a different calculation, the average daily flow rate for each sump shall be calculated weekly during the active life and closure period, and monthly during the long-term care period when monthly monitoring is required under s. NR 665.0304 c2d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0303 Response actions. c1d The owner or operator of landfill units subject to s. NR 665.0301 c1d shall de-

velop and keep on site until closure of the facility a response action plan. The response action plan shall set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan shall describe the actions specified in sub. [c2d](#).

c2d If the flow rate into the leak detection system exceeds the action leakage rate for any sump, the owner or operator shall do all of the following:

cad Notify the department in writing of the exceedence within 7 days of the determination.

cbd Submit a preliminary written assessment to the department within 14 days of the determination, as to the amount of liquids, likely sources of liquids, possible location, size and cause of any leaks and short-term actions taken and planned.

ccd Determine to the extent practicable the location, size and cause of any leak.

cdd Determine whether waste receipt should cease or be curtailed, whether any waste should be removed from the unit for inspection, repairs or controls and whether or not the unit should be closed.

ced Determine any other short-term and longer-term actions to be taken to mitigate or stop any leaks.

cfD Within 30 days after the notification that the action leakage rate has been exceeded, submit to the department the results of the analyses specified in pars. [ccd](#), [cdd](#) and [ced](#), the results of actions taken and actions planned. Monthly thereafter, as long as the flow rate in the leak detection system exceeds the action leakage rate, the owner or operator shall submit to the department a report summarizing the results of any remedial actions taken and actions planned.

c3d To make the leak and remediation determinations in sub. [c2d](#) [ccd](#), [cdd](#) and [ced](#), the owner or operator shall comply with par. [cad](#) or [cbd](#):

cad Do all of the following:

1. Assess the source of liquids and amounts of liquids by source.

2. Conduct a fingerprint, hazardous constituent or other analyses of the liquids in the leak detection system to identify the source of liquids and possible location of any leaks, and the hazard and mobility of the liquid.

3. Assess the seriousness of any leaks in terms of potential for escaping into the environment.

cbd Document why the assessments are not needed.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0304 Monitoring and inspection. c1d An owner or operator required to have a leak detection system under s. [NR 665.0301 c1d](#) shall record the amount of liquids removed from each leak detection system sump at least once each week during the active life and closure period.

c2d After the final cover is installed, the amount of liquids removed from each leak detection system sump shall be recorded at least monthly. If the liquid level in the sump stays below the pump operating level for 2 consecutive months, the amount of liquids in the sumps shall be recorded at least quarterly. If the liquid level in the sump stays below the pump operating level for 2 consecutive quarters, the amount of liquids in the sumps shall be recorded at least semi-annually. If at any time during the long-term care period the pump operating level is exceeded at units on quarterly or semi-annual recording schedules, the owner or operator shall return to monthly recording of amounts of liquids removed from each sump until the liquid level again stays below the pump operating level for 2 consecutive months.

c3d XPump operating levelY is a liquid level proposed by the owner or operator and approved by the department based on pump activation level, sump dimensions and level that avoids backup into the drainage layer and minimizes head in the sump. The timing for submission and approval of the proposed Xpump operating levelY will be in accordance with s. [NR 665.0302 c1d](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0309 Surveying and recordkeeping. The owner or operator of a landfill shall maintain both of the following items in the operating record required in s. [NR 665.0073](#):

c1d On a map, the exact location and dimensions, including depth, of each cell with respect to permanently surveyed benchmarks.

c2d The contents of each cell and the approximate location of each hazardous waste type within each cell.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0310 Closure and long-term care. c1d At final closure of the landfill or upon closure of any cell, the owner or operator shall cover the landfill or cell with a final cover designed and constructed to do all of the following:

cad Provide long-term minimization of migration of liquids through the closed landfill.

cbd Function with minimum maintenance.

ccd Promote drainage and minimize erosion or abrasion of the cover.

cdd Accommodate settling and subsidence so that the cover[s] integrity is maintained.

ced Have a permeability less than or equal to the permeability of any bottom liner system or natural subsoils present.

c2d After final closure, the owner or operator shall comply with all long-term care requirements contained in ss. [NR 665.0117](#) to [665.0120](#), including maintenance and monitoring throughout the long-term care period. The owner or operator shall do all of the following:

cad Maintain the integrity and effectiveness of the final cover, including making repairs to the cover as necessary to correct the effects of settling, subsidence, erosion or other events.

cbd Maintain and monitor the leak detection system in accordance with ss. [NR 664.0301 c3d ccd 4.](#) and [cdd](#) and [665.0304 c2d](#), and comply with all other applicable leak detection system requirements of this chapter.

ccd Maintain and monitor the groundwater monitoring system and comply with all other applicable requirements of subch. [F](#).

cdd Prevent run-on and run-off from eroding or otherwise damaging the final cover.

ced Protect and maintain surveyed benchmarks used in complying with s. [NR 665.0309](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0312 Special requirements for ignitable or reactive waste. c1d Except as provided in sub. [c2d](#) and s. [NR 665.0316](#), ignitable or reactive waste may not be placed in a landfill, unless the waste and landfill meets all applicable requirements of ch. [NR 668](#) and both of the following:

cad The resulting waste, mixture or dissolution of material no longer meets the definition of ignitable or reactive waste under s. [NR 661.0021](#) or [661.0023](#).

cbd Section [NR 665.0017 c2d](#) is complied with.

c2d Except for prohibited wastes which remain subject to treatment standards in subch. [D of ch. NR 668](#), ignitable wastes in containers may be landfilled without meeting the requirements of sub. [c1d](#), provided that the wastes are disposed of in such a way

that they are protected from any material or conditions which may cause them to ignite. At a minimum, ignitable wastes shall be disposed of in non-leaking containers which are carefully handled and placed so as to avoid heat, sparks, rupture or any other condition that might cause ignition of the wastes; shall be covered daily with soil or other non-combustible material to minimize the potential for ignition of the wastes and may not be disposed of in cells that contain or will contain other wastes which may generate heat sufficient to cause ignition of the waste.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d cad Register August 2020 No. 776, eff. 9-1-20.

NR 665.0313 Special requirements for incompatible wastes. Incompatible wastes, or incompatible wastes and materials, csee ch. NR 665 Appendix V for examplesd may not be placed in the same landfill cell, unless s. NR 665.0017 c2d is complied with.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

NR 665.0314 Special requirements for bulk and containerized liquids. c1d The placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids cwhether or not sorbents have been addedd in any landfill is prohibited.

c2d Containers holding free liquids may not be placed in a landfill unless par. cad, cbd, ccd or cdd applies:

cad All free-standing liquid is handled in one of the following ways:

1. It has been removed by decanting, or other methods.
2. It has been mixed with sorbent or solidified so that free-standing liquid is no longer observed.
3. It has been otherwise eliminated.

cbd The container is very small, such as an ampule.

ccd The container is designed to hold free liquids for use other than storage, such as a battery or capacitor.

cdd The container is a lab pack as defined in s. NR 665.0316 and is disposed of in accordance with s. NR 665.0316.

c3d To demonstrate the absence or presence of free liquids in either a containerized or a bulk waste, the following test shall be used: Method 9095B cpaint filter liquids testd as described in XTest Methods for Evaluating Solid Waste, Physical[Chemical Methods,Y EPA SW-846, incorporated by reference in s. NR 660.11.

c4d The date for compliance with sub. c2d is July 1, 1985.

c5d Sorbents used to treat free liquids to be disposed of in landfills shall be nonbiodegradable. Nonbiodegradable sorbents are materials listed or described in par. cad; materials that pass one of the tests in par. cbd or materials that are determined by EPA to be nonbiodegradable through the 40 CFR part 260 petition process.

cad Nonbiodegradable sorbents are any of the following:

1. Inorganic minerals, other inorganic materials and elemental carbon ce.g., aluminosilicates, clays, smectites, Fuller[s earth, bentonite, calcium bentonite, montmorillonite, calcined montmorillonite, kaolinite, micas cillited, vermiculites, zeolites; calcium carbonate corganic free limestoned; oxides or hydroxides, alumina, lime, silica csandd, diatomaceous earth; perlite cvolcanic glassd; expanded volcanic rock; volcanic ash; cement kiln dust; fly ash; rice hull ash; activated charcoal or activated carbond.

2. High molecular weight synthetic polymers ce.g., polyethylene, high density polyethylene cHDPEd, polypropylene, polystyrene, polyurethane, polyacrylate, polynorborene, polyisobuty-

lene, ground synthetic rubber, cross-linked allylstyrene and tertiary butyl copolymersd. This does not include polymers derived from biological material or polymers specifically designed to be degradable.

3. Mixtures of these nonbiodegradable materials.

cbd The sorbent material may be determined to be nonbiodegradable using any of the following tests:

1. ASTM Method G21-70 c1984ad—Standard Practice for Determining Resistance of Synthetic Polymer Materials to Fungi, incorporated by reference in s. NR 660.11.

2. ASTM Method G22-76 c1984bd—Standard Practice for Determining Resistance of Plastics to Bacteria, incorporated by reference in s. NR 660.11.

3. OECD test 301B [CO₂ Evolution cModified Sturm Testd], incorporated by reference in s. NR 660.11.

c6d The placement of any liquid which is not a hazardous waste in a landfill is prohibited unless the owner or operator of the landfill demonstrates to the department, or the department determines, that both of the following apply:

cad The only reasonably available alternative to the placement in the landfill is placement in a landfill or unlined surface impoundment, whether or not operating under an operating license or interim license, which contains, or may reasonably be anticipated to contain, hazardous waste.

cbd Placement in the owner or operator[s landfill will not present a risk of contamination of any underground source of drinking water cas that term is defined in 40 CFR 144.3d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: r. c1d, renum. c2d to c7d to c1d to c6d and, as renumbered, am. c1d, c3d, c6d cintrod Register July 2017 No. 739, eff. 8-1-17; correction in c4d as renumbered, made under s. 13.97 c4d cbd 7., Stats., Register July 2017 No. 739.

NR 665.0315 Special requirements for containers. Unless they are very small, such as an ampule, containers shall be either of the following:

c1d At least 90 percent full when placed in the landfill.

c2d Crushed, shredded or similarly reduced in volume to the maximum practical extent before burial in the landfill.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0316 Disposal of small containers of hazardous waste in overpacked drums clab packsd. Small containers of hazardous waste in overpacked drums clab packsd may be placed in a landfill if all of the following requirements are met:

c1d Hazardous waste shall be packaged in non-leaking inside containers. The inside containers shall be of a design and constructed of a material that will not react dangerously with, be decomposed by or be ignited by the contained waste. Inside containers shall be tightly and securely sealed. The inside containers shall be of the size and type specified in the U.S. department of transportation cDOTd hazardous materials regulations c49 CFR parts 173, 178 and 179d, if those regulations specify a particular inside container for the waste.

c2d The inside containers shall be overpacked in an open head DOT-specification metal shipping container c49 CFR parts 178 and 179d of no more than 416-liter c110 gallond capacity and surrounded by, at a minimum, a sufficient quantity of sorbent material, determined to be nonbiodegradable in accordance with s. NR 665.0314 c5d, to completely sorb all of the liquid contents of the inside containers. The metal outer container shall be full after it has been packed with inside containers and sorbent material.

c3d The sorbent material used may not be capable of react-

ing dangerously with, being decomposed by or being ignited by the contents of the inside containers, in accordance with s. NR 665.0017 c2d.

c4d Incompatible wastes, as defined in s. NR 660.10, may not be placed in the same outside container.

c5d Reactive waste, other than cyanide- or sulfide-bearing waste as defined in s. NR 661.0023 c1d ced, shall be treated or rendered non-reactive prior to packaging in accordance with subs. c1d to c4d. Cyanide- and sulfide-bearing reactive waste may be packaged in accordance with subs. c1d to c4d without first being treated or rendered non-reactive.

c6d The disposal is in compliance with the requirements of ch. NR 668. Persons who incinerate lab packs according to the requirements in s. NR 668.42 c3d cad may use fiber drums in place of metal outer containers. The fiber drums shall meet the DOT specifications in 49 CFR 173.12 and be overpacked according to the requirements in sub. c2d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c2d, c5d Register August 2020 No. 776, eff. 9-1-20.

Subchapter O — Incinerators

NR 665.0340 Applicability. c1d This subchapter applies to owners and operators of hazardous waste incinerators as defined in s. NR 660.10d, except as s. NR 665.0001 provides otherwise.

c2d cad Except as provided by pars. cbd and ccd, this chapter no longer applies when an owner or operator demonstrates compliance with the maximum achievable control technology cMACTd requirements of 40 CFR part 63, subpart EEE, by conducting a comprehensive performance test and submitting proof of a postmarked notification of compliance to the department under 40 CFR 63.1207 cjd and 63.1210 cdd documenting compliance with 40 CFR part 63, subpart EEE.

cbd Section NR 665.0351 and the applicable requirements of subchs. A to H, BB and CC continue to apply even where the owner or operator has demonstrated compliance with the MACT requirements of 40 CFR part 63, subpart EEE.

ccd Section NR 665.0345 generally prohibiting burning of hazardous waste during startup and shutdown remains in effect if the owner or operator elects to comply with s. NR 670.235 c2d cad 1. to minimize emissions of toxic compounds from startup and shutdown.

c3d Owners and operators of incinerators burning hazardous waste are exempt from this subchapter, except s. NR 665.0351, provided that the owner or operator has documented, in writing, that the waste would not reasonably be expected to contain any of the hazardous constituents in ch. NR 661 Appendix VIII, and has retained that documentation at the facility, if the waste to be burned is one of the following:

cad Listed as a hazardous waste in subch. D of ch. NR 661 solely because it is ignitable hazard code Id, corrosive hazard code Cd or both.

cbd Listed as a hazardous waste in subch. D of ch. NR 661 solely because it is reactive hazard code Rd for characteristics other than those in s. NR 661.0023 c1d cdd and ced, and will not be burned when other hazardous wastes are present in the combustion zone.

ccd A hazardous waste solely because it possesses the characteristic of ignitability, corrosivity or both, as determined by the tests for characteristics of hazardous wastes under subch. C of ch. NR 661.

cdd A hazardous waste solely because it possesses any of the reactivity characteristics in s. NR 661.0023 c1d cad, cbd, ccd,

efd, efd or efd, and will not be burned when other hazardous wastes are present in the combustion zone.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c2d cad Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c2d cad, c3d cbd, cdd Register August 2020 No. 776, eff. 9-1-20; correction in c3d cbd made under s. 35.17, Stats., Register August 2020 No. 776.

NR 665.0341 Waste analysis. In addition to the waste analyses required by s. NR 665.0013, the owner or operator shall sufficiently analyze any waste which the owner or operator has not previously burned in the owner or operator's incinerator to enable the owner or operator to establish steady state normal operating conditions including waste and auxiliary fuel feed and air flow and to determine the type of pollutants which might be emitted. At a minimum, the analysis shall determine all of the following:

c1d Heating value of the waste.

c2d Halogen content and sulfur content in the waste.

c3d Concentrations in the waste of lead and mercury, unless the owner or operator has written, documented data that show that the elements are not present.

Note: As required by s. NR 665.0073, the owner or operator shall place the results from each waste analysis, or the documented information, in the operating record of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0345 General operating requirements. During start-up and shut-down of an incinerator, the owner or operator may not feed hazardous waste unless the incinerator is at steady state normal conditions of operation, including steady state operating temperature and air flow.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0347 Monitoring and inspections. The owner or operator shall conduct, as a minimum, all of the following monitoring and inspections when incinerating hazardous waste:

c1d Monitor existing instruments which relate to combustion and emission control at least every 15 minutes. Immediately make appropriate corrections to maintain steady state combustion conditions either automatically or by the operator. Instruments which relate to combustion and emission control would normally include those measuring waste feed, auxiliary fuel feed, air flow, incinerator temperature, scrubber flow, scrubber pH and relevant level controls.

c2d Inspect the complete incinerator and associated equipment pumps, valves, conveyors, pipes, etc. at least daily for leaks, spills and fugitive emissions, and check all emergency shutdown controls and system alarms to assure proper operation.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0351 Closure. At closure, the owner or operator shall remove all hazardous waste and hazardous waste residues including but not limited to ash, scrubber waters and scrubber sludged from the incinerator.

Note: At closure, as throughout the operating period, unless the owner or operator can demonstrate, according to s. NR 661.0003 c4d, that the residue removed from the owner or operator's incinerator is not hazardous waste, the owner or operator becomes a generator of hazardous waste and shall manage it according to all applicable requirements of chs. NR 662 to 666.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0352 Interim licensed incinerators burning particular hazardous wastes. c1d Owners or operators of incinerators subject to this subchapter may burn EPA hazardous wastes F020, F021, F022, F023, F026 or F027 if they receive an interim license or interim license modification from the department after the owner or operator demonstrates that they can meet

the performance standards of subch. O of ch. NR 664 when they burn these wastes.

c2d The department shall use all of the following standards and procedures to determine whether to issue an interim license or interim license modification:

cad The owner or operator shall submit an application to the department containing applicable information in ss. NR 670.019 and 670.062 demonstrating that the incinerator can meet the performance standards in subch. O of ch. NR 664 when they burn these wastes.

cbd The department shall issue a preliminary determination as to whether the incinerator can meet the performance standards in subch. O of ch. NR 664. The department shall provide notification of this preliminary determination by newspaper advertisement and radio broadcast in the jurisdiction where the incinerator is located. The department shall accept comments on the preliminary determination for 60 days. The department may also hold a public hearing upon request or at the department[s discretion.

ccd After the close of the public comment period, the department shall issue a decision whether or not to issue an interim license or interim license modification for the incinerator.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter P — Thermal Treatment

NR 665.0370 Other thermal treatment. This subchapter applies to owners or operators of facilities that thermally treat hazardous waste in devices other than enclosed devices using controlled flame combustion, except as s. NR 665.0001 provides otherwise. Thermal treatment in enclosed devices using controlled flame combustion is subject to the requirements of subch. O if the unit is an incinerator, and subch. H of ch. NR 666, if the unit is a boiler or an industrial furnace as defined in s. NR 660.10.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0373 General operating requirements. Before adding hazardous waste, the owner or operator shall bring the thermal treatment process to steady state (normal) conditions of operation, including steady state operating temperature, using auxiliary fuel or other means, unless the process is a non-continuous (batch) thermal treatment process which requires a complete thermal cycle to treat a discrete quantity of hazardous waste.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0375 Waste analysis. In addition to the waste analyses required by s. NR 665.0013, the owner or operator shall sufficiently analyze any waste which the owner or operator has not previously treated in the thermal process to enable the owner or operator to establish steady state (normal) or other appropriate (for a non-continuous process) operating conditions (including waste and auxiliary fuel feed) and to determine the type of pollutants which might be emitted. At a minimum, the analysis shall determine all of the following:

- c1d** Heating value of the waste.
- c2d** Halogen content and sulfur content in the waste.
- c3d** Concentrations in the waste of lead and mercury, unless the owner or operator has written, documented data that show that the element is not present.

Note: As required by s. NR 665.0073, the owner or operator shall place the results from each waste analysis, or the documented information, in the operating record of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0377 Monitoring and inspections. The owner or operator shall conduct, as a minimum, all of the follow-

ing monitoring and inspections when thermally treating hazardous waste:

c1d Existing instruments which relate to temperature and emission control (if an emission control device is present) shall be monitored at least every 15 minutes. Appropriate corrections to maintain steady state or other appropriate thermal treatment conditions shall be made immediately either automatically or by the operator. Instruments which relate to temperature and emission control would normally include those measuring waste feed, auxiliary fuel feed, treatment process temperature and relevant process flow and level controls.

c2d The stack plume (emissions), where present, shall be observed visually at least hourly for normal appearance (color and opacity). The operator shall immediately make any indicated operating corrections necessary to return any visible emissions to their normal appearance.

c3d The complete thermal treatment process and associated equipment (pumps, valves, conveyors, pipes, etc.) shall be inspected at least daily for leaks, spills and fugitive emissions, and all emergency shutdown controls and system alarms shall be checked to assure proper operation.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0381 Closure. At closure, the owner or operator shall remove all hazardous waste and hazardous waste residues (concluding, but not limited to, ash) from the thermal treatment process or equipment.

Note: At closure, as throughout the operating period, unless the owner or operator can demonstrate, in accordance with s. NR 661.0003 (c3d or c4d), that any solid waste removed from the thermal treatment process or equipment is not a hazardous waste, the owner or operator becomes a generator of hazardous waste and shall manage it in accordance with all applicable requirements of chs. NR 662 and 663 and this chapter.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0382 Open burning; waste explosives. Open burning of hazardous waste is prohibited except for the open burning and detonation of waste explosives. Waste explosives include waste which has the potential to detonate and bulk military propellants which cannot safely be disposed of through other modes of treatment. Detonation is an explosion in which chemical transformation passes through the material faster than the speed of sound (0.33 kilometers {second at sea level). Owners or operators choosing to open burn or detonate waste explosives shall do so in accordance with the following table and in a manner that does not threaten human health or the environment.

Pounds of waste explosives or propellants	Minimum distance from open burning or detonation to the property of others
0 to 100.....	204 meters (670 feet).
101 to 1,000.....	380 meters (1,250 feet).
1,001 to 10,000.....	530 meters (1,730 feet).
10,001 to 30,000.....	690 meters (2,260 feet).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0383 Interim license thermal treatment devices burning particular hazardous waste. **c1d** Owners or operators of thermal treatment devices subject to this subchapter may burn EPA hazardous wastes F020, F021, F022, F023, F026 or F027 if they demonstrate they can meet the performance standards of subch. O of ch. NR 664 when they burn these wastes and receive approval from the department.

c2d All of the following standards and procedures shall be used in determining whether to approve a thermal treatment unit:

cad The owner or operator shall submit an application to the department containing the applicable information in ss. NR

670.019 and 670.062 demonstrating that the thermal treatment unit can meet the performance standard in subch. O of ch. NR 664 when it burns these wastes.

cbd The department shall issue a tentative decision as to whether the thermal treatment unit can meet the performance standards in subch. O of ch. NR 664. Notification of this tentative decision shall be provided by newspaper advertisement and radio broadcast in the jurisdiction where the thermal treatment device is located. The department shall accept comment on the tentative decision for 60 days. The department also may hold a public hearing upon request or at its discretion.

cd After the close of the public comment period, the department shall issue a decision whether or not to approve the thermal treatment unit.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter Q — Chemical, Physical and Biological Treatment

NR 665.0400 Applicability. This subchapter applies to owners and operators of facilities which treat hazardous wastes by chemical, physical or biological methods in other than tanks and surface impoundments, except as s. NR 665.0001 provides otherwise. Chemical, physical and biological treatment of hazardous waste in tanks and surface impoundments shall be conducted according to subchs. J and K, respectively.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0401 General operating requirements. c1d Chemical, physical or biological treatment of hazardous waste shall comply with s. NR 665.0017 c2d.

c2d Hazardous wastes or treatment reagents may not be placed in the treatment process or equipment if they could cause the treatment process or equipment to rupture, leak, corrode or otherwise fail before the end of its intended life.

c3d Where hazardous waste is continuously fed into a treatment process or equipment, the process or equipment shall be equipped with a means to stop this inflow ce.g., a waste feed cut-off system or by-pass system to a standby containment device.

Note: These systems are intended to be used in the event of a malfunction in the treatment process or equipment.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0402 Waste analysis and trial tests. In addition to the waste analysis required by s. NR 665.0013, whenever a hazardous waste which is substantially different from waste previously treated in a treatment process or equipment at the facility is to be treated in that process or equipment, or a substantially different process than any previously used at the facility is to be used to chemically treat hazardous waste, the owner or operator shall do any of the following to show that this proposed treatment will meet all applicable requirements of s. NR 665.0401 c1d and c2d, before treating the different waste or using the different process or equipment:

c1d Conduct waste analyses and trial treatment tests ce.g., bench scale or pilot plant scale testsd.

c2d Obtain written, documented information on similar treatment of similar waste under similar operating conditions.

Note: As required by s. NR 665.0013, the waste analysis plan shall include analyses needed to comply with ss. NR 665.0405 and 665.0406. As required by s. NR 665.0073, the owner or operator shall place the results from each waste analysis and trial test, or the documented information, in the operating record of the facility.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0403 Inspections. The owner or operator of a treatment facility shall inspect all of the following, where present:

c1d Discharge control and safety equipment ce.g., waste feed

cut-off systems, by-pass systems, drainage systems and pressure relief systemsd at least once each operating day, to ensure that it is in good working order.

c2d Data gathered from monitoring equipment ce.g., pressure and temperature gaugesd, at least once each operating day, to ensure that the treatment process or equipment is being operated according to its design.

c3d The construction materials of the treatment process or equipment, at least weekly, to detect corrosion or leaking of fixtures or seams.

c4d The construction materials of, and the area immediately surrounding, discharge confinement structures ce.g., dikesd, at least weekly, to detect erosion or obvious signs of leakage ce.g., wet spots or dead vegetationd.

Note: As required by s. NR 665.0015c3d, the owner or operator shall remedy any deterioration or malfunction the owner or operator finds.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0404 Closure. At closure, all hazardous waste and hazardous waste residues shall be removed from treatment processes or equipment, discharge control equipment and discharge confinement structures.

Note: At closure, as throughout the operating period, unless the owner or operator can demonstrate, in accordance with s. NR 661.0003 c3d or c4d, that any solid waste removed from the treatment process or equipment is not a hazardous waste, the owner or operator becomes a generator of hazardous waste and shall manage it in accordance with all applicable requirements of chs. NR 662 and 663 and this chapter.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0405 Special requirements for ignitable or reactive waste. Ignitable or reactive waste may not be placed in a treatment process or equipment unless the requirements in sub. c1d or c2d are met:

c1d The waste is treated, rendered or mixed before or immediately after placement in the treatment process or equipment so that both of the following conditions are met:

cad The resulting waste, mixture or dissolution of material no longer meets the definition of ignitable or reactive waste under s. NR 661.0021 or 661.0023.

cbd Section NR 665.0017 c2d is complied with.

c2d The waste is treated in such a way that it is protected from any material or conditions which may cause the waste to ignite or react.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d cad Register August 2020 No. 776, eff. 9-1-20.

NR 665.0406 Special requirements for incompatible wastes. c1d Incompatible wastes, or incompatible wastes and materials, csee ch. NR 665 Appendix V for examplesd may not be placed in the same treatment process or equipment, unless s. NR 665.0017 c2d is complied with.

c2d Hazardous waste may not be placed in unwashed treatment equipment which previously held an incompatible waste or material, unless s. NR 665.0017 c2d is complied with.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c1d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

Subchapter R — Underground Injection

NR 665.0430 Applicability. c1d Except as provided in sub. c2d, underground injection of any hazardous waste through a well is prohibited.

c2d Underground injection of contaminated groundwater that meets the definition of hazardous waste or contains a hazardous waste may be allowed as part of a remedial action necessary for the cleanup of soil or groundwater contamination, and is

not subject to the requirements of chs. NR 664 and 665 subchs. A to E, G, H and N, and chs. NR 668 and 670, provided that all of the following requirements are met:

cad A person who proposes to perform the injection obtains written approval from the department.

cbd The criteria in s. NR 140.28 c5d are met.

ccd The contaminated groundwater is treated before it is injected.

cdd The groundwater is injected into the same formation from which it was withdrawn.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter W — Drip Pads

NR 665.0440 Applicability. c1d The requirements of this subchapter apply to owners and operators of facilities that use new or existing drip pads to convey treated wood drippage, precipitation or surface water run-off to an associated collection system. Existing drip pads are those constructed before June 1, 1995 and those for which the owner or operator has a design and has entered into binding financial or other agreements for construction prior to June 1, 1995. All other drip pads are new drip pads.

c2d The owner or operator of any drip pad that is inside or under a structure that provides protection from precipitation so that neither run-off nor run-on is generated is not regulated under s. NR 665.0443 c5d or c6d, as appropriate.

c3d The requirements of this subchapter are not applicable to the management of infrequent and incidental drippage in storage yards provided that the owner or operator maintains and complies with a written contingency plan that describes how the owner or operator will respond immediately to the discharge of the infrequent and incidental drippage. At a minimum, the contingency plan shall describe how the facility will do all of the following:

cad Clean up the drippage.

cbd Document the cleanup of the drippage.

ccd Retain documents regarding cleanup for 3 years.

cdd Manage the contaminated media in a manner consistent with state rules.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d Register August 2020 No. 776, eff. 9-1-20.

NR 665.0441 Assessment of existing drip pad integrity. c1d For each existing drip pad as defined in s. NR 665.0440, the owner or operator shall evaluate the drip pad and determine that it meets all of the requirements of this subchapter, except the requirements for liners and leak detection systems of s. NR 665.0443 c2d. No later than August 1, 2017, the owner or operator shall obtain and keep on file at the facility a written assessment of the drip pad, reviewed and certified by a qualified professional engineer that attests to the results of the evaluation. The assessment shall be reviewed, updated and re-certified annually until all upgrades, repairs or modifications necessary to achieve compliance with all of the standards of s. NR 665.0443 are complete. The evaluation shall document the extent to which the drip pad meets each of the design and operating standards of s. NR 665.0443, except the standards for liners and leak detection systems, specified in s. NR 665.0443 c2d.

c2d The owner or operator shall develop a written plan for upgrading, repairing and modifying the drip pad to meet the requirements of s. NR 665.0443 c2d, and submit the plan to the department no later than 2 years before the date that all repairs, upgrades and modifications are complete. This written plan shall describe all changes to be made to the drip pad in sufficient detail

to document compliance with all the requirements of s. NR 665.0443. The plan shall be reviewed and certified by a qualified professional engineer.

c3d Upon completion of all upgrades, repairs and modifications, the owner or operator shall submit to the department, the as-built drawings for the drip pad together with a certification by a qualified professional engineer attesting that the drip pad conforms to the drawings.

c4d If the drip pad is found to be leaking or unfit for use, the owner or operator shall comply with the provisions of s. NR 665.0443 c13d or close the drip pad in accordance with s. NR 665.0445.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d to c3d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0442 Design and installation of new drip pads. Owners and operators of new drip pads shall ensure that the pads are designed, installed and operated in accordance with one of the following:

c1d All of the applicable requirements of s. NR 665.0443 cexcept 665.0443c1dcccc, s. NR 665.0444 and s. NR 665.0445.

c2d All of the applicable requirements of s. NR 665.0443 cexcept 665.0443c2dd, s. NR 665.0444 and s. NR 665.0445.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.0443 Design and operating requirements. c1d Drip pads shall comply with all of the following:

cad Be constructed of non-earthen materials, excluding wood and non-structurally supported asphalt.

cbd Be sloped to free-drain treated wood drippage, rain and other waters, or solutions of drippage and water or other wastes to the associated collection system.

ccd Have a curb or berm around the perimeter.

cdd 1. Have a hydraulic conductivity of less than or equal to 1×10^{-7} centimeters per second, e.g., existing concrete drip pads shall be sealed, coated or covered with a surface material with a hydraulic conductivity of less than or equal to 1×10^{-7} centimeters per second such that the entire surface where drippage occurs or may run across is capable of containing the drippage and mixtures of drippage and precipitation, materials or other wastes while being routed to an associated collection system. This surface material shall be maintained free of cracks and gaps that could adversely affect its hydraulic conductivity, and the material shall be chemically compatible with the preservatives that contact the drip pad. The requirements of this provision apply only to existing drip pads and those drip pads for which the owner or operator elects to comply with s. NR 665.0442 c2d instead of s. NR 665.0442 c1d.

2. The owner or operator shall obtain and keep on file at the facility a written assessment of the drip pad, reviewed and certified by a qualified professional engineer that attests to the results of the evaluation. The assessment shall be reviewed, updated, and recertified annually. The evaluation shall document the extent to which the drip pad meets the design and operating standards of this section, except for sub. c2d.

ced Be of sufficient structural strength and thickness to prevent failure due to physical contact, climatic conditions, the stress of installation and the stress of daily operations, including variable and moving loads such as vehicle traffic or movement of wood.

Note: The department will generally consider applicable standards established by professional organizations generally recognized by industry such as the American Concrete Institute cACI and the American Society of Testing Materials cASTM in judging the structural integrity requirement of par. ced.

c2d If an owner or operator elects to comply with s. NR

665.0442 c1d instead of s. NR 665.0442 c2d, the drip pad shall have all of the following:

cad A synthetic liner installed below the drip pad that is designed, constructed and installed to prevent leakage from the drip pad into the adjacent subsurface soil or groundwater or surface water at any time during the active life including the closure period of the drip pad. The liner shall be constructed of materials that will prevent waste from being absorbed into the liner and prevent releases into the adjacent subsurface soil or groundwater or surface water during the active life of the facility. The liner shall comply with all of the following:

1. Be constructed of materials that have appropriate chemical properties and sufficient strength and thickness to prevent failure due to pressure gradients including static head and external hydrogeologic forces, physical contact with the waste or drip pad leakage to which they are exposed, climatic conditions, the stress of installation and the stress of daily operation including stresses from vehicular traffic on the drip pad.

2. Be placed upon a foundation or base capable of providing support to the liner and resistance to pressure gradients above and below the liner to prevent failure of the liner due to settlement, compression or uplift.

3. Be installed to cover all surrounding earth that could come in contact with the waste or leakage.

cbd A leakage detection system immediately above the liner that is designed, constructed, maintained and operated to detect leakage from the drip pad. The leakage detection system shall comply with all of the following:

1. Be constructed of materials that are all of the following:

- a. Chemically resistant to the waste managed in the drip pad and the leakage that might be generated.

- b. Of sufficient strength and thickness to prevent collapse under the pressures exerted by overlaying materials and by any equipment used at the drip pad.

2. Be designed and operated to function without clogging through the scheduled closure of the drip pad.

3. Be designed so that it will detect the failure of the drip pad or the presence of a release of hazardous waste or accumulated liquid at the earliest practicable time.

ccd A leakage collection system immediately above the liner that is designed, constructed, maintained and operated to collect leakage from the drip pad such that it can be removed from below the drip pad. The date, time and quantity of any leakage collected in this system and removed shall be documented in the operating log.

c3d Drip pads shall be maintained such that they remain free of cracks, gaps, corrosion or other deterioration that could cause hazardous waste to be released from the drip pad.

Note: See sub. c13d for remedial action required if deterioration or leakage is detected.

c4d The drip pad and associated collection system shall be designed and operated to convey, drain and collect liquid resulting from drippage or precipitation in order to prevent run-off.

c5d Unless protected by a structure, as described in s. NR 665.0440 c2d, the owner or operator shall design, construct, operate and maintain a run-on control system capable of preventing flow onto the drip pad during peak discharge from at least a 24-hour, 25-year storm unless the system has sufficient excess capacity to contain any run-on that might enter the system, or the drip pad is protected by a structure or cover, as described in s. NR 665.0440 c2d.

c6d Unless protected by a structure or cover, as described in s. NR 665.0440 c2d, the owner or operator shall design, con-

struct, operate and maintain a run-off management system to collect and control at least the water volume resulting from a 24-hour, 25-year storm.

c7d The drip pad shall be evaluated to determine that it meets the requirements of subs. c1d to c6d, and the owner or operator shall obtain a statement from a qualified professional engineer certifying that the drip pad design meets the requirements of this section.

c8d Drillage and accumulated precipitation shall be removed from the associated collection system as necessary to prevent overflow onto the drip pad.

c9d The drip pad surface shall be cleaned thoroughly in a manner and frequency such that accumulated residues of hazardous waste or other materials are removed, with residues being properly managed as hazardous waste, so as to allow weekly inspections of the entire drip pad surface without interference or hindrance from accumulated residues of hazardous waste or other materials on the drip pad. The owner or operator shall document the date and time of each cleaning and the cleaning procedure used in the facility's operating log.

c10d Drip pads shall be operated and maintained in a manner to minimize tracking of hazardous waste or hazardous waste constituents off the drip pad as a result of activities by personnel or equipment.

c11d After being removed from the treatment vessel, treated wood from pressure and non-pressure processes shall be held on the drip pad until drippage has ceased. The owner or operator shall maintain records sufficient to document that all treated wood is held on the pad following treatment in accordance with this requirement.

c12d Collection and holding units associated with run-on and run-off control systems shall be emptied or otherwise managed as soon as possible after storms to maintain design capacity of the system.

c13d Throughout the active life of the drip pad, if the owner or operator detects a condition that may have caused or has caused a release of hazardous waste, the condition shall be repaired within a reasonably prompt period of time following discovery, in accordance with all of the following procedures:

cad Upon detection of a condition that may have caused or has caused a release of hazardous waste (e.g., upon detection of leakage by the leak detection system), the owner or operator shall do all of the following:

1. Enter a record of the discovery in the facility operating log.

2. Immediately remove the portion of the drip pad affected by the condition from service.

3. Determine what steps must be taken to repair the drip pad and remove any leakage from below the drip pad, and establish a schedule for accomplishing the clean up and repairs.

4. Immediately after discovery of the condition, notify the department of the condition and, within 10 working days, provide a written notice to the department with a description of the steps that will be taken to repair the drip pad and clean up any leakage, and the schedule for accomplishing this work.

cbd The department will review the information submitted, make a determination regarding whether the pad must be removed from service completely or partially until repairs and clean up are complete, and notify the owner or operator of the determination and the underlying rationale in writing.

ccd Upon completing all repairs and clean up, the owner or operator shall notify the department in writing and provide a certification, signed by an independent qualified, registered profes-

sional engineer, that the repairs and clean up have been completed according to the written plan submitted in accordance with par. [cad 4](#).

c14d The owner or operator shall maintain, as part of the facility operating log, documentation of past operating and waste handling practices. This shall include identification of preservative formulations used in the past, a description of drippage management practices and a description of treated wood storage and handling practices.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d cdd 2., c7d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0444 Inspections. c1d During construction or installation, liners, and cover systems for example, membranes, sheets, or coatings shall be inspected for uniformity, damage, and imperfections for example, holes, cracks, thin spots, or foreign materials. Immediately after construction or installation, liners shall be inspected and certified as meeting the requirements of s. [NR 665.0443](#) by a qualified professional engineer. The certification shall be maintained at the facility as part of the facility operating record. After installation, liners, and covers shall be inspected to ensure tight seams and joints and the absence of tears, punctures, or blisters.

c2d While a drip pad is in operation, it shall be inspected weekly and after storms to detect evidence of any of the following:

cad Deterioration, malfunctions or improper operation of run-on and run-off control systems.

cbd The presence of leakage in and proper functioning of the leakage detection system.

ccd Deterioration or cracking of the drip pad surface.

Note: See s. [NR 665.0443c13d](#) for remedial action required if deterioration or leakage is detected.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d Register July 2017 No. 739, eff. 8-1-17.

NR 665.0445 Closure. c1d At closure, the owner or operator shall remove or decontaminate all waste residues, contaminated containment system components such as pads and liners, contaminated subsoils, and structures and equipment contaminated with waste and leakage, and manage them as hazardous waste.

c2d If, after removing or decontaminating all residues and making all reasonable efforts to effect removal or decontamination of contaminated components, subsoils, structures and equipment as required in sub. [c1d](#), the owner or operator finds that not all contaminated subsoils can be practicably removed or decontaminated, the owner or operator shall close the facility and perform long-term care in accordance with closure and long-term care requirements that apply to landfills in s. [NR 665.0310d](#). For licensed units, the requirement to have a license continues throughout the long-term care period.

c3d cad The owner or operator of an existing drip pad, as defined in s. [NR 665.0440](#), that does not comply with the liner requirements of s. [NR 665.0443 c2d cad](#) shall do all of the following:

1. Include in the closure plan for the drip pad under s. [NR 665.0112](#) both a plan for complying with sub. [c1d](#) and a contingent plan for complying with sub. [c2d](#) in case not all contaminated subsoils can be practicably removed at closure.

2. Prepare a contingent long-term care plan under s. [NR 665.0118](#) for complying with sub. [c2d](#) in case not all contaminated subsoils can be practicably removed at closure.

cbd The cost estimates calculated under ss. [NR 665.0112](#) and [665.0144](#) for closure and long-term care of a drip pad subject to

this subsection shall include the cost of complying with the contingent closure plan and the contingent long-term care plan, but are not required to include the cost of expected closure under sub. [c1d](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter AA — Air Emission Standards for Process Vents

NR 665.1030 Applicability. c1d This subchapter applies to owners and operators of facilities that treat, store or dispose of hazardous wastes except as provided in s. [NR 665.0001d](#).

c2d Except for s. [NR 665.1034 c4d](#) and [c5d](#), this subchapter applies to process vents associated with distillation, fractionation, thin-film evaporation, solvent extraction or air or steam stripping operations that manage hazardous wastes with organic concentrations of at least 10 ppmw, if these operations are conducted in one of the following:

cad A unit that is subject to the licensing requirements of ch. [NR 670](#).

cbd A unit including a hazardous waste recycling unit that is not exempt from licensing under s. [NR 662.017](#) *ci.e.*, a hazardous waste recycling unit that is not a 90-day tank or container and that is located at a hazardous waste management facility otherwise subject to the licensing requirements of ch. [NR 670](#).

ccd A unit that is exempt from licensing under s. [NR 662.017](#) *ci.e.*, a 90-day tank or container and is not a recycling unit under s. [NR 661.0006](#).

Note: Sections [NR 665.1032](#) to [665.1035](#) apply to process vents on hazardous waste recycling units previously exempt under s. [NR 661.0006 c3d cad](#). Other exemptions under ss. [NR 661.0004](#) and [665.0001 c3d](#) are not affected by these requirements.

c4d This subchapter does not apply to the process vents at a facility where the facility owner or operator certifies that all of the process vents that would otherwise be subject to this subchapter are equipped with and operating air emission controls according to the process vent requirements in [40 CFR part 60, 61 or 63](#), and corresponding provisions of ch. [NR 440](#), subch. III of ch. [NR 446](#) and chs. [NR 447](#) to [469](#). Keep the documentation of compliance under [40 CFR part 60, 61 or 63](#) and corresponding provisions of ch. [NR 440](#), subch. III of ch. [NR 446](#) and chs. [NR 447](#) to [469](#) with, or make it readily available with, the facility operating record.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c2d cbd, ccd Register August 2020 No. 776, eff. 9-1-20.

NR 665.1031 Definitions. As used in this subchapter, all terms shall have the meaning given them in s. [NR 664.1031](#), ch. [291](#), Stats., and chs. [NR 660](#) to [666](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1032 Standards: process vents. c1d The owner or operator of a facility with process vents associated with distillation, fractionation, thin-film evaporation, solvent extraction or air or steam stripping operations managing hazardous wastes with organic concentrations at least 10 ppmw shall do any of the following:

cad Reduce total organic emissions from all affected process vents at the facility below 1.4 kg/h (3 lb/h) and 2.8 Mg/yr (3.1 tons/yr).

cbd Reduce, by use of a control device, total organic emissions from all affected process vents at the facility by 95 weight percent.

c2d If the owner or operator installs a closed-vent system and

control device to comply with sub. [c1d](#), the closed-vent system and control device shall meet s. [NR 665.1033](#).

c3d Determinations of vent emissions and emission reductions or total organic compound concentrations achieved by add-on control devices may be based on engineering calculations or performance tests. If performance tests are used to determine vent emissions, emission reductions or total organic compound concentrations achieved by add-on control devices, the performance tests shall conform with s. [NR 665.1034 c3d](#).

c4d When an owner or operator and the department do not agree on determinations of vent emissions, emission reductions or total organic compound concentrations achieved by add-on control devices based on engineering calculations, use the test methods in s. [NR 665.1034 c3d](#) to resolve the disagreement.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1033 Standards: closed-vent systems and control devices. c1d cad Owners or operators of closed-vent systems and control devices used to comply with provisions of this chapter shall comply with this section.

cbd 1. The owner or operator of an existing facility who cannot install a closed-vent system and control device to comply with this subchapter on the effective date that the facility becomes subject to this subchapter shall prepare an implementation schedule that includes dates by which the closed-vent system and control device will be installed and in operation. The controls shall be installed as soon as possible, but the implementation schedule may allow up to 30 months after the effective date that the facility becomes subject to this subchapter for installation and startup.

2. Any unit that begins operation after June 1, 1995, and is subject to this subchapter when operation begins, shall comply with the rules immediately *ci.e.*, shall have control devices installed and operating on startup of the affected unit; the 30-month implementation schedule does not apply.

3. The owner or operator of any facility in existence on the effective date of a department rule amendment that renders the facility subject to this subchapter shall comply with this subchapter as soon as practicable but no later than 30 months after the amendment's effective date. When control equipment required by this subchapter can not be installed and begin operation by the effective date of the amendment, the facility owner or operator shall prepare an implementation schedule that includes specific calendar dates for award of contracts or issuance of purchase orders for the control equipment, initiation of on-site installation of the control equipment, completion of the control equipment installation and performance of any testing to demonstrate that the installed equipment meets the applicable standards of this subchapter. The owner or operator shall enter the implementation schedule in the operating record or in a permanent, readily available file located at the facility.

4. Owners and operators of facilities and units that become newly subject to this subchapter after August 1, 2006, due to an action other than those described in subd. 3. shall comply with all applicable requirements immediately *ci.e.*, shall have control devices installed and operating on the date the facility or unit becomes subject to this subchapter; the 30-month implementation schedule does not apply.

c2d Design and operate a control device involving vapor recovery *ce.g.*, a condenser or adsorber to recover the organic vapors vented to it with an efficiency of 95 weight percent or greater unless the total organic emission limits of s. [NR 665.1032 c1d cad](#) for all affected process vents can be attained at an efficiency less than 95 weight percent.

c3d Design and operate an enclosed combustion device *ce.g.*,

a vapor incinerator, boiler or process heater to reduce the organic emissions vented to it by 95 weight percent or greater; to achieve a total organic compound concentration of 20 ppmv, expressed as the sum of the actual compounds, not carbon equivalents, on a dry basis corrected to 3 percent oxygen; or to provide a minimum residence time of 0.50 seconds at a minimum temperature of 760 vC. If a boiler or process heater is used as the control device, introduce the vent stream into the flame combustion zone of the boiler or process heater.

c4d cad A flare shall be designed for and operated with no visible emissions as determined by the methods specified in sub. [c5d cad](#), except for periods not to exceed a total of 5 minutes during any 2 consecutive hours.

cbd Operate a flare with a flame present at all times, as determined by the methods specified in sub. [c6d cbd 3](#).

ccd Use a flare only if the net heating value of the gas being combusted is 11.2 MJ{scm c300 Btu{scfd or greater, if the flare is steam-assisted or air-assisted, or if the net heating value of the gas being combusted is 7.45 MJ{scm c200 Btu{scfd or greater if the flare is nonassisted. Determine the net heating value of the gas being combusted by the methods specified in sub. [c5d cbd](#).

cdd 1. Design a steam-assisted or nonassisted flare for and operate it with an exit velocity, determined by the methods specified in sub. [c5d ccd](#), less than 18.3 m{s c60 ft{sd, except as provided in subds. 2. and 3.

2. A steam-assisted or nonassisted flare designed for and operated with an exit velocity, determined by the methods specified in sub. [c5d ccd](#), equal to or greater than 18.3 m{s c60 ft{sd but less than 122 m{s c400 ft{sd is allowed if the net heating value of the gas being combusted is greater than 37.3 MJ{scm c1,000 Btu{scfd.

3. A steam-assisted or nonassisted flare designed for and operated with an exit velocity, determined by the methods specified in sub. [c5d ccd](#), less than the velocity, V_{max} , determined by the method specified in sub. [c5d cdd](#), and less than 122 m{s c400 ft{sd is allowed.

ced Design and operate an air-assisted flare with an exit velocity less than the velocity, V_{max} , determined by the method specified in sub. [c5d ced](#).

cfid A flare used to comply with this section shall be steam-assisted, air-assisted or nonassisted.

c5d cad Use Method 22 in appendix A of 40 CFR part 60, incorporated by reference in s. [NR 660.11](#), to determine the compliance of a flare with the visible emission provisions of this subchapter. Use an observation period of 2 hours according to Method 22.

cbd Calculate the net heating value of the gas being combusted in a flare using the following equation:

$$H_T = K \left[\sum_{i=1}^n C_i H_i \right]$$

where:

H_T = Net heating value of the sample, MJ{scm; where the net enthalpy per mole of offgas is based on combustion at 25 vC and 760 mm Hg, but the standard temperature for determining the volume corresponding to 1 mol is 20 vC

K = Constant, 1.74×10^{-7} c1{ppmd cg mol{scmd cMJ{kcald where standard temperature for cg mol{scmd is 20 vC

C_i = Concentration of sample component i in ppm on a wet basis, measured for organics by Method 18 in appendix A of 40 CFR part 60 and measured for hydrogen and carbon monoxide by

ASTM D1946-82, both incorporated by reference in s. NR 660.11

H_i = Net heat of combustion of sample component i , kcal/g mol at 25 °C and 760 mm Hg. The heats of combustion may be determined using ASTM D2382-83, incorporated by reference in s. NR 660.11, if published values are not available or cannot be calculated

ccd Determine the actual exit velocity of a flare by dividing the volumetric flow rate (in units of standard temperature and pressure, determined by Methods 2, 2A, 2C or 2D in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11, as appropriate, by the unobstructed free cross-sectional area of the flare tip.

cdd Determine the maximum allowed velocity in m/s, V_{max} , for a flare complying with sub. **c4d cdd 3**, by the following equation:

$$\log_{10} (V_{max}) = (H_T + 28.8) / 31.7$$

where:

H_T = The net heating value determined in par. **cbd**

28.8 = Constant

31.7 = Constant

ced Determine the maximum allowed velocity in m/s, V_{max} , for an air-assisted flare by the following equation:

$$V_{max} = 8.706 + 0.7084 (H_T)$$

where:

8.706 = Constant

0.7084 = Constant

H_T = The net heating value determined in par. **cbd**

c6d The owner or operator shall monitor and inspect each control device required to comply with this section to ensure proper operation and maintenance of the control device by implementing all of the following requirements:

cad Install, calibrate, maintain and operate according to the manufacturer's specifications a flow indicator that provides a record of vent stream flow from each affected process vent to the control device at least once every hour. Install the flow indicator sensor in the vent stream at the nearest feasible point to the control device inlet, but before being combined with other vent streams.

cbd Install, calibrate, maintain and operate according to the manufacturer's specifications a device to continuously monitor control device operation according to one of the following:

1. For a thermal vapor incinerator, a temperature monitoring device equipped with a continuous recorder. The device shall have an accuracy of 0.1 percent of the temperature being monitored in °C or 0.5 °C, whichever is greater. Install the temperature sensor at a location in the combustion chamber downstream of the combustion zone.

2. For a catalytic vapor incinerator, a temperature monitoring device equipped with a continuous recorder. The device shall be capable of monitoring temperature at 2 locations and have an accuracy of 0.1 percent of the temperature being monitored in °C or 0.5 °C, whichever is greater. Install one temperature sensor in the vent stream at the nearest feasible point to the catalyst bed inlet and install a second temperature sensor in the vent stream at the nearest feasible point to the catalyst bed outlet.

3. For a flare, a heat sensing monitoring device equipped with a continuous recorder that indicates the continuous ignition of the pilot flame.

4. For a boiler or process heater having a design heat input capacity less than 44 MW, a temperature monitoring device equipped with a continuous recorder. The device shall have an accuracy of 0.1 percent of the temperature being monitored in °C or 0.5 °C, whichever is greater. Install the temperature sensor at a location in the furnace downstream of the combustion zone.

5. For a boiler or process heater having a design heat input capacity greater than or equal to 44 MW, a monitoring device equipped with a continuous recorder to measure a parameter or parameters that indicates good combustion operating practices are being used.

6. For a condenser, any of the following:

a. A monitoring device equipped with a continuous recorder to measure the concentration level of the organic compounds in the exhaust vent stream from the condenser.

b. A temperature monitoring device equipped with a continuous recorder. The device shall be capable of monitoring temperature with an accuracy of 0.1 percent of the temperature being monitored in °C or 0.5 °C, whichever is greater. Install the temperature sensor at a location in the exhaust vent stream from the condenser exit (i.e., product sided).

7. For a carbon adsorption system such as a fixed-bed carbon adsorber that regenerates the carbon bed directly in the control device, any of the following:

a. A monitoring device equipped with a continuous recorder to measure the concentration level of the organic compounds in the exhaust vent stream from the carbon bed.

b. A monitoring device equipped with a continuous recorder to measure a parameter that indicates the carbon bed is regenerated on a regular, predetermined time cycle.

ccd Inspect the readings from each monitoring device required by pars. **cad** and **cbd** at least once each operating day to check control device operation and, if necessary, immediately implement the corrective measures necessary to ensure the control device operates in compliance with this section.

c7d An owner or operator using a carbon adsorption system such as a fixed-bed carbon adsorber that regenerates the carbon bed directly onsite in the control device, shall replace the existing carbon in the control device with fresh carbon at a regular, predetermined time interval that is no longer than the carbon service life established as a requirement of s. NR 665.1035 **c2d cdd 3. f**.

c8d An owner or operator using a carbon adsorption system such as a carbon canister that does not regenerate the carbon bed directly onsite in the control device shall replace the existing carbon in the control device with fresh carbon on a regular basis using one of the following procedures:

cad Monitor the concentration level of the organic compounds in the exhaust vent stream from the carbon adsorption system on a regular schedule and replace the existing carbon with fresh carbon immediately when carbon breakthrough is indicated. The monitoring frequency shall be daily or at an interval no greater than 20 percent of the time required to consume the total carbon working capacity established as a requirement of s. NR 665.1035 **c2d cdd 3. g.**, whichever is longer.

cbd Replace the existing carbon with fresh carbon at a regular, predetermined time interval that is less than the design carbon replacement interval established as a requirement of s. NR 665.1035 **c2d cdd 3. g.**

c9d An owner or operator of an affected facility seeking to comply with this chapter by using a control device other than a thermal vapor incinerator, catalytic vapor incinerator, flare, boiler, process heater, condenser or carbon adsorption system shall develop documentation including sufficient information to

describe the control device operation and identify the process parameter or parameters that indicate proper operation and maintenance of the control device.

c10d A closed-vent system shall meet any of the following design requirements:

cad Design a closed-vent system to operate with no detectable emissions, as indicated by an instrument reading of less than 500 ppmv above background determined by the procedure in s. NR 665.1034 c2d, and by visual inspections.

cbd Design a closed-vent system to operate at a pressure below atmospheric pressure. Equip the system with at least one pressure gauge or other pressure measurement device that can be read from a readily accessible location to verify that negative pressure is being maintained in the closed-vent system when the control device is operating.

c11d The owner or operator shall monitor and inspect each closed-vent system required to comply with this section to ensure proper operation and maintenance of the closed-vent system by implementing all of the following requirements:

cad Inspect and monitor each closed-vent system that is used to comply with sub. c10d cad according to all of the following requirements:

1. Conduct an initial leak detection monitoring of the closed-vent system on or before the date that the system becomes subject to this section. Monitor the closed-vent system components and connections using the procedures in s. NR 665.1034 c2d to demonstrate that the closed-vent system operates with no detectable emissions, as indicated by an instrument reading of less than 500 ppmv above background.

2. After initial leak detection monitoring required in subd. 1., inspect and monitor the closed-vent system as follows:

a. Visually inspect closed-vent system joints, seams or other connections that are permanently or semi-permanently sealed ce.g., a welded joint between 2 sections of hard piping or a bolted and gasketed ducting flanged at least once per year to check for defects that could result in air pollutant emissions. Monitor a component or connection using the procedures in s. NR 665.1034 c2d to demonstrate that it operates with no detectable emissions following any time the component is repaired or replaced ce.g., a section of damaged hard piping is replaced with new hard piping or the connection is unsealed ce.g., a flange is unbolted.

b. Monitor closed-vent system components or connections other than those specified in subd. 2. a. annually and at other times requested by the department, except as provided for in sub. c14d, using the procedures in s. NR 665.1034 c2d to demonstrate that the components or connections operate with no detectable emissions.

3. In the event that a defect or leak is detected, repair the defect or leak according to par. ccd.

4. Maintain a record of the inspection and monitoring according to s. NR 665.1035.

cbd Inspect and monitor each closed-vent system that is used to comply with sub. c10d cbd according to all of the following requirements:

1. Visually inspect the closed-vent system to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, visible cracks, holes or gaps in ductwork or piping or loose connections.

2. Perform an initial inspection of the closed-vent system on or before the date that the system becomes subject to this section. Thereafter, perform the inspections at least once every year.

3. In the event that a defect or leak is detected, repair the defect according to par. ccd.

4. Maintain a record of the inspection and monitoring according to s. NR 665.1035.

ccd Repair all detected defects according to all of the following:

1. Control detectable emissions, as indicated by visual inspection, or by an instrument reading greater than 500 ppmv above background, as soon as practicable, but not later than 15 calendar days after the emission is detected, except as provided for in subd. 3.

2. Make a first attempt at repair no later than 5 calendar days after the emission is detected.

3. Delay of repair of a closed-vent system for which leaks have been detected is allowed if the repair is technically infeasible without a process unit shutdown, or if the owner or operator determines that emissions resulting from immediate repair would be greater than the fugitive emissions likely to result from delay of repair. Complete repair of the equipment by the end of the next process unit shutdown.

4. Maintain a record of the defect repair according to s. NR 665.1035.

c12d Operate closed-vent systems and control devices used to comply with this subchapter at all times when emissions may be vented to them.

c13d The owner or operator using a carbon adsorption system to control air pollutant emissions shall document that all carbon that is a hazardous waste and that is removed from the control device is managed in one of the following manners, regardless of the average volatile organic concentration of the carbon:

cad Regenerated or reactivated in a thermal treatment unit that meets one of the following:

1. The owner or operator of the unit has been issued an operating license under ch. NR 670 which implements the requirements of subch. X of ch. NR 664.

2. The unit is equipped with and operating air emission controls according to the applicable requirements of this subchapter and subch. CC or subch. AA of ch. NR 664 and subch. CC of ch. NR 664.

3. The unit is equipped with and operating air emission controls according to a national emission standard for hazardous air pollutants under 40 CFR part 61 or 63, or corresponding provisions of subch. III of ch. NR 446 and chs. NR 447 to 469.

cbd Incinerated in a hazardous waste incinerator for which any of the following conditions has been met:

1. The owner or operator has been issued an operating license under ch. NR 670 which implements the requirements of subch. O of ch. NR 664.

2. The owner or operator has designed and operates the incinerator according to the interim license requirements of subch. O.

ccd Burned in a boiler or industrial furnace for which any of the following conditions has been met:

1. The owner or operator has been issued an operating license under ch. NR 670 which implements the requirements of subch. H of ch. NR 666.

2. The owner or operator has designed and operates the boiler or industrial furnace according to the interim license requirements of subch. H of ch. NR 666.

c14d Any components of a closed-vent system that are designated, as described in s. NR 665.1035 c3d cid, as unsafe to monitor are exempt from sub. c11d cad 2. b. if the owner or operator does all of the following:

cad Determines that the components of the closed-vent sys-

tem are unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with sub. [c11d cad 2. b.](#)

cbd Adheres to a written plan that requires monitoring the closed-vent system components using the procedure in sub. [c11d cad 2. b.](#) as frequently as practicable during safe-to-monitor times.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c13d cad 2. made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

NR 665.1034 Test methods and procedures. c1d

Each owner or operator subject to this subchapter shall comply with the test methods and procedures requirements in this section.

c2d When a closed-vent system is tested for compliance with no detectable emissions, as required in s. [NR 665.1033 c11d](#), the test shall comply with all of the following requirements:

cad Monitoring shall comply with Method 21 in appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#).

cbd The detection instrument shall meet the performance criteria of Method 21 in appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#).

ccd The instrument shall be calibrated before use on each day of its use by the procedures in Method 21 in appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#).

cdd Calibration gases shall be all of the following:

1. Zero air less than 10 ppm of hydrocarbon in air.
2. A mixture of methane or n-hexane and air at a concentration of approximately, but less than, 10,000 ppm methane or n-hexane.

ced Determine the background level according to Method 21 in appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#).

cfđ Traverse the instrument probe around all potential leak interfaces as close to the interface as possible as described in Method 21 in appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#).

cgd Compare the arithmetic difference between the maximum concentration indicated by the instrument and the background level with 500 ppm for determining compliance.

c3d Performance tests to determine compliance with s. [NR 665.1032 c1d](#) and with the total organic compound concentration limit of s. [NR 665.1033 c3d](#) shall comply with all of the following:

cad Conduct performance tests to determine total organic compound concentrations and mass flow rates entering and exiting control devices and reduce data according to all of the following methods and calculation procedures:

1. Method 2 in appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#), for velocity and volumetric flow rate.

2. Method 18 or Method 25A in Appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#), for organic content. If Method 25A is used, the organic HAP used as the calibration gas shall be the single organic HAP representing the largest percent by volume of the emissions. The use of Method 25A is acceptable if the response from the high-level calibration gas is at least 20 times the standard deviation of the response from the zero calibration gas when the instrument is zeroed on the most sensitive scale.

3. Each performance test shall consist of 3 separate runs; conduct each run for at least one hour under the conditions that exist when the hazardous waste management unit is operating at the highest load or capacity level reasonably expected to occur.

For the purpose of determining total organic compound concentrations and mass flow rates, average the results of all runs. Compute the average on a time-weighted basis.

4. Determine total organic mass flow rates by the following equation:

- a. For sources using Method 18.

$$E_h = Q_{2sd} \left[\sum_{i=1}^n C_i MW_i \right] [0.0416] [10^{-6}]$$

where:

E_h = Total organic mass flow rate, kg{h

Q_{2sd} = Volumetric flow rate of gases entering or exiting control device, determined by Method 2, dscm{h

n = Number of organic compounds in the vent gas

C_i = Organic concentration in ppm, dry basis, of compound i in the vent gas, determined by Method 18

MW_i = Molecular weight of organic compound i in the vent gas, kg{kg-mol

0.0416 = Conversion factor for molar volume, kg-mol{m³ cat 293 K and 760 mm Hgd

10⁻⁶ = Conversion from ppm

- b. For sources using Method 25A.

$E_h = cQdcCdcMWdc0.0416dc10^{-6}d$

where:

E_h = Total organic mass flow rate, kg{h

Q = Volumetric flow rate of gases entering or exiting control device, as determined by Method 2, dscm{h;

C = Organic concentration in ppm, dry basis, as determined by Method 25A

MW = Molecular weight of propane, 44

0.0416 = Conversion factor for molar volume, kg-mol{m³ cat 293 K and 760 mm Hgd

10⁻⁶ = Conversion from ppm.

5. Determine the annual total organic emission rate by the following equation:

$$E_A = (E_h)(H)$$

where:

E_A = Total organic mass emission rate, kg{y

E_h = Total organic mass flow rate for the process vent, kg{h

H = Total annual hours of operations for the affected unit, h

6. Determine total organic emissions from all affected process vents at the facility by summing the hourly total organic mass emission rates cE_h , determined in subd. 4.d and by summing the annual total organic mass emission rates cE_A , determined in subd. 5.d for all affected process vents at the facility.

cbd Record the process information as may be necessary to determine the conditions of the performance tests. Operations during periods of startup, shutdown and malfunction may not constitute representative conditions for the purpose of a performance test.

ccd For an affected facility, provide, or cause to be provided, all of the following performance testing facilities:

1. Sampling ports adequate for the test methods specified in par. [cad](#).

2. A safe sampling platform or platforms.

3. Safe access to the sampling platform or platforms.

4. Utilities for sampling and testing equipment.

cdd For the purpose of making compliance determinations, use the time-weighted average of the results of the 3 runs. In the event that a sample is accidentally lost or conditions occur in which one of the 3 runs must be discontinued because of forced shutdown, failure of an irreplaceable portion of the sample train, extreme meteorological conditions or other circumstances beyond the owner or operator's control, compliance may, upon the department's approval, be determined using the average of the results of the 2 other runs.

c4d To show that a process vent associated with a hazardous waste distillation, fractionation, thin-film evaporation, solvent extraction or air or steam stripping operation is not subject to this subchapter, the owner or operator shall make an initial determination that the time-weighted, annual average total organic concentration of the waste managed by the waste management unit is less than 10 ppmw using one of the following 2 methods:

cad *Direct measurement of the organic concentration of the waste.* This method requires all of the following:

1. Take a minimum of 4 grab samples of waste for each waste stream managed in the affected unit under process conditions expected to cause the maximum waste organic concentration.

2. For waste generated onsite, collect the grab samples at a point before the waste is exposed to the atmosphere such as in an enclosed pipe or other closed system that is used to transfer the waste after generation to the first affected distillation, fractionation, thin-film evaporation, solvent extraction or air or steam stripping operation. For waste generated off-site, collect the grab samples at the inlet to the first waste management unit that receives the waste provided the waste has been transferred to the facility in a closed system such as a tank truck and the waste is not diluted or mixed with other waste.

3. Analyze each sample and compute the total organic concentration of the sample using Method 9060A of EPA SW-846, incorporated by reference in s. NR 660.11, or analyzed for its individual organic constituents.

4. Use the arithmetic mean of the results of the analyses of the 4 samples for each waste stream managed in the unit in determining the time-weighted, annual average total organic concentration of the waste. Calculate the time-weighted average using the annual quantity of each waste stream processed and the mean organic concentration of each waste stream managed in the unit.

cbd *Using knowledge of the waste to determine that its total organic concentration is less than 10 ppmw.* This method requires documentation of the waste determination. Examples of documentation that shall be used to support a determination under this paragraph include production process information documenting that no organic compounds are used, information that the waste is generated by a process that is identical to a process at the same or another facility that has previously been demonstrated by direct measurement to generate a waste stream having a total organic content less than 10 ppmw, or prior speciation analysis results on the same waste stream where it can also be documented that no process changes have occurred since that analysis that could affect the waste total organic concentration.

c5d Make the determination that distillation, fractionation, thin-film evaporation, solvent extraction or air or steam stripping operations manage hazardous wastes with time-weighted, annual average total organic concentrations less than 10 ppmw according to pars. **cad** and **cbd** or **ccd**:

cad By the effective date that the facility becomes subject to this subchapter or by the date when the waste is first managed in a waste management unit, whichever is later.

cbd For continuously generated waste, annually.

ccd Whenever there is a change in the waste being managed or a change in the process that generates or treats the waste.

c6d When an owner or operator and the department do not agree on whether a distillation, fractionation, thin-film evaporation, solvent extraction or air or steam stripping operation manages a hazardous waste with organic concentrations of at least 10 ppmw based on knowledge of the waste, the dispute may be resolved by using direct measurement as specified in sub. **c4d cad**.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c3d cad 2., 4., c4d cad 3., c6d Register July 2017 No. 739, eff. 8-1-16.

NR 665.1035 Recordkeeping requirements. c1d cad Each owner or operator subject to this subchapter shall comply with this section.

cbd An owner or operator of more than one hazardous waste management unit subject to this subchapter may comply with the recordkeeping requirements for these hazardous waste management units in one recordkeeping system if the system identifies each record by each hazardous waste management unit.

c2d Record all of the following information in the facility operating record:

cad For facilities that comply with s. NR 665.1033 **c1d cbd**, an implementation schedule that includes dates by which the closed-vent system and control device will be installed and in operation. The schedule shall also include a rationale of why the installation cannot be completed at an earlier date. The implementation schedule shall be in the facility operating record by the effective date that the facility becomes subject to this subchapter.

cbd Up-to-date documentation of compliance with the process vent standards in s. NR 665.1032, including all of the following:

1. Information and data identifying all affected process vents, annual throughput and operating hours of each affected unit, estimated emission rates for each affected vent and for the overall facility *ci.e.*, the total emissions for all affected vents at the facility and the approximate location within the facility of each affected unit *ce.g.*, identify the hazardous waste management units on a facility plot plan.

2. Information and data supporting determinations of vent emissions and emission reductions achieved by add-on control devices based on engineering calculations or source tests. For the purpose of determining compliance, make determinations of vent emissions and emission reductions using operating parameter values *ce.g.*, temperatures, flow rates or vent stream organic compounds and concentrations that represent the conditions that result in maximum organic emissions, such as when the waste management unit is operating at the highest load or capacity level reasonably expected to occur. If the owner or operator takes any action *ce.g.*, managing a waste of different composition or increasing operating hours of affected waste management units that would result in an increase in total organic emissions from affected process vents at the facility, a new determination is required.

ccd Where an owner or operator chooses to use test data to determine the organic removal efficiency or total organic compound concentration achieved by the control device, a performance test plan. The test plan shall include all of the following:

1. A description of how it is determined that the planned test is going to be conducted when the hazardous waste management unit is operating at the highest load or capacity level reasonably expected to occur. This shall include the estimated or design flow rate and organic content of each vent stream and define the acceptable operating ranges of key process and control device parameters during the test program.

2. A detailed engineering description of the closed-vent system and control device including all of the following:

- a. Manufacturer[s] name and model number of control device.
- b. Type of control device.
- c. Dimensions of the control device.
- d. Capacity.
- e. Construction materials.

3. A detailed description of sampling and monitoring procedures, including sampling and monitoring locations in the system, the equipment to be used, sampling and monitoring frequency and planned analytical procedures for sample analysis.

cdd Documentation of compliance with s. NR 665.1033 shall include all of the following information:

1. A list of all information references and sources used in preparing the documentation.

2. Records, including the dates, of each compliance test required by s. NR 665.1033 c10d.

3. If engineering calculations are used, a design analysis, specifications, drawings, schematics and piping and instrumentation diagrams based on the appropriate sections of XAPTI Course 415: Control of Gaseous EmissionsY, incorporated by reference in s. NR 660.11, or other engineering texts acceptable to the department that present basic control device design information. Documentation provided by the control device manufacturer or vendor that describes the control device design according to subd. 3. a. to g. may be used to comply with this requirement. The design analysis shall address the vent stream characteristics and control device operation parameters as follows:

a. For a thermal vapor incinerator, the design analysis shall consider the vent stream composition, constituent concentrations and flow rate. The design analysis shall also establish the design minimum and average temperature in the combustion zone and the combustion zone residence time.

b. For a catalytic vapor incinerator, the design analysis shall consider the vent stream composition, constituent concentrations and flow rate. The design analysis shall also establish the design minimum and average temperatures across the catalyst bed inlet and outlet.

c. For a boiler or process heater, the design analysis shall consider the vent stream composition, constituent concentrations and flow rate. The design analysis shall also establish the design minimum and average flame zone temperatures, combustion zone residence time and description of method and location where the vent stream is introduced into the combustion zone.

d. For a flare, the design analysis shall consider the vent stream composition, constituent concentrations and flow rate. The design analysis shall also consider the requirements in s. NR 665.1033 c4d.

e. For a condenser, the design analysis shall consider the vent stream composition, constituent concentrations, flow rate, relative humidity and temperature. The design analysis shall also establish the design outlet organic compound concentration level, design average temperature of the condenser exhaust vent stream and design average temperatures of the coolant fluid at the condenser inlet and outlet.

f. For a carbon adsorption system such as a fixed-bed adsorber that regenerates the carbon bed directly onsite in the control device, the design analysis shall consider the vent stream composition, constituent concentrations, flow rate, relative humidity and temperature. The design analysis shall also establish the design exhaust vent stream organic compound concentration level, number and capacity of carbon beds, type and working capacity

of activated carbon used for carbon beds, design total steam flow over the period of each complete carbon bed regeneration cycle, duration of the carbon bed steaming and cooling or drying cycles, design carbon bed temperature after regeneration, design carbon bed regeneration time and design service life of carbon.

g. For a carbon adsorption system such as a carbon canister that does not regenerate the carbon bed directly onsite in the control device, the design analysis shall consider the vent stream composition, constituent concentrations, flow rate, relative humidity and temperature. The design analysis shall also establish the design outlet organic concentration level, capacity of carbon bed, type and working capacity of activated carbon used for carbon bed and design carbon replacement interval based on the total carbon working capacity of the control device and source operating schedule.

4. A statement signed and dated by the owner or operator certifying that the operating parameters used in the design analysis reasonably represent the conditions that exist when the hazardous waste management unit is or would be operating at the highest load or capacity level reasonably expected to occur.

5. A statement signed and dated by the owner or operator certifying that the control device is designed to operate at an efficiency of 95 percent or greater, unless the total organic concentration limit of s. NR 665.1032 c1d is achieved at an efficiency less than 95 weight percent or the total organic emission limits of s. NR 665.1032 c1d for affected process vents at the facility can be attained by a control device involving vapor recovery at an efficiency less than 95 weight percent. A statement provided by the control device manufacturer or vendor certifying that the control equipment meets the design specifications may be used to comply with this requirement.

6. If performance tests are used to demonstrate compliance, all test results.

c3d Record and keep up-to-date in the facility operating record design documentation and monitoring, operating and inspection information for each closed-vent system and control device required to comply with this chapter. The information shall include all of the following:

cad Description and date of each modification that is made to the closed-vent system or control device design.

cbd Identification of operating parameter, description of monitoring device and diagram of monitoring sensor location or locations used to comply with s. NR 665.1033 c6d cad and cbd.

ccd Monitoring, operating and inspection information required by s. NR 665.1033 c6d to c11d.

cdd Date, time and duration of each period that occurs while the control device is operating when any monitored parameter exceeds the value established in the control device design analysis as follows:

1. For a thermal vapor incinerator designed to operate with a minimum residence time of 0.50 seconds at a minimum temperature of 760 vC, period when the combustion temperature is below 760 vC.

2. For a thermal vapor incinerator designed to operate with an organic emission reduction efficiency of 95 percent or greater, period when the combustion zone temperature is more than 28 vC below the design average combustion zone temperature established as a requirement of sub. c2d cdd 3. a.

3. For a catalytic vapor incinerator, period when any of the following occurs:

a. Temperature of the vent stream at the catalyst bed inlet is more than 28 vC below the average temperature of the inlet vent stream established as a requirement of sub. c2d cdd 3. b.

b. Temperature difference across the catalyst bed is less than 80 percent of the design average temperature difference established as a requirement of sub. [c2d cdd 3. b.](#)

4. For a boiler or process heater, period when any of the following occurs:

a. Flame zone temperature is more than 28 vC below the design average flame zone temperature established as a requirement of sub. [c2d cdd 3. c.](#)

b. Position changes where the vent stream is introduced to the combustion zone from the location established as a requirement of sub. [c2d cdd 3. c.](#)

5. For a flare, period when the pilot flame is not ignited.

6. For a condenser that complies with s. [NR 665.1033 c6d cbd 6. a.](#), period when the organic compound concentration level or readings of organic compounds in the exhaust vent stream from the condenser are more than 20 percent greater than the design outlet organic compound concentration level established as a requirement of sub. [c2d cdd 3. e.](#)

7. For a condenser that complies with s. [NR 665.1033 c6d cbd 6. b.](#), period when any of the following occurs:

a. Temperature of the exhaust vent stream from the condenser is more than 6 vC above the design average exhaust vent stream temperature established as a requirement of sub. [c2d cdd 3. e.](#)

b. Temperature of the coolant fluid exiting the condenser is more than 6 vC above the design average coolant fluid temperature at the condenser outlet established as a requirement of sub. [c2d cdd 3. e.](#)

8. For a carbon adsorption system such as a fixed-bed carbon adsorber that regenerates the carbon bed directly onsite in the control device and complies with s. [NR 665.1033 c6d cbd 7. a.](#), period when the organic compound concentration level or readings of organic compounds in the exhaust vent stream from the carbon bed are more than 20 percent greater than the design exhaust vent stream organic compound concentration level established as a requirement of sub. [c2d cdd 3. f.](#)

9. For a carbon adsorption system such as a fixed-bed carbon adsorber that regenerates the carbon bed directly onsite in the control device and complies with s. [NR 665.1033 c6d cbd 7. b.](#), period when the vent stream continues to flow through the control device beyond the predetermined carbon bed regeneration time established as a requirement of sub. [c2d cdd 3. f.](#)

ced Explanation for each period recorded under par. [cdd](#) of the cause for control device operating parameter exceeding the design value and the measures implemented to correct the control device operation.

efd For carbon adsorption systems operated subject to s. [NR 665.1033 c7d](#) or [c8d cbd](#), date when existing carbon in the control device is replaced with fresh carbon.

cgd For carbon adsorption systems operated subject to s. [NR 665.1033 c8d cad](#), a log that records all of the following:

1. Date and time when control device is monitored for carbon breakthrough and the monitoring device reading.

2. Date when existing carbon in the control device is replaced with fresh carbon.

chd Date of each control device startup and shutdown.

cid An owner or operator designating any components of a closed-vent system as unsafe to monitor pursuant to s. [NR 665.1033 c14d](#) shall record in a log that is kept in the facility operating record the identification of closed-vent system components that are designated as unsafe to monitor according to s. [NR 665.1033 c14d](#), an explanation for each closed-vent system component stating why the closed-vent system component is unsafe to

monitor and the plan for monitoring each closed-vent system component.

cjd When each leak is detected as specified in s. [NR 665.1033 c11d](#), record all of the following information:

1. The instrument identification number, the closed-vent system component identification number and the operator name, initials or identification number.

2. The date the leak was detected and the date of first attempt to repair the leak.

3. The date of successful repair of the leak.

4. Maximum instrument reading measured by Method 21 in appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#), after the leak is successfully repaired or determined to be nonrepairable.

5. XRepair delayedY and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.

a. The owner or operator may develop a written procedure that identifies the conditions that justify a delay of repair. In those cases, reasons for delay of repair may be documented by citing the relevant sections of the written procedure.

b. If delay of repair was caused by depletion of stocked parts, there shall be documentation that the spare parts were sufficiently stocked on-site before depletion and the reason for depletion.

c4d Maintain records of the monitoring, operating and inspection information required by sub. [c3d ccd](#) to [cjd](#) for at least 3 years following the date of each occurrence, measurement, maintenance, corrective action or record.

c5d For a control device other than a thermal vapor incinerator, catalytic vapor incinerator, flare, boiler, process heater, condenser or carbon adsorption system, record monitoring and inspection information indicating proper operation and maintenance of the control device in the facility operating record.

c6d Record up-to-date information and data used to determine whether or not a process vent is subject to s. [NR 665.1032](#), including supporting documentation required by s. [NR 665.1034 c4d cbd](#) when application of the knowledge of the nature of the hazardous waste stream or the process by which it was produced is used, in a log that is kept in the facility operating record.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter BB — Air Emission Standards for Equipment Leaks

NR 665.1050 Applicability. **c1d** This subchapter applies to owners and operators of facilities that treat, store or dispose of hazardous wastes except as provided in s. [NR 665.0001d](#).

c2d Except as provided in s. [NR 665.1064 c11d](#), this subchapter applies to equipment that contains or contacts hazardous wastes with organic concentrations of at least 10 percent by weight that are managed in one of the following:

cad A unit that is subject to the licensing requirements of ch. [NR 670](#).

cbd A unit including a hazardous waste recycling unit that is not exempt from licensing under s. [NR 662.017](#) ci.e., a hazardous waste recycling unit that is not a X90-dayY tank or containerd and that is located at a hazardous waste management facility otherwise subject to the licensing requirements of ch. [NR 670](#).

ccd A unit that is exempt from licensing under s. [NR 662.017](#) ci.e., a X90-dayY tank or containerd and is not a recycling unit under s. [NR 661.0006](#).

c3d Each piece of equipment to which this subchapter applies shall be marked in such a manner that it can be distinguished readily from other pieces of equipment.

c4d Equipment that is in vacuum service is excluded from ss. NR 665.1052 to 665.1060 if it is identified as required in s. NR 665.1064 c7d ced.

c5d Equipment that contains or contacts hazardous waste with an organic concentration of at least 10 percent by weight for less than 300 hours per calendar year is excluded from ss. NR 665.1052 to 665.1060 if it is identified, as required in s. NR 665.1064 c7d cfd.

c7d Purged coatings and solvents from surface coating operations subject to the national emission standards for hazardous air pollutants cNESHAPd for the surface coating of automobiles and light-duty trucks at 40 CFR part 63, subpart IIII, are not subject to the requirements of this subchapter.

Note: Sections NR 665.1052 to 665.1064 apply to equipment associated with hazardous waste recycling units previously exempt under s. NR 661.0006 c3d cad. Other exemptions under ss. NR 661.0004 and 665.0001 c3d are not affected by these requirements.

History: CR 05-032; cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007; cr. c7d Register July 2017 No. 739, eff. 8-1-17; CR 19-082; am. c2d cbd, ced Register August 2020 No. 776, eff. 9-1-20.

NR 665.1051 Definitions. As used in this subchapter, all terms shall have the meaning given them in s. NR 664.1031, ch. 291, Stats., and chs. NR 660 to 666.

History: CR 05-032; cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1052 Standards: pumps in light liquid service. **c1d** cad Monitor each pump in light liquid service monthly to detect leaks by the methods specified in s. NR 665.1063 c2d, except as provided in subs. c4d to c6d.

cbd Check each pump in light liquid service by visual inspection each calendar week for indications of liquids dripping from the pump seal.

c2d cad If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.

cbd If there are indications of liquids dripping from the pump seal, a leak is detected.

c3d cad When a leak is detected, repair it as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in s. NR 665.1059.

cbd Make a first attempt at repair ce.g., tightening the packing gland no later than 5 calendar days after each leak is detected.

c4d Each pump equipped with a dual mechanical seal system that includes a barrier fluid system is exempt from sub. c1d, provided all of the following requirements are met:

cad Each dual mechanical seal system shall be one of the following:

1. Operated with the barrier fluid at a pressure that is at all times greater than the pump stuffing box pressure.

2. Equipped with a barrier fluid degassing reservoir that is connected by a closed-vent system to a control device that complies with s. NR 665.1060.

3. Equipped with a system that purges the barrier fluid into a hazardous waste stream with no detectable emissions to the atmosphere.

cbd The barrier fluid system may not be a hazardous waste with organic concentrations 10 percent or greater by weight.

ccd Equip each barrier fluid system with a sensor that will detect failure of the seal system, the barrier fluid system or both.

cdd Check each pump by visual inspection, each calendar week, for indications of liquids dripping from the pump seals.

ced 1. Check each sensor described in par. ccd daily, or equip

it with an audible alarm and check the alarm monthly to ensure it is functioning properly.

2. Determine, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system or both.

cfd 1. If there are indications of liquids dripping from the pump seal or the sensor indicates failure of the seal system, the barrier fluid system or both based on the criterion determined in par. ced 2., a leak is detected.

2. When a leak is detected, repair it as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in s. NR 665.1059.

3. Make a first attempt at repair ce.g., relapping the seal no later than 5 calendar days after each leak is detected.

c5d Any pump that is designated, as described in s. NR 665.1064 c7d cbd, for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from subs. c1d, c3d and c4d if the pump meets all of the following requirements:

cad It has no externally actuated shaft penetrating the pump housing.

cbd It operates with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background measured by the methods specified in s. NR 665.1063 c3d.

ccd It is tested for compliance with par. cbd initially upon designation, annually and at other times requested by the department.

c6d If any pump is equipped with a closed-vent system capable of capturing and transporting any leakage from the seal or seals to a control device that complies with s. NR 665.1060, it is exempt from subs. c1d to c5d.

History: CR 05-032; cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1053 Standards: compressors. **c1d** Equip each compressor with a seal system that includes a barrier fluid system and that prevents leakage of total organic emissions to the atmosphere, except as provided in subs. c8d and c9d.

c2d Each compressor seal system as required in sub. c1d shall be one of the following:

cad Operated with the barrier fluid at a pressure that is at all times greater than the compressor stuffing box pressure.

cbd Equipped with a barrier fluid system that is connected by a closed-vent system to a control device that complies with s. NR 665.1060.

ccd Equipped with a system that purges the barrier fluid into a hazardous waste stream with no detectable emissions to atmosphere.

c3d The barrier fluid may not be a hazardous waste with organic concentrations 10 percent or greater by weight.

c4d Equip each barrier fluid system described in subs. c1d to c3d with a sensor that will detect failure of the seal system, barrier fluid system or both.

c5d cad Check each sensor required in sub. c4d daily, or equip it with an audible alarm and check the alarm monthly to ensure it is functioning properly, unless the compressor is located within the boundary of an unmanned plant site, in which case check the sensor daily.

cbd Determine, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system or both.

c6d If the sensor indicates failure of the seal system, the barrier fluid system or both based on the criterion determined under sub. c5d cbd, a leak is detected.

c7d cad When a leak is detected, repair it as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in s. [NR 665.1059](#).

cbd Make a first attempt at repair ce.g., tightening the packing gland no later than 5 calendar days after each leak is detected.

c8d A compressor is exempt from subs. [c1d](#) and [c2d](#) if it is equipped with a closed-vent system capable of capturing and transporting any leakage from the seal to a control device that complies with s. [NR 665.1060](#), except as provided in sub. [c9d](#).

c9d Any compressor that is designated, as described in s. [NR 665.1064 c7d cbd](#), for no detectable emission as indicated by an instrument reading of less than 500 ppm above background is exempt from subs. [c1d](#) to [c8d](#) if the compressor meets all of the following requirements:

cad It is determined to be operating with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, measured by the method specified in s. [NR 665.1063 c3d](#).

cbd It is tested for compliance with par. [cad](#) initially upon designation, annually and at other times requested by the department.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1054 Standards: pressure relief devices in gas or vapor service. c1d Except during pressure releases, operate each pressure relief device in gas or vapor service with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, measured by the method specified in s. [NR 665.1063 c3d](#).

c2d cad After each pressure release, return the pressure relief device to a condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as soon as practicable, but no later than 5 calendar days after each pressure release, except as provided in s. [NR 665.1059](#).

cbd No later than 5 calendar days after the pressure release, monitor the pressure relief device to confirm the condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, measured by the method specified in s. [NR 665.1063 c3d](#).

c3d Any pressure relief device that is equipped with a closed-vent system capable of capturing and transporting leakage from the pressure relief device to a control device described in s. [NR 665.1060](#) is exempt from subs. [c1d](#) and [c2d](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1055 Standards: sampling connection systems. c1d Equip each sampling connection system with a closed-purge, closed-loop or closed-vent system. The system shall collect the sample purge for return to the process or for routing to the appropriate treatment system. Gases displaced during filling of the sample container are not required to be collected or captured.

c2d Each closed-purge, closed-loop or closed-vent system required in sub. [c1d](#) shall meet one of the following requirements:

cad It returns the purged process fluid directly to the process line.

cbd It collects and recycles the purged process fluid.

ccd It is designed and operated to capture and transport all the purged process fluid to a waste management unit that complies with the applicable requirements of ss. [NR 665.1085](#) to [665.1087](#) or a control device that complies with s. [NR 665.1060](#).

c3d In-situ sampling systems and sampling systems without purges are exempt from subs. [c1d](#) and [c2d](#).

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1056 Standards: open-ended valves or lines. c1d cad Equip each open-ended valve or line with a cap, blind flange, plug or a second valve.

cbd The cap, blind flange, plug or second valve shall seal the open end at all times except during operations requiring hazardous waste stream flow through the open-ended valve or line.

c2d Operate each open-ended valve or line equipped with a second valve in a manner such that the valve on the hazardous waste stream end is closed before the second valve is closed.

c3d When a double block and bleed system is being used, the bleed valve or line may remain open during operations that require venting the line between the block valves but shall comply with sub. [c1d](#) at all other times.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1057 Standards: valves in gas or vapor service or in light liquid service. c1d Monitor each valve in gas or vapor or light liquid service monthly to detect leaks by the methods specified in s. [NR 665.1063 c2d](#) and comply with subs. [c2d](#) to [c5d](#), except as provided in subs. [c6d](#) to [c8d](#) and ss. [NR 665.1061](#) and [665.1062](#).

c2d If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.

c3d cad Any valve for which a leak is not detected for 2 successive months may be monitored the first month of every succeeding quarter, beginning with the next quarter, until a leak is detected.

cbd If a leak is detected, monitor the valve monthly until a leak is not detected for 2 successive months.

c4d cad When a leak is detected, repair it as soon as practicable, but no later than 15 calendar days after the leak is detected, except as provided in s. [NR 665.1059](#).

cbd Make a first attempt at repair no later than 5 calendar days after each leak is detected.

c5d First attempts at repair include, but are not limited to, the following best practices where practicable:

cad Tightening of bonnet bolts.

cbd Replacement of bonnet bolts.

ccd Tightening of packing gland nuts.

cdd Injection of lubricant into lubricated packing.

c6d Any valve that is designated, as described in s. [NR 665.1064 c7d cbd](#), for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from sub. [c1d](#) if the valve meets all of the following requirements:

cad It has no external actuating mechanism in contact with the hazardous waste stream.

cbd It is operated with emissions less than 500 ppm above background determined by the method specified in s. [NR 665.1063 c3d](#).

ccd It is tested for compliance with par. [cbd](#) initially upon designation, annually and at other times requested by the department.

c7d Any valve that is designated, as described in s. [NR 665.1064 c8d cad](#), as an unsafe-to-monitor valve is exempt from sub. [c1d](#) if the owner or operator does all of the following:

cad Determines that the valve is unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with sub. [c1d](#).

cbd Adheres to a written plan that requires monitoring of the valve as frequently as practicable during safe-to-monitor times.

c8d Any valve that is designated, as described in s. [NR](#)

665.1064 c8d cbd, as a difficult-to-monitor valve is exempt from sub. **c1d** if all of the following requirements are met:

cad The owner or operator of the valve determines that the valve cannot be monitored without elevating the monitoring personnel more than 2 meters above a support surface.

cbd The hazardous waste management unit within which the valve is located was in operation before June 1, 1995.

ccd The owner or operator of the valve follows a written plan that requires monitoring of the valve at least once per calendar year.

Note: The equivalent federal RCRA regulations have a compliance date of June 1, 1990, based on when those rules took effect. The Wisconsin rules, initially promulgated in **CR 94-076**, became effective on June 1, 1995.

History: **CR 05-032**; cr. **Register July 2006 No. 607**, eff. 8-1-06.

NR 665.1058 Standards: pumps and valves in heavy liquid service, pressure relief devices in light liquid or heavy liquid service and flanges and other connectors. c1d Monitor pumps and valves in heavy liquid service, pressure relief devices in light liquid or heavy liquid service and flanges and other connectors within 5 days by the method specified in s. **NR 665.1063 c2d** if evidence of a potential leak is found by visual, audible, olfactory or any other detection method.

c2d If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.

c3d cad When a leak is detected, repair it as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in s. **NR 665.1059**.

cbd Make the first attempt at repair no later than 5 calendar days after each leak is detected.

c4d First attempts at repair include, but are not limited to, the best practices described under s. **NR 665.1057 c5d**.

c5d Any connector that is inaccessible or is ceramic or ceramic-lined (e.g., porcelain, glass or glass-lined) is exempt from sub. **c1d** and from s. **NR 665.1064**.

History: **CR 05-032**; cr. **Register July 2006 No. 607**, eff. 8-1-06.

NR 665.1059 Standards: delay of repair. c1d Delay of repair of equipment for which leaks have been detected shall be allowed if the repair is technically infeasible without a hazardous waste management unit shutdown. In such a case, repair the equipment before the end of the next hazardous waste management unit shutdown.

c2d Delay of repair of equipment for which leaks have been detected shall be allowed for equipment that is isolated from the hazardous waste management unit and that does not continue to contain or contact hazardous waste with organic concentrations at least 10 percent by weight.

c3d Delay of repair for valves shall be allowed if all of the following conditions are met:

cad The owner or operator determines that emissions of purged material resulting from immediate repair are greater than the emissions likely to result from delay of repair.

cbd When repair procedures are effected, collect and destroy or recover the purged material in a control device complying with s. **NR 665.1060**.

c4d Delay of repair for pumps shall be allowed if all of the following conditions are met:

cad The repair requires use of a dual mechanical seal system that includes a barrier fluid system.

cbd The repair is completed as soon as practicable, but not later than 6 months after the leak was detected.

c5d Delay of repair beyond a hazardous waste management unit shutdown shall be allowed for a valve if valve assembly replacement is necessary during the hazardous waste management unit shutdown, valve assembly supplies have been depleted and valve assembly supplies had been sufficiently stocked before the supplies were depleted. Repair may not be delayed beyond the next hazardous waste management unit shutdown unless the next hazardous waste management unit shutdown occurs sooner than 6 months after the first hazardous waste management unit shutdown.

History: **CR 05-032**; cr. **Register July 2006 No. 607**, eff. 8-1-06.

NR 665.1060 Standards: closed-vent systems and control devices. c1d Owners and operators of closed-vent systems and control devices subject to this subchapter shall comply with s. **NR 665.1033**.

c2d cad The owner or operator of an existing facility who can not install a closed-vent system and control device to comply with this subchapter on the effective date that the facility becomes subject to this subchapter shall prepare an implementation schedule that includes dates by which the closed-vent system and control device will be installed and in operation. Install the controls as soon as possible, but the implementation schedule may allow up to 30 months after the effective date that the facility becomes subject to this subchapter for installation and startup.

cbd Any units that begin operation after June 1, 1995, and are subject to this subchapter when operation begins, shall comply with the rules immediately (i.e., shall have control devices installed and operating on startup of the affected unit; the 30-month implementation schedule does not apply).

ccd The owner or operator of any facility in existence on the effective date of a department rule amendment that renders the facility subject to this subchapter shall comply with this subchapter as soon as practicable but no later than 30 months after the amendment[s] effective date. When control equipment required by this subchapter can not be installed and begin operation by the effective date of the amendment, prepare an implementation schedule that includes specific calendar dates for award of contracts or issuance of purchase orders for the control equipment, initiation of on-site installation of the control equipment, completion of the control equipment installation and performance of any testing to demonstrate that the installed equipment meets the applicable standards of this subchapter. Enter the implementation schedule in the operating record or in a permanent, readily available file located at the facility.

cdd Owners and operators of facilities and units that become newly subject to this subchapter after August 1, 2006 due to an action other than those described in par. **ccd** shall comply with all applicable requirements immediately (i.e., shall have control devices installed and operating on the date the facility or unit becomes subject to this subchapter; the 30-month implementation schedule does not apply).

History: **CR 05-032**; cr. **Register July 2006 No. 607**, eff. 8-1-06.

NR 665.1061 Alternative standards for valves in gas or vapor service or in light liquid service: percentage of valves allowed to leak. c1d An owner or operator subject to s. **NR 665.1057** may elect to have all valves within a hazardous waste management unit comply with an alternative standard which allows no greater than 2 percent of the valves to leak.

c2d An owner or operator who decides to comply with the alternative standard of allowing 2 percent of valves to leak shall meet all of the following requirements:

cad Conduct a performance test as specified in sub. **c3d** ini-

tially upon designation, annually and at other times requested by the department.

cbd If a valve leak is detected, repair it according to s. NR 665.1057 c4d and c5d.

c3d Conduct performance tests according to all of the following:

cad Monitor all valves subject to s. NR 665.1057, within the hazardous waste management unit, within one week by the methods specified in s. NR 665.1063 c2d.

cbd If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.

ccd Determine the leak percentage by dividing the number of valves subject to s. NR 665.1057 for which leaks are detected, by the total number of valves subject to s. NR 665.1057 within the hazardous waste management unit.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: r. c2d cad, renum. c2d cbd, ccd to c2d cad, cbd, r. c4d Register July 2017 No. 739, eff. 8-1-17.

NR 665.1062 Alternative standards for valves in gas or vapor service or in light liquid service: skip period leak detection and repair. c1d An owner or operator subject to s. NR 665.1057 may elect for all valves within a hazardous waste management unit to comply with one of the alternative work practices specified in sub. c2d cbd and ccd.

c2d cad An owner or operator shall comply with the requirements for valves in s. NR 665.1057, except as described in pars. cbd and ccd.

cbd After 2 consecutive quarterly leak detection periods with the percentage of valves leaking equal to or less than 2 percent, an owner or operator may begin to skip one of the quarterly leak detection periods *ci.e.*, monitor for leaks once every 6 monthsd for the valves subject to s. NR 665.1057.

ccd After 5 consecutive quarterly leak detection periods with the percentage of valves leaking equal to or less than 2 percent, an owner or operator may begin to skip 3 of the quarterly leak detection periods *ci.e.*, monitor for leaks once every year for the valves subject to s. NR 665.1057.

cdd If the percentage of valves leaking is greater than 2 percent, the owner or operators shall monitor monthly in compliance with s. NR 665.1057, but may again elect to use this section after meeting s. NR 665.1057 c3d cad.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: renum. c1d cad to c1d, r. c1d cbd Register July 2017 No. 739, eff. 8-1-17.

NR 665.1063 Test methods and procedures. c1d Each owner or operator subject to this subchapter shall comply with the test methods and procedures requirements in this section.

c2d Leak detection monitoring, as required in ss. NR 665.1052 to 665.1062, shall comply with all of the following requirements:

cad Monitoring shall comply with Method 21 in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11.

cbd The detection instrument shall meet the performance criteria of Method 21.

ccd Calibrate the instrument before use on each day of its use by the procedures in Method 21.

cdd Calibration gases shall be all of the following:

1. Zero air cless than 10 ppm of hydrocarbon in aird.
2. A mixture of methane or n-hexane and air at a concentration of approximately, but less than, 10,000 ppm methane or n-hexane.

ced Traverse the instrument probe around all potential leak

interfaces as close to the interface as possible as described in Method 21.

c3d When equipment is tested for compliance with no detectable emissions, as required in ss. NR 665.1052 c5d, 665.1053 c9d, 665.1054 and 665.1057 c6d, the test shall comply with all of the following requirements:

cad Comply with sub. c2d cad to cdd.

cbd Determine the background level, as set forth in Method 21.

ccd Traverse the instrument probe around all potential leak interfaces as close to the interface as possible as described in Method 21.

cdd Compare the arithmetic difference between the maximum concentration indicated by the instrument and the background level with 500 ppm for determining compliance.

c4d According to the waste analysis plan required by s. NR 665.0013 c2d, an owner or operator of a facility shall determine, for each piece of equipment, whether the equipment contains or contacts a hazardous waste with an organic concentration that equals or exceeds 10 percent by weight using any of the following:

cad Methods described in ASTM Methods D2267-88, E169-87, E168-88 or E260-85, incorporated by reference in s. NR 660.11.

cbd Analyze each sample and compute the total organic concentration of the sample using Method 9060A of EPA SW-846, incorporated by reference in s. NR 660.11, or analyze for its individual organic constituents.

ccd Application of the knowledge of the nature of the hazardous waste stream or the process by which it was produced. This method requires documentation of a waste determination. Examples of documentation that shall be used to support a determination under this paragraph include production process information documenting that no organic compounds are used, information that the waste is generated by a process that is identical to a process at the same or another facility that has previously been demonstrated by direct measurement to have a total organic content less than 10 percent or prior speciation analysis results on the same waste stream where it can also be documented that no process changes have occurred since that analysis that could affect the waste total organic concentration.

c5d If an owner or operator determines that a piece of equipment contains or contacts a hazardous waste with organic concentrations at least 10 percent by weight, the determination can be revised only after following the procedures in sub. c4d cad or cbd.

c6d When an owner or operator and the department do not agree on whether a piece of equipment contains or contacts a hazardous waste with organic concentrations at least 10 percent by weight, the procedures in sub. c4d cad or cbd can be used to resolve the dispute.

c7d Samples used in determining the percent organic content shall be representative of the highest total organic content hazardous waste that is expected to be contained in or contact the equipment.

c8d To determine if pumps or valves are in light liquid service, the vapor pressures of constituents may be obtained from standard reference texts or may be determined by ASTM D2879-86, incorporated by reference in s. NR 660.11.

c9d Performance tests to determine if a control device achieves 95 weight percent organic emission reduction shall comply with s. NR 665.1034 c3d cad to cdd.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-700: am.

c4d cbd Register July 2017 No. 739, eff. 8-1-17; CR 19-082; am. c2d cdd 2. Register August 2020 No. 776, eff. 9-1-20.

NR 665.1064 Recordkeeping requirements. c1d
cad Each owner or operator subject to this subchapter shall comply with this section.

cbd An owner or operator of more than one hazardous waste management unit subject to this subchapter may comply with the recordkeeping requirements for these hazardous waste management units in one recordkeeping system if the system identifies each record by each hazardous waste management unit.

c2d Owners and operators shall record all of the following information in the facility operating record:

cad For each piece of equipment to which this subchapter applies:

1. Equipment identification number and hazardous waste management unit identification.
2. Approximate locations within the facility ce.g., identify the hazardous waste management unit on a facility plot plan.
3. Type of equipment ce.g., a pump or pipeline valved.
4. Percent-by-weight total organics in the hazardous waste stream at the equipment.
5. Hazardous waste state at the equipment ce.g., gas or vapor or liquid.
6. Method of compliance with the standard ce.g., Xmonthly leak detection and repairY or Xequipped with dual mechanical sealsYd.

cbd For facilities that comply with s. NR 665.1033 c1d cbd, an implementation schedule as specified in s. NR 665.1033 c1d cbd.

ccd Where an owner or operator chooses to use test data to demonstrate the organic removal efficiency or total organic compound concentration achieved by the control device, a performance test plan as specified in s. NR 665.1035 c2d ccd.

cdd Documentation of compliance with s. NR 665.1060, including the detailed design documentation or performance test results specified in s. NR 665.1035 c2d cdd.

c3d When each leak is detected as specified in ss. NR 665.1052, 665.1053, 665.1057 and 665.1058, all of the following requirements apply:

cad Attach to the leaking equipment a weatherproof and readily visible identification, marked with the equipment identification number, the date evidence of a potential leak was found according to s. NR 665.1058 c1d and the date the leak was detected.

cbd The identification on equipment, except on a valve, may be removed after it has been repaired.

ccd The identification on a valve may be removed after it has been monitored for 2 successive months as specified in s. NR 665.1057 c3d and no leak has been detected during those 2 months.

c4d When each leak is detected as specified in ss. NR 665.1052, 665.1053, 665.1057 and 665.1058, record all of the following information in an inspection log and keep it in the facility operating record:

cad The instrument and operator identification numbers and the equipment identification number.

cbd The date evidence of a potential leak was found according to s. NR 665.1058 c1d.

ccd The date the leak was detected and the dates of each attempt to repair the leak.

cdd Repair methods applied in each attempt to repair the leak.

ced XAbove 10,000Y if the maximum instrument reading

measured by the methods specified in s. NR 665.1063 c2d after each repair attempt is equal to or greater than 10,000 ppm.

cf d XRepair delayedY and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.

cgd Documentation supporting the delay of repair of a valve in compliance with s. NR 665.1059 c3d.

chd The signature of the owner or operator cor designated whose decision it was that repair could not be effected without a hazardous waste management unit shutdown.

cid The expected date of successful repair of the leak if a leak is not repaired within 15 calendar days.

cjd The date of successful repair of the leak.

c5d Record design documentation and monitoring, operating and inspection information for each closed-vent system and control device required to comply s. NR 665.1060 and keep them up-to-date in the facility operating record as specified in s. NR 665.1035 c3d. Design documentation is specified in s. NR 665.1035 c3d cad and cbd and monitoring, operating and inspection information in s. NR 665.1035 c3d ccd to chd.

c6d For a control device other than a thermal vapor incinerator, catalytic vapor incinerator, flare, boiler, process heater, condenser or carbon adsorption system, record, in the facility operating record, monitoring and inspection information indicating proper operation and maintenance of the control device.

c7d Record all of the following information, pertaining to all equipment subject to ss. NR 665.1052 to 665.1060, in a log that is kept in the facility operating record:

cad A list of identification numbers for equipment cexcept welded fittingsd subject to this subchapter.

cbd 1. A list of identification numbers for equipment that the owner or operator elects to designate for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, under ss. NR 665.1052 c5d, 665.1053 c9d and 665.1057 c6d.

2. The designation of this equipment as subject to s. NR 665.1052 c5d, 665.1053 c9d or 665.1057 c6d, signed by the owner or operator.

ccd A list of equipment identification numbers for pressure relief devices required to comply with s. NR 665.1054 c1d.

cdd 1. The dates of each compliance test required in ss. NR 665.1052 c5d, 665.1053 c9d, 665.1054 and 665.1057 c6d.

2. The background level measured during each compliance test.

3. The maximum instrument reading measured at the equipment during each compliance test.

ced A list of identification numbers for equipment in vacuum service.

cf d Identification, either by list or location carea or group of equipment that contains or contacts hazardous waste with an organic concentration of at least 10 percent by weight for less than 300 hours per calendar year.

c8d Record all of the following information, pertaining to all valves subject to s. NR 665.1057 c7d and c8d, in a log that is kept in the facility operating record:

cad A list of identification numbers for valves that are designated as unsafe to monitor, an explanation for each valve stating why the valve is unsafe to monitor and the plan for monitoring each valve.

cbd A list of identification numbers for valves that are designated as difficult to monitor, an explanation for each valve stating why the valve is difficult to monitor and the planned schedule for monitoring each valve.

c9d Record all of the following information in the facility operating record for valves complying with s. NR 665.1062:

cad A schedule of monitoring.

cbd The percent of valves found leaking during each monitoring period.

c10d Record all of the following information in a log that is kept in the facility operating record:

cad Criteria required in ss. NR 665.1052 c4d ced 2. and 665.1053 c5d cbd and an explanation of the criteria.

cbd Any changes to these criteria and the reasons for the changes.

c11d Record all of the following information in a log that is kept in the facility operating record for use in determining exemptions in the applicability section of this subchapter and other specific subchapters:

cad An analysis determining the design capacity of the hazardous waste management unit.

cbd A statement listing the hazardous waste influent to and effluent from each hazardous waste management unit subject to ss. NR 665.1052 to 665.1060 and an analysis determining whether these hazardous wastes are heavy liquids.

ccd An up-to-date analysis and the supporting information and data used to determine whether or not equipment is subject to ss. NR 665.1052 to 665.1060. The record shall include supporting documentation as required by s. NR 665.1063 c4d ccd when application of the knowledge of the nature of the hazardous waste stream or the process by which it was produced is used. If the owner or operator takes any action ce.g., changing the process that produced the waste that could result in an increase in the total organic content of the waste contained in or contacted by equipment determined not to be subject to ss. NR 665.1052 to 665.1060, then a new determination is required.

c12d Keep records of the equipment leak information required by sub. c4d and the operating information required by sub. c5d for at least 3 years.

c13d The owner or operator of a facility with equipment that is subject to this subchapter and to 40 CFR part 60, 61 or 63, or to corresponding provisions of ch. NR 440, subch. III of ch. NR 446 and chs. NR 447 to 469, may elect to determine compliance with this subchapter either by documentation pursuant to this section, or by documentation of compliance with 40 CFR part 60, 61 or 63, or with corresponding provisions of ch. NR 440, subch. III of ch. NR 446 and chs. NR 447 to 469, pursuant to the relevant provisions of 40 CFR part 60, 61 or 63, or the corresponding provisions of ch. NR 440, subch. III of ch. NR 446 and chs. NR 447 to 469. The owner or operator shall keep the documentation of compliance required by 40 CFR part 60, 61 or 63, or corresponding provisions of ch. NR 440, subch. III of ch. NR 446 and chs. NR 447 to 469 readily available with the facility operating record.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c13d Register August 2020 No. 776, eff. 9-1-20.

Subchapter CC — Air Emission Standards for Tanks, Surface Impoundments and Containers

NR 665.1080 Applicability. **c1d** This subchapter applies to owners and operators of all facilities that treat, store or dispose of hazardous waste in containers, tanks or surface impoundments subject to subch. I, J or K except as s. NR 665.0001 and sub. c2d provide otherwise.

c2d This subchapter does not apply to the following waste management units at the facility:

cad A waste management unit that holds hazardous waste

placed in the unit before June 1, 1998, and in which no hazardous waste is added to the unit on or after June 1, 1998.

cbd A container that has a design capacity less than or equal to 0.1 m³.

ccd A tank in which an owner or operator has stopped adding hazardous waste and the owner or operator has begun implementing or completed closure pursuant to an approved closure plan.

cdd A surface impoundment in which an owner or operator has stopped adding hazardous waste except to implement an approved closure plan and the owner or operator has begun implementing or completed closure pursuant to an approved closure plan.

ced A waste management unit that is used solely for on-site treatment or storage of hazardous waste that is placed in the unit as a result of implementing remedial activities required under the corrective action authorities of 42 USC 6924cud or cvd, 6928chd or 9601 to 9675, similar federal authorities or s. 291.37 or 292.11, Stats.

cfid A waste management unit that is used solely for the management of radioactive mixed waste according to all applicable regulations under the authority of 42 USC 2011 to 2297 and 10101 to 10270.

Note: The U.S. code cUSCd cites in this paragraph are also known as the federal atomic energy act and the federal nuclear waste policy act, respectively.

cgd A hazardous waste management unit that the owner or operator certifies is equipped with and operating air emission controls according to 40 CFR part 60, 61 or 63, or to corresponding provisions of ch. NR 440, subch. III of ch. NR 446 and chs. NR 447 to 469. For the purpose of complying with this paragraph, a tank for which the air emission control includes an enclosure, as opposed to a cover, shall be in compliance with the enclosure and control device requirements of s. NR 665.1085 c9d, except as provided in s. NR 665.1083 c3d ced.

chd A tank that has a process vent as defined in s. NR 664.1031.

c3d For the owner and operator of a facility subject to this subchapter who has received an operating license under s. 291.25, Stats., prior to June 1, 1998, all of the following requirements apply:

cad The requirements of subch. CC of ch. NR 664 shall be incorporated into the license when it is reissued according to s. NR 670.415 or reviewed according to s. NR 670.050 c4d.

cbd Until the date when the license is reissued according to s. NR 670.415 or reviewed according to s. NR 670.050 c4d, the owner and operator is subject to this subchapter.

c4d The requirements of this subchapter, except for the recordkeeping requirements in s. NR 665.1090 c9d, are administratively stayed for a tank or a container used to manage hazardous waste generated by organic peroxide manufacturing and its associated laboratory operations when the owner or operator of the unit meets all of the following conditions:

cad The owner or operator identifies that the tank or container receives hazardous waste generated by an organic peroxide manufacturing process producing more than one functional family of organic peroxides or multiple organic peroxides within one functional family, that one or more of these organic peroxides could potentially undergo self-accelerating thermal decomposition at or below ambient temperatures and that organic peroxides are the predominant products manufactured by the process. For the purpose of meeting the conditions of this subsection, Xorganic peroxideY means an organic compound that contains the bivalent -O-O- structure and which may be considered to be a structural derivative of hydrogen peroxide where one or both of the hydrogen atoms has been replaced by an organic radical.

cbd The owner or operator prepares documentation, according to s. NR 665.1090 c9d, explaining why an undue safety hazard would be created if air emission controls specified in ss. NR 665.1085 to 665.1088 are installed and operated on the tanks and containers used at the facility to manage the hazardous waste generated by the organic peroxide manufacturing process or processes meeting par. cad.

ccd The owner or operator notifies the department in writing that hazardous waste generated by an organic peroxide manufacturing process or processes meeting par. cad are managed at the facility in tanks or containers meeting par. cbd. The notification shall state the name and address of the facility and be signed and dated by an authorized representative of the facility owner or operator.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1081 Definitions. As used in this subchapter, all terms not defined in this section shall have the meaning given them in ch. 291, Stats., and chs. NR 660 to 666.

c1d XAverage volatile organic concentrationY or Xaverage VO concentrationY means the mass-weighted average volatile organic concentration of a hazardous waste determined according to s. NR 665.1084.

c2d XClosure deviceY means a cap, hatch, lid, plug, seal, valve or other type of fitting that blocks an opening in a cover such that when the device is secured in the closed position it prevents or reduces air pollutant emissions to the atmosphere. Closure devices include devices that are detachable from the cover ce.g., a sampling port capd, manually operated ce.g., a hinged access lid or hatchd or automatically operated ce.g., a spring-loaded pressure relief valved.

c3d XContinuous sealY means a seal that forms a continuous closure that completely covers the space between the edge of the floating roof and the wall of a tank. A continuous seal may be a vapor-mounted seal, liquid-mounted seal or metallic shoe seal. A continuous seal may be constructed of fastened segments so as to form a continuous seal.

c4d XCoverY means a device that provides a continuous barrier over the hazardous waste managed in a unit to prevent or reduce air pollutant emissions to the atmosphere. A cover may have openings csuch as access hatches, sampling ports, gauge wellsd that are necessary for operation, inspection, maintenance and repair of the unit on which the cover is used. A cover may be a separate piece of equipment which can be detached and removed from the unit or a cover may be formed by structural features permanently integrated into the design of the unit.

c5d XEnclosureY means a structure that surrounds a tank or container, captures organic vapors emitted from the tank or container and vents the captured vapors through a closed-vent system to a control device.

c6d XExternal floating roofY means a pontoon-type or double-deck type cover that rests on the surface of the material managed in a tank with no fixed roof.

c7d XFixed roofY means a cover that is mounted on a unit in a stationary position and does not move with fluctuations in the level of the material managed in the unit.

c8d XFloating membrane coverY means a cover consisting of a synthetic flexible membrane material that rests upon and is supported by the hazardous waste being managed in a surface impoundment.

c9d XFloating roofY means a cover consisting of a double deck, pontoon single deck or internal floating cover which rests upon and is supported by the material being contained, and is equipped with a continuous seal.

c10d XHard-pipingY means pipe or tubing that is manufactured and properly installed according to relevant standards and good engineering practices.

c11d XIn light material serviceY means the container is used to manage a material for which all of the following conditions apply:

cad The vapor pressure of one or more of the organic constituents in the material is greater than 0.3 kilopascals ckPad at 20 vC.

cbd The total concentration of the pure organic constituents having a vapor pressure greater than 0.3 kPa at 20 vC is equal to or greater than 20 percent by weight.

c12d XInternal floating roofY means a cover that rests or floats on the material surface cbut not necessarily in complete contact with itd inside a tank that has a fixed roof.

c13d XLiquid-mounted sealY means a foam or liquid-filled primary seal mounted in contact with the hazardous waste between the tank wall and the floating roof continuously around the circumference of the tank.

c14d XMalfunctionY means any sudden, infrequent and not reasonably preventable failure of air pollution control equipment, process equipment or a process to operate in a normal or usual manner. Failures that are caused in part by poor maintenance or careless operation are not malfunctions.

c15d XMaximum organic vapor pressureY means the sum of the individual organic constituent partial pressures exerted by the material contained in a tank, at the maximum vapor pressure-causing conditions ci.e., temperature, agitation, pH effects of combining wastes, etc.d reasonably expected to occur in the tank. For the purpose of this subchapter, maximum organic vapor pressure is determined using the procedures specified in s. NR 665.1084 c3d.

c16d XMetallic shoe sealY means a continuous seal that is constructed of metal sheets which are held vertically against the wall of the tank by springs, weighted levers or other mechanisms and is connected to the floating roof by braces or other means. A flexible coated fabric cenveloped spans the annular space between the metal sheet and the floating roof.

c17d XNo detectable organic emissionsY means no escape of organics to the atmosphere determined using the procedure in s. NR 665.1084 c4d.

c18d XPoint of waste originationY means one of the following:

cad When the facility owner or operator is the generator of the hazardous waste, the point where a solid waste produced by a system, process or waste management unit is determined to be hazardous waste as defined in ch. NR 661.

Note: In this case, this term is being used in a manner similar to the use of the term Xpoint of generationY in air standards established for waste management operations in 40 CFR parts 60, 61 and 63.

cbd When the facility owner or operator is not the generator of the hazardous waste, the point where the owner or operator accepts delivery or takes possession of the hazardous waste.

c19d XPoint of waste treatmentY means the point where a hazardous waste to be treated according to s. NR 665.1083 c3d cbd exits the treatment process. Make any waste determination before the waste is conveyed, handled or otherwise managed in a manner that allows the waste to volatilize to the atmosphere.

c20d XSafety deviceY means a closure device such as a pressure relief valve, frangible disc, fusible plug or any other type of device which functions exclusively to prevent physical damage or permanent deformation to a unit or its air emission control equipment by venting gases or vapors directly to the atmosphere

during unsafe conditions resulting from an unplanned, accidental or emergency event. For the purpose of this subchapter, a safety device is not used for routine venting of gases or vapors from the vapor headspace underneath a cover such as during filling of the unit or to adjust the pressure in this vapor headspace in response to normal daily diurnal ambient temperature fluctuations. A safety device is designed to remain in a closed position during normal operations and open only when the internal pressure, or another relevant parameter, exceeds the device threshold setting applicable to the air emission control equipment as determined by the owner or operator based on manufacturer recommendations, applicable rules, fire protection and prevention codes, standard engineering codes and practices or other requirements for the safe handling of flammable, ignitable, explosive, reactive or hazardous materials.

c21d XSingle-seal systemY means a floating roof having one continuous seal. This seal may be vapor-mounted, liquid-mounted or a metallic shoe seal.

c22d XVapor-mounted sealY means a continuous seal that is mounted such that there is a vapor space between the hazardous waste in the unit and the bottom of the seal.

c23d XVolatile organic concentrationY or XVO concentrationY means the fraction by weight of the volatile organic compounds contained in a hazardous waste expressed in terms of parts per million ppmwd as determined by direct measurement or by knowledge of the waste according to s. NR 665.1084. For the purpose of determining the VO concentration of a hazardous waste, organic compounds with a Henry[s law constant value of at least 0.1 mole-fraction-in-the-gas-phase{mole-fraction-in the liquid-phase c0.1 Y{Xd cwhich can also be expressed as 1.8×10^{-6} atmospheres{gram-mole{m³d at 25 °C shall be included. Ch. NR 665 Appendix VI presents a list of compounds known to have a Henry[s law constant value less than the cutoff level.

c24d XWaste determinationY means performing all applicable procedures according to s. NR 665.1084 to determine whether a hazardous waste meets standards specified in this subchapter. Examples of a waste determination include performing the procedures according to s. NR 665.1084 to determine the average VO concentration of a hazardous waste at the point of waste origination, the average VO concentration of a hazardous waste at the point of waste treatment and comparing the results to the exit concentration limit specified for the process used to treat the hazardous waste, the organic reduction efficiency and the organic biodegradation efficiency for a biological process used to treat a hazardous waste and comparing the results to the applicable standards, or the maximum volatile organic vapor pressure for a hazardous waste in a tank and comparing the results to the applicable standards.

c25d XWaste stabilization processY means any physical or chemical process used to either reduce the mobility of hazardous constituents in a hazardous waste or eliminate free liquids as determined by Method 9095B cPaint Filter Liquids Testd in XTest Methods for Evaluating Solid Waste, Physical{Chemical Methods,Y of EPA SW-846, incorporated by reference in s. NR 660.11. A waste stabilization process includes mixing the hazardous waste with binders or other materials, and curing the resulting hazardous waste and binder mixture. Other synonymous terms used to refer to this process are Xwaste fixationY or Xwaste solidification.Y This does not include the adding of absorbent materials to the surface of a waste, without mixing, agitation or subsequent curing, to absorb free liquid.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c23d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; CR 16-007: am. c25d Register July 2017 No. 739, eff. 8-1-17.

NR 665.1082 Schedule for implementation of air emission standards. c1d Owners or operators of facilities existing on June 1, 1998 and subject to subch. I, J or K shall meet all of the following requirements:

cad Install and begin operation of all control equipment or waste management units required to comply with this subchapter and complete modifications of production or treatment processes to satisfy exemption criteria according to s. NR 665.1083 c3d by June 1, 1998, except as provided for in par. cbd.

cbd When control equipment or waste management units required to comply with this subchapter cannot be installed and in operation or modifications of production or treatment processes to satisfy exemption criteria according to s. NR 665.1083 c3d cannot be completed by June 1, 1998, the owner or operator shall do all of the following:

1. Install and begin operation of the control equipment and waste management units, and complete modifications of production or treatment processes as soon as possible but no later than June 1, 1999.

2. Prepare an implementation schedule that includes specific calendar dates for award of contracts or issuance of purchase orders for control equipment, waste management units and production or treatment process modifications; initiation of on-site installation of control equipment or waste management units, and modifications of production or treatment processes; completion of control equipment or waste management unit installation, and production or treatment process modifications; and performance of testing to demonstrate that the installed equipment or waste management units, and modified production or treatment processes meet the applicable standards of this subchapter.

3. For facilities subject to the recordkeeping requirements of s. NR 665.0073, the owner or operator shall enter the implementation schedule specified in subd. 2. in the operating record no later than June 1, 1998.

4. For facilities not subject to s. NR 665.0073, the owner or operator shall enter the implementation schedule specified in subd. 2. in a permanent, readily available file located at the facility no later than June 1, 1998.

c2d Owners or operators of facilities and units in existence on the effective date of a department rule amendment that renders the facility subject to subch. I, J or K shall meet all of the following requirements:

cad Install and begin operation of control equipment or waste management units required to comply with this subchapter, and complete modifications of production or treatment processes to satisfy exemption criteria of s. NR 665.1083 c3d by the effective date of the amendment, except as provided for in par. cbd.

cbd When control equipment or waste management units required to comply with this subchapter cannot be installed and begin operation, or when modifications of production or treatment processes to satisfy exemption criteria of s. NR 665.1083 c3d cannot be completed by the effective date of the amendment, the owner or operator shall do all of the following:

1. Install and begin operation of the control equipment or waste management unit, and complete modification of production or treatment processes as soon as possible but no later than 30 months after the effective date of the amendment.

2. For facilities subject to the recordkeeping requirements of s. NR 665.0073, enter and maintain the implementation schedule specified in sub. c1d cbd 2. in the operating record no later than the effective date of the amendment.

3. For facilities not subject to s. NR 665.0073, the owner or operator shall enter and maintain the implementation schedule

specified in sub. [c1d cbd 2](#). in a permanent, readily available file located at the facility site no later than the effective date of the amendment.

c3d Owners and operators of facilities and units that become newly subject to this subchapter after June 1, 1999 due to an action other than those described in sub. [c2d](#) shall comply with all applicable requirements immediately *ci.e.*, shall have control devices installed and operating on the date the facility or unit becomes subject to this subchapter; the 30-month implementation schedule does not apply.

c4d The department may elect to extend the implementation date for control equipment at a facility, on a case by case basis, to a date later than June 1, 1999, when special circumstances that are beyond the facility owner[s] or operator[s] control delay installation or operation of control equipment, and the owner or operator has made all reasonable and prudent attempts to comply with this subchapter.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1083 Standards: general. c1d This section applies to the management of hazardous waste in tanks, surface impoundments and containers subject to this subchapter.

c2d The owner or operator shall control air pollutant emissions from each hazardous waste management unit according to the standards in ss. [NR 665.1085](#) to [665.1088](#), as applicable to the hazardous waste management unit, except as provided in sub. [c3d](#).

c3d A tank, surface impoundment or container is exempt from the standards in ss. [NR 665.1085](#) to [665.1088](#), as applicable, provided that the waste management unit is one of the following:

cad A tank, surface impoundment or container for which all hazardous waste entering the unit has an average VO concentration at the point of waste origination of less than 500 parts per million by weight *ppmw*. Determine the average VO concentration using the procedures in s. [NR 665.1084 c1d](#). Review and update, as necessary, this determination at least once every 12 months following the date of the initial determination for the hazardous waste streams entering the unit.

cbd A tank, surface impoundment or container for which the organic content of all the hazardous waste entering the waste management unit has been reduced by an organic destruction or removal process that achieves any one of the following conditions:

1. A process that removes or destroys the organics contained in the hazardous waste to a level such that the average VO concentration of the hazardous waste at the point of waste treatment is less than the exit concentration limit *cC,d* established for the process. Determine the average VO concentration of the hazardous waste at the point of waste treatment and the exit concentration limit for the process using the procedures in s. [NR 665.1084 c2d](#).

2. A process that removes or destroys the organics contained in the hazardous waste to a level such that the organic reduction efficiency *cRd* for the process is equal to or greater than 95 percent, and the average VO concentration of the hazardous waste at the point of waste treatment is less than 100 *ppmw*. Determine the organic reduction efficiency for the process and the average VO concentration of the hazardous waste at the point of waste treatment using the procedures in s. [NR 665.1084 c2d](#).

3. A process that removes or destroys the organics contained in the hazardous waste to a level such that the actual organic mass removal rate *cMRd* for the process is equal to or greater than the required organic mass removal rate *cRMRd* established for the

process. Determine the required organic mass removal rate and the actual organic mass removal rate for the process using the procedures in s. [NR 665.1084 c2d](#).

4. A biological process that destroys or degrades the organics contained in the hazardous waste, such that any of the following conditions is met:

- a. The organic reduction efficiency *cRd* for the process is equal to or greater than 95 percent, and the organic biodegradation efficiency *cR_{bio,d}* for the process is equal to or greater than 95 percent. Determine the organic reduction efficiency and the organic biodegradation efficiency for the process using the procedures in s. [NR 665.1084 c2d](#).

- b. The total actual organic mass biodegradation rate *cMR_{bio,d}* for all hazardous waste treated by the process is equal to or greater than the required organic mass removal rate *cRMRd*. Determine the required organic mass removal rate and the actual organic mass biodegradation rate for the process using the procedures in s. [NR 665.1084 c2d](#).

5. A process that removes or destroys the organics contained in the hazardous waste and meets all of the following conditions:

- a. From the point of waste origination through the point where the hazardous waste enters the treatment process, the hazardous waste is managed continuously in waste management units which use air emission controls according to the standards in ss. [NR 665.1085](#) to [665.1088](#), as applicable to the waste management unit.

- b. From the point of waste origination through the point where the hazardous waste enters the treatment process, any transfer of the hazardous waste is accomplished through continuous hard-piping or other closed system transfer that does not allow exposure of the waste to the atmosphere. A drain system that meets [40 CFR part 63](#), subpart RR—National Emission Standards for Individual Drain Systems is a closed system.

- c. The average VO concentration of the hazardous waste at the point of waste treatment is less than the lowest average VO concentration at the point of waste origination determined for each of the individual waste streams entering the process or 500 *ppmw*, whichever value is lower. Determine the average VO concentration of each individual waste stream at the point of waste origination using the procedures in s. [NR 665.1084 c1d](#). Determine the average VO concentration of the hazardous waste at the point of waste treatment using the procedures in s. [NR 665.1084 c2d](#).

6. A process that removes or destroys the organics contained in the hazardous waste to a level such that the organic reduction efficiency *cRd* for the process is equal to or greater than 95 percent and the owner or operator certifies that the average VO concentration at the point of waste origination for each of the individual waste streams entering the process is less than 10,000 *ppmw*. Determine the organic reduction efficiency for the process and the average VO concentration of the hazardous waste at the point of waste origination using the procedures in s. [NR 665.1084 c2d](#) and [c1d](#), respectively.

7. A hazardous waste incinerator for which any of the following conditions has been met:

- a. The owner or operator has been issued an operating license under ch. [NR 670](#) which implements subch. [O](#) of ch. [NR 664](#).

- b. The owner or operator has designed and operates the incinerator according to the interim license requirements of subch. [O](#).

8. A boiler or industrial furnace for which any of the following conditions has been met:

a. The owner or operator has been issued an operating license under ch. NR 670 which implements subch. H of ch. NR 666.

b. The owner or operator has designed and operates the boiler or industrial furnace according to the interim license requirements of subch. H of ch. NR 666.

9. For the purpose of determining the performance of an organic destruction or removal process according to subds. 1. to 6., the owner or operator shall account for VO concentrations determined to be below the limit of detection of the analytical method using the following VO concentration:

a. If Method 25D in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11, is used for the analysis, one-half the blank value determined in the method at section 4.4, or a value of 25 ppmw, whichever is less.

b. If any other analytical method is used, one-half the sum of the limits of detection established for each organic constituent in the waste that has a Henry's law constant value at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in-the-liquid-phase $c_0.1 Y \{X_d$ [which can also be expressed as 1.8×10^{-6} atmospheres/gram-mole/m³] at 25 °C.

ccd A tank or surface impoundment used for biological treatment of hazardous waste according to par. cbd 4.

cdd A tank, surface impoundment or container for which all hazardous waste placed in the unit meets any of the following conditions:

1. The waste meets the numerical concentration limits for organic hazardous constituents, applicable to the hazardous waste, as specified in ch. NR 668—Hazardous Waste Land Disposal Restrictions under Table XTreatment Standards for Hazardous WasteY in s. NR 668.40.

2. The organic hazardous constituents in the waste have been treated by the treatment technology established by the department for the waste in s. NR 668.42 c1d, or have been removed or destroyed by an equivalent method of treatment approved by EPA pursuant to 40 CFR 268.42cbd.

ced A tank used for bulk feed of hazardous waste to a waste incinerator and all of the following conditions are met:

1. The tank is located inside an enclosure vented to a control device that is designed and operated according to all applicable requirements in 40 CFR part 61, subpart FF—National Emission Standards for Benzene Waste Operations, for a facility at which the total annual benzene quantity from the facility waste is equal to or greater than 10 megagrams per year.

2. The enclosure and control device serving the tank were installed and began operation prior to June 1, 1998.

3. The enclosure is designed and operated according to the criteria for a permanent total enclosure in Method 204—XCriteria for and Verification of a Permanent or Temporary Total EnclosureY of appendix M of 40 CFR part 51, incorporated by reference in s. NR 660.11. The enclosure may have permanent or temporary openings to allow worker access, passage of material into or out of the enclosure by conveyor, vehicles or other mechanical or electrical equipment or to direct air flow into the enclosure. Perform the verification procedure for the enclosure in Section 8 of Method 204 annually.

c4d The department may at any time perform or request that the owner or operator perform a waste determination for a hazardous waste managed in a tank, surface impoundment or container exempted from using air emission controls under this section as follows:

cad Perform the waste determination for average VO concentration of a hazardous waste at the point of waste origination us-

ing direct measurement according to the applicable requirements of s. NR 665.1084 c1d. Perform the waste determination for a hazardous waste at the point of waste treatment according to the applicable requirements of s. NR 665.1084 c2d.

cbd In performing a waste determination pursuant to par. cad, conduct the sample preparation and analysis as follows:

1. According to the method used by the owner or operator to perform the waste analysis, except in the case specified in subd. 2.

2. If the department determines that the method used by the owner or operator was not appropriate for the hazardous waste managed in the tank, surface impoundment or container, then the department may choose an appropriate method.

ccd In a case when the owner or operator is requested to perform the waste determination, the department may elect to have an authorized representative observe the collection of the hazardous waste samples used for the analysis.

cdd In a case when the results of the waste determination performed or requested by the department do not agree with the results of a waste determination performed by the owner or operator using knowledge of the waste, the department may use the results of the waste determination performed according to par. cad to establish compliance with this subchapter.

ced In a case when the owner or operator has used an averaging period greater than one hour for determining the average VO concentration of a hazardous waste at the point of waste origination, the department may elect to establish compliance with this subchapter by performing, or requesting that the owner or operator perform, a waste determination using direct measurement based on waste samples collected within a one-hour period as follows:

1. Determine the average VO concentration of the hazardous waste at the point of waste origination by direct measurement according to s. NR 665.1084 c1d.

2. Results of the waste determination performed or requested by the department showing that the average VO concentration of the hazardous waste at the point of waste origination is equal to or greater than 500 ppmw shall constitute noncompliance with this subchapter except in a case provided for in subd. 3.

3. For the case when the average VO concentration of the hazardous waste at the point of waste origination previously has been determined by the owner or operator using an averaging period greater than one hour to be less than 500 ppmw but because of normal operating process variations the VO concentration of the hazardous waste determined by direct measurement for any given one-hour period may be equal to or greater than 500 ppmw, the department shall consider information that was used by the owner or operator to determine the average VO concentration of the hazardous waste ce.g., test results, measurements, calculations and other documentation and recorded in the facility records according to ss. NR 665.1084 c1d and 665.1090 together with the results of the waste determination performed or requested by the department in establishing compliance with this subchapter.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1084 Waste determination procedures.
c1d PROCEDURE TO DETERMINE AVERAGE VO CONCENTRATION OF A HAZARDOUS WASTE AT THE POINT OF WASTE ORIGINATION.
cad An owner or operator shall determine the average VO concentration at the point of waste origination for each hazardous waste placed in a waste management unit exempted under s. NR 665.1083 c3d cad from using air emission controls according to the standards in ss. NR 665.1085 to 665.1088, as applicable to

the waste management unit. Make the determinations according to all of the following:

1. Make an initial determination of the average VO concentration of the waste stream before the first time any portion of the material in the hazardous waste stream is placed in a waste management unit exempted under s. NR 665.1083 c3d cad from using air emission controls, and thereafter make an initial determination of the average VO concentration of the waste stream for each averaging period that a hazardous waste is managed in the unit.

2. Perform a new waste determination whenever changes to the source generating the waste stream are reasonably likely to cause the average VO concentration of the hazardous waste to increase to a level that is equal to or greater than the VO concentration limit in s. NR 665.1083 c3d cad.

cbd For a waste determination that is required by par. cad, determine the average VO concentration of a hazardous waste at the point of waste origination using either direct measurement as specified in par. ccd or by knowledge as specified in par. cdd.

ccd If the owner or operator uses direct measurement to determine average VO concentration of a hazardous waste at the point of waste origination, the owner or operator shall do all of the following:

1. ZIdentification.[Identify and record the point of waste origination for the hazardous waste.

2. ZSampling.[Collect samples of the hazardous waste stream at the point of waste origination in a manner that minimizes volatilization of organics contained in the waste and in the subsequent sample and collects and maintains an adequately representative sample for analysis by the selected method.

a. Designate and record the averaging period to be used for determining the average VO concentration for the hazardous waste stream on a mass-weighted average basis. The averaging period can represent any time interval that the owner or operator determines is appropriate for the hazardous waste stream but may not exceed one year.

b. Collect and analyze a sufficient number of samples, but no less than 4, for a hazardous waste determination. Collect all of the samples for a given waste determination within a one-hour period. The average of the 4 or more sample results constitutes a waste determination for the waste stream. One or more waste determinations may be required to represent the complete range of waste compositions and quantities that occur during the entire averaging period due to normal variations in the operating conditions for the source or process generating the hazardous waste stream. Examples of the normal variations are seasonal variations in waste quantity or fluctuations in ambient temperature.

c. Collect and handle all samples according to written procedures prepared by the owner or operator and documented in a site sampling plan. The plan shall describe the procedure for collecting representative samples of the hazardous waste stream which minimizes loss of organics throughout the sample collection and handling process and maintains sample integrity. Maintain a copy of the written sampling plan on-site in the facility operating records. An example of acceptable sample collection and handling procedures for a total volatile organic constituent concentration may be found in Method 25D in Appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11.

d. Prepare and record sufficient information, as specified in the site sampling plan required under subd. 2. c., to document the waste quantity represented by the samples and, as applicable, the operating conditions for the source or process generating the hazardous waste represented by the samples.

3. ZAnalysis.[Prepare and analyze each collected sample according to Method 25D in Appendix A of 40 CFR part 60 for

the total concentration of volatile organic constituents, or using one or more methods when the individual organic compound concentrations are identified and summed and the summed waste concentration accounts for and reflects all organic compounds in the waste with Henry's law constant values of at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in-the-liquid-phase $c_0.1 Y\{X_d$ [which can also be expressed as 1.8×10^{-6} atmospheres/gram-mole/m³ at 25vC. At the owner or operator's discretion, the owner or operator may adjust test data obtained by any appropriate method to discount any contribution to the total volatile organic concentration that is a result of including a Henry's law constant value of less than 0.1 $Y\{X$ at 25vC. To adjust these data, the measured concentration of each individual chemical constituent contained in the waste is multiplied by the appropriate constituent-specific adjustment factor cfm_{25Dd} . If the owner or operator elects to adjust test data, the adjustment shall be made to all individual chemical constituents with a Henry's law constant value greater than or equal to 0.1 $Y\{X$ at 25vC contained in the waste. Constituent specific adjustment factors cfm_{25Dd} can be obtained by contacting the Waste and Chemical Processes Group, Office of Air Quality Planning and Standards, Research Triangle Park, NC 27711. Other test methods may be used if they meet the requirements in subd. 3. a. or b. and provided the requirement to reflect all organic compounds in the waste with Henry's law constant values greater than or equal to 0.1 $Y\{X$ [which can also be expressed as 1.8×10^{-6} atmospheres/gram-mole/m³ at 25vC, is met.

a. Any EPA standard method that has been validated according to XAlternative Validation Procedure for EPA Waste and Wastewater Methods, Y Appendix D of 40 CFR part 63.

b. Any other analysis method that has been validated according to the procedures specified in Section 5.1 or Section 5.3, and the corresponding calculations in Section 6.1 or Section 6.3, of Method 301 in Appendix A of 40 CFR part 63, incorporated by reference in s. NR 660.11. The data are acceptable if they meet the criteria specified in Section 6.1.5 or Section 6.3.3 of Method 301. If correction is required under section 6.3.3 of Method 301, the data are acceptable if the correction factor is within the range 0.7 to 1.30. Other sections of Method 301 are not required.

4. ZCalculations.[

a. Calculate the average VO concentration \bar{C}_d on a mass-weighted basis using the results for all waste determinations conducted according to subds. 2. and 3. and the following equation:

$$\bar{C} = \frac{1}{Q_T} \times \sum_{i=1}^n (Q_i \times C_i)$$

where:

\bar{C} = Average VO concentration of the hazardous waste at the point of waste origination on a mass-weighted basis, ppmw

i = Individual waste determination X_iY of the hazardous waste

n = Total number of waste determinations of the hazardous waste conducted for the averaging period (not to exceed 1 year)

Q_i = Mass quantity of hazardous waste stream represented by C_i , kg/hr

Q_T = Total mass quantity of hazardous waste during the averaging period, kg/hr

C_i = Measured VO concentration of waste determination X_iY determined according to subd. 3. c.i.e. the average of the 4 or more samples specified in subd. 2. b.d, ppmw

b. For the purpose of determining C_i , for individual waste samples analyzed according to subd. 3., account for VO concen-

trations determined to be below the limit of detection of the analytical method by using the following VO concentration:

1d If Method 25D in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11, is used for the analysis, one-half the blank value determined in the method at section 4.4 of Method 25D.

2d If any other analytical method is used, one-half the sum of the limits of detection established for each organic constituent in the waste that has a Henry's law constant value of at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in-the-liquid-phase $c_0.1 Y\{X_d$ [which can also be expressed as 1.8×10^{-6} atmospheres/gram-mole/m³] at 25 vC.

5. ZCompliance determination.[Provided that the test method is appropriate for the waste as required under subd. 3., the department shall determine compliance based on the test method used by the owner or operator recorded pursuant to s. NR 665.1090 c6d cad.

cdd If the owner or operator uses knowledge to determine average VO concentration of a hazardous waste at the point of waste origination, the owner or operator shall do the following:

1. Prepare documentation that presents the information used as the basis for the owner's or operator's knowledge of the hazardous waste stream's average VO concentration. Examples of information that may be used as the basis for knowledge include material balances for the source or process generating the hazardous waste stream, constituent-specific chemical test data for the hazardous waste stream from previous testing that are still applicable to the current waste stream, previous test data for other locations managing the same type of waste stream or other knowledge based on information included in manifests, shipping papers or waste certification notices.

2. If test data are used as the basis for knowledge, document the test method, sampling protocol and the means by which sampling variability and analytical variability are accounted for in the determination of the average VO concentration. For example, an owner or operator may use organic concentration test data for the hazardous waste stream that are validated according to Method 301 in appendix A of 40 CFR part 63, incorporated by reference in s. NR 660.11, as the basis for knowledge of the waste.

3. If chemical constituent-specific concentration test data are used as the basis for knowledge, the test data may be adjusted to the corresponding average VO concentration value which would have been obtained had the waste samples been analyzed using Method 25D in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11. To adjust these data, multiply the measured concentration for each individual chemical constituent contained in the waste by the appropriate constituent-specific adjustment factor cf_{m25Dd} .

4. In the event that the department and the owner or operator disagree on a determination of the average VO concentration for a hazardous waste stream using knowledge, the department may use the results from a determination of average VO concentration using direct measurement as specified in par. ccd to establish compliance with the applicable requirements of this subchapter. The department may perform or request that the owner or operator perform this determination using direct measurement. The owner or operator may choose one or more appropriate methods to analyze each collected sample according to par. ccd 3.

c2d PROCEDURES FOR TREATED HAZARDOUS WASTE. cad An owner or operator shall perform the applicable waste determination for each treated hazardous waste placed in a waste management unit exempted under s. NR 665.1083 c3d cbd 1. to 6. from using air emission controls according to standards in ss. NR

665.1085 to 665.1088, as applicable to the waste management unit. Make the determinations according to all of the following:

1. Make an initial determination of the average VO concentration of the waste stream before the first time any portion of the material in the treated waste stream is placed in a waste management unit exempted under s. NR 665.1083 c3d cbd, ccd or cdd from using air emission controls, and thereafter update the information used for the waste determination at least once every 12 months following the date of the initial waste determination.

2. Perform a new waste determination whenever changes to the process generating or treating the waste stream are reasonably likely to cause the average VO concentration of the hazardous waste to increase to a level such that the applicable treatment conditions specified in s. NR 665.1083 c3d cbd, ccd or cdd are not achieved.

cbd The owner or operator shall designate and record the specific provision in s. NR 665.1083 c3d cbd under which the owner or operator is performing the waste determination. Perform the waste determination for the treated hazardous waste using the applicable procedures in pars. ccd to cid.

ccd Procedure to determine the average VO concentration of a hazardous waste at the point of waste treatment:

1. ZIdentification.[Identify and record the point of waste treatment for the hazardous waste.

2. ZSampling.[Collect samples of the hazardous waste stream at the point of waste treatment in a manner that minimizes volatilization of organics contained in the waste and in the subsequent sample and collects and maintains an adequately representative sample for analysis by the selected method.

a. Designate and record the averaging period to be used for determining the average VO concentration for the hazardous waste stream on a mass-weighted average basis. The averaging period can represent any time interval that the owner or operator determines is appropriate for the hazardous waste stream but may not exceed 1 year.

b. Collect and analyze a sufficient number of samples, but no less than 4, for a hazardous waste determination. Collect all of the samples for a given waste determination within a one-hour period. The average of the 4 or more sample results constitutes a waste determination for the waste stream. One or more waste determinations may be required to represent the complete range of waste compositions and quantities that occur during the entire averaging period due to normal variations in the operating conditions for the process generating or treating the hazardous waste stream. Examples of the normal variations are seasonal variations in waste quantity or fluctuations in ambient temperature.

c. Collect and handle all samples according to written procedures prepared by the owner or operator and documented in a site sampling plan. The plan shall describe the procedure for collecting representative samples of the hazardous waste stream which minimizes loss of organics throughout the sample collection and handling process and maintains sample integrity. Maintain a copy of the written sampling plan on-site in the facility operating records. An example of acceptable sample collection and handling procedures for a total volatile organic constituent concentration may be found in Method 25D in Appendix A of 40 CFR part 60, both incorporated by reference in s. NR 660.11.

d. Prepare and record sufficient information, as specified in the site sampling plan required under subd. 2. c., to document the waste quantity represented by the samples and, as applicable, the operating conditions for the process treating the hazardous waste represented by the samples.

3. ZAnalysis.[Prepare and analyze each collected sample according to Method 25D in Appendix A of 40 CFR part 60 for

the total concentration of volatile organic constituents, or using one or more methods when the individual organic compound concentrations are identified and summed and the summed waste concentration accounts for and reflects all organic compounds in the waste with Henry's law constant values of at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in-the-liquid-phase ≤ 0.1 $\times 10^{-6}$ at 25°C. At the owner or operator's discretion, the owner or operator may adjust test data obtained by any appropriate method to discount any contribution to the total volatile organic concentration that is a result of including a Henry's law constant value of less than 0.1 $\times 10^{-6}$ at 25°C. To adjust these data, the measured concentration of each individual chemical constituent contained in the waste is multiplied by the appropriate constituent-specific adjustment factor. If the owner or operator elects to adjust test data, the adjustment shall be made to all individual chemical constituents with a Henry's law constant value greater than or equal to 0.1 $\times 10^{-6}$ at 25°C contained in the waste. Constituent specific adjustment factors can be obtained by contacting the Waste and Chemical Processes Group, Office of Air Quality Planning and Standards, Research Triangle Park, NC 27711. Other test methods may be used if they meet the requirements in subd. 3. a. or b. and provided the requirement to reflect all organic compounds in the waste with Henry's law constant values greater than or equal to 0.1 $\times 10^{-6}$ at 25°C, is met.

a. Any EPA standard method that has been validated according to Alternative Validation Procedure for EPA Waste and Wastewater Methods, Appendix D of 40 CFR part 63.

b. Any other analysis method that has been validated according to the procedures specified in Section 5.1 or Section 5.3, and the corresponding calculations in Section 6.1 or Section 6.3, of Method 301 in Appendix A of 40 CFR part 63. The data are acceptable if they meet the criteria specified in Section 6.1.5 or Section 6.3.3 of Method 301. If correction is required under section 6.3.3 of Method 301, the data are acceptable if the correction factor is within the range 0.7 to 1.30. Other sections of Method 301 are not required.

4. **Calculations.** Calculate the average VO concentration \bar{C}_d on a mass-weighted basis using the results for all waste determinations conducted according to subds. 2. and 3. and the following equation:

$$\bar{C} = \frac{1}{Q_T} \times \sum_{i=1}^n (Q_i \times C_i)$$

where:

\bar{C} = Average VO concentration of the hazardous waste at the point of waste treatment on a mass-weighted basis, ppmw

i = Individual waste determination X_iY of the hazardous waste

n = Total number of waste determinations of the hazardous waste conducted for the averaging period not to exceed 1 year

Q_i = Mass quantity of hazardous waste stream represented by C_i , kg/hr

Q_T = Total mass quantity of hazardous waste during the averaging period, kg/hr

C_i = Measured VO concentration of waste determination X_iY determined according to subd. 3. c.i.e. the average of the 4 or more samples specified in subd. 2. b.d, ppmw

5. **Compliance determination.** Provided that the test

method is appropriate for the waste as required under subd. 3., determine compliance based on the test method used by the owner or operator recorded pursuant to s. NR 665.1090 c6d cad.

cdd Procedure to determine the exit concentration limit C_{td} for a treated hazardous waste:

1. Identify the point of waste origination for each hazardous waste treated by the process at the same time.

2. If a single hazardous waste stream is identified in subd. 1., the exit concentration limit C_{td} shall be 500 ppmw.

3. If more than one hazardous waste stream is identified in subd. 1., determine the average VO concentration of each hazardous waste stream at the point of waste origination according to sub. c1d. Calculate the exit concentration limit C_{td} using the results determined for each individual hazardous waste stream and the following equation:

$$C_t = \frac{\sum_{x=1}^m Q_x \times \bar{C}_x + \sum_{y=1}^n Q_y \times 500 \text{ ppmw}}{\sum_{x=1}^m Q_x + \sum_{y=1}^n Q_y}$$

where:

C_t = Exit concentration limit for treated hazardous waste, ppmw

x = Individual hazardous waste stream X_xY that has an average VO concentration less than 500 ppmw at the point of waste origination determined according to sub. c1d

y = Individual hazardous waste stream X_yY that has an average VO concentration equal to or greater than 500 ppmw at the point of waste origination determined according to sub. c1d

m = Total number of X_xY hazardous waste streams treated by process

n = Total number of X_yY hazardous waste streams treated by process

Q_x = Annual mass quantity of hazardous waste stream X_xY , kg/yr

Q_y = Annual mass quantity of hazardous waste stream X_yY , kg/yr

\bar{C}_x = Average VO concentration of hazardous waste stream X_xY at the point of waste origination determined according to sub. c1d, ppmw

ced Procedure to determine the organic reduction efficiency C_{rd} for a treated hazardous waste:

1. Determine the organic reduction efficiency C_{rd} for a treatment process based on results for a minimum of 3 consecutive runs.

2. Identify all hazardous waste streams entering the treatment process and all hazardous waste streams exiting the treatment process. Prepare a sampling plan for measuring these streams that accurately reflects the retention time of the hazardous waste in the process.

3. For each run, determine information for each hazardous waste stream identified in subd. 2. using all of the following procedures:

a. Determine the mass quantity of each hazardous waste stream entering the process $C_{Q,d}$ and the mass quantity of each hazardous waste stream exiting the process $C_{Q,d}$.

b. Determine the average VO concentration at the point of waste origination of each hazardous waste stream entering the

process c \bar{C}_b d during the run according to sub. c1d ccd. Determine the average VO concentration at the point of waste treatment of each waste stream exiting the process c \bar{C}_a d during the run according to par. ccd.

4. Calculate the waste volatile organic mass flow entering the process c E_b d and the waste volatile organic mass flow exiting the process c E_a d using the results determined according to subd. 3. and the following equations:

$$E_b = \frac{1}{10^6} \sum_{j=1}^m Q_{bj} \times \bar{C}_{bj} \delta$$

$$E_a = \frac{1}{10^6} \sum_{j=1}^m Q_{aj} \times \bar{C}_{aj} \delta$$

where:

E_a = Waste volatile organic mass flow exiting process, kg{hr

E_b = Waste volatile organic mass flow entering process, kg{hr

m = Total number of runs cat least 3d

j = Individual run XjY

Q_b = Mass quantity of hazardous waste entering process during run XjY, kg{hr

Q_a = Average mass quantity of hazardous waste exiting process during run XjY, kg{hr

\bar{C}_a = Average VO concentration of hazardous waste exiting process during run XjY determined according to par. ccd, ppmw

\bar{C}_b = Average VO concentration of hazardous waste entering process during run XjY determined according to sub. c1d ccd, ppmw

5. Calculate the organic reduction efficiency of the process using the results determined according to subd. 4. and the following equation:

$$R = \frac{E_b - E_a}{E_b} \times 100\%$$

where:

R = Organic reduction efficiency, percent

E_b = Waste volatile organic mass flow entering process determined according to subd. 4., kg{hr

E_a = Waste volatile organic mass flow exiting process determined according to subd. 4., kg{hr

cf \bar{d} Procedure to determine the organic biodegradation efficiency c R_{bio} d for a treated hazardous waste:

1. Determine the fraction of organics biodegraded c F_{bio} d using the procedure specified in appendix C of 40 CFR part 63, incorporated by reference in s. NR 660.11.

2. Calculate the R_{bio} using the following equation:

$$R_{bio} = F_{bio} \times 100\%$$

where:

R_{bio} = Organic biodegradation efficiency, percent

F_{bio} = Fraction of organic biodegraded determined according to subd. 1.

cg \bar{d} Procedure to determine the required organic mass removal rate c RMR d for a treated hazardous waste:

1. Identify all of the hazardous waste streams entering the treatment process.

2. Determine the average VO concentration of each hazardous waste stream at the point of waste origination according to sub. c1d.

3. For each individual hazardous waste stream that has an average VO concentration equal to or greater than 500 ppmw at the point of waste origination, determine the average volumetric flow rate and the density of the hazardous waste stream at the point of waste origination.

4. Calculate the RMR using the average VO concentration, average volumetric flow rate and density determined for each individual hazardous waste stream, and the following equation:

$$RMR = \sum_{y=1}^n \left[V_y \times k_y \times \frac{\bar{C}_y - 500 \text{ ppmw} \delta}{10^6} \right]$$

where:

RMR = Required organic mass removal rate, kg{hr

y = Individual hazardous waste stream XyY that has an average VO concentration equal to or greater than 500 ppmw at the point of waste origination determined according to sub. c1d

n = Total number of XyY hazardous waste streams treated by process

V_y = Average volumetric flow rate of hazardous waste stream XyY at the point of waste origination, m³{hr

k_y = Density of hazardous waste stream XyY, kg{m³

\bar{C}_y = Average VO concentration of hazardous waste stream XyY at the point of waste origination determined according to sub. c1d, ppmw

ch \bar{d} Procedure to determine the actual organic mass removal rate c MR d for a treated hazardous waste:

1. Determine the MR based on results for a minimum of 3 consecutive runs. The sampling time for each run shall be one hour.

2. Determine the waste volatile organic mass flow entering the process c E_b d and the waste volatile organic mass flow exiting the process c E_a d according to par. ced 4.

3. Calculate the MR using the mass flow rate determined according to subd. 2. and the following equation:

$$MR = E_b - E_a$$

where:

MR = Actual organic mass removal rate, kg{hr

E_b = Waste volatile organic mass flow entering process determined according to par. ced 4., kg{hr

E_a = Waste volatile organic mass flow exiting process determined according to par. ced 4., kg{hr

ci \bar{d} Procedure to determine the actual organic mass biodegradation rate c MR_{bio} d for a treated hazardous waste:

1. Determine the MR_{bio} based on results for a minimum of 3 consecutive runs. The sampling time for each run shall be one hour.

2. Determine the waste organic mass flow entering the process c E_b d according to par. ced 4.

3. Determine the fraction of organic biodegraded c F_{bio} d using the procedure in appendix C of 40 CFR part 63, incorporated by reference in s. NR 660.11.

4. Calculate the MR_{bio} using the mass flow rates and fraction

of organic biodegraded determined according to subds. 2. and 3., respectively, and the following equation:

$$MR_{\text{bio}} = E_b \times F_{\text{bio}}$$

where:

MR_{bio} = Actual organic mass biodegradation rate, kg{hr

E_b = Waste organic mass flow entering process determined according to par. ced 4., kg{hr

F_{bio} = Fraction of organic biodegraded determined according to subd. 3.

c3d PROCEDURE TO DETERMINE THE MAXIMUM ORGANIC VAPOR PRESSURE OF A HAZARDOUS WASTE IN A TANK. cad An owner or operator shall determine the maximum organic vapor pressure for each hazardous waste placed in a tank using Tank Level 1 controls according to the standards in s. NR 665.1085 c3d.

cbd An owner or operator shall use either direct measurement as specified in par. ccd or knowledge of the waste as specified in par. cdd to determine the maximum organic vapor pressure which is representative of the hazardous waste composition stored or treated in the tank.

ccd If the owner or operator uses direct measurement to determine the maximum organic vapor pressure of a hazardous waste, the owner or operator shall do all of the following:

1. ZSampling.[Collect a sufficient number of samples to be representative of the waste contained in the tank. Collect and handle all samples according to written procedures prepared by the owner or operator and documented in a site sampling plan. The plan shall describe the procedure for collecting representative samples of the hazardous waste which minimizes loss of organics throughout the sample collection and handling process and maintains sample integrity. Maintain a copy of the written sampling plan on-site in the facility operating records. An example of acceptable sample collection and handling procedures may be found in Method 25D in Appendix A of 40 CFR part 60, both incorporated by reference in s. NR 660.11.

2. ZAnalysis.[Any appropriate one of the following methods may be used to analyze the samples and compute the maximum organic vapor pressure of the hazardous waste:

a. Method 25E in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11.

b. Methods described in American Petroleum Institute Publication 2517, Third Edition, February 1989, XEvaporative Loss from External Floating-Roof TanksY, incorporated by reference in s. NR 660.11.

c. Methods obtained from standard reference texts.

d. ASTM Method D2879-92, incorporated by reference in s. NR 660.11.

e. Any other method approved by the department.

cdd If the owner or operator uses knowledge to determine the maximum organic vapor pressure of the hazardous waste, the owner or operator shall prepare and record documentation that presents the information used as the basis for the owner[s] or operator[s] knowledge that the maximum organic vapor pressure of the hazardous waste is less than the maximum vapor pressure limit listed in s. NR 665.1085 c2d cad 1. for the applicable tank design capacity category. An example of information that may be used is documentation that the hazardous waste is generated by a process for which at other locations it previously has been determined by direct measurement that the waste maximum organic vapor pressure is less than the maximum vapor pressure limit for the appropriate tank design capacity category.

c4d PROCEDURE FOR DETERMINING NO DETECTABLE ORGANIC EMISSIONS FOR THE PURPOSE OF COMPLYING WITH THIS SUBCHAPTER. cad Conduct the test according to Method 21 in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11. Check each potential leak interface c.i.e., a location where organic vapor leakage could occur on the cover and associated closure devices. Potential leak interfaces that are associated with covers and closure devices include, but are not limited to, the interface of the cover and its foundation mounting, the periphery of any opening on the cover and its associated closure device and the sealing seat interface on a spring-loaded pressure relief valve.

cbd Perform the test when the unit contains a hazardous waste having an organic concentration representative of the range of concentrations for the hazardous waste expected to be managed in the unit. During the test, secure the cover and closure devices in the closed position.

ccd The detection instrument shall meet the performance criteria of Method 21 in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11, except the instrument response factor criteria in section 3.1.2.cad shall be for the average composition of the organic constituents in the hazardous waste placed in the waste management unit, not for each individual organic constituent.

cdd Calibrate the detection instrument before use on each day of its use by the procedures in Method 21 in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11.

ced Calibration gases shall be all of the following:

1. Zero air cless than 10 ppmv hydrocarbon in aird.

2. A mixture of methane or n-hexane and air at a concentration of approximately, but less than, 10,000 ppmv methane or n-hexane.

cfd Determine the background level according to Method 21 in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11.

cgd Check each potential leak interface by traversing the instrument probe around the potential leak interface as close to the interface as possible, as described in Method 21 in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11. In the case when the configuration of the cover or closure device prevents a complete traverse of the interface, sample all accessible portions of the interface. In the case when the configuration of the closure device prevents any sampling at the interface and the device is equipped with an enclosed extension or horn ce.g., some pressure relief devicesd, place the instrument probe inlet at approximately the center of the exhaust area to the atmosphere.

chd Compare the arithmetic difference between the maximum organic concentration indicated by the instrument and the background level with the value of 500 ppmv except when monitoring a seal around a rotating shaft that passes through a cover opening, in which case the comparison shall be as specified in par. cid. If the difference is less than 500 ppmv, then the potential leak interface is determined to operate with no detectable organic emissions.

cid For the seals around a rotating shaft that passes through a cover opening, compare the arithmetic difference between the maximum organic concentration indicated by the instrument and the background level with the value of 10,000 ppmw. If the difference is less than 10,000 ppmw, then the potential leak interface is determined to operate with no detectable organic emissions.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d ccd 2. c., 3., c2d ccd 2. c., r. and recr. c2d ccd 3., am. c3d ccd 1. Register July 2017 No. 739, eff. 8-1-17; correction in c1d ccd 3. cintro.d, c2d ccd 3. cintro.d made under s. 35.17, Stats., Register July 2017 No. 739.

NR 665.1085 Standards: tanks. c1d This section applies to the control of air pollutant emissions from tanks for which s. NR 665.1083 c2d references the use of this section for the air emission control.

c2d The owner or operator shall control air pollutant emissions from each tank subject to this section according to one of the following requirements, as applicable:

cad For a tank that manages hazardous waste that meets all of the following conditions, control air pollutant emissions from the tank according to the Tank Level 1 controls specified in sub. c3d or the Tank Level 2 controls specified in sub. c4d:

1. The hazardous waste in the tank has a maximum organic vapor pressure which is less than the maximum organic vapor pressure limit for the tank[s design capacity category as follows:

a. For a tank design capacity equal to or greater than 151 m³, the maximum organic vapor pressure limit for the tank is 5.2 kPa.

b. For a tank design capacity equal to or greater than 75 m³ but less than 151 m³, the maximum organic vapor pressure limit for the tank is 27.6 kPa.

c. For a tank design capacity less than 75 m³, the maximum organic vapor pressure limit for the tank is 76.6 kPa.

2. The hazardous waste in the tank is not heated to a temperature that is greater than the temperature at which the maximum organic vapor pressure of the hazardous waste is determined for the purpose of complying with subd. 1.

3. The hazardous waste in the tank is not treated using a waste stabilization process, as defined in s. NR 665.1081.

cbd For a tank that manages hazardous waste that does not meet all of the conditions in par. cad 1. to 3., control air pollutant emissions from the tank using Tank Level 2 controls according to sub. c4d. Examples of tanks required to use Tank Level 2 controls include a tank used for a waste stabilization process, and a tank for which the hazardous waste in the tank has a maximum organic vapor pressure that is equal to or greater than the maximum organic vapor pressure limit for the tank[s design capacity category as specified in par. cad 1.

c3d Owners and operators controlling air pollutant emissions from a tank using Tank Level 1 controls shall meet all of the following requirements:

cad Determine the maximum organic vapor pressure for a hazardous waste to be managed in the tank using Tank Level 1 controls before the first time the hazardous waste is placed in the tank. Determine the maximum organic vapor pressure using the procedures in s. NR 665.1084 c3d. Thereafter, perform a new determination whenever changes to the hazardous waste managed in the tank could potentially cause the maximum organic vapor pressure to increase to a level that is equal to or greater than the maximum organic vapor pressure limit for the tank design capacity category specified in sub. c2d cad 1., as applicable to the tank.

cbd Equip the tank with a fixed roof designed to meet all of the following specifications:

1. Design the fixed roof and its closure devices to form a continuous barrier over the entire surface area of the hazardous waste in the tank. The fixed roof may be a separate cover installed on the tank ce.g., a removable cover mounted on an open-top tankd or may be an integral part of the tank structural design ce.g., a horizontal cylindrical tank equipped with a hatchd.

2. Install the fixed roof in a manner such that there are no visible cracks, holes, gaps or other open spaces between roof section joints or between the interface of the roof edge and the tank wall.

3. Each opening in the fixed roof, and any manifold system associated with the fixed roof, shall be any of the following:

a. Equipped with a closure device designed to operate such that when the closure device is secured in the closed position there are no visible cracks, holes, gaps or other open spaces in the closure device or between the perimeter of the opening and the closure device.

b. Connected by a closed-vent system that is vented to a control device. The control device shall remove or destroy organics in the vent stream, and shall be operating whenever hazardous waste is managed in the tank, except as follows:

1d During periods it is necessary to provide access to the tank for performing the activities of subd. 3. b. 2d, venting of the vapor headspace underneath the fixed roof to the control device is not required, opening of closure devices is allowed and removal of the fixed roof is allowed. After completing the activity, promptly secure the closure device in the closed position or reinstall the cover, as applicable, and resume operation of the control device.

2d During periods of routine inspection, maintenance or other activities needed for normal operations, and for the removal of accumulated sludge or other residues from the bottom of the tank.

4. Make the fixed roof and its closure devices of suitable materials that will minimize exposure of the hazardous waste to the atmosphere, to the extent practical, and will maintain the integrity of the fixed roof and closure devices throughout their intended service life. Factors to consider when selecting the materials for and designing the fixed roof and closure devices shall include organic vapor permeability, the effects of any contact with the hazardous waste or its vapors managed in the tank, the effects of outdoor exposure to wind, moisture and sunlight and the operating practices used for the tank on which the fixed roof is installed.

ccd Whenever a hazardous waste is in the tank, install the fixed roof with each closure device secured in the closed position except as follows:

1. Opening of closure devices or removal of the fixed roof is allowed at the following times:

a. To provide access to the tank for performing routine inspection, maintenance or other activities needed for normal operations. Examples of those activities include those times when a worker needs to open a port to sample the liquid in the tank, or when a worker needs to open a hatch to maintain or repair equipment. After completing the activity, promptly secure the closure device in the closed position or reinstall the cover, as applicable, to the tank.

b. To remove accumulated sludge or other residues from the bottom of the tank.

2. Opening of a spring-loaded pressure-vacuum relief valve, conservation vent or similar type of pressure relief device which vents to the atmosphere is allowed during normal operations for the purpose of maintaining the tank internal pressure according to the tank design specifications. Design the device to operate with no detectable organic emissions when the device is secured in the closed position. Establish the settings at which the device opens such that the device remains in the closed position whenever the tank internal pressure is within the internal pressure operating range determined by the owner or operator based on the tank manufacturer recommendations, applicable rules, fire protection and prevention codes, standard engineering codes and practices or other requirements for the safe handling of flammable, ignitable, explosive, reactive or hazardous materials. Examples of normal operating conditions that may require these devices to open are during those times when the tank internal pressure exceeds the internal pressure operating range for the tank as a result of loading operations or diurnal ambient temperature fluctuations.

3. Opening of a safety device, as defined in s. NR 665.1081, is allowed at any time conditions require doing so to avoid an unsafe condition.

cdd Inspect the air emission control equipment according to all of the following requirements:

1. Visually inspect the fixed roof and its closure devices to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, visible cracks, holes or gaps in the roof sections or between the roof and the tank wall, broken, cracked or otherwise damaged seals or gaskets on closure devices and broken or missing hatches, access covers, caps or other closure devices.

2. Perform an initial inspection of the fixed roof and its closure devices on or before the date that the tank becomes subject to this section. Thereafter, perform the inspections at least once every year except under the special conditions provided for in sub. c12d.

3. In the event that a defect is detected, repair the defect according to sub. c11d.

4. Maintain a record of the inspection according to s. NR 665.1090 c2d.

c4d Owners and operators controlling air pollutant emissions from a tank using Tank Level 2 controls shall use one of the following tanks:

cad A fixed-roof tank equipped with an internal floating roof according to sub. c5d.

cbd A tank equipped with an external floating roof according to sub. c6d.

ccd A tank vented through a closed-vent system to a control device according to sub. c7d.

cdd A pressure tank designed and operated according to sub. c8d.

ced A tank located inside an enclosure that is vented through a closed-vent system to an enclosed combustion control device according to sub. c9d.

c5d The owner or operator who controls air pollutant emissions from a tank using a fixed-roof with an internal floating roof shall meet pars. cad to ccd.

cad Equip the tank with a fixed roof and an internal floating roof according to all of the following requirements:

1. Design the internal floating roof to float on the liquid surface except when the floating roof must be supported by the leg supports.

2. Equip the internal floating roof with a continuous seal between the wall of the tank and the floating roof edge that meets any of the following requirements:

a. A single continuous seal that is either a liquid-mounted seal or a metallic shoe seal, as defined in s. NR 665.1081.

b. Two continuous seals mounted one above the other. The lower seal may be a vapor-mounted seal.

3. The internal floating roof shall meet all of the following specifications:

a. Each opening in a non-contact internal floating roof, except for automatic bleeder vents vacuum breaker vents and the rim space vents, provides a projection below the liquid surface.

b. Each opening in the internal floating roof is equipped with a gasketed cover or a gasketed lid except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells and stub drains.

c. Each penetration of the internal floating roof for the purpose of sampling has a slit fabric cover that covers at least 90 percent of the opening.

d. Each automatic bleeder vent and rim space vent is gasketed.

e. Each penetration of the internal floating roof that allows for passage of a ladder has a gasketed sliding cover.

f. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof has a flexible fabric sleeve seal or a gasketed sliding cover.

cbd Operate the tank according to all of the following requirements:

1. When the floating roof is resting on the leg supports, the process of filling, emptying or refilling shall be continuous and shall be completed as soon as practical.

2. Set automatic bleeder vents to closed at all times when the roof is floating, except when the roof is being floated off or is being landed on the leg supports.

3. Prior to filling the tank, bolt or fasten closed c.i.e., no visible gaps each cover, access hatch, gauge float well or lid on any opening in the internal floating roof. Set rim space vents to open only when the internal floating roof is not floating or when the pressure beneath the rim exceeds the manufacturer[s] recommended setting.

ccd Inspect the internal floating roof according to all of the following requirements:

1. Visually inspect the floating roof and its closure devices to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, the internal floating roof is not floating on the surface of the liquid inside the tank, liquid has accumulated on top of the internal floating roof, any portion of the roof seals have detached from the roof rim, holes, tears or other openings are visible in the seal fabric, the gaskets no longer close off the hazardous waste surface from the atmosphere or the slotted membrane has more than 10 percent open area.

2. Inspect the internal floating roof components as follows, except as provided in subd. 3.:

a. Visually inspect the internal floating roof components through openings on the fixed-roof c.e.g., manholes and roof hatches at least once every 12 months after initial fill.

b. Visually inspect the internal floating roof, primary seal, secondary seal c.i.f. one is serviced, gaskets, slotted membranes and sleeve seals c.i.f. anyd each time the tank is emptied and degassed and at least every 10 years.

3. As an alternative to performing the inspections in subd. 2. for an internal floating roof equipped with 2 continuous seals mounted one above the other, visually inspect the internal floating roof, primary and secondary seals, gaskets, slotted membranes and sleeve seals c.i.f. anyd each time the tank is emptied and degassed and at least every 5 years.

4. Prior to each inspection required by subd. 2. or 3., notify the department in advance of each inspection to provide the department with the opportunity to have an observer present during the inspection. Notify the department of the date and location of the inspection as follows:

a. Prior to each visual inspection of an internal floating roof in a tank that has been emptied and degassed, prepare and send written notification so that the department receives it at least 30 calendar days before refilling the tank, except when an inspection is not planned as provided for in subd. 4. b.

b. When a visual inspection is not planned and the owner or operator could not have known about the inspection 30 calendar days before refilling the tank, notify the department as soon as possible, but no later than 7 calendar days before refilling the tank. Make this notification by telephone and immediately follow with a written explanation for why the inspection is un-

planned. Alternatively, send written notification, including the explanation for the unplanned inspection, so that the department receives it at least 7 calendar days before refilling the tank.

5. In the event that a defect is detected, repair the defect according to sub. [c11d](#).

6. Maintain a record of the inspection according to the requirements in s. [NR 665.1090 c2d](#).

cdd Safety devices, as defined in s. [NR 665.1081](#), may be installed and operated as necessary on any tank complying with this subsection.

c6d The owner or operator who controls air pollutant emissions from a tank using an external floating roof shall meet pars. [cad](#) to [ccd](#).

cad Design the external floating roof according to all of the following requirements:

1. Design the external floating roof to float on the liquid surface except when the floating roof must be supported by the leg supports.

2. Equip the floating roof with 2 continuous seals, one above the other, between the wall of the tank and the roof edge. The lower seal is referred to as the primary seal, and the upper seal is referred to as the secondary seal.

a. The primary seal shall be a liquid-mounted seal or a metallic shoe seal, as defined in s. [NR 665.1081](#). The total area of the gaps between the tank wall and the primary seal may not exceed 212 square centimeters ccm^2d per meter of tank diameter, and the width of any portion of these gaps may not exceed 3.8 centimeters ccmd . If a metallic shoe seal is used for the primary seal, design the metallic shoe seal so that one end extends into the liquid in the tank and the other end extends a vertical distance of at least 61 centimeters above the liquid surface.

b. Mount the secondary seal above the primary seal and cover the annular space between the floating roof and the wall of the tank. The total area of the gaps between the tank wall and the secondary seal may not exceed 21.2 square centimeters ccm^2d per meter of tank diameter, and the width of any portion of these gaps may not exceed 1.3 centimeters ccmd .

3. The external floating roof shall meet all of the following specifications:

a. Except for automatic bleeder vents, vacuum breaker vents and rim space vents, each opening in a non-contact external floating roof shall project below the liquid surface.

b. Except for automatic bleeder vents, rim space vents, roof drains and leg sleeves, equip each opening in the roof with a gasketed cover, seal or lid.

c. Equip each access hatch and each gauge float well with a cover designed to be bolted or fastened when the cover is secured in the closed position.

d. Equip each automatic bleeder vent and each rim space vent with a gasket.

e. Equip each roof drain that empties into the liquid managed in the tank with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening.

f. Equip each unslotted and slotted guide pole well with a gasketed sliding cover or a flexible fabric sleeve seal.

g. Equip each unslotted guide pole with a gasketed cap on the end of the pole.

h. Equip each slotted guide pole with a gasketed float or other device which closes off the liquid surface from the atmosphere.

i. Equip each gauge hatch and each sample well with a gasketed cover.

cbd Operate the tank according to all of the following requirements:

1. When the floating roof is resting on the leg supports, the process of filling, emptying or refilling shall be continuous and shall be completed as soon as practical.

2. Except for automatic bleeder vents, rim space vents, roof drains and leg sleeves, secure and maintain each opening in the roof in a closed position at all times except when the closure device must be open for access.

3. Bolt or fasten covers on each access hatch and each gauge float well when secured in the closed position.

4. Set closed automatic bleeder vents at all times when the roof is floating, except when the roof is being floated off or is being landed on the leg supports.

5. Set to open rim space vents only at those times that the roof is being floated off the roof leg supports or when the pressure beneath the rim seal exceeds the manufacturer[s] recommended setting.

6. Secure the cap on the end of each unslotted guide pole in the closed position at all times except when measuring the level of the liquid in the tank or collecting samples of the liquid.

7. Secure the cover on each gauge hatch or sample well in the closed position at all times except when the hatch or well must be opened for access.

8. Both the primary seal and the secondary seal shall completely cover the annular space between the external floating roof and the wall of the tank in a continuous fashion except during inspections.

ccd Inspect the external floating roof according to all of the following procedures:

1. Measure the external floating roof seal gaps according to all of the following requirements:

a. Perform measurements of gaps between the tank wall and the primary seal within 60 calendar days after initial operation of the tank following installation of the floating roof and, thereafter, at least once every 5 years.

b. Perform measurements of gaps between the tank wall and the secondary seal within 60 calendar days after initial operation of the tank following installation of the floating roof and, thereafter, at least once every year.

c. If a tank ceases to hold hazardous waste for a period of one year or more, subsequent introduction of hazardous waste into the tank is an initial operation for the purposes of subd. [1. a.](#) and [b.](#)

d. Determine the total surface area of gaps in the primary seal and in the secondary seal individually using the following procedure:

1d Perform the seal gap measurements at one or more floating roof levels when the roof is floating off the roof supports.

2d Measure seal gaps, if any, around the entire perimeter of the floating roof in each place where a 0.32-centimeter ccmd diameter uniform probe passes freely without forcing or binding against the seal between the seal and the wall of the tank and measure the circumferential distance of each location.

3d For a seal gap measured under this paragraph, determine the gap surface area using probes of various widths to measure accurately the actual distance from the tank wall to the seal and multiplying each width by its respective circumferential distance.

4d Calculate the total gap area by adding the gap surface areas determined for each identified gap location for the primary seal and the secondary seal individually, and then dividing the sum for each seal type by the nominal diameter of the tank. Then compare these total gap areas per unit of tank diameter for the pri-

mary seal and secondary seal to the respective standards for the seal type in par. cad 2.

e. In the event that the seal gap measurements do not conform to the specifications in par. cad 2., repair the defect according to sub. c11d.

f. Maintain a record of the inspection according to s. NR 665.1090 c2d.

2. Visually inspect the external floating roof according to all of the following requirements:

a. Visually inspect the floating roof and its closure devices to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, holes, tears or other openings in the rim seal or seal fabric of the floating roof, a rim seal detached from the floating roof, all or a portion of the floating roof deck being submerged below the surface of the liquid in the tank, broken, cracked or otherwise damaged seals or gaskets on closure devices and broken or missing hatches, access covers, caps or other closure devices.

b. Perform an initial inspection of the external floating roof and its closure devices on or before the date that the tank becomes subject to this section. Thereafter, perform the inspections at least once every year except for the special conditions provided for in sub. c12d.

c. In the event that a defect is detected, repair the defect according to sub. c11d.

d. Maintain a record of the inspection according to s. NR 665.1090 c2d.

3. Prior to each inspection required by subd. 1. or 2., notify the department in advance of each inspection to provide the department with the opportunity to have an observer present during the inspection. Notify the department of the date and location of the inspection as follows:

a. Prior to each inspection to measure external floating roof seal gaps as required under subd. 1., prepare and send written notification so that the department receives it at least 30 calendar days before the date the measurements are scheduled to be performed.

b. Prior to each visual inspection of an external floating roof in a tank that has been emptied and degassed, prepare and send written notification so that the department receives it at least 30 calendar days before refilling the tank except when an inspection is not planned as provided for in subd. 3. c.

c. When a visual inspection is not planned and the owner or operator could not have known about the inspection 30 calendar days before refilling the tank, notify the department as soon as possible, but no later than 7 calendar days before refilling the tank. This notification may be made by telephone and immediately followed by a written explanation for why the inspection is unplanned. Alternatively, written notification, including the explanation for the unplanned inspection, may be sent so that the department receives it at least 7 calendar days before refilling the tank.

cdd Safety devices, as defined in s. NR 665.1081, may be installed and operated as necessary on any tank complying with this subsection.

c7d The owner or operator who controls air pollutant emissions from a tank by venting the tank to a control device shall meet all of the following requirements:

cad Cover the tank with a fixed roof and vent the tank directly through a closed-vent system to a control device according to all of the following requirements:

1. Design the fixed roof and its closure devices to form a con-

tinuous barrier over the entire surface area of the liquid in the tank.

2. Equip each opening in the fixed roof not vented to the control device with a closure device. If the pressure in the vapor headspace underneath the fixed roof is less than atmospheric pressure when the control device is operating, design the closure devices to operate such that when the closure device is secured in the closed position there are no visible cracks, holes, gaps or other open spaces in the closure device or between the perimeter of the cover opening and the closure device. If the pressure in the vapor headspace underneath the fixed roof is equal to or greater than atmospheric pressure when the control device is operating, design the closure device to operate with no detectable organic emissions.

3. Make the fixed roof and its closure devices of suitable materials that will minimize exposure of the hazardous waste to the atmosphere, to the extent practical, and will maintain the integrity of the fixed roof and closure devices throughout their intended service life. Factors to consider when selecting the materials for and designing the fixed roof and closure devices shall include organic vapor permeability, the effects of any contact with the liquid and its vapor managed in the tank, the effects of outdoor exposure to wind, moisture and sunlight and the operating practices used for the tank on which the fixed roof is installed.

4. Design and operate the closed-vent system and control device according to s. NR 665.1088.

cbd Whenever a hazardous waste is in the tank, install the fixed roof with each closure device secured in the closed position and the vapor headspace underneath the fixed roof vented to the control device except as follows:

1. Venting to the control device is not required, and opening of closure devices or removal of the fixed roof is allowed at the following times:

a. To provide access to the tank for performing routine inspection, maintenance or other activities needed for normal operations. Examples of those activities include those times when a worker needs to open a port to sample liquid in the tank or when a worker needs to open a hatch to maintain or repair equipment. After completing the activity, promptly secure the closure device in the closed position or reinstall the cover, as applicable, to the tank.

b. To remove accumulated sludge or other residues from the bottom of the tank.

2. Opening of a safety device, as defined in s. NR 665.1081, is allowed at any time conditions require doing so to avoid an unsafe condition.

ccd Inspect and monitor the air emission control equipment according to all of the following procedures:

1. Visually inspect the fixed roof and its closure devices to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, visible cracks, holes or gaps in the roof sections or between the roof and the tank wall, broken, cracked or otherwise damaged seals or gaskets on closure devices and broken or missing hatches, access covers, caps or other closure devices.

2. Inspect and monitor the closed-vent system and control device according to the procedures in s. NR 665.1088.

3. Perform an initial inspection of the air emission control equipment on or before the date that the tank becomes subject to this section. Thereafter, perform the inspections at least once every year except for the special conditions provided for in sub. c12d.

4. In the event that a defect is detected, repair the defect according to sub. [c11d](#).

5. Maintain a record of the inspection according to s. [NR 665.1090 c2d](#).

c8d The owner or operator who controls air pollutant emissions by using a pressure tank shall meet all of the following requirements.

cad Design the tank to not vent to the atmosphere as a result of compression of the vapor headspace in the tank during filling of the tank to its design capacity.

cbd Equip all tank openings with closure devices designed to operate with no detectable organic emissions determined using the procedure in s. [NR 665.1084 c4d](#).

ccd Whenever hazardous waste is in the tank, operate the tank as a closed system that does not vent to the atmosphere except under any of the following conditions:

1. At those times when opening of a safety device, as defined in s. [NR 665.1081](#), is required to avoid an unsafe condition.

2. At those times when purging of inerts from the tank is required and the purge stream is routed to a closed-vent system and control device designed and operated according to s. [NR 665.1088](#).

c9d The owner or operator who controls air pollutant emissions by using an enclosure vented through a closed-vent system to an enclosed combustion control device shall meet all of the following requirements:

cad Locate the tank inside an enclosure. Design and operate the enclosure according to the criteria for a permanent total enclosure in Method 204—XCriteria for and Verification of a Permanent or Temporary Total EnclosureY of appendix M of [40 CFR part 51](#), incorporated by reference in s. [NR 660.11](#). The enclosure may have permanent or temporary openings to allow worker access; passage of material into or out of the enclosure by conveyor, vehicles or other mechanical means; entry of permanent mechanical or electrical equipment or direct airflow into the enclosure. Perform the verification procedure for the enclosure in Section 8 of Method 204 initially when the enclosure is first installed and, thereafter, annually.

cbd Vent the enclosure through a closed-vent system to an enclosed combustion control device that is designed and operated according to the standards for a vapor incinerator, boiler or process heater in s. [NR 665.1088](#).

ccd Safety devices, as defined in s. [NR 665.1081](#), may be installed and operated as necessary on any enclosure, closed-vent system or control device used to comply with pars. [cad](#) and [cbd](#).

cdd Inspect and monitor the closed-vent system and control device as specified in s. [NR 665.1088](#).

c10d The owner or operator shall transfer hazardous waste to a tank subject to this section according to all of the following requirements:

cad Except as provided in par. [cbd](#), transfer hazardous waste to the tank from another tank subject to this section or from a surface impoundment subject to s. [NR 665.1086](#) using continuous hard-piping or another closed system that does not allow exposure of the hazardous waste to the atmosphere. For the purpose of complying with this paragraph, an individual drain system is a closed system when it meets [40 CFR part 63](#), subpart RR—National Emission Standards for Individual Drain Systems.

cbd Paragraph [cad](#) does not apply when transferring a hazardous waste to the tank under any of the following conditions:

1. The hazardous waste meets the average VO concentration conditions in s. [NR 665.1083 c3d cad](#) at the point of waste origination.

2. The hazardous waste has been treated by an organic destruction or removal process to meet s. [NR 665.1083 c3d cbd](#).

3. The hazardous waste meets s. [NR 665.1083 c3d cbd](#).

c11d The owner or operator shall repair each defect detected during an inspection performed according to sub. [c3d cdd](#), [c5d ccd](#), [c6d ccd](#) or [c7d ccd](#) as follows:

cad Make first efforts at repair of the defect no later than 5 calendar days after detection, and complete the repair as soon as possible but no later than 45 calendar days after detection except as provided in par. [cbd](#).

cbd Repair of a defect may be delayed beyond 45 calendar days if the owner or operator determines that repair of the defect requires emptying or temporary removal from service of the tank and no alternative tank capacity is available at the site to accept the hazardous waste normally managed in the tank. In this case, repair the defect the next time the process or unit that is generating the hazardous waste managed in the tank stops operation. Complete repair of the defect before the process or unit resumes operation.

c12d Following the initial inspection and monitoring of the cover as required by the applicable provisions of this subchapter, subsequent inspection and monitoring may be performed at intervals longer than one year under the following special conditions:

cad In the case when inspecting or monitoring the cover would expose a worker to dangerous, hazardous or other unsafe conditions, the owner or operator may designate a cover as an Xunsafe to inspect and monitor coverY and comply with all of the following requirements:

1. Prepare a written explanation for the cover stating the reasons why the cover is unsafe to visually inspect or to monitor, if required.

2. Develop and implement a written plan and schedule to inspect and monitor the cover, using the procedures specified in the applicable section of this subchapter, as frequently as practicable during those times when a worker can safely access the cover.

cbd In the case when a tank is buried partially or entirely underground, inspect and monitor, as required by the applicable provisions of this section, only those portions of the tank cover and those connections to the tank (e.g., fill ports, access hatches, gauge wells, etc.) that are located on or above the ground surface.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1086 Standards: surface impoundments.

c1d This section applies to the control of air pollutant emissions from surface impoundments for which s. [NR 665.1083 c2d](#) references the use of this section for the air emission control.

c2d The owner or operator shall control air pollutant emissions from the surface impoundment by installing and operating any of the following:

cad A floating membrane cover according to sub. [c3d](#).

cbd A cover that is vented through a closed-vent system to a control device according to sub. [c4d](#).

c3d The owner or operator who controls air pollutant emissions from a surface impoundment using a floating membrane cover shall meet all of the following requirements:

cad Equip the surface impoundment with a floating membrane cover designed to meet all of the following specifications:

1. Design the floating membrane cover to float on the liquid surface during normal operations and form a continuous barrier over the entire surface area of the liquid.

2. Fabricate the cover from a synthetic membrane material that is any of the following:

a. High density polyethylene cHDPEd with a thickness no less than 2.5 millimeters cmmd.

b. A material or a composite of different materials determined to have both organic permeability properties that are equivalent to those of the material listed in subd. 2. a. and chemical and physical properties that maintain the material integrity for the intended service life of the material.

3. Install the cover in a manner such that there are no visible cracks, holes, gaps or other open spaces between cover section seams or between the interface of the cover edge and its foundation mountings.

4. Except as provided for in subd. 5., equip each opening in the floating membrane cover with a closure device designed to operate such that when the closure device is secured in the closed position there are no visible cracks, holes, gaps or other open spaces in the closure device or between the perimeter of the cover opening and the closure device.

5. The floating membrane cover may be equipped with one or more emergency cover drains for removal of stormwater. Equip each emergency cover drain with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening or a flexible fabric sleeve seal.

6. Make the closure devices of suitable materials that will minimize exposure of the hazardous waste to the atmosphere, to the extent practical, and will maintain the integrity of the closure devices throughout their intended service life. Factors to consider when selecting the materials of construction and designing the cover and closure devices shall include organic vapor permeability, the effects of any contact with the liquid and its vapor managed in the surface impoundment, the effects of outdoor exposure to wind, moisture and sunlight and the operating practices used for the surface impoundment on which the floating membrane cover is installed.

cbd Whenever hazardous waste is in the surface impoundment, float the floating membrane cover on the liquid and secure each closure device in the closed position except as follows:

1. Opening of closure devices or removal of the cover is allowed at the following times:

a. To provide access to the surface impoundment for performing routine inspection, maintenance or other activities needed for normal operations. Examples of those activities include those times when a worker needs to open a port to sample the liquid in the surface impoundment, or when a worker needs to open a hatch to maintain or repair equipment. After completing the activity, promptly replace the cover and secure the closure device in the closed position, as applicable.

b. To remove accumulated sludge or other residues from the bottom of the surface impoundment.

2. Opening of a safety device, as defined in s. NR 665.1081, is allowed at any time conditions require doing so to avoid an unsafe condition.

cd Inspect the floating membrane cover according to all of the following procedures:

1. Visually inspect the floating membrane cover and its closure devices to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, visible cracks, holes or gaps in the cover section seams or between the interface of the cover edge and its foundation mountings; broken, cracked or otherwise damaged seals or gaskets on closure devices and broken or missing hatches, access covers, caps or other closure devices.

2. Perform an initial inspection of the floating membrane cover and its closure devices on or before the date that the surface

impoundment becomes subject to this section. Thereafter, perform the inspections at least once every year except for the special conditions provided for in sub. c7d.

3. In the event that a defect is detected, repair the defect according to sub. c6d.

4. Maintain a record of the inspection according to s. NR 665.1090 c3d.

c4d The owner or operator who controls air pollutant emissions from a surface impoundment using a cover vented to a control device shall meet all of the following requirements:

cad Cover the surface impoundment and directly vent it through a closed-vent system to a control device according to all of the following requirements:

1. Design the cover and its closure devices to form a continuous barrier over the entire surface area of the liquid in the surface impoundment.

2. Equip each opening in the cover not vented to the control device with a closure device. If the pressure in the vapor headspace underneath the cover is less than atmospheric pressure when the control device is operating, design the closure devices to operate such that when the closure device is secured in the closed position there are no visible cracks, holes, gaps or other open spaces in the closure device or between the perimeter of the cover opening and the closure device. If the pressure in the vapor headspace underneath the cover is equal to or greater than atmospheric pressure when the control device is operating, design the closure device to operate with no detectable organic emissions using the procedure in s. NR 665.1084 c4d.

3. Make the cover and its closure devices of suitable materials that will minimize exposure of the hazardous waste to the atmosphere, to the extent practical, and will maintain the integrity of the cover and closure devices throughout their intended service life. Factors to consider when selecting the materials of construction and designing the cover and closure devices shall include organic vapor permeability, the effects of any contact with the liquid or its vapors managed in the surface impoundment, the effects of outdoor exposure to wind, moisture and sunlight and the operating practices used for the surface impoundment on which the cover is installed.

4. Design and operate the closed-vent system and control device according to s. NR 665.1088.

cbd Whenever hazardous waste is in the surface impoundment, install the cover with each closure device secured in the closed position and the vapor headspace underneath the cover vented to the control device except as follows:

1. Venting to the control device is not required, and opening of closure devices or removal of the cover is allowed at the following times:

a. To provide access to the surface impoundment for performing routine inspection, maintenance or other activities needed for normal operations. Examples of those activities include those times when a worker needs to open a port to sample liquid in the surface impoundment, or when a worker needs to open a hatch to maintain or repair equipment. After completing the activity, promptly secure the closure device in the closed position or reinstall the cover, as applicable, to the surface impoundment.

b. To remove accumulated sludge or other residues from the bottom of the surface impoundment.

2. Opening of a safety device, as defined in s. NR 665.1081, is allowed at any time conditions require doing so to avoid an unsafe condition.

ccd Inspect and monitor the air emission control equipment according to all of the following procedures:

1. Visually inspect the surface impoundment cover and its closure devices to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, visible cracks, holes or gaps in the cover section seams or between the interface of the cover edge and its foundation mountings, broken, cracked or otherwise damaged seals or gaskets on closure devices and broken or missing hatches, access covers, caps or other closure devices.

2. Inspect and monitor the closed vent system and control device according to s. NR 665.1088.

3. Perform an initial inspection of the air emission control equipment on or before the date that the surface impoundment becomes subject to this section. Thereafter, perform the inspections at least once every year except for the special conditions provided for in sub. c7d.

4. In the event that a defect is detected, repair the defect according to sub. c6d.

5. Maintain a record of the inspection according to s. NR 665.1090 c3d.

c5d The owner or operator shall transfer hazardous waste to a surface impoundment subject to this section according to all of the following requirements:

cad Except as provided in par. cbd, transfer hazardous waste to the surface impoundment from another surface impoundment subject to this section or from a tank subject to s. NR 665.1085 using continuous hard-piping or another closed system that does not allow exposure of the waste to the atmosphere. For the purpose of complying with this paragraph, an individual drain system is a closed system when it meets 40 CFR part 63, subpart RR—National Emission Standards for Individual Drain Systems.

cbd Paragraph cad does not apply when transferring a hazardous waste to the surface impoundment under any of the following conditions:

1. The hazardous waste meets the average VO concentration conditions in s. NR 665.1083 c3d cad at the point of waste origination.

2. The hazardous waste has been treated by an organic destruction or removal process to meet s. NR 665.1083 c3d cbd.

3. The hazardous waste meets s. NR 665.1083 c3d cdd.

c6d The owner or operator shall repair each defect detected during an inspection performed according to sub. c3d ccd or c4d ccd as follows:

cad Make first efforts at repair of the defect no later than 5 calendar days after detection, and complete the repair as soon as possible but no later than 45 calendar days after detection except as provided in par. cbd.

cbd Repair of a defect may be delayed beyond 45 calendar days if the owner or operator determines that repair of the defect requires emptying or temporary removal from service of the surface impoundment and no alternative capacity is available at the site to accept the hazardous waste normally managed in the surface impoundment. In this case, repair the defect the next time the process or unit that is generating the hazardous waste managed in the surface impoundment stops operation. Complete repair of the defect before the process or unit resumes operation.

c7d Following the initial inspection and monitoring of the cover as required by the applicable provisions of this subchapter, subsequent inspection and monitoring may be performed at intervals longer than one year in the case when inspecting or monitoring the cover would expose a worker to dangerous, hazardous or other unsafe conditions. In this case, the owner or operator may

designate the cover as an Xunsafe to inspect and monitor coverY and comply with all of the following requirements:

cad Prepare a written explanation for the cover stating the reasons why the cover is unsafe to visually inspect or to monitor, if required.

cbd Develop and implement a written plan and schedule to inspect and monitor the cover using the procedures in the applicable section of this subchapter as frequently as practicable during those times when a worker can safely access the cover.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1087 Standards: containers. c1d APPLICABILITY. This section applies to the control of air pollutant emissions from containers for which s. NR 665.1083 c2d references the use of this section for the air emission control.

c2d GENERAL REQUIREMENTS. cad The owner or operator shall control air pollutant emissions from each container subject to this section according to the following requirements, as applicable to the container, except when the special provisions for waste stabilization processes specified in par. cbd apply to the container.

1. For a container having a design capacity greater than 0.1 m³ and less than or equal to 0.46 m³, control air pollutant emissions from the container according to the Container Level 1 standards in sub. c3d.

2. For a container having a design capacity greater than 0.46 m³ that is not in light material service, control air pollutant emissions from the container according to the Container Level 1 standards in sub. c3d.

3. For a container having a design capacity greater than 0.46 m³ that is in light material service, control air pollutant emissions from the container according to the Container Level 2 standards in sub. c4d.

cbd When a container having a design capacity greater than 0.1 m³ is used for treatment of a hazardous waste by a waste stabilization process, control air pollutant emissions from the container according to the Container Level 3 standards in sub. c5d at those times during the waste stabilization process when the hazardous waste in the container is exposed to the atmosphere.

c3d CONTAINER LEVEL 1 STANDARDS. cad A container using Container Level 1 controls is one of the following:

1. A container that meets the applicable U.S. department of transportation cDOTd regulations on packaging hazardous materials for transportation as specified in sub. cbd.

2. A container equipped with a cover and closure devices that form a continuous barrier over the container openings such that when the cover and closure devices are secured in the closed position there are no visible holes, gaps or other open spaces into the interior of the container. The cover may be a separate cover installed on the container ce.g., a lid on a drum or a suitably secured tarp on a roll-off boxd or may be an integral part of the container structural design ce.g., a Xportable tankY or bulk cargo container equipped with a screw-type capd.

3. An open-top container in which an organic-vapor suppressing barrier is placed on or over the hazardous waste in the container such that no hazardous waste is exposed to the atmosphere. One example of such a barrier is application of a suitable organic-vapor suppressing foam.

cbd Equip a container used to meet par. cad 2. or 3. with covers and closure devices, as applicable to the container, that are composed of suitable materials to minimize exposure of the hazardous waste to the atmosphere and to maintain the equipment integrity for as long as it is in service. Factors to consider in selecting the materials of construction and designing the cover and clo-

sure devices shall include organic vapor permeability, the effects of contact with the hazardous waste or its vapor managed in the container, the effects of outdoor exposure of the closure device or cover material to wind, moisture and sunlight and the operating practices for which the container is intended to be used.

ccd Whenever hazardous waste is in a container using Container Level 1 controls, install all covers and closure devices for the container, as applicable to the container, and secure and maintain each closure device in the closed position except as follows:

1. Opening of a closure device or cover is allowed for the purpose of adding hazardous waste or other material to the container as follows:

a. In the case when the container is filled to the intended final level in one continuous operation, promptly secure the closure devices in the closed position and install the covers, as applicable to the container, upon conclusion of the filling operation.

b. In the case when discrete quantities or batches of material are intermittently added to the container over a period of time, promptly secure the closure devices in the closed position and install covers, as applicable to the container, upon either the container being filled to the intended final level, the completion of a batch loading after which no additional material will be added to the container within 15 minutes, the person performing the loading operation leaving the immediate vicinity of the container or the shutdown of the process generating the material being added to the container, whichever condition occurs first.

2. Opening of a closure device or cover is allowed for the purpose of removing hazardous waste from the container as follows:

a. For the purpose of meeting the requirements of this section, an empty container as defined in s. NR 661.0007 c2d may be open to the atmosphere at any time c.i.e., covers and closure devices are not required to be secured in the closed position on an empty containerd.

b. In the case when discrete quantities or batches of material are removed from the container but the container does not meet the conditions to be an empty container in s. NR 661.0007 c2d, promptly secure the closure devices in the closed position and install covers, as applicable to the container, upon the completion of a batch removal after which no additional material will be removed from the container within 15 minutes or the person performing the unloading operation leaves the immediate vicinity of the container, whichever condition occurs first.

3. Opening of a closure device or cover is allowed when access inside the container is needed to perform routine activities other than transfer of hazardous waste. Examples of those activities include those times when a worker needs to open a port to measure the depth of or sample the material in the container, or when a worker needs to open a manhole hatch to access equipment inside the container. After completing the activity, promptly secure the closure device in the closed position or reinstall the cover, as applicable to the container.

4. Opening of a spring-loaded, pressure-vacuum relief valve, conservation vent or similar type of pressure relief device which vents to the atmosphere is allowed during normal operations for the purpose of maintaining the container internal pressure according to the design specifications of the container. Design the device to operate with no detectable organic emissions when the device is secured in the closed position. Establish the settings at which the device opens such that the device remains in the closed position whenever the internal pressure of the container is within the internal pressure operating range determined by the owner or operator based on container manufacturer recommendations, applicable rules, fire protection and prevention codes, standard engineering codes and practices or other requirements for the safe

handling of flammable, ignitable, explosive, reactive or hazardous materials. Examples of normal operating conditions that may require these devices to open are during those times when the internal pressure of the container exceeds the internal pressure operating range for the container as a result of loading operations or diurnal ambient temperature fluctuations.

5. Opening of a safety device, as defined in s. NR 665.1081, is allowed at any time conditions require doing so to avoid an unsafe condition.

cdd For containers using Container Level 1 controls, inspect the containers and their covers and closure devices as follows:

1. In the case when hazardous waste is already in the container at the time the owner or operator first accepts possession of the container at the facility and the container is not emptied within 24 hours after the container is accepted at the facility c.i.e., does not meet the conditions for an empty container in s. NR 661.0007 c2dd, the owner or operator shall visually inspect the container and its cover and closure devices to check for visible cracks, holes, gaps or other open spaces into the interior of the container when the cover and closure devices are secured in the closed position. The container visual inspection shall be conducted on or before the date that the container is accepted at the facility c.i.e., the date the container becomes subject to the container standards in this subchapterd. For purposes of this subdivision, the date of acceptance is the date of signature that the facility owner or operator enters on Item 20 of the uniform hazardous waste manifest cEPA forms 8700-22 and 8700-22Ad, as required in s. NR 665.0071. If a defect is detected, the owner or operator shall repair the defect according to subd. 3.

2. In the case when a container used for managing hazardous waste remains at the facility for a period of one year or more, visually inspect the container and its cover and closure devices initially and thereafter, at least once every 12 months, to check for visible cracks, holes, gaps or other open spaces into the interior of the container when the cover and closure devices are secured in the closed position. If a defect is detected, repair the defect according to subd. 3.

3. When a defect is detected for the container, cover or closure devices, make first efforts at repair of the defect no later than 24 hours after detection, and complete the repair as soon as possible but no later than 5 calendar days after detection. If repair of a defect cannot be completed within 5 calendar days, remove the hazardous waste from the container and do not use the container to manage hazardous waste until the defect is repaired.

ced Maintain at the facility a copy of the procedure used to determine that containers with capacity of 0.46 m³ or greater, which do not meet applicable U.S. department of transportation cDOTd regulations as specified in sub. c6d, are not managing hazardous waste in light material service.

c4d CONTAINER LEVEL 2 STANDARDS. cad A container using Container Level 2 controls is one of the following:

1. A container that meets the applicable U.S. department of transportation cDOTd regulations on packaging hazardous materials for transportation as specified in sub. c6d.

2. A container that operates with no detectable organic emissions as defined in s. NR 665.1081 and determined according to sub. c7d.

3. A container that has been demonstrated within the preceding 12 months to be vapor-tight using Method 27 in appendix A of 40 CFR part 60, incorporated by reference in s. NR 660.11, according to sub. c8d.

cbd Transfer hazardous waste in or out of a container using Container Level 2 controls in such a manner as to minimize exposure of the hazardous waste to the atmosphere, to the extent prac-

tical, considering the physical properties of the hazardous waste and good engineering and safety practices for handling flammable, ignitable, explosive, reactive or other hazardous materials. Examples of container loading procedures that meet this paragraph include using a submerged-fill pipe or other submerged-fill method to load liquids into the container, a vapor-balancing system or a vapor-recovery system to collect and control the vapors displaced from the container during filling operations or a fitted opening in the top of a container through which the hazardous waste is filled and subsequently purging the transfer line before removing it from the container opening.

ccd Whenever hazardous waste is in a container using Container Level 2 controls, install all covers and closure devices for the container, and secure and maintain each closure device in the closed position except as follows:

1. Opening of a closure device or cover is allowed for the purpose of adding hazardous waste or other material to the container as follows:

a. In the case when the container is filled to the intended final level in one continuous operation, promptly secure the closure devices in the closed position and install the covers, as applicable to the container, upon conclusion of the filling operation.

b. In the case when discrete quantities or batches of material are intermittently added to the container over a period of time, promptly secure the closure devices in the closed position and install covers, as applicable to the container, upon the container being filled to the intended final level, the completion of a batch loading after which no additional material will be added to the container within 15 minutes, the person performing the loading operation leaving the immediate vicinity of the container or the shutdown of the process generating the material being added to the container, whichever condition occurs first.

2. Opening of a closure device or cover is allowed for the purpose of removing hazardous waste from the container as follows:

a. For the purpose of meeting the requirements of this section, an empty container as defined in s. NR 661.0007 c2d may be open to the atmosphere at any time *ci.e.*, covers and closure devices are not required to be secured in the closed position on an empty container.

b. In the case when discrete quantities or batches of material are removed from the container but the container does not meet the conditions to be an empty container in s. NR 661.0007 c2d, promptly secure the closure devices in the closed position and install covers, as applicable to the container, upon the completion of a batch removal after which no additional material will be removed from the container within 15 minutes or the person performing the unloading operation leaves the immediate vicinity of the container, whichever condition occurs first.

3. Opening of a closure device or cover is allowed when access inside the container is needed to perform routine activities other than transfer of hazardous waste. Examples of those activities include those times when a worker needs to open a port to measure the depth of or sample the material in the container, or when a worker needs to open a manhole hatch to access equipment inside the container. After completing the activity, promptly secure the closure device in the closed position or reinstall the cover, as applicable to the container.

4. Opening of a spring-loaded, pressure-vacuum relief valve, conservation vent or similar type of pressure relief device which vents to the atmosphere is allowed during normal operations for the purpose of maintaining the internal pressure of the container according to the container design specifications. Design the device to operate with no detectable organic emission when the device is secured in the closed position. Establish the settings at

which the device opens such that the device remains in the closed position whenever the internal pressure of the container is within the internal pressure operating range determined by the owner or operator based on container manufacturer recommendations, applicable rules, fire protection and prevention codes, standard engineering codes and practices or other requirements for the safe handling of flammable, ignitable, explosive, reactive or hazardous materials. Examples of normal operating conditions that may require these devices to open are during those times when the internal pressure of the container exceeds the internal pressure operating range for the container as a result of loading operations or diurnal ambient temperature fluctuations.

5. Opening of a safety device, as defined in s. NR 665.1081, is allowed at any time conditions require doing so to avoid an unsafe condition.

cdd Inspect containers using Container Level 2 controls and their covers and closure devices as follows:

1. In the case when hazardous waste is already in the container at the time the owner or operator first accepts possession of the container at the facility and the container is not emptied within 24 hours after the container is accepted at the facility *ci.e.*, does not meet the conditions for an empty container in s. NR 661.0007 c2dd, the owner or operator shall visually inspect the container and its cover and closure devices to check for visible cracks, holes, gaps or other open spaces into the interior of the container when the cover and closure devices are secured in the closed position. The container visual inspection shall be conducted on or before the date that the container is accepted at the facility *ci.e.*, the date the container becomes subject to the container standards in this subchapter. For purposes of this subdivision, the date of acceptance is the date of signature that the facility owner or operator enters on Item 20 of the uniform hazardous waste manifest *cEPA* forms 8700-22 and 8700-22Ad, as required in s. NR 665.0071. If a defect is detected, the owner or operator shall repair the defect according to subd. 3.

2. In the case when a container used for managing hazardous waste remains at the facility for a period of one year or more, visually inspect the container and its cover and closure devices initially and thereafter, at least once every 12 months, to check for visible cracks, holes, gaps or other open spaces into the interior of the container when the cover and closure devices are secured in the closed position. If a defect is detected, repair the defect according to subd. 3.

3. When a defect is detected for the container, cover or closure devices, make first efforts at repair of the defect no later than 24 hours after detection, and complete the repair as soon as possible but no later than 5 calendar days after detection. If repair of a defect cannot be completed within 5 calendar days, remove the hazardous waste from the container and do not use the container to manage hazardous waste until the defect is repaired.

c5d CONTAINER LEVEL 3 STANDARDS. **cad** A container using Container Level 3 controls is one of the following:

1. A container that is vented directly through a closed-vent system to a control device according to par. **cbd** 2.

2. A container that is vented inside an enclosure which is exhausted through a closed-vent system to a control device according to par. **cbd** 1. and 2.

cbd Meet the following requirements, as applicable to the type of air emission control equipment selected:

1. Design and operate the container enclosure according to the criteria for a permanent total enclosure in Method 204—XCriteria for and Verification of a Permanent or Temporary Total EnclosureY in appendix M of 40 *CFR* part 51, incorporated by reference in s. NR 660.11. The enclosure may have

permanent or temporary openings to allow worker access, passage of containers through the enclosure by conveyor or other mechanical means, entry of permanent mechanical or electrical equipment or direct airflow into the enclosure. Perform the verification procedure for the enclosure in Section 8 of Method 204 initially when the enclosure is first installed and, thereafter, annually.

2. Design and operate the closed-vent system and control device according to s. [NR 665.1088](#).

ccd Safety devices, as defined in s. [NR 665.1081](#), may be installed and operated as necessary on any container, enclosure, closed-vent system or control device used to comply with par. [cad](#).

cdd If using Container Level 3 controls according to this subchapter, inspect and monitor the closed-vent systems and control devices as specified in s. [NR 665.1088](#).

ced If using Container Level 3 controls according to this subchapter, prepare and maintain the records specified in s. [NR 665.1090 c4d](#).

cfD Transfer hazardous waste in or out of a container using Container Level 3 controls in such a manner as to minimize exposure of the hazardous waste to the atmosphere, to the extent practical, considering the physical properties of the hazardous waste and good engineering and safety practices for handling flammable, ignitable, explosive, reactive or other hazardous materials. Examples of container loading procedures that meet this paragraph include using a submerged-fill pipe or other submerged-fill method to load liquids into the container, a vapor-balancing system or a vapor-recovery system to collect and control the vapors displaced from the container during filling operations, or a fitted opening in the top of a container through which the hazardous waste is filled and subsequently purging the transfer line before removing it from the container opening.

c6d HAZARDOUS MATERIALS PACKAGING REQUIREMENTS. For the purpose of compliance with sub. [c3d cad 1.](#) or [c4d cad 1.](#), use containers that meet the applicable U.S. department of transportation cDOTd regulations on packaging hazardous materials for transportation as follows:

cad The container meets the applicable requirements in [49 CFR part 178](#)—Specifications for Packaging or part 179—Specifications for Tank Cars.

cbd Hazardous waste is managed in the container according to the applicable requirements in [49 CFR part 107](#), subpart B—Exemptions; [49 CFR part 172](#)—Hazardous Materials Table, Special Provisions, Hazardous Materials Communications, Emergency Response Information, and Training Requirements; [49 CFR part 173](#)—Shippers—General Requirements for Shipments and Packages and [49 CFR part 180](#)—Continuing Qualification and Maintenance of Packagings.

ccd For the purpose of complying with this subchapter, no exceptions to the [49 CFR part 178](#) or [179](#) regulations are allowed except as provided for in par. [cdd](#).

cdd For a lab pack that is managed according to [49 CFR part 178](#) for the purpose of complying with this subchapter, an owner or operator may comply with the exceptions for combination packagings in [49 CFR 173.12cbd](#).

c7d PROCEDURE FOR DETERMINING NO DETECTABLE ORGANIC EMISSIONS. To determine compliance with the no detectable organic emissions requirements of sub. [c4d cad 2.](#), use the procedure in s. [NR 665.1084 c4d](#) as follows:

cad Check each potential leak interface ci.e., a location where organic vapor leakage could occur on the container, its cover and associated closure devices, as applicable to the container.

Potential leak interfaces that are associated with containers include, but are not limited to, the interface of the cover rim and the container wall, the periphery of any opening on the container or container cover and its associated closure device and the sealing seat interface on a spring-loaded, pressure-relief valve.

cbd Perform the test when the container is filled with a material having a volatile organic concentration representative of the range of volatile organic concentrations for the hazardous wastes expected to be managed in this type of container. During the test, secure the container cover and closure devices in the closed position.

c8d PROCEDURE FOR DETERMINING A CONTAINER TO BE VAPOR-TIGHT. To determine compliance with the vapor-tight container requirement of sub. [c4d cad 3.](#), use the following procedure:

cad Perform the test according to Method 27 in appendix A of [40 CFR part 60](#), incorporated by reference in s. [NR 660.11](#).

cbd Use a pressure measurement device that has a precision of 0.25 mm water and is capable of measuring above the pressure at which the container is to be tested for vapor tightness.

ccd If the test results determined by Method 27 indicate that the container sustains a pressure change less than or equal to 750 Pascals within 5 minutes after it is pressurized to a minimum of 4,500 Pascals, the container is vapor-tight.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 06-102: am. c3d cdd 1. and c4d cdd 1. Register March 2007 No. 615, eff. 4-1-07; CR 19-082: am. c3d ccd 2., cdd 1., c4d ccd 2., cdd 1. Register August 2020 No. 776, eff. 9-1-20; correction in c3d cdd 1., c4d cdd 1. made under s. 35.17, Stats., Register August 2020 No. 776.

NR 665.1088 Standards: closed-vent systems and control devices. c1d This section applies to each closed-vent system and control device installed and operated by the owner or operator to control air emissions according to the standards of this subchapter.

c2d The closed-vent system shall meet all of the following requirements:

cad The closed-vent system shall route the gases, vapors and fumes emitted from the hazardous waste in the waste management unit to a control device that meets sub. [c3d](#).

cbd Design and operate the closed-vent system according to s. [NR 665.1033 c10d](#).

ccd In the case when the closed-vent system includes bypass devices that could be used to divert the gas or vapor stream to the atmosphere before entering the control device, equip each bypass device with either a flow indicator as specified in subd. [1.](#) or a seal or locking device as specified in subd. [2.](#) For the purpose of complying with this paragraph, low leg drains, high point bleeds, analyzer vents, open-ended valves or lines, spring-loaded pressure relief valves and other fittings used for safety purposes are not bypass devices.

1. If a flow indicator is used to comply with this paragraph, install the indicator at the inlet to the bypass line used to divert gases and vapors from the closed-vent system to the atmosphere at a point upstream of the control device inlet. For this paragraph, a flow indicator means a device which indicates the presence of either gas or vapor flow in the bypass line.

2. If a seal or locking device is used to comply with this paragraph, place the device on the mechanism by which the bypass device position is controlled ce.g., valve handle, damper leverd when the bypass device is in the closed position such that the bypass device cannot be opened without breaking the seal or removing the lock. Examples of the devices include, but are not limited to, a car-seal or a lock-and-key configuration valve. Visually inspect the seal or closure mechanism at least once every

month to verify that the bypass mechanism is maintained in the closed position.

cdd Inspect and monitor the closed-vent system according to s. NR 665.1033 c11d.

c3d The control device shall meet all of the following applicable requirements:

cad The control device shall be one of the following devices:

1. A control device designed and operated to reduce the total organic content of the inlet vapor stream vented to the control device by at least 95% by weight.

2. An enclosed combustion device designed and operated according to s. NR 665.1033 c3d.

3. A flare designed and operated according to s. NR 665.1033 c4d.

cbd If using a closed-vent system and control device to comply with this section, comply with all of the following requirements:

1. Periods of planned routine maintenance of the control device, during which the control device does not meet par. cad 1., 2. or 3., as applicable, may not exceed 240 hours per year.

2. The specifications and requirements in par. cad 1., 2. and 3. for control devices do not apply during periods of planned routine maintenance.

3. The specifications and requirements in par. cad 1., 2. and 3. for control devices do not apply during a control device system malfunction.

4. Demonstrate compliance with subd. 1. *ci.e.*, planned routine maintenance of a control device, during which the control device does not meet the specifications of par. cad 1., 2. or 3., as applicable, may not exceed 240 hours per year by recording the information specified in s. NR 665.1090 c5d ced.

5. Correct control device system malfunctions as soon as practicable after their occurrence in order to minimize excess emissions of air pollutants.

6. Operate the closed-vent system such that gases, vapors or fumes are not actively vented to the control device during periods of planned maintenance or control device system malfunction *ci.e.*, periods when the control device is not operating or not operating normally except in cases when it is necessary to vent the gases, vapors or fumes to avoid an unsafe condition or to implement malfunction corrective actions or planned maintenance actions.

ccd If using a carbon adsorption system to comply with par. cad, operate and maintain the control device according to all of the following requirements:

1. Following the initial startup of the control device, replace all activated carbon in the control device with fresh carbon on a regular basis according to s. NR 665.1033 c7d or c8d.

2. Manage all carbon that is hazardous waste and that is removed from the control device according to s. NR 665.1033 c13d, regardless of the average volatile organic concentration of the carbon.

cdd If using a control device other than a thermal vapor incinerator, flare, boiler, process heater, condenser or carbon adsorption system to comply with par. cad, operate and maintain the control device according to s. NR 665.1033 c9d.

ced Demonstrate that a control device achieves the performance requirements of par. cad as follows:

1. Demonstrate, using either a performance test in subd. 3. or a design analysis in subd. 4., the performance of each control device except for any of the following:

a. A flare.

b. A boiler or process heater with a design heat input capacity of 44 megawatts or greater.

c. A boiler or process heater into which the vent stream is introduced with the primary fuel.

d. A boiler or industrial furnace burning hazardous waste for which the owner or operator has been issued an operating license under ch. NR 670 and has designed and operates the unit according to subch. H of ch. NR 666.

e. A boiler or industrial furnace burning hazardous waste which the owner or operator has designed and operates according to the interim license requirements of subch. H of ch. NR 666.

2. Demonstrate the performance of each flare according to s. NR 665.1033 c5d.

3. For a performance test conducted to meet subd. 1., use the test methods and procedures in s. NR 665.1034 c3d cad to cdd.

4. For a design analysis conducted to meet subd. 1., meet the requirements in s. NR 665.1035 c2d cdd 3.

5. Demonstrate that a carbon adsorption system achieves the performance requirements of par. cad based on the total quantity of organics vented to the atmosphere from all carbon adsorption system equipment that is used for organic adsorption, organic desorption or carbon regeneration, organic recovery and carbon disposal.

cfD If the owner or operator and the department do not agree on a demonstration of control device performance using a design analysis, resolve the disagreement using the results of a performance test performed by the owner or operator according to par. ced 3. The department may choose to have an authorized representative observe the performance test.

cgD Inspect and monitor the closed-vent system and control device according to s. NR 665.1033 c6d cbd and c11d. Inspect the readings from each monitoring device required by s. NR 665.1033 c6d cbd at least once each operating day to check control device operation. Immediately implement any necessary corrective measures to ensure the control device is operated in compliance with this section.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c3d cfd Register August 2020 No. 776, eff. 9-1-20.

NR 665.1089 Inspection and monitoring requirements. c1d The owner or operator shall inspect and monitor air emission control equipment used to comply with this subchapter according to the applicable requirements in ss. NR 665.1085 to 665.1088.

c2d The owner or operator shall develop and implement a written plan and schedule to perform the inspections and monitoring required by sub. c1d. The owner or operator shall incorporate this plan and schedule into the facility inspection plan required under s. NR 665.0015.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1090 Recordkeeping requirements. c1d Each owner or operator of a facility subject to requirements in this subchapter shall record and maintain the information specified in subs. c2d to c10d, as applicable to the facility. Except for air emission control equipment design documentation and information required by subs. c9d and c10d, maintain records required by this section in the operating record for a minimum of 3 years. Maintain air emission control equipment design documentation in the operating record until the air emission control equipment is replaced or otherwise no longer in service. Maintain information required by subs. c9d and c10d in the operating record for as long as the waste management unit is not using air emission controls specified in ss. NR 665.1085 to 665.1088 according to the conditions in s. NR 665.1080 c4d or c2d cgd, respectively.

c2d The owner or operator of a tank using air emission controls according to s. NR 665.1085 shall prepare and maintain records for the tank that include all of the following information:

cad For each tank using air emission controls according to s. NR 665.1085, record all of the following:

1. A tank identification number cor other unique identification description selected by the owner or operator.

2. A record for each inspection required by s. NR 665.1085 that includes all of the following information:

- a. Date inspection was conducted.
- b. For each defect detected during the inspection, the location of the defect, a description of the defect, the date of detection and corrective action taken to repair the defect. In the event that repair of the defect is delayed according to s. NR 665.1085, also record the reason for the delay and the date that completion of repair of the defect is expected.

cbd In addition to the information required by par. cad , record the following information, as applicable to the tank:

1. If using a fixed roof to comply with the Tank Level 1 control requirements in s. NR 665.1085 c3d, prepare and maintain records for each determination for the maximum organic vapor pressure of the hazardous waste in the tank performed according to s. NR 665.1085 c3d. The records shall include the date and time the samples were collected, the analysis method used and the analysis results.

2. If using an internal floating roof to comply with the Tank Level 2 control requirements in s. NR 665.1085 c5d, prepare and maintain documentation describing the floating roof design.

3. If using an external floating roof to comply with the Tank Level 2 control requirements in s. NR 665.1085 c6d, prepare and maintain all of the following records:

a. Documentation describing the floating roof design and the dimensions of the tank.

b. Records for each seal gap inspection required by s. NR 665.1085 c6d ccd describing the results of the seal gap measurements. The records shall include the date that the measurements were performed, the raw data obtained for the measurements and the calculations of the total gap surface area. In the event that the seal gap measurements do not conform to the specifications in s. NR 665.1085 c6d cad, the records shall include a description of the repairs that were made, the date the repairs were made and the date the tank was emptied, if necessary.

4. If using an enclosure to comply with the Tank Level 2 control requirements in s. NR 665.1085 c9d, prepare and maintain all of the following records:

a. Records for the most recent set of calculations and measurements performed by the owner or operator to verify that the enclosure meets the criteria for a permanent total enclosure in Method 204—XCriteria for and Verification of a Permanent or Temporary Total EnclosureY in appendix M of 40 CFR part 51, incorporated by reference in s. NR 660.11.

b. Records required for the closed-vent system and control device according to sub. c5d .

c3d The owner or operator of a surface impoundment using air emission controls according to s. NR 665.1086 shall prepare and maintain records for the surface impoundment that include all of the following information:

cad A surface impoundment identification number cor other unique identification description selected by the owner or operator.

cbd Documentation describing the floating membrane cover or cover design, as applicable to the surface impoundment, that includes information prepared by the owner or operator or pro-

vided by the cover manufacturer or vendor describing the cover design, and certification by the owner or operator that the cover meets the specifications in s. NR 665.1086 c3d.

ccd A record for each inspection required by s. NR 665.1086 that includes all of the following information:

1. Date inspection was conducted.

2. For each defect detected during the inspection, the location of the defect, a description of the defect, the date of detection and corrective action taken to repair the defect. In the event that repair of the defect is delayed according to s. NR 665.1086 c6d, also record the reason for the delay and the date that completion of repair of the defect is expected.

cdd For a surface impoundment equipped with a cover and vented through a closed-vent system to a control device, prepare and maintain the records specified in sub. c5d.

c4d The owner or operator of containers using Container Level 3 air emission controls according to s. NR 665.1087 shall prepare and maintain records that include all of the following information:

cad Records for the most recent set of calculations and measurements performed to verify that the enclosure meets the criteria for a permanent total enclosure in Method 204—XCriteria for and Verification of a Permanent or Temporary Total EnclosureY in appendix M of 40 CFR part 51, incorporated by reference in s. NR 660.11.

cbd Records required for the closed-vent system and control device according to sub. c5d.

c5d The owner or operator using a closed-vent system and control device according to s. NR 665.1088 shall prepare and maintain records for the closed-vent system and control device that include all of the following information:

cad Certification that is signed and dated by the owner or operator stating that the control device is designed to operate at the performance level documented by a design analysis as specified in par. cbd or by performance tests as specified in par. ccd when the tank, surface impoundment or container is or would be operating at capacity or the highest level reasonably expected to occur.

cbd If a design analysis is used, design documentation as specified in s. NR 665.1035 c2d cdd. The documentation shall include information prepared by the owner or operator or provided by the control device manufacturer or vendor that describes the control device design according to s. NR 665.1035 c2d cdd 3. and certification by the owner or operator that the control equipment meets the applicable specifications.

ccd If performance tests are used, a performance test plan as specified in s. NR 665.1035 c2d ccd and all test results.

cdd Information required by s. NR 665.1035 c3d cad and cbd, as applicable.

ced On a semiannual basis record all of the following information for those planned routine maintenance operations that would require the control device not to meet s. NR 665.1088 c3d cad 1., 2. or 3., as applicable:

1. A description of the planned routine maintenance that is anticipated to be performed for the control device during the next 6-month period. This description shall include the type of maintenance necessary, planned frequency of maintenance and lengths of maintenance periods.

2. A description of the planned routine maintenance that was performed for the control device during the previous 6-month period. The description shall include the type of maintenance performed and the total number of hours during those 6 months that the control device did not meet s. NR 665.1088 c3d cad 1., 2. or 3., as applicable, due to planned routine maintenance.

cf^d Record all of the following information for those unexpected control device system malfunctions that would require the control device not to meet s. NR 665.1088 c3d cad 1., 2. or 3., as applicable:

1. The occurrence and duration of each malfunction of the control device system.
2. The duration of each period during a malfunction when gases, vapors or fumes are vented from the waste management unit through the closed-vent system to the control device while the control device is not properly functioning.
3. Actions taken during periods of malfunction to restore a malfunctioning control device to its normal or usual manner of operation.

c^gd Records of the management of carbon removed from a carbon adsorption system conducted according to s. NR 665.1088 c3d ccd 2.

c6d The owner or operator of a tank, surface impoundment or container exempted from standards according to s. NR 665.1083 c3d shall prepare and maintain all of the following records, as applicable:

cad For tanks, surface impoundments or containers exempted under the hazardous waste organic concentration conditions specified in s. NR 665.1083 c3d cad or cbd 1. to 6., record the information used for each waste determination ce.g., test results, measurements, calculations and other documentation in the facility operating log. If analysis results for waste samples are used for the waste determination, record the date, time and location that each waste sample is collected according to the applicable requirements of s. NR 665.1084.

cbd For tanks, surface impoundments or containers exempted under s. NR 665.1083 c3d cbd 7. or 8., record the identification number for the incinerator, boiler or industrial furnace in which the hazardous waste is treated.

c7d An owner or operator designating a cover as Xunsafe to inspect and monitorY pursuant to s. NR 665.1085 c12d or 665.1086 c7d shall record in a log that is kept in the facility operating record the identification numbers for waste management units with covers that are designated as Xunsafe to inspect and monitorY, the explanation for each cover stating why the cover is unsafe to inspect and monitor and the plan and schedule for inspecting and monitoring each cover.

c8d The owner or operator of a facility that is subject to this subchapter and to the control device standards in 40 CFR part 60, subpart VV, or s. NR 440.62, or 40 CFR part 61, subpart V, may demonstrate compliance with the applicable sections of this subchapter by documentation either pursuant to this subchapter, or pursuant to 40 CFR part 60, subpart VV, or s. NR 440.62, or 40 CFR part 61, subpart V, to the extent that the documentation required by 40 CFR part 60 or 61 or ch. NR 440 duplicates the documentation required by this section.

c9d For each tank or container not using air emission controls specified in ss. NR 665.1085 to 665.1088 according to the conditions in s. NR 665.1080 c4d, the owner or operator shall record and maintain all of the following information:

cad A list of the individual organic peroxide compounds manufactured at the facility that meet the conditions in s. NR 665.1080 c4d cad.

cbd A description of how the hazardous waste containing the organic peroxide compounds identified in par. cad is managed at the facility in tanks and containers. The description shall include all of the following information:

1. For the tanks used at the facility to manage this hazardous waste, provide sufficient information to describe for each tank a

facility identification number for the tank, the purpose and placement of this tank in the management train of this hazardous waste and the procedures used to ultimately dispose of the hazardous waste managed in the tanks.

2. For containers used at the facility to manage these hazardous wastes, provide sufficient information to describe a facility identification number for the container or group of containers, the purpose and placement of this container, or group of containers, in the management train of this hazardous waste and the procedures used to ultimately dispose of the hazardous waste handled in the containers.

ccd An explanation of why managing the hazardous waste containing the organic peroxide compounds identified in par. cad in the tanks and containers described in par. cbd would create an undue safety hazard if the air emission controls, required under ss. NR 665.1085 to 665.1088, were installed and operated on these waste management units. This explanation shall include all of the following information:

1. For tanks used at the facility to manage these hazardous wastes, provide sufficient information to explain how use of the required air emission controls on the tanks would affect the tank design features and facility operating procedures currently used to prevent an undue safety hazard during the management of this hazardous waste in the tanks, and why installation of safety devices on the required air emission controls, as allowed under this subchapter, will not address those situations in which evacuation of tanks equipped with these air emission controls is necessary and consistent with good engineering and safety practices for handling organic peroxides.

2. For containers used at the facility to manage these hazardous wastes, provide sufficient information to explain how use of the required air emission controls on the containers would affect the container design features and handling procedures used to prevent an undue safety hazard during the management of this hazardous waste in the containers, and why installation of safety devices on the required air emission controls, as allowed under this subchapter, will not address those situations in which evacuation of containers equipped with these air emission controls is necessary and consistent with good engineering and safety practices for handling organic peroxides.

c10d For each hazardous waste management unit not using air emission controls specified in ss. NR 665.1085 to 665.1088 according to s. NR 665.1080 c2d cgd, the owner and operator shall record and maintain all of the following information:

cad Certification that the waste management unit is equipped with and operating air emission controls according to 40 CFR part 60, 61 or 63 or corresponding provisions of ch. NR 440, subch. III of ch. NR 446 and chs. NR 447 to 469.

cbd Identification of the specific requirements in 40 CFR part 60, 61 or 63 or in ch. NR 440, subch. III of ch. NR 446 and chs. NR 447 to 469 with which the waste management unit is in compliance.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

Subchapter DD — Containment Buildings

NR 665.1100 Applicability. The requirements of this subchapter apply to owners or operators who store or treat hazardous waste in units designed and operated under s. NR 665.1101. The owner or operator is not subject to the definition of land disposal in s. NR 668.02 c3d provided that the unit complies with all of the following:

- c1d** The unit is a completely enclosed, self-supporting structure that is designed and constructed of manmade materials of sufficient strength and thickness to support themselves, the waste

contents and any personnel and heavy equipment that operate within the unit, and to prevent failure due to pressure gradients, settlement, compression, uplift, physical contact with the hazardous wastes to which they are exposed, climatic conditions and the stresses of daily operation, including the movement of heavy equipment within the unit and contact of the equipment with containment walls.

c2d The unit has a primary barrier that is designed to be sufficiently durable to withstand the movement of personnel and handling equipment within the unit.

c3d If the unit is used to manage liquids, it has all of the following:

cad A primary barrier designed and constructed of materials to prevent migration of hazardous constituents into the barrier.

cbd A liquid collection system designed and constructed of materials to minimize the accumulation of liquid on the primary barrier.

ccd A secondary containment system designed and constructed of materials to prevent migration of hazardous constituents into the barrier, with a leak detection and liquid collection system capable of detecting, collecting and removing leaks of hazardous constituents at the earliest possible time.

c4d The unit has controls as needed to prevent fugitive dust emissions.

c5d The unit is designed and operated to ensure containment and prevent the tracking of materials from the unit by personnel or equipment.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1101 Design and operating standards. c1d

All containment buildings shall comply with all of the following design standards:

cad The containment building shall be completely enclosed with a floor, walls and a roof to prevent exposure to the elements, ce.g., precipitation, wind, run-ond, and to assure containment of managed wastes.

cbd The floor and containment walls of the unit, including the secondary containment system if required under sub. **c2d**, shall be designed and constructed of materials of sufficient strength and thickness to support themselves, the waste contents and any personnel and heavy equipment that operate within the unit, and to prevent failure due to pressure gradients, settlement, compression, uplift, physical contact with the hazardous wastes to which they are exposed, climatic conditions and the stresses of daily operation, including the movement of heavy equipment within the unit and contact of the equipment with containment walls. The unit shall be designed so that it has sufficient structural strength to prevent collapse or other failure. All surfaces to be in contact with hazardous wastes shall be chemically compatible with those wastes. The department will consider standards established by professional organizations generally recognized by the industry such as the American Concrete Institute cACId and the American Society of Testing Materials cASTMd in judging the structural integrity requirements of this paragraph. If appropriate to the nature of the waste management operation to take place in the unit, an exception to the structural strength requirement may be made for lightweight doors and windows that meet both of the following criteria:

1. They provide an effective barrier against fugitive dust emissions under sub. **c3d cad 4**.

2. The unit is designed and operated in a fashion that assures that wastes will not actually come in contact with these openings.

ccd Incompatible hazardous wastes or treatment reagents may not be placed in the unit or its secondary containment system if

they could cause the unit or secondary containment system to leak, corrode or otherwise fail.

cdd A containment building shall have a primary barrier designed to withstand the movement of personnel, waste and handling equipment in the unit during the operating life of the unit and appropriate for the physical and chemical characteristics of the waste to be managed.

c2d For a containment building used to manage hazardous wastes containing free liquids or treated with free liquids cthe presence of which is determined by the paint filter test, a visual examination or other appropriate meansd, the owner or operator shall include all of the following:

cad A primary barrier designed and constructed of materials to prevent the migration of hazardous constituents into the barrier ce.g., a geomembrane covered by a concrete wear surfaced.

cbd A liquid collection and removal system to prevent the accumulation of liquid on the primary barrier of the containment building in compliance with both of the following:

1. The primary barrier shall be sloped to drain liquids to the associated collection system.

2. Liquids and waste shall be collected and removed to minimize hydraulic head on the containment system at the earliest practicable time that protects human health and the environment.

ccd A secondary containment system including a secondary barrier designed and constructed to prevent migration of hazardous constituents into the barrier, and a leak detection system that is capable of detecting failure of the primary barrier and collecting accumulated hazardous wastes and liquids at the earliest practicable time.

1. The requirements of the leak detection component of the secondary containment system are satisfied by installation of a system that is, at a minimum, all of the following:

a. Constructed with a bottom slope of one percent or more.

b. Constructed of a granular drainage material with a hydraulic conductivity of 1×10^{-2} cm{sec or more and a thickness of 12 inches c30.5 cmd or more, or constructed of synthetic or geonet drainage materials with a transmissivity of 3×10^{-5} m²{sec or more.

2. If treatment is to be conducted in the building, an area in which the treatment will be conducted shall be designed to prevent the release of liquids, wet materials or liquid aerosols to other portions of the building.

3. The secondary containment system shall be constructed of materials that are chemically resistant to the waste and liquids managed in the containment building and of sufficient strength and thickness to prevent collapse under the pressure exerted by overlaying materials and by any equipment used in the containment building. cContainment buildings can serve as secondary containment systems for tanks placed within the building under certain conditions. A containment building can serve as an external liner system for a tank, provided it meets the requirements of s. NR 665.0193 c4d cad. In addition, the containment building shall meet the requirements of s. NR 665.0193 c2d and c3d to be considered an acceptable secondary containment system for a tank.d

c3d Owners or operators of all containment buildings shall do all of the following:

cad Use controls and practices to ensure containment of the hazardous waste within the unit; and, at a minimum, do all of the following:

1. Maintain the primary barrier to be free of significant cracks, gaps, corrosion or other deterioration that could cause hazardous waste to be released from the primary barrier.

2. Maintain the level of the stored or treated hazardous waste within the containment walls of the unit so that the height of any containment wall is not exceeded.

3. Take measures to prevent the tracking of hazardous waste out of the unit by personnel or by equipment used in handling the waste. An area shall be designated to decontaminate equipment and any rinsate shall be collected and properly managed.

4. Take measures to control fugitive dust emissions such that any openings doors, windows, vents, cracks, etc. exhibit no visible emissions. In addition, all associated particulate collection devices (e.g., fabric filter, electrostatic precipitator) shall be operated and maintained with sound air pollution control practices. This state of no visible emissions shall be maintained effectively at all times during normal operating conditions, including when vehicles and personnel are entering and exiting the unit.

cbd Obtain and keep onsite a certification by a qualified professional engineer that the containment building design meets the requirements of subs. c1d to c3d.

ccd Throughout the active life of the containment building, if the owner or operator detects a condition that could lead to or has caused a release of hazardous waste, repair the condition promptly, in accordance with all of the following procedures:

1. Upon detection of a condition that has led to a release of hazardous waste (e.g., upon detection of leakage from the primary barrier) the owner or operator shall do all of the following:

a. Enter a record of the discovery in the facility operating record.

b. Immediately remove the portion of the containment building affected by the condition from service.

c. Determine what steps must be taken to repair the containment building, remove any leakage from the secondary collection system and establish a schedule for accomplishing the cleanup and repairs.

d. Within 7 days after the discovery of the condition, notify the department of the condition, and within 14 working days, provide a written notice to the department with a description of the steps taken to repair the containment building, and the schedule for accomplishing the work.

2. The department will review the information submitted, make a determination regarding whether the containment building must be removed from service completely or partially until repairs and cleanup are complete and notify the owner or operator of the determination and the underlying rationale in writing.

3. Upon completing all repairs and cleanup the owner or operator shall notify the department in writing and provide a verification, signed by a qualified, registered professional engineer, that the repairs and cleanup have been completed according to the written plan submitted in accordance with subd. 1. d.

cdd Inspect and record in the facility operating record, at least once every 7 days, data gathered from monitoring equipment and leak detection equipment as well as the containment building and the area immediately surrounding the containment building to detect signs of releases of hazardous waste.

c4d For a containment building that contains both areas with and without secondary containment, the owner or operator shall do all of the following:

cad Design and operate each area according to the requirements in subs. c1d to c3d.

cbd Take measures to prevent the release of liquids or wet materials into areas without secondary containment.

ccd Maintain in the facility's operating log a written description of the operating procedures used to maintain the integrity of areas without secondary containment.

c5d Notwithstanding any other provision of this subchapter, the department may waive requirements for secondary containment for a licensed containment building where the owner or operator demonstrates that the only free liquids in the unit are limited amounts of dust suppression liquids required to meet occupational health and safety requirements, and where containment of managed wastes and liquids can be assured without a secondary containment system.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c3d cbd Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c3d cdd Register August 2020 No. 776, eff. 9-1-20.

NR 665.1102 Closure and long-term care. c1d At closure of a containment building, the owner or operator shall remove or decontaminate all waste residues, contaminated containment system components (liners, etc.), contaminated subsoils and structures and equipment contaminated with waste and leachate, and manage them as hazardous waste unless s. NR 661.0003 c4d applies. The closure plan, closure activities, cost estimates for closure and financial responsibility for containment buildings shall meet all of the requirements specified in subchs. G and H.

c2d If, after removing or decontaminating all residues and making all reasonable efforts to effect removal or decontamination of contaminated components, subsoils, structures and equipment as required in sub. c1d, the owner or operator finds that not all contaminated subsoils can be practicably removed or decontaminated, the owner or operator shall close the facility and perform long-term care in accordance with the closure and long-term care requirements that apply to landfills (s. NR 665.0310d). In addition, for the purposes of closure, long-term care and financial responsibility, the containment building is then considered to be a landfill, and the owner or operator shall meet all of the requirements for landfills specified in subchs. G and H.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: renum. c3d to c2d Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c1d Register August 2020 No. 776, eff. 9-1-20.

Subchapter EE — Hazardous Waste Munitions and Explosives Storage

NR 665.1200 Applicability. The requirements of this subchapter apply to owners or operators who store munitions and explosive hazardous wastes, except as s. NR 665.0001 provides otherwise.

Note: Depending on explosive hazards, hazardous waste munitions and explosives may also be managed in other types of storage units, including containment buildings (subch. DD), tanks (subch. Jd) or containers (subch. Id). See s. NR 666.205 for storage of waste military munitions.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1201 Design and operating standards. c1d Hazardous waste munitions and explosives storage units shall be designed and operated with containment systems, controls and monitoring, that do all of the following:

cad Minimize the potential for detonation or other means of release of hazardous waste, hazardous constituents, hazardous decomposition products or contaminated run-off to the soil, groundwater, surface water and atmosphere.

cbd Provide a primary barrier, which may be a container (including a shell) or tank, designed to contain the hazardous waste.

ccd For wastes stored outdoors, provide that the waste and containers will not be in standing precipitation.

cdd For liquid wastes, provide a secondary containment system that assures that any released liquids are contained and promptly detected and removed from the waste area, or vapor detection system that assures that any released liquids or vapors are

promptly detected and an appropriate response taken ce.g., additional containment, such as overpacking, or removal from the waste aread.

ced Provide monitoring and inspection procedures that assure the controls and containment systems are working as designed and that releases that may adversely impact human health or the environment are not escaping from the unit.

c2d Hazardous waste munitions and explosives stored under this subchapter may be stored in one of the following:

cad *Earth-covered magazines.* Earth-covered magazines shall be all of the following:

1. Constructed of waterproofed, reinforced concrete or structural steel arches, with steel doors that are kept closed when not being accessed.

2. Designed and constructed to do all of the following:

- a. Be of sufficient strength and thickness to support the weight of any explosives or munitions stored and any equipment used in the unit.

- b. Provide working space for personnel and equipment in the unit.

- c. Withstand movement activities that occur in the unit.

3. Located and designed, with walls and earthen covers that direct an explosion in the unit in a safe direction, so as to minimize the propagation of an explosion to adjacent units and to minimize other effects of any explosion.

cbd *Above-ground magazines.* Above-ground magazines shall be located and designed so as to minimize the propagation of an explosion to adjacent units and to minimize other effects of any explosion.

ccd *Outdoor or open storage areas.* Outdoor or open storage areas shall be located and designed so as to minimize the propagation of an explosion to adjacent units and to minimize other effects of any explosion.

c3d Hazardous waste munitions and explosives shall be stored in accordance with a standard operating procedure specifying procedures to ensure safety, security and environmental

protection. If these procedures serve the same purpose as the security and inspection requirements of s. NR 665.0014, the preparedness and prevention procedures of subch. C and the contingency plan and emergency procedures requirements of subch. D, then these procedures shall be used to fulfill those requirements.

c4d Hazardous waste munitions and explosives shall be packaged to ensure safety in handling and storage.

c5d Hazardous waste munitions and explosives shall be inventoried at least annually.

c6d Hazardous waste munitions and explosives and their storage units shall be inspected and monitored as necessary to ensure explosives safety and to ensure that there is no migration of contaminants out of the unit.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

NR 665.1202 Closure and long-term care. c1d

At closure of a magazine or unit which stored hazardous waste under this subchapter, the owner or operator shall remove or decontaminate all waste residues, contaminated containment system components, contaminated subsoils, and structures and equipment contaminated with waste, and manage them as hazardous waste unless s. NR 661.0003 c4d applies. The closure plan, closure activities, cost estimates for closure and financial responsibility for magazines or units shall meet all of the requirements specified in subchs. G and H, except that the owner or operator may defer closure of the unit as long as it remains in service as a munitions or explosives magazine or storage unit.

c2d If, after removing or decontaminating all residues and making all reasonable efforts to effect removal or decontamination of contaminated components, subsoils, structures and equipment as required in sub. c1d, the owner or operator finds that not all contaminated subsoils can be practicably removed or decontaminated, the owner or operator shall close the facility and perform long-term care in accordance with the closure and long-term care requirements that apply to landfills cs. NR 664.0310d.

History: CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d Register August 2020 No. 776, eff. 9-1-20.