

## Chapter NR 666

### STANDARDS FOR MANAGING SPECIFIC HAZARDOUS WASTES AND SPECIFIC TYPES OF HAZARDOUS WASTE MANAGEMENT FACILITIES

<b>Subchapter C — Recyclable Materials Used in a Manner Constituting Disposal</b>	
NR 666.020	Applicability.
NR 666.021	Standards applicable to generators and transporters of materials used in a manner that constitutes disposal.
NR 666.022	Standards applicable to storers of materials that are to be used in a manner that constitutes disposal who are not the ultimate users.
NR 666.023	Standards applicable to users of materials that are used in a manner that constitutes disposal.
<b>Subchapter F — Recyclable Materials Used for Precious Metal Recovery</b>	
NR 666.070	Applicability and requirements.
<b>Subchapter G — Spent Lead-Acid Batteries Being Reclaimed</b>	
NR 666.080	Applicability and requirements.
<b>Subchapter H — Hazardous Waste Burned in Boilers and Industrial Furnaces</b>	
NR 666.100	Applicability.
NR 666.101	Management prior to burning.
NR 666.102	License standards for burners.
NR 666.103	Interim license standards for burners.
NR 666.104	Standards to control organic emissions.
NR 666.105	Standards to control particulate matter.
NR 666.106	Standards to control metals emissions.
NR 666.107	Standards to control hydrogen chloride cHCl and chlorine gas cCl <sub>2</sub> emissions.
NR 666.108	Small quantity on-site burner exemption.
NR 666.109	Low risk waste exemption.
NR 666.110	Waiver of DRE trial burn for boilers.
NR 666.111	Standards for direct transfer.
NR 666.112	Regulation of residues.
<b>Subchapter M — Military Munitions</b>	
NR 666.200	Applicability.
NR 666.201	Definitions.
NR 666.202	Definition of solid waste.
NR 666.203	Standards applicable to the transportation of solid waste military munitions.
NR 666.204	Standards applicable to emergency responses.
NR 666.205	Standards applicable to the storage of solid waste military munitions.
NR 666.206	Standards applicable to the treatment and disposal of waste military munitions.
<b>Subchapter N — Conditional Exemption for Low-Level Mixed Waste Storage, Treatment, Transportation and Disposal</b>	
NR 666.210	What definitions apply to this subchapter?
NR 666.220	What does a storage and treatment conditional exemption do?
NR 666.225	What wastes are eligible for the storage and treatment conditional exemption?
NR 666.230	What conditions must you meet for your LLMW to qualify for and maintain a storage and treatment exemption?
NR 666.235	What waste treatment does the storage and treatment conditional exemption allow?
NR 666.240	How could you lose the conditional exemption for your LLMW and what action must you take?
NR 666.245	If you lose the storage and treatment conditional exemption for your LLMW, can the exemption be reclaimed?
NR 666.250	What storage and treatment records must you keep at your facility and for how long?
NR 666.255	When is your LLMW no longer eligible for the storage and treatment conditional exemption?
NR 666.260	Do closure requirements apply to units that stored LLMW prior to the effective date of this subchapter?
NR 666.305	What does the transportation and disposal conditional exemption do?
NR 666.310	What wastes are eligible for the transportation and disposal conditional exemption?
NR 666.315	What are the conditions you must meet for your waste to qualify for and maintain the transportation and disposal conditional exemption?
NR 666.320	What treatment standards must your eligible waste meet?
NR 666.325	Are you subject to the manifest and transportation condition in s. NR 666.315 c2d?
NR 666.330	When does the transportation and disposal exemption take effect?
NR 666.335	Where must your exempted waste be disposed of?
NR 666.340	What type of container must be used for disposal of exempted waste?
NR 666.345	Whom must you notify?
NR 666.350	What general, transportation and disposal records must you keep at your facility and for how long?
NR 666.355	How could you lose the transportation and disposal conditional exemption for your waste and what actions must you take?
NR 666.360	If you lose the transportation and disposal conditional exemption for a waste, can the exemption be reclaimed?
<b>Subchapter P — Hazardous Waste Pharmaceuticals</b>	
NR 666.500	Definitions.
NR 666.501	Applicability.
NR 666.502	Standards for healthcare facilities managing non-creditable hazardous waste pharmaceuticals.
NR 666.503	Standards for healthcare facilities managing potentially creditable hazardous waste pharmaceuticals.
NR 666.504	Healthcare facilities that are very small quantity generators for both hazardous waste pharmaceuticals and non-pharmaceutical hazardous waste.
NR 666.505	Prohibition of sewerage hazardous waste pharmaceuticals.
NR 666.506	Conditional exemptions for hazardous waste pharmaceuticals that are also controlled substances and household waste pharmaceuticals collected in a take-back event or program.
NR 666.507	Residues of hazardous waste pharmaceuticals in empty containers.
NR 666.508	Shipping non-creditable hazardous waste pharmaceuticals from a healthcare facility or evaluated hazardous waste pharmaceuticals from a reverse distributor.
NR 666.509	Shipping potentially creditable hazardous waste pharmaceuticals from a healthcare facility or a reverse distributor to a reverse distributor.
NR 666.510	Standards for the management of potentially creditable hazardous waste pharmaceuticals and evaluated hazardous waste pharmaceuticals at reverse distributors.
<b>Subchapter HH — Household and Very Small Quantity Generator Hazardous Waste Collection Facilities</b>	
NR 666.900	Applicability.
NR 666.901	Definitions.
NR 666.902	Standards for design of permanent collection facilities.
NR 666.903	Standards for operation of permanent collection facilities.
NR 666.904	Standards for operation of temporary collection facilities.
NR 666.905	Transportation requirements.
NR 666.909	Closure requirements.
NR 666.910	Financial responsibility requirements for permanent collection facilities that store more than 80,000 pounds c36,364 kg.d of hazardous waste.

#### Subchapter C — Recyclable Materials Used in a Manner Constituting Disposal

**Note:** This subchapter is similar to federal regulations contained in 40 CFR part 266 subpart C, as revised on July 24, 2002

**NR 666.020 Applicability. c1d** This subchapter applies

to recyclable materials that are applied to or placed on the land in one of the following ways:

cad Without mixing with any other substance.

cbd After mixing or combination with any other substance or substances. These materials will be referred to throughout this

subchapter as Xmaterials used in a manner that constitutes disposalY.

**c2d** Products produced for the general public[s use that are used in a manner that constitutes disposal and that contain recyclable materials are not presently regulated if the recyclable materials have undergone a chemical reaction in the course of producing the products so as to become inseparable by physical means and if the products meet the applicable treatment standards in subch. D of ch. NR 668 cor applicable prohibition levels in s. NR 668.32, where no treatment standards have been establishedd for each recyclable material ci.e., hazardous wasted that they contain, and if the recycler complies with s. NR 668.07 c2d cfd.

**c3d** Anti-skid and deicing uses of slags, which are generated from high temperature metals recovery cHTMRd processing of hazardous waste K061, K062 and F006, in a manner constituting disposal are not covered by the exemption in sub. c2d and remain regulated.

**c4d** Fertilizers that contain recyclable materials are not regulated if any of the following apply:

cad They are zinc fertilizers excluded from the definition of solid waste according to s. NR 661.0004 c1d cud.

cbd They meet the applicable treatment standards in subch. D of ch. NR 668 for each hazardous waste that they contain.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c2d, c4d cad Register August 2020 No. 776, eff. 9-1-20.

**NR 666.021 Standards applicable to generators and transporters of materials used in a manner that constitutes disposal.** Generators and transporters of materials that are used in a manner that constitutes disposal are subject to the applicable requirements of chs. NR 662 and 663, and the notification requirement under s. NR 660.07.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.022 Standards applicable to storers of materials that are to be used in a manner that constitutes disposal who are not the ultimate users.** Owners or operators of facilities that store recyclable materials that are to be used in a manner that constitutes disposal, but who are not the ultimate users of the materials, are regulated under all applicable provisions of subchs. A to L of ch. NR 664, all applicable provisions of subchs. A to L of ch. NR 665, all applicable provisions of subchs. A to J of ch. NR 667, all applicable provisions of NR 670 and the notification requirement under s. NR 660.07.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. Register August 2020 No. 776, eff. 9-1-20; correction made under s. 35.17, Stats., Register August 2020 No. 776.

**NR 666.023 Standards applicable to users of materials that are used in a manner that constitutes disposal. c1d** Owners or operators of facilities that use recyclable materials in a manner that constitutes disposal are regulated under all applicable provisions of subchs. A to N of chs. NR 664 and 665, and chs. NR 668 and 670 and the notification requirement under s. NR 660.07. cThese requirements do not apply to products which contain these recyclable materials under the provisions of s. NR 666.020 c2d.d

**c2d** The use of waste or used oil or other material, which is contaminated with dioxin or any other hazardous waste, for dust suppression or road treatment is prohibited.

**Note:** See s. NR 679.82 regarding used oil as a dust suppressant.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c2d Register July 2017 No. 739, eff. 8-1-17.

## Subchapter F — Recyclable Materials Used for Precious Metal Recovery

**NR 666.070 Applicability and requirements. c1d** This subchapter applies to recyclable materials that are reclaimed to recover economically significant amounts of gold, silver, platinum, palladium, iridium, osmium, rhodium, ruthenium or any combination of these.

**c2d** Persons who generate, transport or store recyclable materials that are regulated under this subchapter are subject to all of the following requirements:

cad Notification requirements under s. NR 660.07.

cbd Subchapter B of ch. NR 662 for generators, ss. NR 663.20 and 663.21 for transporters and ss. NR 665.0071 and 665.0072 for persons who store.

**Note:** Hazardous waste transportation licenses are not required for transporting only recyclable materials regulated under this subchapter.

ccd For precious metals exported to or imported from other countries for recovery, subch. H of ch. NR 662 and s. NR 665.0012.

**c3d** Persons who store recycled materials that are regulated under this subchapter shall keep all of the following records to document that they are not accumulating these materials speculatively cas defined in s. NR 661.0001 c3dd:

cad Records showing the volume of these materials stored at the beginning of the calendar year.

cbd The amount of these materials generated or received during the calendar year.

ccd The amount of materials remaining at the end of the calendar year.

**c4d** Recyclable materials that are regulated under this subchapter that are accumulated speculatively cas defined in s. NR 661.0001 c3dd are subject to all applicable provisions of chs. NR 662 to 665, 667 and 670.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c2d ccd, c3d cintro.d, c4d Register August 2020 No. 776, eff. 9-1-20.

## Subchapter G — Spent Lead-Acid Batteries Being Reclaimed

**NR 666.080 Applicability and requirements. c1d** A person that generates, collects, transports, stores or regenerates lead-acid batteries for reclamation purposes may be exempt from certain hazardous waste management requirements. Use the following table to determine which requirements apply. Alternatively, spent lead-acid batteries may be managed under ch. NR 673, the XUniversal WasteY rule.

**Note:** In addition to the requirements under this subchapter or ch. NR 673, s. 287.18, Stats., applies to persons who sell lead-acid batteries.

If your batteries * * *	And if you * * *	Then you * * *	And you * * *
cad Will be reclaimed through regeneration such as by electrolyte replacement.		are exempt from chs. NR 662 except for s. NR 662.011d, 663, 664, 665, 666, 668, and 670, and the notification requirements at s. NR 660.07.	are subject to ch. NR 661 and s. NR 662.011.
cbd Will be reclaimed other than through regeneration.	generate, collect or transport these batteries.	are exempt from chs. NR 662 except for s. NR 662.011d, 663, 664, 665, 666, and 670, and the notification requirements at s. NR 660.07.	are subject to ch. NR 661, s. NR 662.011, and applicable provisions under ch. 668.
ccd Will be reclaimed other than through regeneration.	store these batteries but you aren't the reclaimer.	are exempt from chs. NR 662 except for s. NR 662.011d, 663, 664, 665, 666, and 670, and the notification requirements at s. NR 660.07.	are subject to ch. NR 661, s. NR 662.011, and applicable provisions under ch. NR 668.
cdd Will be reclaimed other than through regeneration.	store these batteries before you reclaim them.	shall comply with the appropriate regulatory provisions described in sub. c2d.	are subject to ch. NR 661, s. NR 662.011, and applicable provisions under ch. NR 668.
ced Will be reclaimed other than through regeneration.	don't store these batteries before you reclaim them.	are exempt from chs. NR 662 except for s. NR 662.011d, 663, 664, 665, 666, and 670, and the notification requirements at s. NR 660.07.	are subject to ch. NR 661, s. NR 662.011, and applicable provisions under ch. NR 668.
cfd Will be reclaimed through regeneration or any other means.	export these batteries for reclamation in a foreign country.	are exempt from chs. NR 662 except for ss. NR 662.011, 662.018, and subch. Hd, 663, 664, 665, 666, 668, and 670, and the notification requirements s. NR 660.07.	are subject to ch. NR 661, ss. NR 662.011 and 662.018, and subch. H of ch. NR 662.
cgd Will be reclaimed through regeneration or any other means.	Transport these batteries in the U.S. to export them for reclamation in a foreign country.	are exempt from chs. NR 663, 664, 665, 666, 668, and 670, and the notification requirements at s. NR 660.07.	must comply with applicable requirements in subch. H of ch. NR 662.

If your batteries * * *	And if you * * *	Then you * * *	And you * * *
chd Will be reclaimed other than through regeneration.	Import these batteries from a foreign country and store these batteries but you aren[t the reclaimer.	are exempt from chs. NR 662 cexcept for ss. NR 662.011, 662.018, and subch. Hd, 663, 664, 665, 666, and 670, and the notification requirements at s. NR 660.07.	are subject to ch. NR 661, ss. NR 662.011 and 662.018, and subch. H of ch. NR 662, and applicable provisions under ch. NR 668.
cid Will be reclaimed other than through regeneration.	Import these batteries from a foreign country and store these batteries before you reclaim them.	shall comply with the appropriate regulatory provisions described in sub. c2d.	are subject to ch. NR 661, ss. NR 662.011 and 662.018, and subch. H of ch. NR 662, and applicable provisions under ch. NR 668.
cjd Will be reclaimed other than through regeneration.	Import these batteries from a foreign country and don[t store these batteries before you reclaim them.	are exempt from chs. NR 662 cexcept for ss. NR 662.011, 662.018 and subch. Hd, 663, 664, 665, 666, and 670, and the notification requirements at s. NR 660.07.	are subject to ch. NR 661, ss. NR 662.011 and 662.018, and subch. H of ch. NR 662, and applicable provisions under ch. NR 668.

**c2d** If I store spent lead-acid batteries before I reclaim them but not through regeneration, which requirements apply? The requirements of this subsection apply to you if you store spent lead-acid batteries before you reclaim them, but you don[t reclaim them through regeneration. The requirements are slightly different depending on your hazardous waste license status.

**cad** If your facility has an interim license, you shall comply with all of the following:

1. Notification requirements under s. NR 660.07.
2. All applicable provisions in subch. A of ch. NR 665.
3. All applicable provisions in subch. B of ch. NR 665 except s. NR 665.0013 cgeneral waste analysisd.
4. All applicable provisions in subchs. C and D of ch. NR 665.
5. All applicable provisions in subch. E of ch. NR 665 except ss. NR 665.0071 and 665.0072 cuse of manifest system and manifest discrepanciesd.
6. All applicable provisions in subchs. F to L of ch. NR 665.
7. All applicable provisions in ch. NR 670.
8. All applicable provisions under ch. NR 667.

**cbd** If your facility has an operating license, you shall comply with all of the following:

1. Notification requirements under s. NR 660.07.
2. All applicable provisions in subch. A of ch. NR 664.
3. All applicable provisions in subch. B of ch. NR 664 except s. NR 664.0013 cgeneral waste analysisd.

4. All applicable provisions in subchs. C and D of ch. NR 664.

5. All applicable provisions in subch. E of ch. NR 664 except ss. NR 664.0071 and 664.0072 cuse of manifest system and manifest discrepanciesd.

6. All applicable provisions in subchs. F to L of ch. NR 664.

7. All applicable provisions in ch. NR 670.

8. All applicable provisions under ch. NR 667.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d cad to ced, cr. c2d Register July 2017 No. 739, eff. 8-1-17; CR 19-082: r. and recr. c1d, cr. c2d cad 8., cbd 8. Register August 2020 No. 776, eff. 9-1-20; correction in c1d cdd, cfd to cjd made under s. 35.17, Stats., Register August 2020 No. 776.

**Subchapter H — Hazardous Waste Burned in Boilers and Industrial Furnaces**

**Note:** This subchapter is similar to federal regulations contained in 40 CFR part 266 subpart H, revised as of July 1, 2003.

**NR 666.100 Applicability. c1d** The regulations of this subchapter apply to hazardous waste burned or processed in a boiler or industrial furnace as defined in s. NR 660.10d irrespective of the purpose of burning or processing, except as provided by subs. c2d, c3d, c4d, c7d and c8d. In this subchapter, the term XburnY means burning for energy recovery or destruction, or processing for materials recovery or as an ingredient. The emissions standards of ss. NR 666.104, 666.105, 666.106 and 666.107 apply to facilities operating under an interim license or under a license as specified in ss. NR 666.102 and 666.103.

**c2d** cad Except as provided by pars. **cbd**, **ccd**, and **cdd**, the standards of this subchapter do not apply to a new hazardous waste boiler or industrial furnace unit that becomes subject to hazardous waste license requirements after October 12, 2005; or no longer apply when an affected source demonstrates compliance with the maximum achievable control technology cMACTd requirements of **40 CFR part 63**, subpart EEE, by conducting a comprehensive performance test and submitting to the department a notification of compliance under **40 CFR 63.1207cjd** and **63.1210cdd** documenting compliance with **40 CFR part 63**, subpart EEE. Nevertheless, even after this demonstration of compliance with the MACT standards, hazardous waste license conditions that were based on the standards of this chapter shall continue to be in effect until the conditions are removed from the license or the license is terminated or revoked, unless the license expressly provides otherwise.

**cbd** The following standards all continue to apply:

1. If you elect to comply with s. **NR 670.235 c1d cad 1**. to minimize emissions of toxic compounds from startup, shutdown and malfunction events, s. **NR 666.102 c5d cad** requiring operations in accordance with the operating requirements specified in the license at all times that hazardous waste is in the unit, and s. **NR 666.102 c5d cbd 3**. requiring compliance with the emission standards and operating requirements during startup and shutdown if hazardous waste is in the combustion chamber, except for particular hazardous wastes. These provisions apply only during startup, shutdown and malfunction events.

2. The closure requirements of ss. **NR 666.102 c5d ckd** and **666.103 c12d**.

3. The standards for direct transfer of s. **NR 666.111**.

4. The standards for regulation of residues of s. **NR 666.112**.

5. The applicable requirements of subchs. **A** to **H**, **BB** and **CC** of ch. **NR 664** and subchs. **A** to **H**, **BB** and **CC** of ch. **NR 665**.

**ccd** If an owner or operator of a boiler or hydrochloric acid production furnace that is an area source under **40 CFR 63.2** and the owner or operator elects not to comply with the emission standards under **40 CFR 63.1216**, **63.1217**, and **63.1218** for particulate matter, semi-volatile and low volatile metals and total chlorine, the owner or operator remains subject to:

1. Section **NR 666.105**—Standards to control particulate matter.

2. Section **NR 666.106**—Standards to control metals emissions, except for mercury.

3. Section **NR 666.107**—Standards to control hydrogen chloride and chlorine gas.

**cdd** The particulate matter standard of s. **NR 666.105** remains in effect for boilers that elect to comply with the alternative to the particulate matter standard under **40 CFR 63.1216ced** and **63.1217ced**.

**c3d** The following hazardous wastes and facilities are not subject to regulation under this subchapter:

**cad** Used oil burned for energy recovery that is also a hazardous waste solely because it exhibits a characteristic of hazardous waste identified in subch. **C** of ch. **NR 661**. Such used oil is subject to regulation under ch. **NR 679**.

**cbd** Gas recovered from hazardous or solid waste landfills when such gas is burned for energy recovery.

**ccd** Hazardous wastes that are exempt from regulation under ss. **NR 661.0004** and **661.0006 c1d ccd 3**. and **4**., and hazardous wastes that are subject to the special requirements for very small quantity generators under ss. **NR 662.013** and **662.014**.

**cdd** Coke ovens, if the only hazardous waste burned is EPA

hazardous waste number K087, decanter tank tar sludge from coking operations.

**c4d** Owners and operators of smelting, melting and refining furnaces including pyrometallurgical devices such as cupolas, sintering machines, roasters and foundry furnaces, but not including cement kilns, aggregate kilns or halogen acid furnaces burning hazardous waste that process hazardous waste solely for metal recovery are conditionally exempt from regulation under this subchapter, except for ss. **NR 666.101** and **666.112**.

**cad** To be exempt from ss. **NR 666.102** to **666.111**, an owner or operator of a metal recovery furnace or mercury recovery furnace shall comply with all of the following requirements, except that an owner or operator of a lead or a nickel-chromium recovery furnace, or a metal recovery furnace that burns baghouse bags used to capture metallic dusts emitted by steel manufacturing, shall comply with par. **ccd**, and owners or operators of lead recovery furnaces that are subject to regulation under the Secondary Lead Smelting national emission standards for hazardous air pollutants cNESHAPd shall comply with sub. **c8d**.

1. Provide a one-time written notice to the department indicating all of the following:

- a. The owner or operator claims exemption under this subsection.

- b. The hazardous waste is burned solely for metal recovery consistent with par. **cbd**.

- c. The hazardous waste contains recoverable levels of metals.

- d. The owner or operator will comply with the sampling and analysis and recordkeeping requirements of this subsection.

2. Sample and analyze the hazardous waste and other feedstocks as necessary to comply with this subsection by using appropriate methods.

3. Maintain at the facility for at least 3 years records to document compliance with this subsection including limits on levels of toxic organic constituents and Btu value of the waste, and levels of recoverable metals in the hazardous waste compared to normal nonhazardous waste feedstocks.

**cbd** A hazardous waste meeting either of the following criteria is not processed solely for metal recovery:

1. The hazardous waste has a total concentration of organic compounds listed in ch. **NR 661 Appendix VIII**, exceeding 500 ppm by weight, as-fired, and so is considered to be burned for destruction. The concentration of organic compounds in a waste as-generated may be reduced to the 500 ppm limit by bona fide treatment that removes or destroys organic constituents. Blending for dilution to meet the 500 ppm limit is prohibited and documentation that the waste has not been impermissibly diluted shall be retained in the records required by par. **cad3**.

2. The hazardous waste has a heating value of 5,000 Btu{lb or more, as-fired, and so is considered to be burned as fuel. The heating value of a waste as-generated may be reduced to below the 5,000 Btu{lb limit by bona fide treatment that removes or destroys organic constituents. Blending for dilution to meet the 5,000 Btu{lb limit is prohibited and documentation that the waste has not been impermissibly diluted shall be retained in the records required by par. **cad 3**.

**ccd** To be exempt from ss. **NR 666.102** to **666.111**, an owner or operator of a lead or nickel-chromium or mercury recovery furnace except for owners or operators of lead recovery furnaces subject to regulation under the Secondary Lead Smelting national emission standards for hazardous air pollutants cNESHAPd or a metal recovery furnace that burns baghouse bags used to capture metallic dusts emitted by steel manufacturing, shall provide a one-time written notice to the department identifying each hazardous waste burned and specifying whether the owner or opera-



tor claims an exemption for each waste under this paragraph or par. *cad*. The owner or operator shall comply with par. *cad* for those wastes claimed to be exempt under par. *cad* and shall comply with the requirements below for those wastes claimed to be exempt under this paragraph.

1. The hazardous wastes listed in ch. [NR 666 Appendix XI](#), ch. [NR 666 Appendix XII](#), and ch. [NR 666 Appendix XIII](#), and baghouse bags used to capture metallic dusts emitted by steel manufacturing, are exempt from par. *cad*, if all of the following conditions are met:

a. A waste listed in ch. [NR 666 Appendix IX](#) shall contain recoverable levels of lead, a waste listed in ch. [NR 666 Appendix XII](#) shall contain recoverable levels of nickel or chromium, a waste listed in ch. [NR 666 Appendix XIII](#) shall contain recoverable levels of mercury and contain less than 500 ppm of ch. [NR 661 Appendix VIII](#) organic constituents, and baghouse bags used to capture metallic dusts emitted by steel manufacturing shall contain recoverable levels of metal.

b. The waste does not exhibit the toxicity characteristic specified in s. [NR 661.0024](#) for an organic constituent.

c. The waste is not a hazardous waste listed in subch. [D of ch. NR 661](#) because it is listed for an organic constituent as identified in ch. [NR 661 Appendix VII](#).

d. The owner or operator certifies in the one-time notice that hazardous waste is burned under this paragraph and that sampling and analysis will be conducted or other information will be obtained as necessary to ensure continued compliance with these requirements. Sampling and analysis shall be conducted according to par. *cad 2*. and records to document compliance with this paragraph shall be kept for at least 3 years.

2. The department may decide on a case-by-case basis that the toxic organic constituents in a material listed in ch. [NR 666 Appendix XI](#), ch. [NR 666 Appendix XII](#), or ch. [NR 666 Appendix XIII](#) that contains a total concentration of more than 500 ppm toxic organic compounds listed in ch. [NR 661 Appendix VIII](#) may pose a hazard to human health and the environment when burned in a metal recovery furnace exempt from this subchapter. In that situation, after adequate notice and opportunity for comment, the metal recovery furnace shall become subject to this subchapter when burning that material. In making the hazard determination, the department will consider all of the following factors:

a. The concentration and toxicity of organic constituents in the material.

b. The level of destruction of toxic organic constituents provided by the furnace.

c. Whether the acceptable ambient levels established in ch. [NR 666 Appendix IV](#) or ch. [NR 666 Appendix V](#) may be exceeded for any toxic organic compound that may be emitted based on dispersion modeling to predict the maximum annual average off-site ground level concentration.

**c5d** The standards for direct transfer operations under s. [NR 666.111](#) apply only to facilities subject to the license standards of s. [NR 666.102](#) or the interim license standards of s. [NR 666.103](#).

**c6d** The management standards for residues under s. [NR 666.112](#) apply to any boiler or industrial furnace burning hazardous waste.

**c7d** Owners and operators of smelting, melting and refining furnaces including pyrometallurgical devices such as cupolas, sintering machines, roasters and foundry furnaces that process hazardous waste for recovery of economically significant amounts of the precious metals gold, silver, platinum, palladium, iridium, osmium, rhodium or ruthenium, or any combination of

these are conditionally exempt from regulation under this subchapter, except for s. [NR 666.112](#). To be exempt from ss. [NR 666.101](#) to [666.111](#), an owner or operator shall do all of the following:

*cad* Provide a one-time written notice to the department indicating all of the following:

1. The owner or operator claims exemption under this subsection.

2. The hazardous waste is burned for legitimate recovery of precious metal.

3. The owner or operator will comply with the sampling and analysis and recordkeeping requirements of this subsection.

*cbd* Sample and analyze the hazardous waste as necessary to document that the waste contains economically significant amounts of the metals and that the treatment recovers economically significant amounts of precious metal.

*ccd* Maintain at the facility for at least 3 years records to document that all hazardous wastes burned are burned for recovery of economically significant amounts of precious metal.

**c8d** Starting June 23, 1997, owners or operators of lead recovery furnaces that process hazardous waste for recovery of lead and that are subject to regulation under the Secondary Lead Smelting national standards for hazardous air pollutants cNE-SHAPd, are conditionally exempt from regulation under this subchapter, except for s. [NR 666.101](#). To be exempt, an owner or operator shall provide a one-time notice to the department identifying each hazardous waste burned and specifying that the owner or operator claims an exemption under this subsection. The notice also shall state that the waste burned has a total concentration of non-metal compounds listed in ch. [NR 661 Appendix VIII](#), of less than 500 ppm by weight, as fired and as provided in sub. [c4d cbd 1.](#), or is listed in ch. [NR 666 Appendix XI](#).

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; corrections in c2d cbd 5., c4d ccd 1. cintro.d, a., 2. cintro.d, c., c8d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; CR 16-007: am. c2d cad, cr. c2d ccd, cdd, am. c4d cad 2., r. and rec. c7d cbd Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c3d ccd, c4d ccd 1. b. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.101 Management prior to burning. c1d** GENERATORS. Generators of hazardous waste that is burned in a boiler or industrial furnace are subject to ch. [NR 662](#).

**c2d** TRANSPORTERS. Transporters of hazardous waste that is burned in a boiler or industrial furnace are subject to ch. [NR 663](#).

**c3d** STORAGE AND TREATMENT FACILITIES. *cad* Owners and operators of facilities that store or treat hazardous waste that is burned in a boiler or industrial furnace are subject to the applicable provisions of chs. [NR 664](#), [665](#), [667](#) and [670](#), except as provided by sub. [c3d cbd](#). These standards apply to storage and treatment by the burner as well as to storage and treatment facilities operated by intermediaries cprocessors, blenders, distributors, etc.d between the generator and the burner.

*cbd* Owners and operators of facilities that burn, in an on-site boiler or industrial furnace exempt from regulation under the small quantity burner provisions of s. [NR 666.108](#), hazardous waste that they generate are exempt from the regulations of chs. [NR 664](#), [665](#), [667](#) and [670](#) applicable to storage units for those storage units that store mixtures of hazardous waste and the primary fuel to the boiler or industrial furnace in tanks that feed the fuel mixture directly to the burner. Storage of hazardous waste prior to mixing with the primary fuel is subject to regulation as prescribed in par. *cad*.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.102 License standards for burners. c1d** APPLICABILITY. *cad* *General*. Owners and operators of boilers

and industrial furnaces burning hazardous waste and not operating under an interim license shall comply with this section and ss. NR 670.022 and 670.066, unless exempt under the small quantity burner exemption of s. NR 666.108.

*cbd Applicability of ch. NR 664 standards.* Owners and operators of boilers and industrial furnaces that burn hazardous waste are subject to the following provisions of ch. NR 664, except as provided otherwise by this subchapter:

1. In subch. A of ch. NR 664 cGeneral, s. NR 664.0004.
2. In subch. B of ch. NR 664 cGeneral facility standards, s. NR 664.0011 to 664.0018.
3. In subch. C of ch. NR 664 cPreparedness and prevention, ss. NR 664.0031 to 664.0037.
4. In subch. D of ch. NR 664 cContingency plan and emergency procedures, ss. NR 664.0051 to 664.0056.
5. In subch. E of ch. NR 664 cManifest system, recordkeeping and reporting, the applicable provisions of ss. NR 664.0071 to 664.0077.
6. In subch. F of ch. NR 664 cCorrective Action, ss. NR 664.0090 and 664.0101.
7. In subch. G of ch. NR 664 cClosure and post-closure, ss. NR 664.0111 to 664.0115.
8. In subch. H of ch. NR 664 cFinancial requirements, ss. NR 664.0141, 664.0142, 664.0143 and 664.0147 to 664.0151, except that states and the federal government are exempt from s. NR 664.0147.
9. Subchapter BB of ch. NR 664 cAir emission standards for equipment leaks, except s. NR 664.1050 c1d.

**c2d HAZARDOUS WASTE ANALYSIS.** *cad* The owner or operator shall provide an analysis of the hazardous waste that quantifies the concentration of any constituent identified in ch. NR 661 Appendix VIII that may reasonably be expected to be in the waste. Such constituents shall be identified and quantified if present, at levels detectable by using appropriate analytical procedures. The ch. NR 661 Appendix VIII constituents excluded from this analysis shall be identified and the basis for their exclusion explained. This analysis shall be used to provide all information required by this subchapter and ss. NR 670.022 and 670.066 and to enable the department to prescribe such license conditions as necessary to protect human health and the environment. Such analysis shall be included as a portion of the feasibility and plan of operation report, or, for facilities operating under the interim license standards of this subchapter, as a portion of the trial burn plan that may be submitted before the feasibility and plan of operation report under provisions of s. NR 670.066 c7d as well as any other analysis required by the department in preparing the license. Owners and operators of boilers and industrial furnaces not operating under the interim license standards shall provide the information required by s. NR 670.022 or 670.066 c3d in the feasibility and plan of operation report to the greatest extent possible.

*cbd* Throughout normal operation, the owner or operator shall conduct sampling and analysis as necessary to ensure that the hazardous waste, other fuels, and industrial furnace feedstocks fired into the boiler or industrial furnace are within the physical and chemical composition limits specified in the license.

**c3d EMISSIONS STANDARDS.** Owners and operators shall comply with emissions standards provided by ss. NR 666.104 to 666.107.

**c4d LICENSES.** *cad* The owner or operator may burn only hazardous wastes specified in the facility license and only under the operating conditions specified under sub. c5d, except in ap-

proved trial burns under the conditions specified in s. NR 670.066.

*cbd* Hazardous wastes not specified in the license may not be burned until operating conditions have been specified under a new license or license modification, as applicable. Operating requirements for new wastes may be based on either trial burn results or alternative data included with feasibility and plan of operation report under s. NR 670.022.

*ccd* Boilers and industrial furnaces operating under the interim license standards of s. NR 666.103 are permitted under procedures provided by s. NR 670.066 c7d.

*cdd* A license for a new boiler or industrial furnace whose boilers and industrial furnaces not operating under the interim license standards shall establish appropriate conditions for each of the applicable requirements of this section, including but not limited to allowable hazardous waste firing rates and operating conditions necessary to meet sub. c5d, in order to comply with all of the following standards:

1. For the period beginning with initial introduction of hazardous waste and ending with initiation of the trial burn, and only for the minimum time required to bring the device to a point of operational readiness to conduct a trial burn, not to exceed a duration of 720 hours operating time when burning hazardous waste, the operating requirements shall be those most likely to ensure compliance with the emission standards of ss. NR 666.104 to 666.107, based on the department's engineering judgment. If the applicant is seeking a waiver from a trial burn to demonstrate conformance with a particular emission standard, the operating requirements during this initial period of operation shall include those specified by the applicable provisions of s. NR 666.104, 666.105, 666.106 or 666.107. The department may extend the duration of this period for up to 720 additional hours when good cause for the extension is demonstrated by the applicant.

2. For the duration of the trial burn, the operating requirements shall be sufficient to demonstrate compliance with the emissions standards of ss. NR 666.104 to 666.107 and shall be in accordance with the approved trial burn plan.

3. For the period immediately following completion of the trial burn, and only for the minimum period sufficient to allow sample analysis, data computation, submission of the trial burn results by the applicant, review of the trial burn results and modification of the facility license by the department to reflect the trial burn results, the operating requirements shall be those most likely to ensure compliance with the emission standards of ss. NR 666.104 to 666.107 based on the department's engineering judgment.

4. For the remaining duration of the license, the operating requirements shall be those demonstrated in a trial burn or by alternative data specified in s. NR 670.022, as sufficient to ensure compliance with the emissions standards of ss. NR 666.104 to 666.107.

**c5d OPERATING REQUIREMENTS.** *cad General.* A boiler or industrial furnace burning hazardous waste shall be operated in accordance with the operating requirements specified in the license at all times where there is hazardous waste in the unit.

*cbd Requirements to ensure compliance with the organic emissions standards.* 1. ZDRE standard. [ Operating conditions shall be specified either on a case-by-case basis for each hazardous waste burned as those demonstrated in a trial burn or by alternative data as specified in s. NR 670.022d to be sufficient to comply with the destruction and removal efficiency cDREd performance standard of s. NR 666.104 c1d or as those special operating requirements provided by s. NR 666.104 c1d cdd for the waiver of the DRE trial burn. When the DRE trial burn is not

waived under s. NR 666.104 c1d cdd, each set of operating requirements shall specify the composition of the hazardous waste including acceptable variations in the physical and chemical properties of the hazardous waste which will not affect compliance with the DRE performance standard to which the operating requirements apply. For each such hazardous waste, the license shall specify acceptable operating limits including, but not limited to, the following conditions as appropriate:

- a. Feed rate of hazardous waste and other fuels measured and specified as prescribed in par. cfd.
- b. Minimum and maximum device production rate when producing normal product expressed in appropriate units, measured and specified as prescribed in par. cfd.
- c. Appropriate controls of the hazardous waste firing system.
- d. Allowable variation in boiler and industrial furnace system design or operating procedures.
- e. Minimum combustion gas temperature measured at a location indicative of combustion chamber temperature, measured and specified as prescribed in par. cfd.
- f. An appropriate indicator of combustion gas velocity, measured and specified as prescribed in par. cfd, unless documentation is provided under s. NR 670.066 demonstrating adequate combustion gas residence time.
- g. Such other operating requirements as are necessary to ensure that the DRE performance standard of s. NR 666.104 c1d is met.

2. ZCarbon monoxide and hydrocarbon standards.[ The license shall incorporate a carbon monoxide cCOd limit and, as appropriate, a hydrocarbon cHCd limit as provided by s. NR 666.104 c2d, c3d, c4d, c5d and c6d. The license limits shall be specified as follows:

- a. When complying with the CO standard of s. NR 666.104 c2d cad, the license limit is 100 ppmv.
- b. When complying with the alternative CO standard under s. NR 666.104 c3d, the license limit for CO is based on the trial burn and is established as the average over all valid runs of the highest hourly rolling average CO level of each run, and the license limit for HC is 20 ppmv as defined in s. NR 666.104 c3d cadd, except as provided in s. NR 666.104 c6d.
- c. When complying with the alternative HC limit for industrial furnaces under s. NR 666.104 c6d, the license limit for HC and CO is the baseline level when hazardous waste is not burned as specified by that subsection.

3. ZStartup and shutdown.[ During startup and shutdown of the boiler or industrial furnace, hazardous waste except waste fed solely as an ingredient under the Tier I or adjusted Tier Id feed rate screening limits for metals and chloride or chlorine, and except low risk waste exempt from the trial burn requirements under ss. NR 666.104 c1d ced, 666.105, 666.106 and 666.107d may not be fed into the device unless the device is operating within the conditions of operation specified in the license.

*cd Requirements to ensure conformance with the particulate standard.* 1. Except as provided in subs. 2. and 3., the license shall specify the following operating requirements to ensure conformance with the particulate standard specified in s. NR 666.105:

- a. Total ash feed rate to the device from hazardous waste, other fuels and industrial furnace feedstocks, measured and specified as prescribed in par. cfd.
- b. Maximum device production rate when producing normal product expressed in appropriate units, and measured and specified as prescribed in par. cfd.

c. Appropriate controls on operation and maintenance of the hazardous waste firing system and any air pollution control system.

d. Allowable variation in boiler and industrial furnace system design including any air pollution control system or operating procedures.

e. Such other operating requirements as are necessary to ensure that the particulate standard in s. NR 666.111 c2d is met.

2. License conditions to ensure conformance with the particulate matter standard may not be provided for facilities exempt from the particulate matter standard under s. NR 666.105 c2d.

3. For cement kilns and light-weight aggregate kilns, license conditions to ensure compliance with the particulate standard may not limit the ash content of hazardous waste or other feed materials.

*cdd Requirements to ensure conformance with the metals emissions standard.* 1. For conformance with the Tier I or adjusted Tier Id metals feed rate screening limits of s. NR 666.106 c2d or c5d, the license shall specify the following operating requirements:

- a. Total feed rate of each metal in hazardous waste, other fuels, and industrial furnace feedstocks measured and specified under provisions of par. cfd.
- b. Total feed rate of hazardous waste measured and specified as prescribed in par. cfd.

c. A sampling and metals analysis program for the hazardous waste, other fuels and industrial furnace feedstocks.

2. For conformance with the Tier II metals emission rate screening limits under s. NR 666.106 c3d and the Tier III metals controls under s. NR 666.106 c4d, the license shall specify the following operating requirements:

- a. Maximum emission rate for each metal specified as the average emission rate during the trial burn.
- b. Feed rate of total hazardous waste and pumpable hazardous waste, each measured and specified as prescribed in par. cfd 1.
- c. Feed rate of each metal in the following feedstreams, measured and specified as prescribed in par. cfd:
  - 1d Total feedstreams.
  - 2d Total hazardous waste feed.
  - 3d Total pumpable hazardous waste feed.
- d. Total feed rate of chlorine and chloride in total feedstreams measured and specified as prescribed in par. cfd.
- e. Maximum combustion gas temperature measured at a location indicative of combustion chamber temperature, and measured and specified as prescribed in par. cfd.
- f. Maximum flue gas temperature at the inlet to the particulate matter air pollution control system measured and specified as prescribed in par. cfd.

g. Maximum device production rate when producing normal product expressed in appropriate units and measured and specified as prescribed in par. cfd.

h. Appropriate controls on operation and maintenance of the hazardous waste firing system and any air pollution control system.

i. Allowable variation in boiler and industrial furnace system design including any air pollution control system or operating procedures.

j. Such other operating requirements as are necessary to ensure that the metals standards under s. NR 666.106 c3d or c4d are met.

3. For conformance with an alternative implementation ap-



proach approved by the department under s. NR 666.106 c6d, the license shall specify all of the following operating requirements:

- a. Maximum emission rate for each metal specified as the average emission rate during the trial burn.
- b. Feed rate of total hazardous waste and pumpable hazardous waste, each measured and specified as prescribed in par. cfd 1.
- c. Feed rate of each metal in the following feedstreams, measured and specified as prescribed in par. cfd:
  - 1d Total hazardous waste feed.
  - 2d Total pumpable hazardous waste feed.
- d. Total feed rate of chlorine and chloride in total feedstreams measured and specified prescribed in par. cfd.
- e. Maximum combustion gas temperature measured at a location indicative of combustion chamber temperature, and measured and specified as prescribed in par. cfd.
- f. Maximum flue gas temperature at the inlet to the particulate matter air pollution control system measured and specified as prescribed in par. cfd.
- g. Maximum device production rate when producing normal product expressed in appropriate units and measured and specified as prescribed in par. cfd.
- h. Appropriate controls on operation and maintenance of the hazardous waste firing system and any air pollution control system.
- i. Allowable variation in boiler and industrial furnace system design including any air pollution control system or operating procedures.
- j. Such other operating requirements as are necessary to ensure that the metals standards under s. NR 666.106 c3d or c4d are met.

ced *Requirements to ensure conformance with the hydrogen chloride and chlorine gas standards.* 1. For conformance with the Tier I total chloride and chlorine feed rate screening limits of s. NR 666.107 c2d cad, the license shall specify all of the following operating requirements:

- a. Feed rate of total chloride and chlorine in hazardous waste, other fuels, and industrial furnace feedstocks measured and specified as prescribed in par. cfd.
  - b. Feed rate of total hazardous waste measured and specified as prescribed in par. cfd.
  - c. A sampling and analysis program for total chloride and chlorine for the hazardous waste, other fuels and industrial furnace feedstocks.
2. For conformance with the Tier II HCl and Cl<sub>2</sub> emission rate screening limits under s. NR 666.107 c2d cbd and the Tier III HCl and Cl<sub>2</sub> controls under s. NR 666.107 c3d, the license shall specify the following operating requirements:
- a. Maximum emission rate for HCl and for Cl<sub>2</sub> specified as the average emission rate during the trial burn.
  - b. Feed rate of total hazardous waste measured and specified as prescribed in par. cfd.
  - c. Total feed rate of chlorine and chloride in total feedstreams, measured and specified as prescribed in par. cfd.
  - d. Maximum device production rate when producing normal product expressed in appropriate units, measured and specified as prescribed in par. cfd.
  - e. Appropriate controls on operation and maintenance of the hazardous waste firing system and any air pollution control system.
  - f. Allowable variation in boiler and industrial furnace system

design including any air pollution control system or operating procedures.

- g. Such other operating requirements as are necessary to ensure that the HCl and Cl<sub>2</sub> standards under s. NR 666.107 c2d cbd or c3d are met.

cfcd *Measuring parameters and establishing limits based on trial burn data.* 1. ZGeneral requirements.[ As specified in pars. cbd to ced, each operating parameter shall be measured, and license limits on the parameter shall be established, according to either of the following procedures:

- a. A parameter may be measured and recorded on an instantaneous basis ci.e., the value that occurs at any timed and the license limit specified as the time-weighted average during all valid runs of the trial burn.
- b. 1dThe limit for a parameter may be established and continuously monitored on an hourly rolling average basis defined as follows:

ad A continuous monitor is one which continuously samples the regulated parameter without interruption, and evaluates the detector response at least once each 15 seconds, and computes and records the average value at least every 60 seconds.

bd An hourly rolling average is the arithmetic mean of the 60 most recent 1-minute average values recorded by the continuous monitoring system.

2d The license limit for the parameter shall be established based on trial burn data as the average over all valid test runs of the highest hourly rolling average value for each run.

2. ZRolling average limits for carcinogenic metals and lead.[ Feed rate limits for the carcinogenic metals ci.e., arsenic, beryllium, cadmium and chromiumd and lead may be established either on an hourly rolling average basis as prescribed by subd. 1, or on cup tod a 24 hour rolling average basis. If the owner or operator elects to use an average period from 2 to 24 hours:

- a. The feed rate of each metal shall be limited at any time to 10 times the feed rate that would be allowed on an hourly rolling average basis.

- b. The continuous monitor shall meet all of the following specifications:

1d A continuous monitor is one which continuously samples the regulated parameter without interruption, and evaluates the detector response at least once each 15 seconds, and computes and records the average value at least every 60 seconds.

2d The rolling average for the selected averaging period is defined as the arithmetic mean of one hour block averages for the averaging period. A one hour block average is the arithmetic mean of the one minute averages recorded during the 60-minute period beginning at one minute after the beginning of preceding clock hour.

- c. The license limit for the feed rate of each metal shall be established based on trial burn data as the average over all valid test runs of the highest hourly rolling average feed rate for each run.

3. ZFeed rate limits for metals, total chloride and chlorine, and ash.[ Feed rate limits for metals, total chlorine and chloride, and ash are established and monitored by knowing the concentration of the substance ci.e., metals, chloride and chlorine, and ashd in each feedstream and the flow rate of the feedstream. To monitor the feed rate of these substances, the flow rate of each feedstream shall be monitored under the continuous monitoring requirements of subds. 1, and 2.

4. ZConduct of trial burn testing.[ a. If compliance with all applicable emissions standards of ss. NR 666.104 to 666.107 is not demonstrated simultaneously during a set of test runs, the operating conditions of additional test runs required to demonstrate

compliance with remaining emissions standards shall be as close as possible to the original operating conditions.

b. Prior to obtaining test data for purposes of demonstrating compliance with the emissions standards of ss. NR 666.104 to 666.107 or establishing limits on operating parameters under this section, the facility shall operate under trial burn conditions for a sufficient period to reach steady-state operations. The department may determine, however, that industrial furnaces that recycle collected particulate matter back into the furnace and that comply with an alternative implementation approach for metals under s. NR 666.106 c6d need not reach steady state conditions with respect to the flow of metals in the system prior to beginning compliance testing for metals emissions.

c. Trial burn data on the level of an operating parameter for which a limit shall be established in the license shall be obtained during emissions sampling for the pollutant or pollutants (i.e., metals, PM, HCl, Cl<sub>2</sub>, organic compounds) for which the parameter shall be established as specified by this subsection.

cgd *General requirements.* 1. ZFugitive emissions. [ Fugitive emissions shall be controlled by one of the following:

a. Keeping the combustion zone totally sealed against fugitive emissions.

b. Maintaining the combustion zone pressure lower than atmospheric pressure.

c. An alternate means of control demonstrated (with the feasibility and plan of operation reported) to provide fugitive emissions control equivalent to maintenance of combustion zone pressure lower than atmospheric pressure.

2. ZAutomatic waste feed cutoff. [ A boiler or industrial furnace shall be operated with a functioning system that automatically cuts off the hazardous waste feed when operating conditions deviate from those established under this section. The department may limit the number of cutoffs per an operating period on a case-by-case basis. In addition, all of the following conditions shall be met:

a. The license limit for the indicator of minimum combustion chamber temperature shall be maintained while hazardous waste or hazardous waste residues remain in the combustion chamber.

b. Exhaust gases shall be ducted to the air pollution control system operated in accordance with the license requirements while hazardous waste or hazardous waste residues remain in the combustion chamber.

c. Operating parameters for which license limits are established shall continue to be monitored during the cutoff, and the hazardous waste feed may not be restarted until the levels of those parameters comply with the license limits. For parameters that may be monitored on an instantaneous basis, the department shall establish a minimum period of time after a waste feed cutoff during which the parameter may not exceed the license limit before the hazardous waste feed may be restarted.

3. ZChanges. [ A boiler or industrial furnace shall cease burning hazardous waste when changes in combustion properties, or feed rates of the hazardous waste, other fuels or industrial furnace feedstocks, or changes in the boiler or industrial furnace design or operating conditions deviate from the limits as specified in the license.

chd *Monitoring and inspections.* 1. The owner or operator shall monitor and record all of the following, at a minimum, while burning hazardous waste:

a. If specified by the license, feed rates and composition of hazardous waste, other fuels and industrial furnace feedstocks, and feed rates of ash, metals, and total chloride and chlorine.

b. If specified by the license, carbon monoxide (CO), hydrocarbons (HC) and oxygen on a continuous basis at a common point in the boiler or industrial furnace downstream of the combustion zone and prior to release of stack gases to the atmosphere in accordance with operating requirements specified in par. cbd 2. CO, HC and oxygen monitors shall be installed, operated and maintained in accordance with methods specified in ch. NR 666 Appendix IX.

c. Upon the request of the department, sampling and analysis of the hazardous waste (and other fuels and industrial furnace feedstocks as appropriated, residues and exhaust emissions shall be conducted to verify that the operating requirements established in the license achieve the applicable standards of ss. NR 666.104, 666.105, 666.106 and 666.107.

2. All monitors shall record data in units corresponding to the license limit unless otherwise specified in the license.

3. The boiler or industrial furnace and associated equipment (pumps, valves, pipes, fuel storage tanks, etc.) shall be subjected to thorough visual inspection when it contains hazardous waste, at least daily for leaks, spills, fugitive emissions and signs of tampering.

4. The automatic hazardous waste feed cutoff system and associated alarms shall be tested at least once every 7 days when hazardous waste is burned to verify operability, unless the applicant demonstrates to the department that weekly inspections will unduly restrict or upset operations and that less frequent inspections will be adequate. At a minimum, operational testing shall be conducted at least once every 30 days.

5. These monitoring and inspection data shall be recorded and the records shall be placed in the operating record required by s. NR 664.0073.

cid *Direct transfer to the burner.* If hazardous waste is directly transferred from a transport vehicle to a boiler or industrial furnace without the use of a storage unit, the owner and operator shall comply with s. NR 666.111.

cjd *Recordkeeping.* The owner or operator shall keep in the operating record of the facility all information and data required by this section for a minimum of 5 years.

ckd *Closure.* At closure, the owner or operator shall remove all hazardous waste and hazardous waste residues (including, but not limited to, ash, scrubber waters and scrubber sludges) from the boiler or industrial furnace.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; corrections in c1d cbd 9., c5d chd 1. b. made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; CR 16-007: am. c2d cad, c5d cjd Register July 2017 No. 739, eff. 8-1-17.

### NR 666.103 Interim license standards for burners.

**c1d PURPOSE, SCOPE, APPLICABILITY.** cad *General.* 1. The purpose of this section is to establish minimum national standards for owners and operators of existing boilers and industrial furnaces that burn hazardous waste where such standards define the acceptable management of hazardous waste during the period of interim license. The standards of this section apply to owners and operators of existing facilities until either a license is issued under s. NR 666.102 c4d or until closure responsibilities identified in this section are fulfilled.

2. XExisting or Xin existence Y means a boiler or industrial furnace that on or before August 21, 1991 is either in operation burning or processing hazardous waste or for which construction (including the ancillary facilities to burn or to process the hazardous waste) has commenced. A facility has commenced construction if the owner or operator has obtained the federal, state and local approvals or licenses necessary to begin physical construction; and one of the following applies:

a. A continuous on-site, physical construction program has begun.

b. The owner or operator has entered into contractual obligations—which cannot be canceled or modified without substantial loss—for physical construction of the facility to be completed within a reasonable time.

3. If a boiler or industrial furnace is located at a facility that already has a license or interim license, then the facility shall comply with the applicable regulations dealing with license modifications in s. NR 670.042 or changes in interim license in s. NR 670.072.

cbd *Exemptions.* The requirements of this section do not apply to hazardous waste and facilities exempt under ss. NR 666.100 c2d or 666.108.

ccd *Prohibition on burning dioxin-listed wastes.* The following hazardous waste listed for dioxin and hazardous waste derived from any of these wastes may not be burned in a boiler or industrial furnace operating under an interim license: F020, F021, F022, F023, F026 and F027.

cdd *Applicability of ch. NR 665 standards.* Owners and operators of boilers and industrial furnaces that burn hazardous waste and are operating under an interim license are subject to all of the following provisions of ch. NR 665, except as provided otherwise by this section:

1. In subch. A of ch. NR 665 cGenerald, s. NR 665.0004.
2. In subch. B of ch. NR 665 cGeneral facility standardsd, ss. NR 665.0011 to 665.0017.
3. In subch. C of ch. NR 665 cPreparedness and prevention, ss. NR 665.0031 to 665.0037.
4. In subch. D of ch. NR 665 cContingency plan and emergency procedured, ss. NR 665.0051 to 665.0056.
5. In subch. E of ch. NR 665 cManifest system, recordkeeping and reportingd, ss. NR 665.0071 to 665.0077, except that ss. NR 665.0071, 665.0072 and 665.0076 do not apply to owners and operators of on-site facilities that do not receive any hazardous waste from off-site sources.
6. In subch. G of ch. NR 665 cClosure and long-term cared, ss. NR 665.0111 to 665.0115.
7. In subch. H of ch. NR 665 cFinancial requirementsd, ss. NR 665.0141, 665.0142, 665.0143 and 665.0147 to 665.0148, except that states and the federal government are exempt from s. NR 665.0147.
8. Subchapter BB of ch. NR 665 cAir emission standards for equipment leaksd, except s. NR 665.1050 c1d.

ced *Special requirements for furnaces.* The following controls apply during an interim license to industrial furnaces ce.g., kilns, cupolasd that feed hazardous waste for a purpose other than solely as an ingredient csee subd. 2.d at any location other than the hot end where products are normally discharged or where fuels are normally fired:

1. ZControls.[ a. The hazardous waste shall be fed at a location where combustion gas temperatures are at least 1800 vF.
- b. The owner or operator shall determine that adequate oxygen is present in combustion gases to combust organic constituents in the waste and retain documentation of such determination in the facility record.
- c. For cement kiln systems, the hazardous waste shall be fed into the kiln.
- d. The hydrocarbon controls of s. NR 666.104 c3d or sub. c3d ced apply upon certification of compliance under sub. c3d ir-respective of the CO level achieved during the compliance test.
2. ZBurning hazardous waste solely as an ingredient.[ A

hazardous waste is burned for a purpose other than solely as an ingredient if it meets one of these criteria:

a. The hazardous waste has a total concentration of nonmetal compounds listed in ch. NR 661 Appendix VIII, exceeding 500 ppm by weight, as-fired, and so is considered to be burned for destruction. The concentration of nonmetal compounds in a waste as-generated may be reduced to the 500 ppm limit by bona fide treatment that removes or destroys nonmetal constituents. Blending for dilution to meet the 500 ppm limit is prohibited and documentation that the waste has not been impermissibly diluted shall be retained in the facility record.

b. The hazardous waste has a heating value of 5,000 Btu{lb or more, as-fired, and so is considered to be burned as fuel. The heating value of a waste as-generated may be reduced to below the 5,000 Btu{lb limit by bona fide treatment that removes or destroys organic constituents. Blending to augment the heating value to meet the 5,000 Btu{lb limit is prohibited and documentation that the waste has not been impermissibly blended shall be retained in the facility record.

cf d *Restrictions on burning hazardous waste that is not a fuel.* Prior to certification of compliance under sub. c3d, owners and operators may not feed hazardous waste that has a heating value less than 5,000 Btu{lb, as-generated, cexcept that the heating value of a waste as-generated may be increased to above the 5,000 Btu{lb limit by bona fide treatment; however, blending to augment the heating value to meet the 5,000 Btu{lb limit is prohibited and records shall be kept to document that impermissible blending has not occurredd in a boiler or industrial furnace, except that:

1. Hazardous waste may be burned solely as an ingredient.
2. Hazardous waste may be burned for purposes of compliance testing cor testing prior to compliance testingd for a total period of time not to exceed 720 hours.
3. Such waste may be burned if the department has documentation to show that, prior to August 21, 1991, all of the following conditions were met:
  - a. The boiler or industrial furnace was operating under the interim license standards for incinerators provided by subch. O of ch. NR 665, or the interim license standards for thermal treatment units provided by subch. P of ch. NR 665.
  - b. The boiler or industrial furnace met the interim license eligibility requirements under s. NR 670.070 for subch. O or subch. P of ch. NR 665.
  - c. Hazardous waste with a heating value less than 5,000 Btu{lb was burned prior to that date.
  4. Such waste may be burned in a halogen acid furnace if the waste was burned as an excluded ingredient under s. NR 661.0002 c5d prior to February 21, 1991 and documentation is kept on file supporting this claim.

cgd *Direct transfer to the burner.* If hazardous waste is directly transferred from a transport vehicle to a boiler or industrial furnace without the use of a storage unit, the owner and operator shall comply with s. NR 666.111.

**c2d CERTIFICATION OF PRECOMPLIANCE.** cad *General.* The owner or operator shall provide complete and accurate information specified in par. cbd to the department on or before August 21, 1991, and shall establish limits for the operating parameters specified in par. ccd. Such information is termed a Xcertification of precomplianceY and constitutes a certification that the owner or operator has determined that, when the facility is operated within the limits specified in par. ccd, the owner or operator believes that, using best engineering judgment, emissions of particulate matter, metals, HCl and Cl<sub>2</sub> are not likely to exceed the limits provided by ss. NR 666.105, 666.106 and 666.107. The facil-

ity may burn hazardous waste only under the operating conditions that the owner or operator establishes under par. [ccd](#) until the owner or operator submits a revised certification of precompliance under par. [chd](#) or a certification of compliance under sub. [c3d](#), or until a license is issued.

*cbd Information required.* All of the following information shall be submitted with the certification of precompliance to support the determination that the limits established for the operating parameters identified in par. [ccd](#) are not likely to result in an exceedance of the allowable emission rates for particulate matter, metals, HCl and Cl<sub>2</sub>:

1. General facility information:
  - a. EPA facility ID number.
  - b. Facility name, contact person, telephone number and address.
  - c. Description of boilers and industrial furnaces burning hazardous waste, including type and capacity of device.
  - d. A scaled plot plan showing the entire facility and location of the boilers and industrial furnaces burning hazardous waste.
  - e. A description of the air pollution control system on each device burning hazardous waste, including the temperature of the flue gas at the inlet to the particulate matter control system.
2. Except for facilities complying with the Tier I or adjusted Tier I feed rate screening limits for metals or total chlorine and chloride provided by ss. [NR 666.106 c2d](#) or [c5d](#) and [666.107 c2d cad](#) or [c5d](#), respectively, the estimated uncontrolled cat the inlet to the air pollution control systemd emissions of particulate matter, each metal controlled by s. [NR 666.106](#), and hydrogen chloride and chlorine, and all of the following information to support such determinations:
  - a. The feed rate clb{hrd of ash, chlorine, antimony, arsenic, barium, beryllium, cadmium, chromium, lead, mercury, silver and thallium in each feedstream chazardous waste, other fuels, industrial furnace feedstocksd.
  - b. The estimated partitioning factor to the combustion gas for the materials identified in subd. [2. a.](#) and the basis for the estimate and an estimate of the partitioning to HCl and Cl<sub>2</sub> of total chloride and chlorine in feed materials. To estimate the partitioning factor, the owner or operator shall use either best engineering judgment or the procedures specified in ch. [NR 666 Appendix IX](#).
  - c. For industrial furnaces that recycle collected particulate matter cPMd back into the furnace and that will certify compliance with the metals emissions standards under sub. [c3d ccd 2. a.](#), the estimated enrichment factor for each metal. To estimate the enrichment factor, the owner or operator shall use either best engineering judgment or the procedures specified in XAlternative Methodology for Implementing Metals ControlsY in ch. [NR 666 Appendix IX](#).
  - d. If best engineering judgment is used to estimate partitioning factors or enrichment factors under subd. [2. b.](#) or [c.](#) respectively, the basis for the judgment. When best engineering judgment is used to develop or evaluate data or information and make determinations under this section, the determinations shall be made by a qualified, registered professional engineer and a certification of the engineer[s determinations in accordance with s. [NR 670.011 c4d](#) shall be provided in the certification of precompliance.
3. For facilities complying with the Tier I or adjusted Tier I feed rate screening limits for metals or total chlorine and chloride provided by ss. [NR 666.106 c2d](#) or [c5d](#) and [666.107 c2d cad](#) or [c5d](#), the feed rate clb{hrd of total chloride and chlorine, antimony, arsenic, barium, beryllium, cadmium, chromium, lead,

mercury, silver and thallium in each feed stream chazardous waste, other fuels, industrial furnace feedstocksd.

4. For facilities complying with the Tier II or Tier III emission limits for metals or HCl and Cl<sub>2</sub> cunder ss. [NR 666.106 c3d](#) or [c4d](#) or [666.107 c2d cbd](#) or [c3dd](#), the estimated controlled coutlet of the air pollution control systemd emissions rates of particulate matter, each metal controlled by s. [NR 666.106](#), and HCl and Cl<sub>2</sub>, and the following information to support such determinations:

- a. The estimated air pollution control system cAPCSd removal efficiency for particulate matter, HCl, Cl<sub>2</sub>, antimony, arsenic, barium, beryllium, cadmium, chromium, lead, mercury, silver and thallium.
- b. To estimate APCS removal efficiency, the owner or operator shall use either best engineering judgment or the procedures prescribed in ch. [NR 666 Appendix IX](#).
- c. If best engineering judgment is used to estimate APCS removal efficiency, the basis for the judgment. Use of best engineering judgment shall be in conformance with provisions of subd. [2. d.](#)
5. Determination of allowable emissions rates for HCl, Cl<sub>2</sub>, antimony, arsenic, barium, beryllium, cadmium, chromium, lead, mercury, silver and thallium, and the following information to support such determinations:
  - a. For all facilities, all of the following:
    - 1d Physical stack height.
    - 2d Good engineering practice stack height as defined by [40 CFR 51.100ciid](#).
    - 3d Maximum flue gas flow rate.
    - 4d Maximum flue gas temperature.
    - 5d Attach a US geological service topographic map cor equivalentd showing the facility location and surrounding land within 5 km of the facility.
    - 6d Identify terrain type: complex or noncomplex.
    - 7d Identify land use: urban or rural.
  - b. For owners and operators using Tier III site specific dispersion modeling to determine allowable levels under s. [NR 666.106 c4d](#) or [666.107 c3d](#), or adjusted Tier I feed rate screening limits under s. [NR 666.106 c5d](#) or [666.107 c5d](#):
    - 1d Dispersion model and version used.
    - 2d Source of meterological data.
    - 3d The dilution factor in micrograms per cubic meter per gram per second of emissions for the maximum annual average off-site cunless on-site is requiredd ground level concentration cMEI locationd.
    - 4d Indicate the MEI location on the map required under subd. [5. a. 5d.](#)
6. For facilities complying with the Tier II or III emissions rate controls for metals or HCl and Cl<sub>2</sub>, a comparison of the estimated controlled emissions rates determined under subd. [4.](#) with the allowable emission rates determined under subd. [5.](#)
7. For facilities complying with the Tier I cor adjusted Tier Id feed rate screening limits for metals or total chloride and chlorine, a comparison of actual feed rates of each metal and total chlorine and chloride determined under subd. [3.](#) to the Tier I allowable feed rates.
8. For industrial furnaces that feed hazardous waste for any purpose other than solely as an ingredient cas defined by sub. [c1d ccd 2.d](#) at any location other than the product discharge end of the device, documentation of compliance with sub. [c1d ced 1. a., b. and c.](#)
9. For industrial furnaces that recycle collected particulate



matter cPMD back into the furnace and that will certify compliance with the metals emissions standards under sub. [c3d ccd 2. a.](#), both of the following:

- a. The applicable particulate matter standard in lb/hr.
- b. The precompliance limit on the concentration of each metal in collected PM.

*ccd Limits on operating conditions.* The owner and operator shall establish limits on the following parameters consistent with the determinations made under par. [cbd](#) and certify under provisions of par. [cidd](#) to the department that the facility will operate within the limits during interim license when there is hazardous waste in the unit until revised certification of precompliance under par. [chd](#) or certification of compliance under sub. [c3d](#):

1. Feed rate of total hazardous waste and unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d](#) or [c5dd](#) pumpable hazardous waste.

2. Feed rate of each metal in all of the following feed streams:

- a. Total feed streams, except that industrial furnaces that comply with the alternative metals implementation approach under par. [cdd](#) shall specify limits on the concentration of each metal in collected particulate matter in lieu of feed rate limits for total feedstreams.

- b. Total hazardous waste feed, unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d](#) or [c5d](#).

- c. Total pumpable hazardous waste feed, unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d](#) or [c5d](#).

3. Total feed rate of chlorine and chloride in total feed streams.

4. Total feed rate of ash in total feed streams, except that the ash feed rate for cement kilns and light-weight aggregate kilns is not limited.

5. Maximum production rate of the device in appropriate units when producing normal product, unless complying with the Tier I or adjusted Tier I feed rate screening limits for chlorine under s. [NR 666.107 c2d cad](#) or [c5d](#) and for all metals under s. [NR 666.106 c2d](#) or [c5d](#), and the uncontrolled particulate emissions do not exceed the standard under s. [NR 666.105](#).

*cdd Operating requirements for furnaces that recycle PM.* Owners and operators of furnaces that recycle collected particulate matter cPMD back into the furnace and that will certify compliance with the metals emissions controls under sub. [c3d ccd 2. a.](#) shall comply with the special operating requirements provided in XAlternative Methodology for Implementing Metals ControlsY in ch. [NR 666 Appendix IX](#).

*ced Measurement of feed rates and production rate.* 1. ZGeneral requirements.[ Limits on each of the parameters specified in par. [ccd](#) except for limits on metals concentrations in collected particulate matter cPMD for industrial furnaces that recycle collected PMd shall be established and continuously monitored under either of the following methods:

- a. A limit for a parameter may be established and continuously monitored and recorded on an instantaneous basis c.i.e., the value that occurs at any time not to be exceeded at any time.

- b. A limit for a parameter may be established and continuously monitored on an hourly rolling average basis defined as follows:

1d A continuous monitor is one which continuously samples the regulated parameter without interruption, and evaluates the detector response at least once each 15 seconds, and computes and records the average value at least every 60 seconds.

2d An hourly rolling average is the arithmetic mean of the 60 most recent 1-minute average values recorded by the continuous monitoring system.

2. ZRolling average limits for carcinogenic metals and lead.[ Feed rate limits for the carcinogenic metals arsenic, beryllium, cadmium and chromiumd and lead may be established either on an hourly rolling average basis as prescribed by subd. [1. b.](#) or on a 24 hour rolling average basis. If the owner or operator elects to use an averaging period from 2 to 24 hours:

- a. The feed rate of each metal shall be limited at any time to 10 times the feed rate that would be allowed on a hourly rolling average basis.

- b. The continuous monitor shall meet all of the following specifications:

1d A continuous monitor is one which continuously samples the regulated parameter without interruption, and evaluates the detector response at least once each 15 seconds, and computes and records the average value at least every 60 seconds.

2d The rolling average for the selected averaging period is defined as the arithmetic mean of one hour block averages for the averaging period. A one hour block average is the arithmetic mean of the one minute averages recorded during the 60-minute period beginning at one minute after the beginning of preceding clock hour.

3. ZFeed rate limits for metals, total chloride and chlorine, and ash.[ Feed rate limits for metals, total chlorine and chloride, and ash are established and monitored by knowing the concentration of the substance c.i.e., metals, chloride and chlorine, and ashd in each feedstream and the flow rate of the feedstream. To monitor the feed rate of these substances, the flow rate of each feedstream shall be monitored under the continuous monitoring requirements of subd. [1.](#) and [2.](#)

*cfid Public notice requirements at precompliance.* On or before August 21, 1991 the owner or operator shall submit a notice with the following information for publication in a major local newspaper of general circulation and send a copy of the notice to the appropriate units of state and local government. The owner and operator shall provide to the department with the certification of precompliance evidence of submitting the notice for publication. The notice, which shall be entitled XNotice of Certification of Precompliance with Hazardous Waste Burning Requirements of s. [NR 666.103 c2d](#), Wis. Adm. CodeY, shall include all of the following:

1. Name and address of the owner and operator of the facility as well as the location of the device burning hazardous waste.

2. Date that the certification of precompliance is submitted to the department.

3. Brief description of the regulatory process required to comply with the interim license requirements including required emissions testing to demonstrate conformance with emissions standards for organic compounds, particulate matter, metals, HCl and Cl<sub>2</sub>.

4. Types and quantities of hazardous waste burned including, but not limited to, source, whether solids or liquids, as well as an appropriate description of the waste.

5. Type of device or devices in which the hazardous waste is burned including a physical description and maximum production rate of each device.

6. Types and quantities of other fuels and industrial furnace feedstocks fed to each unit.

7. Brief description of the basis for this certification of precompliance as specified in par. [cbd](#).

8. Locations where the record for the facility can be viewed

and copied by interested parties. These records and locations shall at a minimum include both of the following:

a. The administrative record kept by the department office where the supporting documentation was submitted or another location designated by the department.

b. The BIF correspondence file kept at the facility site where the device is located. The correspondence file shall include all correspondence between the facility and the department, state and local regulatory officials, including copies of all certifications and notifications, such as the precompliance certification, precompliance public notice, notice of compliance testing, compliance test report, compliance certification, time extension requests and approvals or denials, enforcement notifications of violations, and copies of EPA and state site visit reports submitted to the owner or operator.

9. Notification of the establishment of a facility mailing list whereby interested parties may notify the department that they wish to be placed on the mailing list to receive future information and notices about this facility.

10. Location mailing address of the department bureau of waste management where further information can be obtained on department regulation of hazardous waste burning.

*cgd Monitoring other operating parameters.* When the monitoring systems for the operating parameters listed in sub. [c3d cad 5.](#) to [13.](#) are installed and operating in conformance with vendor specifications or for CO, HC and oxygen specifications provided by [ch. NR 666 Appendix IX](#), as appropriate, the parameters shall be continuously monitored and records shall be maintained in the operating record.

*chd Revised certification of precompliance.* The owner or operator may revise at any time the information and operating conditions documented under [pars. cbd and ccd](#) in the certification of precompliance by submitting a revised certification of precompliance under procedures provided by those paragraphs.

1. The public notice requirements of [par. cfd](#) do not apply to recertifications.

2. The owner and operator shall operate the facility within the limits established for the operating parameters under [par. ccd](#) until a revised certification is submitted under this paragraph or a certification of compliance is submitted under [sub. c3d](#).

*cid Certification of precompliance statement.* The owner or operator shall include the following signed statement with the certification of precompliance submitted to the department:

XI certify under penalty of law that this information was prepared under my direction or supervision in accordance with a system designed to ensure that qualified personnel properly gathered and evaluated the information and supporting documentation. Copies of all emissions tests, dispersion modeling results and other information used to determine conformance with [s. NR 666.103 c2d](#) are available at the facility and can be obtained from the facility contact person listed above. Based on my inquiry of the person or persons who manages the facility, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

I also acknowledge that the operating limits established in this certification pursuant to [s. NR 666.103 c2d ccd and cdd](#) are enforceable limits at which the facility can legally operate during interim license until: [c1d](#) A revised certification of precompliance is submitted, [c2d](#) a certification of compliance is submitted, or [c3d](#) an operating license is issued.Y

**c3d CERTIFICATION OF COMPLIANCE.** The owner or operator

shall conduct emissions testing to document compliance with the emissions standards of [ss. NR 666.104 c2d to c5d, 666.105, 666.106, 666.107](#) and [sub. c1d ced 1. d.](#), under the procedures prescribed by this subsection, except under extensions of time provided by [par. cgd](#). Based on the compliance test, the owner or operator shall submit to the department on or before August 21, 1992 a complete and accurate Xcertification of compliance Y under [par. cddd](#) with those emission standards establishing limits on the operating parameters specified in [par. cad](#).

*cad Limits on operating conditions.* The owner or operator shall establish limits on the following parameters based on operations during the compliance test under procedures prescribed in [par. cdd 4.d](#) or as otherwise specified and include these limits with the certification of compliance. The boiler or industrial furnace shall be operated in accordance with these operating limits and the applicable emissions standards of [ss. NR 666.104 c2d to c5d, 666.105, 666.106, 666.107](#) and [sub. c1d ced 1. d.](#) at all times when there is hazardous waste in the unit.

1. Feed rate of total hazardous waste and unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under [s. NR 666.106 c2d or c5d](#) and the total chlorine and chloride feed rate screening limits under [s. NR 666.107 c2d or c5dd](#), pumpable hazardous waste.

2. Feed rate of each metal in the following feedstreams:

a. Total feedstreams, except that:

1d Facilities that comply with Tier I or adjusted Tier I metals feed rate screening limits may set their operating limits at the metals feed rate screening limits determined under [s. NR 666.106 c2d or c5d](#).

2d Industrial furnaces that shall comply with the alternative metals implementation approach under [par. ccd 2.](#) shall specify limits on the concentration of each metal in the collected particulate matter in lieu of feed rate limits for total feedstreams.

b. Total hazardous waste feed unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under [s. NR 666.106 c2d or c5dd](#).

c. Total pumpable hazardous waste feed unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under [s. NR 666.106 c2d or c5dd](#).

3. Total feed rate of chlorine and chloride in total feed streams, except that facilities that comply with Tier I or adjusted Tier I feed rate screening limits may set their operating limits at the total chlorine and chloride feed rate screening limits determined under [s. NR 666.107 c2d cad or c5d](#).

4. Total feed rate of ash in total feed streams, except that the ash feed rate for cement kilns and light-weight aggregate kilns is not limited.

5. Carbon monoxide concentration, and where required, hydrocarbon concentration in stack gas. When complying with the CO controls of [s. NR 666.104 c2d](#), the CO limit is 100 ppmv, and when complying with the HC controls of [s. NR 666.104 c3d](#), the HC limit is 20 ppmv. When complying with the CO controls of [s. NR 666.104 c3d](#), the CO limit is established based on the compliance test.

6. Maximum production rate of the device in appropriate units when producing normal product, unless complying with the Tier I or adjusted Tier I feed rate screening limits for chlorine under [s. NR 666.107 c2d cad or c5d](#) and for all metals under [s. NR 666.106 c2d or c5d](#), and the uncontrolled particulate emissions do not exceed the standard under [s. NR 666.105](#).

7. Maximum combustion chamber temperature where the temperature measurement is as close to the combustion zone as possible and is upstream of any quench water injection unless

complying with the Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d](#) or [c5dd](#).

8. Maximum flue gas temperature entering a particulate matter control device unless complying with Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d](#) or [c5d](#) and the total chlorine and chloride feed rate screening limits under s. [NR 666.107 c2d](#) or [c5dd](#).

9. For systems using wet scrubbers, including wet ionizing scrubbers unless complying with Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d cad](#) or [c5dd](#):

- a. Minimum liquid to flue gas ration.
- b. Minimum scrubber blowdown from the system or maximum suspended solids content of scrubber water.
- c. Minimum pH level of the scrubber water.

10. For systems using venturi scrubbers, the minimum differential gas pressure across the venturi unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d](#) or [c5d](#) and the total chlorine and chloride feed rate screening limits under s. [NR 666.107 c2d cad](#) or [c5dd](#).

11. For systems using dry scrubbers unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d](#) or [c5d](#) and the total chlorine and chloride feed rate screening limits under s. [NR 666.107 c2d cad](#) or [c5dd](#):

- a. Minimum caustic feed rate.
- b. Maximum flue gas flow rate.

12. For systems using wet ionizing scrubbers or electrostatic precipitators unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under s. [NR 666.106 c2d](#) or [c5d](#) and the total chlorine and chloride feed rate screening limits under s. [NR 666.107 c2d cad](#) or [c5dd](#):

- a. Minimum electrical power in kilovolt amperes cKVAd to the precipitator plates.
- b. Maximum flue gas flow rate.

13. For systems using fabric filters cbaghousesd, the minimum pressure drop unless complying with the Tier I or adjusted Tier I metal feed rate screening limits under s. [NR 666.106 c2d](#) or [c5d](#) and the total chlorine and chloride feed rate screening limits under s. [NR 666.107 c2d cad](#) or [c5dd](#).

*cbd Prior notice of compliance testing.* At least 30 days prior to the compliance testing required by par. [ccd](#), the owner or operator shall notify the department and submit all of the following information:

1. General facility information including:
  - a. EPA facility ID number.
  - b. Facility name, contact person, telephone number and address.
  - c. Person responsible for conducting compliance test, including company name, address and telephone number, and a statement of qualifications.
  - d. Planned date of the compliance test.
2. Specific information on each device to be tested including:
  - a. Description of boiler or industrial furnace.
  - b. A scaled plot plan showing the entire facility and location of the boiler or industrial furnace.
  - c. A description of the air pollution control system.
  - d. Identification of the continuous emission monitors that are installed, including:
    - 1d Carbon monoxide monitor.
    - 2d Oxygen monitor.
    - 3d Hydrocarbon monitor, specifying the minimum temperature of the system and, if the temperature is less than 150 vC, an

explanation of why a heated system is not used csee par. [cedd](#) and a brief description of the sample gas conditioning system.

e. Indication of whether the stack is shared with another device that will be in operation during the compliance test.

f. Other information useful to an understanding of the system design or operation.

3. Information on the testing planned, including a complete copy of the test protocol and quality assurance{quality control cQA{QCd plan, and a summary description for each test providing all of the following information at a minimum:

a. Purpose of the test ce.g., demonstrate compliance with emissions of particulate matterd.

b. Planned operating conditions, including levels for each pertinent parameter specified in par. [cad](#).

*ccd Compliance testing.* 1. ZGeneral.[ Compliance testing shall be conducted under conditions for which the owner or operator has submitted a certification of precompliance under sub. [c2d](#) and under conditions established in the notification of compliance testing required by par. [cbd](#). The owner or operator may seek approval on a case-by-case basis to use compliance test data from one unit in lieu of testing a similar onsite unit. To support the request, the owner or operator shall provide a comparison of the hazardous waste burned and other feedstreams, and the design, operation and maintenance of both the tested unit and the similar unit. The department shall provide a written approval to use compliance test data in lieu of testing a similar unit if it finds that the hazardous wastes, the devices and the operating conditions are sufficiently similar, and the data from the other compliance test is adequate to meet the requirements of this subsection.

2. ZSpecial requirements for industrial furnaces that recycle collected PM.[ Owners and operators of industrial furnaces that recycle back into the furnace particulate matter cPMd from the air pollution control system shall comply with one of the following procedures for testing to determine compliance with the metals standards of s. [NR 666.106 c3d](#) or [c4d](#):

a. The special testing requirements prescribed in XAlternative Method for Implementing Metals ControlsY in ch. [NR 666 Appendix IX](#).

b. Stack emissions testing for a minimum of 6 hours each day while hazardous waste is burned during an interim license. The testing shall be conducted when burning normal hazardous waste for that day at normal feed rates for that day and when the air pollution control system is operated under normal conditions. During an interim license, hazardous waste analysis for metals content shall be sufficient for the owner or operator to determine if changes in metals content may affect the ability of the facility to meet the metals emissions standards established under s. [NR 666.106 c3d](#) or [c4d](#). Under this option, operating limits cunder par. [cadd](#) shall be established during compliance testing under this paragraph only on the following parameters:

- 1d Feed rate of total hazardous waste.
- 2d Total feed rate of chlorine and chloride in total feed streams.
- 3d Total feed rate of ash in total feed streams, except that the ash feed rate for cement kilns and light-weight aggregate kilns is not limited.
- 4d Carbon monoxide concentration, and where required, hydrocarbon concentration in stack gas.
- 5d Maximum production rate of the device in appropriate units when producing normal product.

c. Conduct compliance testing to determine compliance with the metals standards to establish limits on the operating parameters of par. [cad](#) only after the kiln system has been conditioned to

enable it to reach equilibrium with respect to metals fed into the system and metals emissions. During conditioning, hazardous waste and raw materials having the same metals content as will be fed during the compliance test shall be fed at the feed rates that will be fed during the compliance test.

3. ZConduct of compliance testing.[ a. If compliance with all applicable emissions standards of ss. NR 666.104 to 666.107 is not demonstrated simultaneously during a set of test runs, the operating conditions of additional test runs required to demonstrate compliance with remaining emissions standards shall be as close as possible to the original operating conditions.

b. Prior to obtaining test data for purposes of demonstrating compliance with the applicable emissions standards of ss. NR 666.104 to 666.107 or establishing limits on operating parameters under this section, the facility shall operate under compliance test conditions for a sufficient period to reach steady-state operations. Industrial furnaces that recycle collected particulate matter back into the furnace and that comply with subd. 2. a. or b., however, need not reach steady state conditions with respect to the flow of metals in the system prior to beginning compliance testing for metals.

c. Compliance test data on the level of an operating parameter for which a limit shall be established in the certification of compliance shall be obtained during emissions sampling for the pollutant or pollutants ci.e., metals, PM, HCl{Cl<sub>2</sub>, organic compoundsd for which the parameter shall be established as specified by par. cad.

cdd *Certification of compliance.* Within 90 days of completing compliance testing, the owner or operator shall certify to the department compliance with the emissions standards of ss. NR 666.104 c2d, c3d and c5d, 666.105, 666.106, 666.107 and sub. c1d ced 1. d. The certification of compliance shall include all of the following information:

1. General facility and testing information including:
  - a. EPA facility ID number.
  - b. Facility name, contact person, telephone number and address.
  - c. Person responsible for conducting compliance testing, including company name, address and telephone number, and a statement of qualifications.
  - d. Date or dates of each compliance test.
  - e. Description of boiler or industrial furnace tested.
  - f. Person responsible for quality assurance{quality control cQA{QCd, title and telephone number, and statement that procedures prescribed in the QA{QC plan submitted under s. NR 666.103 c3d cbd 3. have been followed, or a description of any changes and an explanation of why changes were necessary.
  - g. Description of any changes in the unit configuration prior to or during testing that would alter any of the information submitted in the prior notice of compliance testing under par. cbd, and an explanation of why the changes were necessary.
  - h. Description of any changes in the planned test conditions prior to or during the testing that alter any of the information submitted in the prior notice of compliance testing under par. cbd, and an explanation of why the changes were necessary.
  - i. The complete report on results of emissions testing.
2. Specific information on each test including:
  - a. Purpose or purposes of test ce.g., demonstrate conformance with the emissions limits for particulate matter, metals, HCl, Cl<sub>2</sub> and COd.
  - b. Summary of test results for each run and for each test including the following information:
    - 1d Date of run.

2d Duration of run.

3d Time-weighted average and highest hourly rolling average CO level for each run and for the test.

4d Highest hourly rolling average HC level, if HC monitoring is required for each run and for the test.

5d If dioxin and furan testing is required under s. NR 666.104 c5d, time-weighted average emissions for each run and for the test of chlorinated dioxin and furan emissions, and the predicted maximum annual average ground level concentration of the toxicity equivalency factor.

6d Time-weighted average particulate matter emissions for each run and for the test.

7d Time-weighted average HCl and Cl<sub>2</sub> emissions for each run and for the test.

8d Time-weighted average emissions for the metals subject to regulation under s. NR 666.106 for each run and for the test.

9d QA{QC results.

3. Comparison of the actual emissions during each test with the emissions limits prescribed by ss. NR 666.104 c2d, c3d and c5d, 666.105, 666.106 and 666.107 and established for the facility in the certification of precompliance under sub. c2d.

4. Determination of operating limits based on all valid runs of the compliance test for each applicable parameter listed in par. cad using either of the following procedures:

a. A parameter may be measured and recorded on an instantaneous basis ci.e., the value that occurs at any timed and the operating limit specified as the time-weighted average during all runs of the compliance test.

b. 1d The limit for a parameter may be established and continuously monitored on an hourly rolling average basis defined as follows:

ad A continuous monitor is one which continuously samples the regulated parameter without interruption, and evaluates the detector response at least once each 15 seconds, and computes and records the average value at least every 60 seconds.

bd An hourly rolling average is the arithmetic mean of the 60 most recent 1-minute average values recorded by the continuous monitoring system.

2d The operating limit for the parameter shall be established based on compliance test data as the average over all test runs of the highest hourly rolling average value for each run.

c. Feed rate limits for the carcinogenic metals ci.e., arsenic, beryllium, cadmium and chromiumd and lead may be established either on an hourly rolling average basis as prescribed by subd. 4. b. or on cup tod a 24 hour rolling average basis. If the owner or operator elects to use an averaging period from 2 to 24 hours:

1d The feed rate of each metal shall be limited at any time to 10 times the feed rate that would be allowed on a hourly rolling average basis.

2d The continuous monitor shall meet the following specifications:

ad A continuous monitor is one which continuously samples the regulated parameter without interruption, and evaluates the detector response at least once each 15 seconds, and computes and records the average value at least every 60 seconds.

bd The rolling average for the selected averaging period is defined as arithmetic mean of one hour block averages for the averaging period. A one hour block average is the arithmetic mean of the one minute averages recorded during the 60-minute period beginning at one minute after the beginning of preceding clock hour.

3d The operating limit for the feed rate of each metal shall be



established based on compliance test data as the average over all test runs of the highest hourly rolling average feed rate for each run.

d. Feed rate limits for metals, total chlorine and chloride, and ash are established and monitored by knowing the concentration of the substance *ci.e.*, metals, chloride and chlorine, and ash in each feedstream and the flow rate of the feedstream. To monitor the feed rate of these substances, the flow rate of each feedstream shall be monitored under the continuous monitoring requirements of subd. 4. a. to c.

5. The following statement shall accompany the certification of compliance:

XI certify under penalty of law that this information was prepared under my direction or supervision in accordance with a system designed to ensure that qualified personnel properly gathered and evaluated the information and supporting documentation. Copies of all emissions tests, dispersion modeling results and other information used to determine conformance with s. NR 666.103 c3d are available at the facility and can be obtained from the facility contact person listed above. Based on my inquiry of the person or persons who manages the facility, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

I also acknowledge that the operating conditions established in this certification pursuant to s. NR 666.103 c3d cdd 4. are enforceable limits at which the facility can legally operate during an interim license until a revised certification of compliance is submitted.Y

ced *Special requirements for HC monitoring systems.* When an owner or operator is required to comply with the hydrocarbon cHCd controls provided by s. NR 666.104 c3d or sub. c1d ced 1. d., a conditioned gas monitoring system may be used in conformance with specifications provided in ch. NR 666 Appendix IX if the owner or operator submits a certification of compliance without using extensions of time provided by par. cgd.

cfd *Special operating requirements for industrial furnaces that recycle collected PM.* Owners and operators of industrial furnaces that recycle back into the furnace particulate matter cPMd from the air pollution control system shall do all of the following:

1. When complying with par. ccd 2. a., comply with the operating requirements prescribed in XAlternative Method to Implement the Metals ControlsY in ch. NR 666 Appendix IX.

2. When complying with par. ccd 2. b., comply with the operating requirements prescribed by that subdivision paragraph.

cgd *Extensions of time.* 1. If the owner or operator does not submit a complete certification of compliance for all of the applicable emissions standards of ss. NR 666.104, 666.105, 666.106 and 666.107 by August 21, 1992, the owner or operator shall do one of the following:

a. Stop burning hazardous waste and begin closure activities under sub. c12d for the hazardous waste portion of the facility.

b. Limit hazardous waste burning only for purposes of compliance testing and pretesting to prepare for compliance testing a total period of 720 hours for the period of time beginning August 21, 1992, submit a notification to the department by August 21, 1992 stating that the facility is operating under restricted interim license and intends to resume burning hazardous waste, and submit a complete certification of compliance by August 23, 1993.

c. Obtain a case-by-case extension of time under subd. 2.

2. The owner or operator may request a case-by-case extension of time to extend any time limit provided by this paragraph if compliance with the time limit is not practicable for reasons beyond the control of the owner or operator.

a. In granting an extension, the department may apply conditions as the facts warrant to ensure timely compliance with this section and that the facility operates in a manner that does not pose a hazard to human health and the environment.

b. When an owner or operator requests an extension of time to enable the facility to comply with the alternative hydrocarbon provisions of s. NR 666.104 c6d and obtain a hazardous waste license because the facility cannot meet the HC limit of s. NR 666.104 c3d:

1d The department shall, in considering whether to grant the extension, do all of the following:

ad Determine whether the owner and operator have submitted in a timely manner a complete feasibility and plan of operation report that includes information required under s. NR 670.022 c2d.

bd Consider whether the owner and operator have made a good faith effort to certify compliance with all other emission controls, including the controls on dioxins and furans of s. NR 666.104 c5d and the controls on PM, metals, HCl and Cl<sub>2</sub>.

2d If an extension is granted, the department shall, as a condition of the extension, require the facility to operate under flue gas concentration limits on CO and HC that, based on available information, including information in the feasibility and plan of operation report, are baseline CO and HC levels as defined by s. NR 666.104 c6d cad.

chd *Revised certification of compliance.* The owner or operator may submit at any time a revised certification of compliance cecertification of compliance under the following procedures:

1. Prior to submittal of a revised certification of compliance, hazardous waste may not be burned for more than a total of 720 hours under operating conditions that exceed those established under a current certification of compliance, and such burning may be conducted only for purposes of determining whether the facility can operate under revised conditions and continue to meet the applicable emissions standards of ss. NR 666.104, 666.105, 666.106 and 666.107.

2. At least 30 days prior to first burning hazardous waste under operating conditions that exceed those established under a current certification of compliance, the owner or operator shall notify the department and submit the following information:

a. EPA facility ID number, and facility name, contact person, telephone number and address.

b. Operating conditions that the owner or operator is seeking to revise and description of the changes in facility design or operation that prompted the need to seek to revise the operating conditions.

c. A determination that when operating under the revised operating conditions, the applicable emissions standards of ss. NR 666.104, 666.105, 666.106 and 666.107 are not likely to be exceeded. To document this determination, the owner or operator shall submit the applicable information required under sub. c2d cbd.

d. Complete emissions testing protocol for any pretesting and for a new compliance test to determine compliance with the applicable emissions standards of ss. NR 666.104, 666.105, 666.106 and 666.107 when operating under revised operating conditions. The protocol shall include a schedule of pre-testing and compliance testing. If the owner or operator revises the scheduled date for the compliance test, the owner or operator

shall notify the department in writing at least 30 days prior to the revised date of the compliance test.

3. Conduct a compliance test under the revised operating conditions and the protocol submitted to the department to determine compliance with the applicable emissions standards of ss. [NR 666.104](#), [666.105](#), [666.106](#) and [666.107](#).

4. Submit a revised certification of compliance under par. [cdd](#).

**c4d PERIODIC RECERTIFICATIONS.** The owner or operator shall conduct compliance testing and submit to the department a recertification of compliance under provisions of sub. [c3d](#) within 5 years from submitting the previous certification or recertification. If the owner or operator seeks to recertify compliance under new operating conditions, the owner or operator shall comply with sub. [c3d chd](#).

**c5d NONCOMPLIANCE WITH CERTIFICATION SCHEDULE.** If the owner or operator does not comply with the interim license compliance schedule provided by subs. [c2d](#), [c3d](#) and [c4d](#), hazardous waste burning shall terminate on the date that the deadline is missed, closure activities shall begin under sub. [c12d](#), and hazardous waste burning may not resume except under an operating license issued under s. [NR 670.066](#). For purposes of compliance with the closure provisions of sub. [c12d](#) and ss. [NR 665.0112 c4d cbd](#) and [665.0113](#) the boiler or industrial furnace has received Xthe known final volume of hazardous wasteY on the date that the deadline is missed.

**c6d STARTUP AND SHUTDOWN.** Hazardous waste except waste fed solely as an ingredient under the Tier I or adjusted Tier Id feed rate screening limits for metals and chloride and chlorinated may not be fed into the device during startup and shutdown of the boiler or industrial furnace, unless the device is operating within the conditions of operation specified in the certification of compliance.

**c7d AUTOMATIC WASTE FEED CUTOFF.** During the compliance test required by sub. [c3d ccd](#), and upon certification of compliance under sub. [c3d](#), a boiler or industrial furnace shall be operated with a functioning system that automatically cuts off the hazardous waste feed when the applicable operating conditions specified in sub. [c3d cad 1](#), and [5](#), to [13](#), deviate from those established in the certification of compliance. In addition:

cad To minimize emissions of organic compounds, the minimum combustion chamber temperature cor the indicator of combustion chamber temperature that occurred during the compliance test shall be maintained while hazardous waste or hazardous waste residues remain in the combustion chamber, with the minimum temperature during the compliance test defined as either of the following:

1. If compliance with the combustion chamber temperature limit is based on a hourly rolling average, the minimum temperature during the compliance test is considered to be the average over all runs of the lowest hourly rolling average for each run.

2. If compliance with the combustion chamber temperature limit is based on an instantaneous temperature measurement, the minimum temperature during the compliance test is considered to be the time-weighted average temperature during all runs of the test.

cbd Operating parameters limited by the certification of compliance shall continue to be monitored during the cutoff, and the hazardous waste feed may not be restarted until the levels of those parameters comply with the limits established in the certification of compliance.

**c8d FUGITIVE EMISSIONS.** Fugitive emissions shall be controlled by one of the following:

cad Keeping the combustion zone totally sealed against fugitive emissions.

cbd Maintaining the combustion zone pressure lower than atmospheric pressure.

ccd An alternate means of control that the owner or operator can demonstrate provide fugitive emissions control equivalent to maintenance of combustion zone pressure lower than atmospheric pressure. Support for such demonstration shall be included in the operating record.

**c9d CHANGES.** A boiler or industrial furnace shall cease burning hazardous waste when changes in combustion properties, or feed rates of the hazardous waste, other fuels, or industrial furnace feedstocks, or changes in the boiler or industrial furnace design or operating conditions deviate from the limits specified in the certification of compliance.

**c10d MONITORING AND INSPECTIONS.** cad The owner or operator shall monitor and record all of the following, at a minimum, while burning hazardous waste:

1. Feed rates and composition of hazardous waste, other fuels, and industrial furnace feed stocks, and feed rates of ash, metals, and total chloride and chlorine as necessary to ensure conformance with the certification of precompliance or certification of compliance.

2. Carbon monoxide cCOd, oxygen, and if applicable, hydrocarbons cHCd, on a continuous basis at a common point in the boiler or industrial furnace downstream of the combustion zone and prior to release of stack gases to the atmosphere in accordance with the operating limits specified in the certification of compliance. CO, HC and oxygen monitors shall be installed, operated and maintained in accordance with methods specified in [ch. NR 666 Appendix IX](#).

3. Upon the request of the department, sampling and analysis of the hazardous waste cand other fuels and industrial furnace feed stocks as appropriated and the stack gas emissions shall be conducted to verify that the operating conditions established in the certification of precompliance or certification of compliance achieve the applicable standards of ss. [NR 666.104](#), [666.105](#), [666.106](#) and [666.107](#).

cbd The boiler or industrial furnace and associated equipment cpumps, valves, pipes, fuel storage tanks, etc.d shall be subjected to thorough visual inspection when they contain hazardous waste, at least daily for leaks, spills, fugitive emissions and signs of tampering.

ccd The automatic hazardous waste feed cutoff system and associated alarms shall be tested at least once every 7 days when hazardous waste is burned to verify operability, unless the owner or operator can demonstrate that weekly inspections will unduly restrict or upset operations and that less frequent inspections will be adequate. Support for such demonstration shall be included in the operating record. At a minimum, operational testing shall be conducted at least once every 30 days.

cdd These monitoring and inspection data shall be recorded and the records shall be placed in the operating log.

**c11d RECORDKEEPING.** The owner or operator shall keep in the operating record of the facility all information and data required by this section for a minimum of 5 years.

**c12d CLOSURE.** At closure, the owner or operator shall remove all hazardous waste and hazardous waste residues including, but not limited to, ash, scrubber waters and scrubber sludged from the boiler or industrial furnace and shall comply with ss. [NR 665.0111](#) to [665.0115](#).

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; corrections in [c2d cbd 2. b., c., ccd 4. b., cdd, cgd, c3d ccd 2. a., ced, cfd 1., c10d cad 2.](#) made under s. [13.92 c4d cbd 7.](#), Stats., Register March 2013 No. 687; CR 16-007: am. [c4d, c11d](#)

Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c1d cfd 4., c3d cdd cintro.d Register August 2020 No. 776, eff. 9-1-20.

**NR 666.104 Standards to control organic emissions. c1d DRE STANDARD.** cad *General.* Except as provided in par. ccd, a boiler or industrial furnace burning hazardous waste shall achieve a destruction and removal efficiency cDREd of 99.99% for all organic hazardous constituents in the waste feed. To demonstrate conformance with this requirement, 99.99% DRE shall be demonstrated during a trial burn for each principal organic hazardous constituent cPOHCd designated under par. cbdd in its license for each waste feed. DRE is determined for each POHC from the following equation:

$$DRE = \left[ 1 - \frac{W_{out}}{W_{in}} \right] \times 100$$

$$DRE = \left[ 1 - \frac{W_{out}}{W_{in}} \right] \times 100$$

where:

$W_{in}$  = Mass feed rate of one principal organic hazardous constituent cPOHCd in the hazardous waste fired to the boiler or industrial furnace

$W_{out}$  = Mass emission rate of the same POHC present in stack gas prior to release to the atmosphere

cbd *Designation of POHCs.* Principal organic hazardous constituents cPOHCsd are those compounds for which compliance with the DRE requirements shall be demonstrated in a trial burn in conformance with procedures prescribed in s. NR 670.066. One or more POHCs shall be designated by the department for each waste feed to be burned. POHCs shall be designated based on the degree of difficulty of destruction of the organic constituents in the waste and on their concentrations or mass in the waste feed considering the results of waste analyses submitted with the feasibility and plan of operation report. POHCs are most likely to be selected from among those compounds listed in ch. NR 661 Appendix VIII that are also present in the normal waste feed. However, if the applicant demonstrates to the department[s] satisfaction in writing that a compound not listed in ch. NR 661 Appendix VIII or not present in the normal waste feed is a suitable indicator of compliance with the DRE requirements, that compound may be designated as a POHC. Such POHCs need not be toxic or organic compounds.

ccd *Dioxin-listed waste.* A boiler or industrial furnace burning hazardous waste containing cor derived from EPA hazardous waste numbers F020, F021, F022, F023, F026 or F027 shall achieve a destruction and removal efficiency cDREd of 99.9999% for each POHC designated under par. cbdd in its license. This performance shall be demonstrated on POHCs that are more difficult to burn than tetra-, penta- and hexachlorodibenzo-*p*-dioxins and dibenzofurans. DRE is determined for each POHC from the equation in par. cad. In addition, the owner or operator of the boiler or industrial furnace shall notify the department of intent to burn EPA hazardous waste numbers F020, F021, F022, F023, F026 or F027.

cdd *Automatic waiver of DRE trial burn.* Owners and operators of boilers operated under the special operating requirements provided by s. NR 666.110 are considered to be in compliance with the DRE standard of par. cad and are exempt from the DRE trial burn.

ced *Low risk waste.* Owners and operators of boilers or industrial furnaces that burn hazardous waste in compliance with s. NR 666.109 c1d are considered to be in compliance with the

DRE standard of par. cad and are exempt from the DRE trial burn.

c2d **CARBON MONOXIDE STANDARD.** cad Except as provided in sub. c3d, the stack gas concentration of carbon monoxide cCOd from a boiler or industrial furnace burning hazardous waste cannot exceed 100 ppmv on an hourly rolling average basis c.i.e., over any 60 minute periodd, continuously corrected to 7% oxygen, dry gas basis.

cbd CO and oxygen shall be continuously monitored in conformance with XPerformance Specifications for Continuous Emission Monitoring of Carbon Monoxide and Oxygen for Incinerators, Boilers and Industrial Furnaces Burning Hazardous WasteY in ch. NR 666 Appendix IX.

ccd Compliance with the 100 ppmv CO limit shall be demonstrated during the trial burn cfor new facilities or an interim license facility applying for an operating licensed or the compliance test cfor interim license facilitiesd. To demonstrate compliance, the highest hourly rolling average CO level during any valid run of the trial burn or compliance test may not exceed 100 ppmv.

c3d **ALTERNATIVE CARBON MONOXIDE STANDARD.** cad The stack gas concentration of carbon monoxide cCOd from a boiler or industrial furnace burning hazardous waste may exceed the 100 ppmv limit if stack gas concentrations of hydrocarbons cHCd do not exceed 20 ppmv, except as provided by sub. c6d for certain industrial furnaces.

cbd HC limits shall be established under this section on an hourly rolling average basis c.i.e., over any 60 minute periodd, reported as propane, and continuously corrected to 7% oxygen, dry gas basis.

ccd HC shall be continuously monitored in conformance with XPerformance Specifications for Continuous Emission Monitoring of Hydrocarbons for Incinerators, Boilers and Industrial Furnaces Burning Hazardous WasteY in ch. NR 666 Appendix IX. CO and oxygen shall be continuously monitored in conformance with sub. c2d cbd.

cdd The alternative CO standard is established based on CO data during the trial burn cfor a new facilityd and the compliance test cfor an interim license facilityd. The alternative CO standard is the average over all valid runs of the highest hourly average CO level for each run. The CO limit is implemented on an hourly rolling average basis, and continuously corrected to 7% oxygen, dry gas basis.

c4d **SPECIAL REQUIREMENTS FOR FURNACES.** Owners and operators of industrial furnaces c.e.g., kilns, cupolasd that feed hazardous waste for a purpose other than solely as an ingredient csee s. NR 666.103 c1d ced 2.d at any location other than the end where products are normally discharged and where fuels are normally fired shall comply with the hydrocarbon limits provided by sub. c3d or c6d irrespective of whether stack gas CO concentrations meet the 100 ppmv limit of sub. c2d.

c5d **CONTROLS FOR DIOXINS AND FURANS.** Owners and operators of boilers and industrial furnaces that are equipped with a dry particulate matter control device that operates within the temperature range of 450 to 750 vF, and industrial furnaces operating under an alternative hydrocarbon limit established under sub. c6d shall conduct a site-specific risk assessment as follows to demonstrate that emissions of chlorinated dibenzo-*p*-dioxins and dibenzofurans do not result in an increased lifetime cancer risk to the hypothetical maximum exposed individual cMEId exceeding 1 in 100,000:

cad During the trial burn cfor new facilities or an interim license facility applying for an operating licensed or compliance test cfor interim license facilitiesd, determine emission rates of the tetra-octa congeners of chlorinated dibenzo-*p*-dioxins and



dibenzofurans cCDDs{CDFsd using Method 0023A, Sampling Method for Polychlorinated Dibenzop-Dioxins and Polychlorinated Dibenzofurans Emissions from Stationary Sources, EPA SW-846, as incorporated by reference in s. NR 660.11.

cbd Estimate the 2,3,7,8-TCDD toxicity equivalence of the tetra-octa CDDs{CDFs congeners using XProcedures for Estimating the Toxicity Equivalence of Chlorinated Dibenzop-Dioxin and Dibenzofuran CongenersY in ch. NR 666 Appendix IX. Multiply the emission rates of CDD{CDF congeners with a toxicity equivalence greater than 0 csee the procedured by the calculated toxicity equivalence factor to estimate the equivalent emission rate of 2,3,7,8-TCDD.

ccd Conduct dispersion modeling using methods recommended in Appendix W of 40 CFR part 51 cYGuideline on Air Quality Models cReviseddY c1986d and its supplements, incorporated by reference in s. NR 660.11d, the XHazardous Waste Combustion Air Quality Screening ProcedureY, provided in ch. NR 666 Appendix IX, or in Screening Procedures for Estimating the Air Quality Impact of Stationary Sources, Revised, EPA-450{R-92-019, incorporated by reference in s. NR 660.11, to predict the maximum annual average off-site ground level concentration of 2,3,7,8-TCDD equivalents determined under par. cbd. The maximum annual average concentration shall be used when a person resides on-site.

cdd The ratio of the predicted maximum annual average ground level concentration of 2,3,7,8-TCDD equivalents to the risk-specific dose for 2,3,7,8-TCDD provided in ch. NR 666 Appendix V c2.2 X 10<sup>17</sup>d may not exceed 1.0.

**c6d MONITORING CO AND HC IN THE BY-PASS DUCT OF A CEMENT KILN.** Cement kilns may comply with the carbon monoxide and hydrocarbon limits provided by subs. c2d, c3d and c4d by monitoring in the by-pass duct if both of the following conditions are met:

cad Hazardous waste is fired only into the kiln and not at any location downstream from the kiln exit relative to the direction of gas flow.

cbd The by-pass duct diverts a minimum of 10% of kiln off-gas into the duct.

**c7d USE OF EMISSIONS TEST DATA TO DEMONSTRATE COMPLIANCE AND ESTABLISH OPERATING LIMITS.** Compliance with this section shall be demonstrated simultaneously by emissions testing or during separate runs under identical operating conditions. Further, data to demonstrate compliance with the CO and HC limits of this section or to establish alternative CO or HC limits under this section shall be obtained during the time that DRE testing, and where applicable, CDD{CDF testing under sub. c5d and comprehensive organic emissions testing under sub. c6d is conducted.

**c8d ENFORCEMENT.** For the purposes of license enforcement, compliance with the operating requirements specified in the license cunder s. NR 666.102d shall be regarded as compliance with this section. However, evidence that compliance with those license conditions is insufficient to ensure compliance with this section may be information justifying modification or revocation and re-issuance of a license under s. NR 670.041.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; corrections in c1d cbd, c2d cbd, c3d ccd, c5d cbd to cdd made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

**NR 666.105 Standards to control particulate matter. c1d** A boiler or industrial furnace burning hazardous waste may not emit particulate matter in excess of 180 milligrams per dry standard cubic meter c0.08 grains per dry standard cubic footd after correction to a stack gas concentration of 7% oxygen, using procedures prescribed in 40 CFR part 60, appendix A,

methods 1 to 5, incorporated by reference in s. NR 660.11, and ch. NR 666 Appendix IX.

**c2d** An owner or operator meeting s. NR 666.109 c2d for the low risk waste exemption is exempt from the particulate matter standard.

**c3d OXYGEN CORRECTION.** cad Measured pollutant levels shall be corrected for the amount of oxygen in the stack gas according to the formula:

$$Pc = Pm \times 14 / (E - Y)$$

where:

Pc is the corrected concentration of the pollutant in the stack gas, Pm is the measured concentration of the pollutant in the stack gas, E is the oxygen concentration on a dry basis in the combustion air fed to the device, and Y is the measured oxygen concentration on a dry basis in the stack.

cbd For devices that feed normal combustion air, E will equal 21%. For devices that feed oxygen-enriched air for combustion cthat is, air with an oxygen concentration exceeding 21%d, the value of E will be the concentration of oxygen in the enriched air.

ccd Compliance with all emission standards provided by this subchapter shall be based on correcting to 7% oxygen using this procedure.

**c4d** For the purposes of license enforcement, compliance with the operating requirements specified in the license cunder s. NR 666.102d shall be regarded as compliance with this section. However, evidence that compliance with those license conditions is insufficient to ensure compliance with this section may be information justifying modification or revocation and re-issuance of a license under s. NR 670.041.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c1d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

**NR 666.106 Standards to control metals emissions. c1d GENERAL.** The owner or operator shall comply with the metals standards provided by subs. c2d, c3d, c4d, c5d, or c6d for each metal listed in sub. c2d that is present in the hazardous waste at detectable levels by using appropriate analytical procedures.

**c2d TIER I FEED RATE SCREENING LIMITS.** Feed rate screening limits for metals are specified in ch. NR 666 Appendix I as a function of terrain-adjusted effective stack height and terrain and land use in the vicinity of the facility. Criteria for facilities that are not eligible to comply with the screening limits are provided in par. cgd.

cad *Noncarcinogenic metals.* The feed rates of antimony, barium, lead, mercury, thallium and silver in all feed streams, including hazardous waste, fuels, and industrial furnace feed stocks may not exceed the screening limits specified in ch. NR 666 Appendix I.

1. The feed rate screening limits for antimony, barium, mercury, thallium and silver are based on either of the following:

a. An hourly rolling average as defined in s. NR 666.102 c5d cfd 1. b.

b. An instantaneous limit not to be exceeded at any time.

2. The feed rate screening limit for lead is based on one of the following:

a. An hourly rolling average as defined in s. NR 666.102 c5d cfd 1. b.

b. An averaging period of 2 to 24 hours as defined in s. NR 666.102 c5d cfd 2. with an instantaneous feed rate limit not to exceed 10 times the feed rate that would be allowed on an hourly rolling average basis.

c. An instantaneous limit not to be exceeded at any time.



cbd *Carcinogenic metals*. 1. The feed rates of arsenic, cadmium, beryllium and chromium in all feed streams, including hazardous waste, fuels, and industrial furnace feed stocks may not exceed values derived from the screening limits specified in ch. NR 666 Appendix I. The feed rate of each of these metals is limited to a level such that the sum of the ratios of the actual feed rate to the feed rate screening limit specified in ch. NR 666 Appendix I may not exceed 1.0, as provided by the following equation:

$$\sum_{i=1}^n \frac{\text{AFR}_{(i)}}{\text{FRSL}_{(i)}} \leq 1.0$$

where:

n = number of carcinogenic metals

AFR = actual feed rate to the device for metal XiY

FRSL = feed rate screening limit provided by ch. NR 666 Appendix I for metal XiY

2. The feed rate screening limits for the carcinogenic metals are based on either of the following:

a. An hourly rolling average.

b. An averaging period of 2 to 24 hours as defined in s. NR 666.102 c5d cfd 2. with an instantaneous feed rate limit not to exceed 10 times the feed rate that would be allowed on an hourly rolling average basis.

ccd *TESH*. 1. The terrain-adjusted effective stack height is determined according to the following equation:

$$\text{TESH} = \text{Ha} + \text{H1} - \text{Tr}$$

where:

Ha = Actual physical stack height

H1 = Plume rise as determined from ch. NR 666 Appendix VI as a function of stack flow rate and stack gas exhaust temperature

Tr = Terrain rise within 5 kilometers of the stack

2. The stack height cHad may not exceed good engineering practice as specified in 40 CFR 51.100cidd.

3. If the TESH for a particular facility is not listed in the table in the appendices, the nearest lower TESH listed in the table shall be used. If the TESH is 4 meters or less, a value of 4 meters shall be used.

cdd *Terrain type*. The screening limits are a function of whether the facility is located in noncomplex or complex terrain. A device located where any part of the surrounding terrain within 5 kilometers of the stack equals or exceeds the elevation of the physical stack height cHad is considered to be in complex terrain and the screening limits for complex terrain apply. Terrain measurements are to be made from U.S. geological survey 7.5-minute topographic maps of the area surrounding the facility.

ced *Land use*. The screening limits are a function of whether the facility is located in an area where the land use is urban or rural. To determine whether land use in the vicinity of the facility is urban or rural, procedures provided in ch. NR 666 Appendix IX shall be used.

cfid *Multiple stacks*. Owners and operators of facilities with more than one on-site stack from a boiler, industrial furnace, incinerator or other thermal treatment unit subject to controls of metals emissions under an operating license or interim license shall comply with the screening limits for all such units assuming all hazardous waste is fed into the device with the worst-case stack based on dispersion characteristics. The worst-case stack is determined from the following equation as applied to each stack:

$$K = \text{HVT}$$

where:

K = a parameter accounting for relative influence of stack height and plume rise

H = physical stack height cmetersd

V = stack gas flow rate cm<sup>3</sup>{secondd

T = exhaust temperature cvKd

The stack with the lowest value of K is the worst-case stack.

cgd *Criteria for facilities not eligible for screening limits*. If any of the following criteria are met, the Tier I and Tier II screening limits do not apply. Owners and operators of such facilities shall comply with either the Tier III standards provided by sub. c4d or with the adjusted Tier I feed rate screening limits provided by sub. c5d.

1. The device is located in a narrow valley less than one kilometer wide.

2. The device has a stack taller than 20 meters and is located such that the terrain rises to the physical height within one kilometer of the facility.

3. The device has a stack taller than 20 meters and is located within 5 kilometers of a shoreline of a large body of water such as an ocean or large lake.

4. The physical stack height of any stack is less than 2.5 times the height of any building within 5 building heights or 5 projected building widths of the stack and the distance from the stack to the closest boundary is within 5 building heights or 5 projected building widths of the associated building.

5. The department determines that standards based on site-specific dispersion modeling are required.

chd *Implementation*. The feed rate of metals in each feed-stream shall be monitored to ensure that the feed rate screening limits are not exceeded.

c3d **TIER II EMISSION RATE SCREENING LIMITS**. Emission rate screening limits are specified in ch. NR 666 Appendix I as a function of terrain-adjusted effective stack height and terrain and land use in the vicinity of the facility. Criteria for facilities that are not eligible to comply with the screening limits are provided in sub. c2d cgd.

cad *Noncarcinogenic metals*. The emission rates of antimony, barium, lead, mercury, thallium and silver may not exceed the screening limits specified in ch. NR 666 Appendix I.

cbd *Carcinogenic metals*. The emission rates of arsenic, cadmium, beryllium and chromium may not exceed values derived from the screening limits specified in ch. NR 666 Appendix I. The emission rate of each of these metals is limited to a level such that the sum of the ratios of the actual emission rate to the emission rate screening limit specified in ch. NR 666 Appendix I may not exceed 1.0, as provided by the following equation:

$$\sum_{i=1}^n \frac{\text{AER}_{(i)}}{\text{ERSL}_{(i)}} \leq 1.0$$

where:

n = number of carcinogenic metals

AER = actual emission rate for metal XiY

ERSL = emission rate screening limit provided by ch. NR 666 Appendix I for metal XiY

ccd *Implementation*. The emission rate limits shall be implemented by limiting feed rates of the individual metals to levels during the trial burn cfor new facilities or an interim license facility applying for a licensed or the compliance test cfor interim license facilitiesd. The feed rate averaging periods are the same as

provided by sub. **c2d cad 1.** and **2.** and **cbd 2.** The feed rate of metals in each feedstream shall be monitored to ensure that the feed rate limits for the feedstreams specified under s. **NR 666.102** or **666.103** are not exceeded.

**cdd Definitions and limitations.** The definitions and limitations provided by sub. **c2d** for the following terms also apply to the Tier II emission rate screening limits provided by this subsection: terrain-adjusted effective stack height, good engineering practice stack height, terrain type, land use and criteria for facilities not eligible to use the screening limits.

**ced Multiple stacks.** 1. Owners and operators of facilities with more than one onsite stack from a boiler, industrial furnace, incinerator or other thermal treatment unit subject to controls on metals emissions under an operating license or interim license shall comply with the emissions screening limits for any such stacks assuming all hazardous waste is fed into the device with the worst-case stack based on dispersion characteristics.

2. The worst-case stack is determined by procedures provided in sub. **c2d cfd.**

3. For each metal, the total emissions of the metal from those stacks may not exceed the screening limit for the worst-case stack.

**c4d TIER III AND ADJUSTED TIER I SITE-SPECIFIC RISK ASSESSMENT.** The requirements of this subsection apply to facilities complying with either the Tier III or adjusted Tier I controls, except where specified otherwise.

**cad General.** Conformance with the Tier III metals controls shall be demonstrated by emissions testing to determine the emission rate for each metal. In addition, conformance with either the Tier III or adjusted Tier I metals controls shall be demonstrated by air dispersion modeling to predict the maximum annual average off-site ground level concentration for each dispersion modeling to predict the maximum annual average off-site ground level concentration for each metal, and a demonstration that acceptable ambient levels are not exceeded.

**cbd Acceptable ambient levels.** Chapter **NR 666 Appendix IV** and ch. **NR 666 Appendix V** list the acceptable ambient levels for purposes of this rule. Reference air concentrations **cRACsd** are listed for the noncarcinogenic metals and  $10^{15}$  risk-specific doses **cRSDsd** are listed for the carcinogenic metals. The RSD for a metal is the acceptable ambient level for that metal if only one of the 4 carcinogenic metals is emitted. If more than one carcinogenic metal is emitted, the acceptable ambient level for the carcinogenic metals is a fraction of the RSD as described in par. **ccd.**

**ccd Carcinogenic metals.** For the carcinogenic metals, arsenic, cadmium, beryllium and chromium, the sum of the ratios of the predicted maximum annual average off-site ground level concentrations except that on-site concentrations shall be considered if a person resides on sited to the risk-specific dose **cRSDd** for all carcinogenic metals emitted may not exceed 1.0 as determined by the following equation:

$$\sum_{i=1}^n \frac{\text{Predicted Ambient Concentration } (i)}{\text{Risk - Specific Dose } (i)} \leq 1.0$$

where:

n = number of carcinogenic metals

**cdd Noncarcinogenic metals.** For the noncarcinogenic metals, the predicted maximum annual average off-site ground level concentration for each metal may not exceed the reference air concentration **cRACd.**

**ced Multiple stacks.** Owners and operators of facilities with more than one on-site stack from a boiler, industrial furnace, in-

cinerator or other thermal treatment unit subject to controls on metals emissions under an operating license or interim license shall conduct emissions testing except that facilities complying with adjusted Tier I controls need not conduct emissions testing and dispersion modeling to demonstrate that the aggregate emissions from all such on-site stacks do not result in an exceedance of the acceptable ambient levels.

**cfid Implementation.** Under Tier III, the metals controls shall be implemented by limiting feed rates of the individual metals to levels during the trial burn **cfid** for new facilities or an interim license facility applying for an operating licensed or the compliance test **cfid** for interim license facilities. The feed rate averaging periods are the same as provided by sub. **c2d cad 1.** and **2.** and **cbd 2.** The feed rate of metals in each feedstream shall be monitored to ensure that the feed rate limits for the feedstreams specified under s. **NR 666.102** or **666.103** are not exceeded.

**c5d ADJUSTED TIER I FEED RATE SCREENING LIMITS.** The owner or operator may adjust the feed rate screening limits provided by ch. **NR 666 Appendix I** to account for site-specific dispersion modeling. Under this approach, the adjusted feed rate screening limit for a metal is determined by back-calculating from the acceptable ambient level provided by ch. **NR 666 Appendix IV** and ch. **NR 666 Appendix V** using dispersion modeling to determine the maximum allowable emission rate. This emission rate becomes the adjusted Tier I feed rate screening limit. The feed rate screening limits for carcinogenic metals are implemented as prescribed in sub. **c2d cbd.**

**c6d ALTERNATIVE IMPLEMENTATION APPROACHES.** **cad** The department may approve on a case-by-case basis approaches to implement the Tier II or Tier III metals emission limits provided by sub. **c3d** or **c4d** alternative to monitoring the feed rate of metals in each feedstream.

**cbd** The emission limits provided by sub. **c4d** shall be determined as follows:

1. For each noncarcinogenic metal, by back-calculating from the RAC provided in ch. **NR 666 Appendix IV** to determine the allowable emission rate for each metal using the dilution factor for the maximum annual average ground level concentration predicted by dispersion modeling in conformance with sub. **c8d.**

2. For each carcinogenic metal by all of the following:

a. Back-calculating from the RSD provided in ch. **NR 666 Appendix V** to determine the allowable emission rate for each metal if that metal were the only carcinogenic metal emitted using the dilution factor for the maximum annual average ground level concentration predicted by dispersion modeling in conformance with sub. **c8d.**

b. If more than one carcinogenic metal is emitted, selecting an emission limit for each carcinogenic metal not to exceed the emission rate determined by subd. **2. a.** such that the sum for all carcinogenic metals of the ratios of the selected emission limit to the emission rate determined by subd. **2. a.** does not exceed 1.0.

**c7d EMISSION TESTING.** **cad General.** Emission testing for metals shall be conducted using Method 0060, Determinations of Metals in Stack Emissions, EPA SW-846, as incorporated by reference in s. **NR 660.11.**

**cbd Hexavalent chromium.** Emissions of chromium are assumed to be hexavalent chromium unless the owner or operator conducts emissions testing to determine hexavalent chromium emissions using procedures prescribed in Method 0061, Determination of Hexavalent Chromium Emissions from Stationary Sources, EPA SW-846, as incorporated by reference in s. **NR 660.11.**

**c8d DISPERSION MODELING.** Dispersion modeling required under this section shall be conducted according to methods rec-

ommended in Appendix W of 40 CFR part 51 cYGuideline on Air Quality Models cRevisedY c1986d and its supplements, incorporated by reference in s. NR 660.11d, the XHazardous Waste Combustion Air Quality Screening ProcedureY, provided in ch. NR 666 Appendix IX , or in Screening Procedures for Estimating the Air Quality Impact of Stationary Sources, Revised, EPA-450(R-92-019, incorporated by reference in s. NR 660.11, to predict the maximum annual average off-site ground level concentration. However, on-site concentrations shall be considered when a person resides on-site.

**c9d ENFORCEMENT.** For the purposes of license enforcement, compliance with the operating requirements specified in the license under s. NR 666.102d shall be regarded as compliance with this section. However, evidence that compliance with those license conditions is insufficient to ensure compliance with this section may be information justifying modification or revocation and re-issuance of a license under s. NR 670.041.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; corrections in c2d cintro.d, cad, cbd 1., ccd, ced, c3d cintro.d, cad, cbd, c4d cbd, c5d, c6d cbd 1., 2. a., c8d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; CR 16-007: am. c1d Register July 2017 No. 739, eff. 8-1-17.

**NR 666.107 Standards to control hydrogen chloride cHCl and chlorine gas cCl<sub>2</sub> emissions. c1d GENERAL.** The owner or operator shall comply with the hydrogen chloride cHCl and chlorine cCl<sub>2</sub> controls provided by sub. c2d, c3d or c5d.

**c2d SCREENING LIMITS. cad Tier I feed rate screening limits.** Feed rate screening limits are specified for total chlorine in ch. NR 666 Appendix II as a function of terrain-adjusted effective stack height and terrain and land use in the vicinity of the facility. The feed rate of total chlorine and chloride, both organic and inorganic, in all feed streams, including hazardous waste, fuels and industrial furnace feed stocks may not exceed the levels specified.

**cbd Tier II emission rate screening limits.** Emission rate screening limits for HCl and Cl<sub>2</sub> are specified in ch. NR 666 Appendix III as a function of terrain-adjusted effective stack height and terrain and land use in the vicinity of the facility. The stack emission rates of HCl and Cl<sub>2</sub> may not exceed the levels specified.

**ccd Definitions and limitations.** The definitions and limitations provided by s. NR 666.106 c2d for the following terms also apply to the screening limits provided by this subsection: terrain-adjusted effective stack height, good engineering practice stack height, terrain type, land use and criteria for facilities not eligible to use the screening limits.

**cdd Multiple stacks.** Owners and operators of facilities with more than one on-site stack from a boiler, industrial furnace, incinerator or other thermal treatment unit subject to controls on HCl or Cl<sub>2</sub> emissions under an operating license or interim license shall comply with the Tier I and Tier II screening limits for those stacks assuming all hazardous waste is fed into the device with the worst-case stack based on dispersion characteristics.

1. The worst-case stack is determined by procedures provided in s. NR 666.106 c2d cfd.

2. Under Tier I, the total feed rate of chlorine and chloride to all subject devices may not exceed the screening limit for the worst-case stack.

3. Under Tier II, the total emissions of HCl and Cl<sub>2</sub> from all subject stacks may not exceed the screening limit for the worst-case stack.

**c3d TIER III SITE-SPECIFIC RISK ASSESSMENTS. cad General.** Conformance with the Tier III controls shall be demonstrated by emissions testing to determine the emission rate for HCl and Cl<sub>2</sub>, air dispersion modeling to predict the maximum annual

average off-site ground level concentration for each compound, and a demonstration that acceptable ambient levels are not exceeded.

**cbd Acceptable ambient levels.** Chapter. NR 666 Appendix IV lists the reference air concentrations cRACs for HCl c7 micrograms per cubic meter and Cl<sub>2</sub> c0.4 micrograms per cubic meter.

**ccd Multiple stacks.** Owners and operators of facilities with more than one on-site stack from a boiler, industrial furnace, incinerator or other thermal treatment unit subject to controls on HCl or Cl<sub>2</sub> emissions under an operating license or interim license shall conduct emissions testing and dispersion modeling to demonstrate that the aggregate emissions from all such on-site stacks do not result in an exceedance of the acceptable ambient levels for HCl and Cl<sub>2</sub>.

**c4d AVERAGING PERIODS.** The HCl and Cl<sub>2</sub> controls are implemented by limiting the feed rate of total chlorine and chloride in all feedstreams, including hazardous waste, fuels and industrial furnace feed stocks. Under Tier I, the feed rate of total chloride and chlorine is limited to the Tier I screening limits. Under Tier II and Tier III, the feed rate of total chloride and chlorine is limited to the feed rates during the trial burn cfor new facilities or an interim license facility applying for a licensed or the compliance test cfor interim license facilitiesd. The feed rate limits are based on either of the following:

**cad** An hourly rolling average as defined in s. NR 666.102 c5d cfd.

**cbd** An instantaneous basis not to be exceeded at any time.

**c5d ADJUSTED TIER I FEED RATE SCREENING LIMITS.** The owner or operator may adjust the feed rate screening limit provided by ch. NR 666 Appendix II to account for site-specific dispersion modeling. Under this approach, the adjusted feed rate screening limit is determined by back-calculating from the acceptable ambient level for Cl<sub>2</sub> provided by ch. NR 666 Appendix IV using dispersion modeling to determine the maximum allowable emission rate. This emission rate becomes the adjusted Tier I feed rate screening limit.

**c6d EMISSIONS TESTING.** Emissions testing for HCl and Cl<sub>2</sub> shall be conducted using the procedures described in Methods 0050 or 0051, EPA SW-846, as incorporated by reference in s. NR 660.11.

**c7d DISPERSION MODELING.** Dispersion modeling shall be conducted according to s. NR 666.106 c8d.

**c8d ENFORCEMENT.** For the purposes of license enforcement, compliance with the operating requirements specified in the license under s. NR 666.102d shall be regarded as compliance with this section. However, evidence that compliance with those license conditions is insufficient to ensure compliance with this section may be information justifying modification or revocation and re-issuance of a license under s. NR 670.041.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; corrections in c2d cad, cbd, c3d cbd, c5d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

**NR 666.108 Small quantity on-site burner exemption. c1d EXEMPT QUANTITIES.** Owners and operators of facilities that burn hazardous waste in a non-site boiler or industrial furnace are exempt from this subchapter if all of the following conditions are met:

**cad** The quantity of hazardous waste burned in a device for a calendar month does not exceed the limits provided in the following table based on the terrain-adjusted effective stack height as defined in s. NR 666.106 c2d ccd.

**Exempt Quantities for Small Quantity Burner Exemption**

Terrain-adjusted effective stack height of device cmetersd	Allowable hazardous waste burning rate cgal-lons{ monthd	Terrain-adjusted effective stack height of device cmetersd	Allowable hazardous waste burning rate cgal-lons{ monthd
0 to 3.9	0	40.0 to 44.9	210
4.0 to 5.9	13	45.0 to 49.9	260
6.0 to 7.9	18	50.0 to 54.9	330
8.0 to 9.9	27	55.0 to 59.9	400
10.0 to 11.9	40	60.0 to 64.9	490
12.0 to 13.9	48	65.0 to 69.9	610
14.0 to 15.9	59	70.0 to 74.9	680
16.0 to 17.9	69	75.0 to 79.9	760
18.0 to 19.9	76	80.0 to 84.9	850
20.0 to 21.9	84	85.0 to 89.9	960
22.0 to 23.9	93	90.0 to 94.9	1,100
24.0 to 25.9	100	95.0 to 99.9	1,200
26.0 to 27.9	110	100.0 to 104.9	1,300
28.0 to 29.9	130	105.0 to 109.9	1,500
30.0 to 34.9	140	110.0 to 114.9	1,700
35.0 to 39.9	170	115.0 or greater	1,900

cbd The maximum hazardous waste firing rate does not exceed at any time one percent of the total fuel requirements for the device chazardous waste plus other fuel on a total heat input or mass input basis, whichever results in the lower mass feed rate of hazardous waste.

ccd The hazardous waste has a minimum heating value of 5,000 Btu{lb, as generated.

cdd The hazardous waste fuel does not contain cand is not derived fromd EPA hazardous waste numbers F020, F021, F022, F023, F026 or F027.

**c2d MIXING WITH NONHAZARDOUS FUELS.** If hazardous waste fuel is mixed with a nonhazardous fuel, the quantity of hazardous waste before such mixing is used to comply with sub. **c1d**.

**c3d MULTIPLE STACKS.** If an owner or operator burns hazardous waste in more than one on-site boiler or industrial furnace exempt under this section, the quantity limits provided by sub. **c1d cad** are implemented according to the following equation:

$$\sum_{i=1}^n \frac{\text{Actual Quantity Burned (i)}}{\text{Allowable Quantity Burned (i)}} \leq 1.0$$

where:

n means the number of stacks.

Actual Quantity Burned means the waste quantity burned per month in device XiY.

Allowable Quantity Burned means the maximum allowable exempt quantity for stack XiY from the table in sub. **c1d cad**.

**Note:** Hazardous wastes that are subject to the special requirements for small quantity generators under ss. **NR 662.013** and **662.016** may be burned in an off-site device under the exemption provided by this section, but shall be included in the quantity determination for the exemption.

**c4d NOTIFICATION REQUIREMENTS.** The owner or operator of facilities qualifying for the small quantity burner exemption under this section shall provide a one-time signed, written notice to the department indicating all of the following:

cad The combustion unit is operating as a small quantity burner of hazardous waste.

cbd The owner and operator are in compliance with this section.

ccd The maximum quantity of hazardous waste that the facility may burn per month as provided by sub. **c1d cad**.

**c5d RECORDKEEPING REQUIREMENTS.** The owner or operator shall maintain at the facility for at least 3 years sufficient

records documenting compliance with the hazardous waste quantity, firing rate and heating value limits of this section. At a minimum, these records shall indicate the quantity of hazardous waste and other fuel burned in each unit per calendar month, and the heating value of the hazardous waste.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.109 Low risk waste exemption. c1d WAIVER OF DRE STANDARD.** The DRE standard of s. **NR 666.104 c1d** does not apply if the boiler or industrial furnace is operated in conformance with par. **cad** and the owner or operator demonstrates by procedures prescribed in par. **cbd** that the burning will not result in unacceptable adverse health effects.

cad The device shall be operated with all of the following conditions:

1. A minimum of 50% of fuel fired to the device shall be fossil fuel, fuels derived from fossil fuel, tall oil, or, if approved by the department on a case-by-case basis, other nonhazardous fuel with combustion characteristics comparable to fossil fuel. Such fuels are termed primary fuel for purposes of this section. cTall oil is a fuel derived from vegetable and rosin fatty acids.d The 50% primary fuel firing rate shall be determined on a total heat or mass input basis, whichever results in the greater mass feed rate of primary fuel fired.

2. Primary fuels and hazardous waste fuels shall have a minimum as-fired heating value of 8,000 Btu{lb.

3. The hazardous waste shall be fired directly into the primary fuel flame zone of the combustion chamber.

4. The device shall operate in conformance with the carbon monoxide controls provided by s. **NR 666.104 c2d cad**. Devices subject to the exemption provided by this section are not eligible for the alternative carbon monoxide controls provided by s. **NR 666.104 c3d**.

cbd Procedures to demonstrate that the hazardous waste burning will not pose unacceptable adverse public health effects are all of the following:

1. Identify and quantify those nonmetal compounds listed in ch. **NR 661 Appendix VIII** that could reasonably be expected to be present in the hazardous waste. The constituents excluded from analysis shall be identified and the basis for their exclusion explained.

2. Calculate reasonable, worst case emission rates for each constituent identified in subd. **1.** by assuming the device achieves



99.9% destruction and removal efficiency. That is, assume that 0.1% of the mass weight of each constituent fed to the device is emitted.

3. For each constituent identified in subd. 1., use emissions dispersion modeling to predict the maximum annual average ground level concentration of the constituent.

a. Dispersion modeling shall be conducted using methods specified in s. NR 666.106 c8d.

b. Owners and operators of facilities with more than one on-site stack from a boiler or industrial furnace that is exempt under this section shall conduct dispersion modeling of emissions from all stacks exempt under this section to predict ambient levels prescribed by this subdivision.

4. Ground level concentrations of constituents predicted under subd. 3. may not exceed all of the following levels:

a. For the noncarcinogenic compounds listed in ch. NR 666 Appendix IV, the levels established in ch. NR 666 Appendix IV.

b. For the carcinogenic compounds listed in ch. NR 666 Appendix V, the sum for all constituents of the ratios of the actual ground level concentration to the level established in ch. NR 666 Appendix V cannot exceed 1.0.

c. For constituents not listed in ch. NR 666 Appendix IV or V, 0.1 micrograms per cubic meter.

**c2d** WAIVER OF PARTICULAR MATTER STANDARD. The particulate matter standard of s. NR 666.105 does not apply if both of the following conditions are met:

cad The DRE standard is waived under sub. c1d.

cbd The owner or operator complies with the Tier I or adjusted Tier I metals feed rate screening limits provided by s. NR 666.106 c2d or c5d.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; corrections in c1d cbd 4. a. to c. made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

#### NR 666.110 Waiver of DRE trial burn for boilers.

Boilers that operate under the special requirements of this section, and that do not burn hazardous waste containing cor derived from EPA hazardous waste numbers F020, F021, F022, F023, F026 or F027, are considered to be in conformance with the DRE standard of s. NR 666.104 c1d, and a trial burn to demonstrate DRE is waived. When burning hazardous waste, all of the following apply:

**c1d** A minimum of 50% of fuel fired to the device shall be fossil fuel, fuels derived from fossil fuel, tall oil, or, if approved by the department on a case-by-case basis, other nonhazardous fuel with combustion characteristics comparable to fossil fuel. Such fuels are termed primary fuel for purposes of this section. cTall oil is a fuel derived from vegetable and rosin fatty acids.d The 50% primary fuel firing rate shall be determined on a total heat or mass input basis, whichever results in the greater mass feed rate of primary fuel fired.

**c2d** Boiler load may not be less than 40%. Boiler load is the ratio at any time of the total heat input to the maximum design heat input.

**c3d** Primary fuels and hazardous waste fuels shall have a minimum as-fired heating value of 8,000 Btu/lb, and each material fired in a burner where hazardous waste is fired shall have a heating value of at least 8,000 Btu/lb, as-fired.

**c4d** The device shall operate in conformance with the carbon monoxide standard provided by s. NR 666.104 c2d cad. Boilers subject to the waiver of the DRE trial burn provided by this section are not eligible for the alternative carbon monoxide standard provided by s. NR 666.104 c3d.

**c5d** The boiler shall be a watertube type boiler that does not feed fuel using a stoker or stoker type mechanism.

**c6d** The hazardous waste shall be fired directly into the primary fuel flame zone of the combustion chamber with an air or steam atomization firing system, mechanical atomization system, or a rotary cup atomization system under any of the following conditions:

cad *Viscosity.* The viscosity of the hazardous waste fuel as-fired may not exceed 300 SSU.

cbd *Particle size.* When a high pressure air or steam atomizer, low pressure atomizer or mechanical atomizer is used, 70% of the hazardous waste fuel shall pass through a 200 mesh c74 micrond screen, and when a rotary cup atomizer is used, 70% of the hazardous waste shall pass through a 100 mesh c150 micrond screen.

ccd *Mechanical atomization systems.* Fuel pressure within a mechanical atomization system and fuel flow rate shall be maintained within the design range taking into account the viscosity and volatility of the fuel.

cdd *Rotary cup atomization systems.* Fuel flow rate through a rotary cup atomization system shall be maintained within the design range taking into account the viscosity and volatility of the fuel.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.111 Standards for direct transfer. c1d** APPLICABILITY. The regulations in this section apply to owners and operators of boilers and industrial furnaces subject to s. NR 666.102 or 666.103 if hazardous waste is directly transferred from a transport vehicle to a boiler or industrial furnace without the use of a storage unit.

**c2d** DEFINITIONS. cad When used in this section, the following terms have the meanings given in subsd. 1. and 2.:

1. XDirect transfer equipmentY means any device including but not limited to, such devices as piping, fittings, flanges, valves and pumpsd that is used to distribute, meter or control the flow of hazardous waste between a container ci.e., transport vehicled and a boiler or industrial furnace.

2. XContainerY means any portable device in which hazardous waste is transported, stored, treated or otherwise handled, and includes transport vehicles that are containers themselves ce.g., tank trucks, tanker-trailers and rail tank carsd, and containers placed on or in a transport vehicle.

cbd This section references several requirements provided in subchs. I and J of chs. NR 664 and 665. For purposes of this section, the term tank systems in those referenced requirements means direct transfer equipment as defined in par. cad.

**c3d** GENERAL OPERATING REQUIREMENTS. cad No direct transfer of a pumpable hazardous waste shall be conducted from an open-top container to a boiler or industrial furnace.

cbd Direct transfer equipment used for pumpable hazardous waste shall always be closed, except when necessary to add or remove the waste, and may not be opened, handled or stored in a manner that may cause any rupture or leak.

ccd The direct transfer of hazardous waste to a boiler or industrial furnace shall be conducted so that it does not do any of the following:

1. Generate extreme heat or pressure, fire, explosion or violent reaction.

2. Produce uncontrolled toxic mists, fumes, dusts or gases in sufficient quantities to threaten human health.

3. Produce uncontrolled flammable fumes or gases in sufficient quantities to pose a risk of fire or explosions.

4. Damage the structural integrity of the container or direct transfer equipment containing the waste.

5. Adversely affect the capability of the boiler or industrial furnace to meet the standards provided by ss. NR 666.104 to 666.107.

6. Threaten human health or the environment.

**cdd** Hazardous waste may not be placed in direct transfer equipment, if it could cause the equipment or its secondary containment system to rupture, leak, corrode or otherwise fail.

**ced** The owner or operator of the facility shall use appropriate controls and practices to prevent spills and overflows from the direct transfer equipment or its secondary containment systems. These include, at a minimum, all of the following:

1. Spill prevention controls ce.g., check valves, dry discount couplingsd.

2. Automatic waste feed cutoff to use if a leak or spill occurs from the direct transfer equipment.

**c4d** AREAS WHERE DIRECT TRANSFER VEHICLES CCONTAINERSD ARE LOCATED. Applying the definition of container under this section, owners and operators shall comply with all of the following requirements:

**cad** The containment requirements of s. NR 664.0175.

**cbd** The use and management requirements of subch. I of ch. NR 665, except for ss. NR 665.0170 and 665.0174, and except that in lieu of the special requirements of s. NR 665.0176 for ignitable or reactive waste, the owner or operator may comply with the requirements for the maintenance of protective distances between the waste management area and any public ways, streets, alleys, or an adjacent property line that can be built upon as required in Tables 2-1 to 2-6 of the National Fire Protection Association[s cNFPAd XFlammable and Combustible Liquids Code, Y c1977 or 1981d, incorporated by reference in s. NR 660.11. The owner or operator shall obtain and keep on file at the facility a written certification by the local fire marshal that the installation meets the subject NFPA codes.

**ccd** The closure requirements of s. NR 664.0178.

**c5d** DIRECT TRANSFER EQUIPMENT. Direct transfer equipment shall meet all of the following requirements:

**cad** *Secondary containment.* Owners and operators shall comply with the secondary containment requirements of s. NR 665.0193, except for s. NR 665.0193 c1d, c4d, c5d and c9d as follows:

1. For all new direct transfer equipment, prior to their being put into service.

2. For existing direct transfer equipment within 2 years after August 21, 1991.

**cbd** *Requirements prior to meeting secondary containment requirements.* 1. For existing direct transfer equipment that does not have secondary containment, the owner or operator shall determine whether the equipment is leaking or is unfit for use. The owner or operator shall obtain and keep on file at the facility a written assessment reviewed and certified by a qualified, registered professional engineer in accordance with s. NR 670.011 that attests to the equipment[s integrity by August 21, 1992.

2. The assessment under subd. 1. shall determine whether the direct transfer equipment is adequately designed and has sufficient structural strength and compatibility with the wastes to be transferred to ensure that it will not collapse, rupture or fail. At a minimum, this assessment shall consider all of the following:

a. Design standards, if available, according to which the direct transfer equipment was constructed.

b. Hazardous characteristics of the wastes that have been or will be handled.

c. Existing corrosion protection measures.

d. Documented age of the equipment, if available cotherwise, an estimate of the aged.

e. Results of a leak test or other integrity examination such that the effects of temperature variations, vapor pockets, cracks, leaks, corrosion and erosion are accounted for.

3. If, as a result of the assessment specified above, the direct transfer equipment is found to be leaking or unfit for use, the owner or operator shall comply with s. NR 665.0196 c1d and c2d.

**ccd** *Inspections and recordkeeping.* 1. The owner or operator shall inspect at least once each operating hour when hazardous waste is being transferred from the transport vehicle ccontainerd to the boiler or industrial furnace all of the following:

a. Overfill or spill control equipment ce.g., waste-feed cutoff systems, bypass systems and drainage systemsd to ensure that it is in good working order.

b. The above ground portions of the direct transfer equipment to detect corrosion, erosion or releases of waste ce.g., wet spots, dead vegetationd.

c. Data gathered from monitoring equipment and leak-detection equipment, ce.g., pressure and temperature gaugesd to ensure that the direct transfer equipment is being operated according to its design.

2. The owner or operator shall inspect cathodic protection systems, if used, to ensure that they are functioning properly according to the schedule provided by s. NR 665.0195 c2d.

3. Records of inspections made under this paragraph shall be maintained in the operating record at the facility, and available for inspection for at least 3 years from the date of the inspection.

**cdd** *Design and installation of new ancillary equipment.* Owners and operators shall comply with s. NR 665.0192.

**ced** *Response to leaks or spills.* Owners and operators shall comply with s. NR 665.0196.

**cf** *Closure.* Owners and operators shall comply with s. NR 665.0197, except for s. NR 665.0197 c3d cbd to cdd.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.112 Regulation of residues.** A residue derived from the burning or processing of hazardous waste in a boiler or industrial furnace is not excluded from the definition of a hazardous waste under s. NR 661.0004 c2d cdd, cgd or chd unless the device and the owner or operator meet all of the following requirements:

**c1d** The device meets the following criteria:

**cad** *Boilers.* Boilers shall burn at least 50% coal on a total heat input or mass input basis, whichever results in the greater mass feed rate of coal.

**cbd** *Ore or mineral furnaces.* Industrial furnaces subject to s. NR 661.0004 c2d cgd shall process at least 50% by weight normal, nonhazardous raw materials.

**ccd** *Cement kilns.* Cement kilns shall process at least 50% by weight normal cement-production raw materials.

**c2d** The owner or operator demonstrates that the hazardous waste does not significantly affect the residue by demonstrating conformance with either of the following criteria:

**cad** *Comparison of waste-derived residue with normal residue.* The waste-derived residue may not contain ch. NR 661 Appendix VIII constituents ctoxic constituentsd that could reasonably be attributable to the hazardous waste at concentrations significantly higher than in residue generated without burning or processing of hazardous waste, using the following procedure. Toxic compounds that could reasonably be attributable to burning or processing the hazardous waste cconstituents of concernd include toxic constituents in the hazardous waste, and the organic compounds listed in ch. NR 661 Appendix VIII that may be gen-

erated as products of incomplete combustion. For polychlorinated dibenzo-p-dioxins and polychlorinated dibenzo-furans, analyses shall be performed to determine specific congeners and homologues, and the results converted to 2,3,7,8-TCDD equivalent values using the procedure specified in section 4.0 of ch. NR 666 Appendix IX.

1. ZNormal residue.[ Concentrations of toxic constituents of concern in normal residue shall be determined based on analyses of a minimum of 10 samples representing a minimum of 10 days of operation. Composite samples may be used to develop a sample for analysis if the compositing period does not exceed 24 hours. The upper tolerance limit at 95% confidence with a 95% proportion of the sample distribution of the concentration in the normal residue shall be considered the statistically-derived concentration in the normal residue. If changes in raw materials or fuels reduce the statistically-derived concentrations of the toxic constituents of concern in the normal residue, the statistically-derived concentrations shall be revised or statistically-derived concentrations of toxic constituents in normal residue shall be established for a new mode of operation with the new raw material or fuel. To determine the upper tolerance limit in the normal residue, the owner or operator shall use statistical procedures prescribed in XStatistical Methodology for Beville Residue Determinations Y in ch. NR 666 Appendix IX .

2. ZWaste-derived residue.[ Waste-derived residue shall be sampled and analyzed as often as necessary to determine whether the residue generated during each 24-hour period has concentrations of toxic constituents that are higher than the concentrations established for the normal residue under subd. 1. If so, hazardous waste burning has significantly affected the residue and the residue may not be excluded from the definition of a hazardous waste. Concentrations of toxic constituents of concern in the waste-derived residue shall be determined based on analysis of one or more samples obtained over a 24-hour period. Multiple samples may be analyzed, and multiple samples may be taken to form a composite sample for analysis if the sampling period does not exceed 24 hours. If more than one sample is analyzed to characterize waste-derived residues generated over a 24-hour period, the concentration of each toxic constituent shall be the arithmetic mean of the concentrations in the samples. No results may be disregarded.

cbd *Comparison of waste-derived residue concentrations with health-based limits.* 1. ZNonmetal constituents.[ The concentration of each nonmetal toxic constituent of concern specified in par. cad in the waste-derived residue may not exceed the health-based level specified in ch. NR 666 Appendix VII, or the level of detection, whichever is higher. If a health-based limit for a constituent of concern is not listed in ch. NR 666 Appendix VII, then a limit of 0.002 micrograms per kilogram or the level of detection which shall be determined using appropriate analytical methods, whichever is higher, shall be used. The levels specified in ch. NR 666 Appendix VII and the default level of 0.002 micrograms per kilogram or the level of detection for constituents as identified in Note 1 of ch. NR 666 Appendix VII are administratively stayed under the condition, for those constituents specified in par. cad, that the owner or operator complies with alternative levels defined as the land disposal restriction limits specified in s. NR 668.43 for F039 nonwastewaters. In complying with those alternative levels, if an owner or operator is unable to detect a constituent despite documenting use of best good-faith efforts as defined by applicable department guidance or standards, the owner or operator is deemed to be in compliance for that constituent. Until new guidance or standards are developed, the owner or operator may demonstrate such good faith efforts by

achieving a detection limit for the constituent that does not exceed an order of magnitude above the level provided by s. NR 668.43 for F039 nonwastewaters. In complying with the s. NR 668.43 F039 nonwastewater levels for polychlorinated dibenzo-p-dioxins and polychlorinated dibenzo-furans, analyses shall be performed for total hexachlorodibenzo-p-dioxins, total hexachlorodibenzofurans, total pentachlorodibenzo-p-dioxins, total pentachlorodibenzofurans, total tetrachlorodibenzo-p-dioxins and total tetrachlorodibenzofurans.

**Note:** The administrative stay, under the condition that the owner or operator complies with alternative levels defined as the land disposal restriction limits specified in s. NR 668.43 for F039 nonwastewaters, remains in effect until further administrative action is taken and notice is published in the federal register and the Code of Federal Regulations.

2. ZMetal constituents.[ The concentration of metals in an extract obtained using the toxicity characteristic leaching procedure of s. NR 661.0024 may not exceed the levels specified in ch. NR 666 Appendix VII.

3. ZSampling and analysis.[ Waste-derived residue shall be sampled and analyzed as often as necessary to determine whether the residue generated during each 24-hour period has concentrations of toxic constituents that are higher than the health-based levels. Concentrations of toxic constituents of concern in the waste-derived residue shall be determined based on analysis of one or more samples obtained over a 24-hour period. Multiple samples may be analyzed, and multiple samples may be taken to form a composite sample for analysis if the sampling period does not exceed 24 hours. If more than one sample is analyzed to characterize waste-derived residues generated over a 24-hour period, the concentration of each toxic constituent shall be the arithmetic mean of the concentrations in the samples. No results may be disregarded.

**c3d** Records sufficient to document compliance with this section shall be retained until closure of the boiler or industrial furnace unit. At a minimum, all of the following shall be recorded:

cad Levels of constituents in ch. NR 661 Appendix VIII that are present in waste-derived residues.

cbd If the waste-derived residue is compared with normal residue under sub. c2d cad, both of the following:

1. The levels of constituents in ch. NR 661 Appendix VIII that are present in normal residues.

2. Data and information, including analyses of samples as necessary, obtained to determine if changes in raw materials or fuels would reduce the concentration of toxic constituents of concern in the normal residue.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; corrections in c2d cad cintro.d. 1., c2d cbd 1., 2. made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687; CR 16-007: am. c2d cad cintro.d, cbd 1. Register July 2017 No. 739, eff. 8-1-17; CR 19-082: am. c1d cbd, c2d cbd 2. Register August 2020 No. 776, eff. 9-1-20; correction in c2d cbd 2. made under s. 35.17, Stats., Register August 2020 No. 776; correction in cintro.d made under s. 13.92 c4d cbd 7., Stats., Register April 2021 No. 784.

## Subchapter M — Military Munitions

**NR 666.200 Applicability.** c1d This subchapter identifies when military munitions become a solid waste, and, if these wastes are also hazardous under this subchapter or ch. NR 661, the management standards that apply to these wastes.

**c2d** Unless otherwise specified in this subchapter, all applicable requirements in chs. NR 660 to 670 apply to waste military munitions.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.201 Definitions.** The following definitions apply to this subchapter:



**c1d** XActive rangeY means a military range that is currently in service and is being regularly used for range activities.

**c2d** XChemical agent and munitionY means an agent or munition that, through its chemical properties, produces lethal or other damaging effects on human beings, except that the term does not include riot control agents, chemical herbicides, smoke and other obscuration materials.

**c3d** XDDESBY means the United States department of defense explosives safety board.

**c4d** XInactive rangeY means a military range that is not currently being used, but that is still under military control and considered by the military to be a potential range area, and that has not been put to a new use that is incompatible with range activities.

**c5d** XMilitaryY means the U.S. department of defense cDODd, U.S. armed services, U.S. coast guard, national guard, U.S. department of energy cDOEd, or other parties under contract or acting as an agent for any of them, who handle military munitions.

**c6d** XMilitary rangeY means designated land and water areas set aside, managed and used to conduct research on, develop, test and evaluate military munitions and explosives, other ordnance or weapon systems, or to train military personnel in their use and handling. Ranges include firing lines and positions, maneuver areas, firing lanes, test pads, detonation pads, impact areas and buffer zones with restricted access and exclusionary areas.

**c7d** XUnexploded ordnanceY or XUXOY means military munitions that have been primed, fused, armed or otherwise prepared for action, and have been fired, dropped, launched, projected or placed in such a manner as to constitute a hazard to operations, installation, personnel or material and remain unexploded either by malfunction, design or any other cause.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.202 Definition of solid waste. c1d** A military munition is not a solid waste when either of the following occurs:

cad It is used for its intended purpose, including any of the following:

1. Use in training military personnel or explosives and munitions emergency response specialists including training in proper destruction of unused propellant or other munitionsd.
2. Use in research, development, testing and evaluation of military munitions, weapons or weapon systems.
3. Recovery, collection and on-range destruction of unexploded ordnance and munitions fragments during range clearance activities at active or inactive ranges. However, Xuse for intended purposeY does not include the on-range disposal or burial of unexploded ordnance and contaminants when the burial is not a result of product use.

cbd It is an unused munition, or component thereof, which is being repaired, reused, recycled, reclaimed, disassembled, reconfigured or otherwise subjected to materials recovery activities, unless the activities involve use constituting disposal as defined in s. NR 661.0002 c3d cad, or burning for energy recovery as defined in s. NR 661.0002 c3d cbd.

**c2d** An unused military munition is a solid waste when any of the following occurs:

cad The munition is abandoned by being disposed of, burned, detonated cexcept during intended use as specified in sub. c1dd, incinerated or treated prior to disposal.

cbd The munition is removed from storage in a military magazine or other storage area for the purpose of being disposed of, burned, incinerated or treated prior to disposal.

ccd The munition is deteriorated or damaged ce.g., the integrity of the munition is compromised by cracks, leaks or other damaged to the point that it cannot be put into serviceable condition, and cannot reasonably be recycled or used for other purposes.

cdd The munition has been declared a solid waste by an authorized military official.

**c3d** A used or fired military munition is a solid waste when either of the following occurs:

cad When it is transported off range or from the site of use, where the site of use is not a range, for the purposes of storage, reclamation, treatment, disposal or treatment prior to disposal.

cbd If it is recovered, collected and then disposed of by burial, or landfilling either on or off a range.

**c4d** For purposes of s. 289.01 c33d, Stats., a used or fired military munition is a solid waste, and, therefore, is potentially subject to corrective action authorities under ss. 291.37, 291.95 and 291.97, Stats., 42 USC 6924 cud and cvd and 6928 chd, and subch. S of ch. NR 664, or imminent danger authorities under s. 291.85, Stats., or 42 USC 6973 cad, if the munition lands off-range and is not promptly rendered safe or retrieved. Any imminent danger threats associated with any remaining material shall be addressed. If remedial action is infeasible, the operator of the range shall maintain a record of the event for as long as any threat remains. The record shall include the type of munition and its location to the extent the location is known.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d cbd, c4d Register August 2020 No. 776, eff. 9-1-20.

**NR 666.203 Standards applicable to the transportation of solid waste military munitions. c1d** CRITERIA FOR HAZARDOUS WASTE REGULATION OF WASTE NON-CHEMICAL MILITARY MUNITIONS IN TRANSPORTATION. cad Waste military munitions that are being transported and that exhibit a hazardous waste characteristic or are listed as hazardous waste under ch. NR 661, are subject to chs. NR 660 to 670, unless all the following conditions are met:

1. The waste military munitions are not chemical agents or chemical munitions.
2. The waste military munitions are transported in accordance with the U.S. department of defense shipping controls applicable to the transport of military munitions.
3. The waste military munitions are transported from a military owned or operated installation to a military owned or operated treatment, storage or disposal facility.
4. The transporter of the waste provides oral notice to the department within 24 hours from the time the transporter becomes aware of any loss or theft of the waste military munitions, or any failure to meet a condition of this paragraph that may endanger health or the environment. In addition, a written submission describing the circumstances shall be provided within 5 days from the time the transporter becomes aware of any loss or theft of the waste military munitions or any failure to meet a condition of this paragraph.

cbd If any waste military munitions shipped under par. cad are not received by the receiving facility within 45 days of the day the waste was shipped, the owner or operator of the receiving facility shall report this non-receipt to the department within 5 days.

ccd The exemption in par. cad from regulation as hazardous waste shall apply only to the transportation of non-chemical waste military munitions. It does not affect the regulatory status of waste military munitions as hazardous wastes with regard to storage, treatment or disposal.



cdd The conditional exemption in par. cad applies only so long as all of the conditions in par. cad are met.

**c2d REINSTATEMENT OF EXEMPTION.** If any waste military munition loses its exemption under sub. c1d cad, an application may be filed with the department for reinstatement of the exemption from hazardous waste transportation regulation with respect to the munition as soon as the munition is returned to compliance with the conditions of sub. c1d cad. If the department finds that reinstatement of the exemption is appropriate based on factors such as the transporter[s] provision of a satisfactory explanation of the circumstances of the violation, or a demonstration that the violations are not likely to recur, the department may reinstate the exemption under sub. c1d cad. If the department does not take action on the reinstatement application within 60 days after receipt of the application, then reinstatement shall be deemed granted, retroactive to the date of the application. However, the department may terminate a conditional exemption reinstated by default in the preceding sentence if the department finds that reinstatement is inappropriate based on factors such as the transporter[s] failure to provide a satisfactory explanation of the circumstances of the violation, or failure to demonstrate that the violations are not likely to recur. In reinstating the exemption under sub. c1d cad, the department may specify additional conditions as are necessary to ensure and document proper transportation to protect human health and the environment.

**c3d AMENDMENTS TO DOD SHIPPING CONTROLS.** The U.S. department of defense shipping controls applicable to the transport of military munitions referenced in sub. c1d cad 2. are U.S. government bill of lading cGBLd c U.S. government services administration cGSA standard form 1103d, DOD single line item requisition system document cmanuald cDD form 1348d, the signature and tally record cDD form 1907d, dangerous goods shipping paper{declaration and emergency response information for hazardous materials transported by government vehicles{containers or vessel cDD form 836d, and the motor vehicle inspection ctransporting hazardous materialsd cDD form 626d in effect on November 8, 1995, except as provided in the following sentence. Any amendments to the U.S. department of defense shipping controls shall become effective for purposes of sub. c1d cad on the date the U.S. department of defense publishes notice in the federal register that the shipping controls referenced in sub. c1d cad 2. have been amended.

**Note:** GSA standard form 1103 may be obtained by calling federal supply customer assistance at c817d 978-2051. DD forms 626, 836, 1348 and 1907 may be obtained at: <http://www.dtic.mil/whs/directives/infomgt/forms/formsprogram.htm>.

**History:** CR 05-032; cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.204 Standards applicable to emergency responses.** Explosives and munitions emergencies involving military munitions or explosives are subject to ss. NR 662.010 c9d, 663.10 c5d, 664.0001 c7d chd, 665.0001 c3d ckd and 670.001 c3d ccd, or alternatively to s. NR 670.061.

**History:** CR 05-032; cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.205 Standards applicable to the storage of solid waste military munitions.** c1d CRITERIA FOR HAZARDOUS WASTE REGULATION OF WASTE NON-CHEMICAL MILITARY MUNITIONS IN STORAGE. cad Waste military munitions in storage that exhibit a hazardous waste characteristic or are listed as hazardous waste under ch. NR 661, are subject to chs. NR 660 to 679, unless all the following conditions are met:

1. The waste military munitions are not chemical agents or chemical munitions.
2. The waste military munitions are subject to the jurisdiction of the DDESB.
3. The waste military munitions are stored in accordance

with the DDESB storage standards applicable to waste military munitions.

4. Within 90 days of August 12, 1997 or within 90 days of when a storage unit is first used to store waste military munitions, whichever is later, the owner or operator notifies the department of the location of any waste storage unit used to store waste military munitions for which the conditional exemption in this paragraph is claimed.

5. The owner or operator provides oral notice to the department within 24 hours from the time the owner or operator becomes aware of any loss or theft of the waste military munitions, or any failure to meet a condition of this paragraph that may endanger health or the environment. In addition, a written submission describing the circumstances shall be provided within 5 days from the time the owner or operator becomes aware of any loss or theft of the waste military munitions or any failure to meet a condition of this paragraph.

6. The owner or operator inventories the waste military munitions at least annually, inspects the waste military munitions at least quarterly for compliance with the conditions of this paragraph and maintains records of the findings of these inventories and inspections for at least 3 years.

7. Access to the stored waste military munitions is limited to appropriately trained and authorized personnel.

cdb The conditional exemption in par. cad from regulation as hazardous waste shall apply only to the storage of non-chemical waste military munitions. It does not affect the regulatory status of waste military munitions as hazardous wastes with regard to transportation, treatment or disposal.

ccd The conditional exemption in par. cad applies only so long as all of the conditions in par. cad are met.

**c2d NOTICE OF TERMINATION OF WASTE STORAGE.** The owner or operator shall notify the department when a storage unit identified in sub. c1d cad 4. will no longer be used to store waste military munitions.

**c3d REINSTATEMENT OF CONDITIONAL EXEMPTION.** If any waste military munition loses its conditional exemption under sub. c1d cad, an application may be filed with the department for reinstatement of the conditional exemption from hazardous waste storage regulation with respect to the munition as soon as the munition is returned to compliance with the conditions of sub. c1d cad. If the department finds that reinstatement of the conditional exemption is appropriate based on factors such as the owner[s] or operator[s] provision of a satisfactory explanation of the circumstances of the violation, or a demonstration that the violations are not likely to recur, the department may reinstate the conditional exemption under sub. c1d cad. If the department does not take action on the reinstatement application within 60 days after receipt of the application, then reinstatement shall be deemed granted, retroactive to the date of the application. However, the department may terminate a conditional exemption reinstated by default in the preceding sentence if it finds that reinstatement is inappropriate based on factors such as the owner[s] or operator[s] failure to provide a satisfactory explanation of the circumstances of the violation, or failure to demonstrate that the violations are not likely to recur. In reinstating the conditional exemption under sub. c1d cad, the department may specify additional conditions as are necessary to ensure and document proper storage to protect human health and the environment.

**c4d WASTE CHEMICAL MUNITIONS.** cad Waste military munitions that are chemical agents or chemical munitions and that exhibit a hazardous waste characteristic or are listed as hazardous waste under ch. NR 661, are subject to chs. NR 660 to 670.

cdb Waste military munitions that are chemical agents or

chemical munitions and that exhibit a hazardous waste characteristic or are listed as hazardous waste under ch. NR 661, are not subject to the storage prohibition in s. NR 668.50.

**c5d** AMENDMENTS TO DDESB STORAGE STANDARDS. The DDESB storage standards applicable to waste military munitions, referenced in sub. c1d cad 3., are DOD 6055.9-STD cY-DOD Ammunition and Explosives Safety StandardsYd, incorporated by reference in s. NR 660.11, except as provided in the following sentence. Any amendments to the DDESB storage standards shall become effective for purposes of sub. c1d cad on the date the U.S. department of defense publishes notice in the federal register that the DDESB standards referenced in sub. c1d cad have been amended.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c1d cad 4. Register July 2017 No. 739, eff. 8-1-17.

**NR 666.206 Standards applicable to the treatment and disposal of waste military munitions.** The treatment and disposal of hazardous waste military munitions are subject to the applicable permitting, procedural and technical standards in chs. NR 660 to 670.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

### Subchapter N — Conditional Exemption for Low-Level Mixed Waste Storage, Treatment, Transportation and Disposal

#### TERMS

**NR 666.210 What definitions apply to this subchapter?** In this subchapter:

**c1d** XAgreement stateY means a state that has entered into an agreement with the NRC under 42 USC 2021cbd, to assume responsibility for regulating within its borders byproduct, source or special nuclear material in quantities not sufficient to form a critical mass.

**c2d** XCertified deliveryY means certified mail with return receipt requested, or equivalent courier service, or other means, which provides the sender with a receipt confirming delivery.

**c3d** XEligible naturally occurring or accelerator-produced radioactive materialY or Xeligible NARMY is NARM that is eligible for the transportation and disposal conditional exemption. It is a NARM waste that contains hazardous waste, meets the waste acceptance criteria of, and is allowed by state NARM rules to be disposed of at a low-level radioactive waste disposal facility licensed according to 10 CFR part 61 or NRC agreement state equivalent rules.

**c4d** XExempted wasteY means a waste that meets the eligibility criteria in s. NR 666.225 and meets all of the conditions in s. NR 666.230, or meets the eligibility criteria in s. NR 666.310 and complies with all of the conditions in s. NR 666.315. That waste is conditionally exempted from the regulatory definition of hazardous waste described in s. NR 661.0003.

**c5d** XHazardous wasteY means any material which is defined to be hazardous waste in accordance with s. NR 661.0003.

**c6d** XLand disposal restriction treatment standardsY or XLDR treatment standardsY means treatment standards under ch. NR 668, which a hazardous waste must meet before it can be disposed of in a hazardous waste land disposal unit.

**c7d** XLicenseY means a license issued by the nuclear regulatory commission, or NRC agreement state, to users that manage radionuclides regulated by NRC, or NRC agreement states, under authority of 42 USC 2011 to 2297.

**c8d** XLow-level mixed wasteY or XLLMWY is a waste that contains both low-level radioactive waste and hazardous waste.

**c9d** XLow-level radioactive wasteY or XLLRWY is a radioactive waste which contains source, special nuclear or byproduct material, and which is not classified as high-level radioactive waste, transuranic waste, spent nuclear fuel or byproduct material as defined in 42 USC 2014cedc2d. cSee also NRC definition of YwasteY at 10 CFR 61.2d

**c10d** XMixed wasteY means a waste that contains both hazardous waste and source, special nuclear or byproduct material subject to 42 USC 2011 to 2297.

**c11d** XNaturally occurring or accelerator-produced radioactive materialY or XNARMY means radioactive materials that are either of the following:

cad Naturally occurring and not source, special nuclear or byproduct materials cas defined by 42 USC 2011 to 2297d.

cbd Produced by an accelerator. NARM is regulated by the states under state law, or by the U.S. department of energy cDOEd cas authorized by 42 USC 2011 to 2297d under DOE orders.

**c12d** XNRCY means the U.S. nuclear regulatory commission.

**c13d** XWe or usY within this subchapter, means the department as defined in s. NR 660.10.

**c14d** XYouY means a generator, treater or other handler of low-level mixed waste or eligible NARM.

**Note:** The U.S. code cUSCd cite is also known as the Atomic Energy Act of 1954, as amended.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c4d, c5d Register August 2020 No. 776, eff. 9-1-20.

#### STORAGE AND TREATMENT CONDITIONAL EXEMPTION AND ELIGIBILITY

**NR 666.220 What does a storage and treatment conditional exemption do?** The storage and treatment conditional exemption exempts your low-level mixed waste from the regulatory definition of hazardous waste in s. NR 661.0003 if your waste meets the eligibility criteria in s. NR 666.225 and you meet the conditions in s. NR 666.230.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.225 What wastes are eligible for the storage and treatment conditional exemption?** Low-level mixed waste cLLMWd, defined in s. NR 666.210, is eligible for this conditional exemption if it is generated and managed by you under a single NRC or NRC agreement state license. cMixed waste generated at a facility with a different license number and shipped to your facility for storage or treatment requires a hazardous waste operating license and is ineligible for this exemption. In addition, NARM waste is ineligible for this exemption.d

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.230 What conditions must you meet for your LLMW to qualify for and maintain a storage and treatment exemption?** **c1d** For your LLMW to qualify for the exemption you shall notify us in writing by certified delivery that you are claiming a conditional exemption for the LLMW stored on your facility. The dated notification shall include your name, address, EPA hazardous waste identification number, NRC or NRC agreement state license number, the hazardous waste codes and storage units for which you are seeking an exemption and a statement that you meet the conditions of this subchapter. Your notification shall be signed by your authorized representative who certifies that the information in the notification is true, accurate and complete. You shall notify us of your claim either

within 90 days of August 1, 2006, or within 90 days of when a storage unit is first used to store conditionally exempt LLMW.

**c2d** To qualify for and maintain an exemption for your LLMW you shall do all of the following:

**cad** Store your LLMW waste in tanks or containers in compliance with the requirements of your NRC or NRC agreement state license that apply to the proper storage of low-level radioactive waste cnot including those license requirements that relate solely to recordkeepingd.

**cbd** Store your LLMW in tanks or containers in compliance with chemical compatibility requirements of a tank or container in s. [NR 664.0177](#) or [664.0199](#), or s. [NR 665.0177](#) or [665.0199](#).

**ccd** Certify that facility personnel who manage stored conditionally exempt LLMW are trained in a manner that ensures that the conditionally exempt waste is safely managed and includes training in chemical waste management and hazardous materials incidents response that meets the personnel training standards found in s. [NR 665.0016 c1d ccd](#).

**cdd** Conduct an inventory of your stored conditionally exempt LLMW at least annually and inspect it at least quarterly for compliance with this subchapter.

**ced** Maintain an accurate emergency plan and provide it to all local authorities who may have to respond to a fire, explosion or release of hazardous waste or hazardous constituents. Your plan shall describe emergency response arrangements with local authorities; describe evacuation plans; list the names, addresses and telephone numbers of all facility personnel qualified to work with local authorities as emergency coordinators and list emergency equipment.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### TREATMENT

**NR 666.235 What waste treatment does the storage and treatment conditional exemption allow?** You may treat your low-level mixed waste at your facility within a tank or container in accordance with the terms of your NRC or NRC agreement state license. Treatment that cannot be done in a tank or container without a hazardous waste operating license csuch as incinerationd is not allowed under this exemption.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### LOSS OF CONDITIONAL EXEMPTION

**NR 666.240 How could you lose the conditional exemption for your LLMW and what action must you take? c1d** Your LLMW will automatically lose the storage and treatment conditional exemption if you fail to meet any of the conditions specified in s. [NR 666.230](#). When your LLMW loses the exemption, you shall immediately manage that waste which failed the condition as hazardous waste under chs. [NR 660](#) to [670](#), and the storage unit storing the LLMW immediately becomes subject to hazardous waste container or tank storage requirements under subch. I of ch. [NR 664](#) or subch. J of ch. [NR 664](#).

**cad** If you fail to meet any of the conditions specified in s. [NR 666.230](#) you shall report to us and the NRC, or the oversight agency in the NRC agreement state, in writing by certified delivery within 30 days of learning of the failure. Your report shall be signed by your authorized representative certifying that the information provided is true, accurate and complete. This report shall include all of the following:

1. The specific conditions you failed to meet.
2. A description of the LLMW cincluding the waste name, hazardous waste codes and quantityd and storage location at the facility.

3. The dates on which you failed to meet the condition.

**cbd** If the failure to meet any of the conditions may endanger human health or the environment, you shall also immediately notify us orally within 24 hours and follow up with a written notification within 5 days. Failures that may endanger human health or the environment include, but are not limited to, discharge of a CERCLA reportable quantity or other leaking or exploding tanks or containers, or detection of radionuclides above background or hazardous constituents in the leachate collection system of a storage area. If the failure may endanger human health or the environment, you shall follow the provisions of your emergency plan.

**c2d** We may terminate your conditional exemption for your LLMW, or require you to meet additional conditions to claim a conditional exemption, for serious or repeated noncompliance with any requirements of this subchapter.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; correction in c1d made under s. 13.92 c4d cbd 7., Stats., Register March 2013 No. 687.

**NR 666.245 If you lose the storage and treatment conditional exemption for your LLMW, can the exemption be reclaimed? c1d** You may reclaim the storage and treatment exemption for your LLMW if you do all of the following:

**cad** Again meet the conditions specified in s. [NR 666.230](#).

**cbd** Send us a notice by certified delivery that you are reclaiming the exemption for your LLMW. Your notice shall be signed by your authorized representative certifying that the information contained in your notice is true, complete and accurate. In your notice you shall do all of the following:

1. Explain the circumstances of each failure.
2. Certify that you have corrected each failure that caused you to lose the exemption for your LLMW and that you again meet all the conditions as of the date you specify.
3. Describe plans that you have implemented, listing specific steps you have taken, to ensure the conditions will be met in the future.
4. Include any other information you want us to consider when we review your notice reclaiming the exemption.

**c2d** We may terminate a reclaimed conditional exemption if we find that your claim is inappropriate based on factors including, but not limited to, your failure to correct the problem, to provide a satisfactory explanation of the circumstances of the failure or to implement a plan with steps to prevent another failure to meet the conditions of s. [NR 666.230](#). In reviewing a reclaimed conditional exemption under this section, we may add conditions to the exemption to ensure that waste management during storage and treatment of the LLMW will protect human health and the environment.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### STORAGE AND TREATMENT RECORDKEEPING

**NR 666.250 What storage and treatment records must you keep at your facility and for how long? c1d** In addition to those records required by your NRC or NRC agreement state license, you shall keep all of the following records:

**cad** Your initial notification records, return receipts, reports to us of failures to meet the exemption conditions and all records supporting any reclaim of an exemption.

**cbd** Records of your LLMW annual inventories, and quarterly inspections.

**ccd** Your certification that facility personnel who manage stored mixed waste are trained in safe management of LLMW including training in chemical waste management and hazardous materials incidents response.



cdd Your emergency plan as specified in s. NR 666.230 c2d.

**c2d** You shall maintain records concerning notification, personnel trained and your emergency plan for as long as you claim this exemption and for 3 years thereafter, or according to NRC regulations under 10 CFR part 20 cor equivalent NRC agreement state rulesd, whichever is longer. You shall maintain records concerning your annual inventory and quarterly inspections for 3 years after the waste is sent for disposal, or according to NRC regulations under 10 CFR part 20 cor equivalent NRC agreement state rulesd, whichever is longer.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### REENTRY INTO HAZARDOUS WASTE REGULATION

#### NR 666.255 When is your LLMW no longer eligible for the storage and treatment conditional exemption?

**c1d** When your LLMW has met the requirements of your NRC or NRC agreement state license for decay-in-storage and can be disposed of as non-radioactive waste, then the conditional exemption for storage no longer applies. On that date your waste is subject to hazardous waste regulation under the relevant sections of chs. NR 660 to 670, and the time period for accumulation of a hazardous waste as specified in s. NR 662.016 or 662.017 begins.

**c2d** When your conditionally exempt LLMW, which has been generated and stored under a single NRC or NRC agreement state license number, is removed from storage, it is no longer eligible for the storage and treatment exemption. However, your waste may be eligible for the transportation and disposal conditional exemption at s. NR 666.305.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c1d Register August 2020 No. 776, eff. 9-1-20.

#### STORAGE UNIT CLOSURE

#### NR 666.260 Do closure requirements apply to units that stored LLMW prior to the effective date of this subchapter?

Interim licensed and operating licensed hazardous waste storage units that have been used to store only LLMW prior to August 1, 2006 and, after that date, store only LLMW which becomes exempt under this subchapter, are not subject to the closure requirements of chs. NR 664 and 665. Storage units cor portions of unitsd that have been used to store both LLMW and non-mixed hazardous waste prior to August 1, 2006 or are used to store both after that date remain subject to closure requirements with respect to the non-mixed hazardous waste.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### TRANSPORTATION AND DISPOSAL CONDITIONAL EXEMPTION

**NR 666.305 What does the transportation and disposal conditional exemption do?** This conditional exemption exempts your waste from the regulatory definition of hazardous waste in s. NR 661.0003 if your waste meets the eligibility criteria under s. NR 666.310, and you meet the conditions in s. NR 666.315.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. Register August 2020 No. 776, eff. 9-1-20.

#### ELIGIBILITY

**NR 666.310 What wastes are eligible for the transportation and disposal conditional exemption?** Eligible waste shall be either of the following:

**c1d** A low-level mixed waste cLLMWd, as defined in s. NR 666.210, that meets the waste acceptance criteria of a LLRW disposal facility.

**c2d** An eligible NARM waste, defined in s. NR 666.210.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### CONDITIONS

**NR 666.315 What are the conditions you must meet for your waste to qualify for and maintain the transportation and disposal conditional exemption?** You shall meet all of the following conditions for your eligible waste to qualify for and maintain the exemption:

**c1d** The eligible waste shall meet or be treated to meet LDR treatment standards as described in s. NR 666.320.

**c2d** If you are not already subject to NRC, or NRC agreement state equivalent manifest and transportation rules for the shipment of your waste, you shall manifest and transport your waste according to NRC regulations as described in s. NR 666.325.

**c3d** The exempted waste shall be in containers when it is disposed of in the LLRW disposal facility as described in s. NR 666.340.

**c4d** The exempted waste shall be disposed of at a designated LLRW disposal facility as described in s. NR 666.335.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.320 What treatment standards must your eligible waste meet?** Your LLMW or eligible NARM waste shall meet the land disposal restriction cLDRd treatment standards specified in subch. D of ch. NR 668.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.325 Are you subject to the manifest and transportation condition in s. NR 666.315 c2d?** If you are not already subject to NRC, or NRC agreement state equivalent manifest and transportation rules for the shipment of your waste, you shall meet the manifest requirements under 10 CFR 20.2006 cor NRC agreement state equivalent rulesd, and the transportation requirements under 10 CFR 1.5 cor NRC agreement state equivalent rulesd to ship the exempted waste.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.330 When does the transportation and disposal exemption take effect?** The exemption becomes effective once all the following have occurred:

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**c1d** Your eligible waste meets the applicable LDR treatment standards.

**c2d** You have received return receipts that you have notified us and the LLRW disposal facility as described in s. NR 666.345.

**c3d** You have completed the packaging and preparation for shipment requirements for your waste according to NRC packaging and transportation regulations found under 10 CFR part 71 cor NRC agreement state equivalent rulesd; and you have prepared a manifest for your waste according to NRC manifest regulations found under 10 CFR part 20 cor NRC agreement state equivalent rulesd.

**c4d** You have placed your waste on a transportation vehicle destined for a LLRW disposal facility licensed by NRC or an NRC agreement state.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.335 Where must your exempted waste be disposed of?** Your exempted waste shall be disposed of in a LLRW disposal facility that is regulated and licensed by NRC under 10 CFR part 61 or by an NRC agreement state under equivalent state rules, including state NARM licensing rules for eligible NARM.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.340 What type of container must be used for disposal of exempted waste?** Your exempted waste



shall be placed in containers before it is disposed. The container shall be any of the following:

**c1d** A carbon steel drum.

**c2d** An alternative container with equivalent containment performance in the disposal environment as a carbon steel drum.

**c3d** A high integrity container as defined by NRC.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### NOTIFICATION

**NR 666.345 Whom must you notify? c1d** You shall provide a one-time notice to us stating that you are claiming the transportation and disposal conditional exemption prior to the initial shipment of an exempted waste from your facility to a LLRW disposal facility. Your dated written notice shall include your facility name, address, phone number and EPA ID number, and be sent by certified delivery.

**c2d** You shall notify the LLRW disposal facility receiving your exempted waste by certified delivery before shipment of each exempted waste. You may only ship the exempted waste after you have received the return receipt of your notice to the LLRW disposal facility. This notification shall include all of the following:

**cad** A statement that you have claimed the exemption for the waste.

**cbd** A statement that the eligible waste meets applicable LDR treatment standards.

**ccd** Your facility[s] name, address and EPA hazardous waste ID number.

**cdd** The hazardous waste codes prior to the exemption of the waste streams.

**ced** A statement that the exempted waste shall be placed in a container according to s. NR 666.340 prior to disposal in order for the waste to remain exempt under the transportation and disposal conditional exemption of this subchapter.

**cfid** The manifest number of the shipment that will contain the exempted waste.

**cgd** A certification that all the information provided is true, complete and accurate. Your authorized representative shall sign the statement.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### GENERAL, TRANSPORTATION AND DISPOSAL RECORDKEEPING

**NR 666.350 What general, transportation and disposal records must you keep at your facility and for how long?** In addition to those records required by your NRC or NRC agreement state license, you shall keep records according to all of the following:

**c1d** You shall follow the applicable existing recordkeeping requirements under ss. NR 664.0073, 665.0073 and 668.07 to demonstrate that your waste has met LDR treatment standards prior to your claiming the exemption.

**c2d** You shall keep a copy of all notifications and return receipts required under ss. NR 666.355 and 666.360 for 3 years after the exempted waste is sent for disposal.

**c3d** You shall keep a copy of all notifications and return receipts required under s. NR 666.345 c1d for 3 years after the last exempted waste is sent for disposal.

**c4d** You shall keep a copy of the notification and return receipt required under s. NR 666.345 c2d for 3 years after the exempted waste is sent for disposal.

**c5d** If you are not already subject to NRC, or NRC agreement

state equivalent manifest and transportation rules for the shipment of your waste, you shall also keep all other documents related to tracking the exempted waste as required under 10 CFR 20.2006 or NRC agreement state equivalent rules, including applicable NARM requirements, in addition to the records specified in subs. c1d to c4d.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

#### LOSS OF TRANSPORTATION AND DISPOSAL CONDITIONAL EXEMPTION

**NR 666.355 How could you lose the transportation and disposal conditional exemption for your waste and what actions must you take? c1d** Any waste will automatically lose the transportation and disposal exemption if you fail to manage it in accordance with all of the conditions specified in s. NR 666.315.

**cad** When you fail to meet any of the conditions specified in s. NR 666.315 for any of your wastes, you shall report to us, in writing by certified delivery, within 30 days of learning of the failure. Your report shall be signed by your authorized representative certifying that the information provided is true, accurate and complete. This report shall include all of the following:

1. The specific conditions that you failed to meet for the waste.
2. A description of the waste including the waste name, hazardous waste codes and quantity that lost the exemption.
3. The dates on which you failed to meet the conditions for the waste.

**cbd** If the failure to meet any of the conditions may endanger human health or the environment, you shall also immediately notify us orally within 24 hours and follow up with a written notification within 5 days.

**c2d** We may terminate your ability to claim a conditional exemption for your waste, or require you to meet additional conditions to claim a conditional exemption, for serious or repeated noncompliance with any requirements of this subchapter.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.360 If you lose the transportation and disposal conditional exemption for a waste, can the exemption be reclaimed? c1d** You may reclaim the transportation and disposal exemption for a waste after you have received a return receipt confirming that we have received your notification of the loss of the exemption specified in s. NR 666.355 c1d if both of the following apply:

**cad** You again meet the conditions specified in s. NR 666.315 for the waste.

**cbd** You send a notice, by certified delivery, to us that you are reclaiming the exemption for the waste. Your notice shall be signed by your authorized representative certifying that the information provided is true, accurate and complete. The notice shall do all of the following:

1. Explain the circumstances of each failure.
2. Certify that each failure that caused you to lose the exemption for the waste has been corrected and that you again meet all conditions for the waste as of the date you specify.
3. Describe plans you have implemented, listing the specific steps that you have taken, to ensure that conditions will be met in the future.
4. Include any other information you want us to consider when we review your notice reclaiming the exemption.

**c2d** We may terminate a reclaimed conditional exemption if we find that your claim is inappropriate based on factors including, but not limited to, your failure to correct the problem, to pro-

vide a satisfactory explanation of the circumstances of the failure or to implement a plan with steps to prevent another failure to meet the conditions of s. NR 666.315. In reviewing a reclaimed conditional exemption under this section, we may add conditions to the exemption to ensure that transportation and disposal activities will protect human health and the environment.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

### Subchapter P—Hazardous Waste Pharmaceuticals

**NR 666.500 Definitions.** The following definitions apply to this subchapter:

**c1d** XEvaluated hazardous waste pharmaceuticalY means a prescription hazardous waste pharmaceutical that has been evaluated by a reverse distributor in accordance with s. NR 666.510 c1d ccd and will not be sent to another reverse distributor for further evaluation or verification of manufacture credit.

**c2d** XHazardous waste pharmaceuticalY means a pharmaceutical that is a solid waste, as defined in s. NR 661.0002, and exhibits one or more characteristics identified in subch. C of ch. NR 661 or is listed in subch. D of ch. NR 661. A pharmaceutical is not a solid waste, as defined in s. NR 661.0002, and therefore not a hazardous waste pharmaceutical, if it is legitimately used, reused, for example lawfully donated for its intended purpose, or reclaimed. An over-the-counter pharmaceutical, dietary supplement, or homeopathic drug is not a solid waste, as defined in s. NR 661.0002, and therefore not a hazardous waste pharmaceutical, if it has a reasonable expectation of being legitimately used, reused, for example lawfully redistributed for its intended purpose, or reclaimed.

**c3d** XHealthcare facilityY means any person that is lawfully authorized to do any of the following:

cad Provide preventative, diagnostic, therapeutic, rehabilitative, maintenance or palliative care, and counseling, service, assessment or procedure with respect to the physical or mental condition, or functional status, of a human or animal or that affects the structure or function of the human or animal body.

cbd Distribute, sell, or dispense pharmaceuticals, including over-the-counter pharmaceuticals, dietary supplements, homeopathic drugs, or prescription pharmaceuticals. Including wholesale distribution, third-party logistics that serve as forward distributors, military medical logistics facilities, hospitals, psychiatric hospitals, ambulatory surgical centers, health clinics, physicians[ offices, optical and dental providers, chiropractors, long-term care facilities, ambulance services, pharmacies, long-term care pharmacies, mail-order pharmacies, retailers of pharmaceuticals, veterinary clinics, and veterinary hospitals. This definition does not include pharmaceutical manufacturers, reverse distributors, or reverse logistics centers.

**c4d** XHousehold waste pharmaceuticalY means a pharmaceutical that is a solid waste, as defined in s. NR 661.0002, but is excluded from being a hazardous waste under s. NR 661.0004 c2d cad.

**c5d** XLong-term care facilityY means a licensed entity that provides assistance with activities of daily living, including managing and administering pharmaceuticals to one or more individuals at the facility. This definition includes hospice facilities, nursing facilities, skilled nursing facilities, and the nursing and skilled nursing care portions of continuing care retirement communities. Not included within the scope of this definition are group homes, independent living communities, assisted living facilities, and the independent and assisted living portions of continuing care retirement communities.

**c6d** XNon-creditable hazardous waste pharmaceuticalY means a prescription hazardous waste pharmaceutical that does

not have a reasonable expectation to be eligible for manufacturer credit or a nonprescription hazardous waste pharmaceutical that does not have a reasonable expectation to be legitimately used, reused, or reclaimed. This includes investigational drugs, free samples of pharmaceuticals received by healthcare facilities, residues of pharmaceuticals remaining in empty containers, contaminated personal protective equipment, floor sweepings, and clean-up material from the spills of pharmaceuticals.

**c7d** XNon-hazardous waste pharmaceuticalY means a pharmaceutical that is a solid waste, as defined in s. NR 661.0002, and is not listed in subch. D of ch. NR 661, and does not exhibit a characteristic identified in subch. C of ch. NR 661.

**c8d** XNon-pharmaceutical hazardous wasteY means a solid waste, as defined in s. NR 661.0002, that is listed in subch. D of ch. NR 661, or exhibits one or more characteristics identified in subch. C of ch. NR 661, but is not a pharmaceutical, as defined in this section.

**c9d** XPharmaceuticalY means any drug or dietary supplement for use by humans or other animals; any electronic nicotine delivery system, for example electronic cigarette or vaping pen; or any liquid nicotine, or e-liquid, packaged for retail sale for use in electronic nicotine delivery systems, such pre-filled cartridges or vials. This definition includes dietary supplements, as defined by the federal food, drug and cosmetic act; prescription drugs, as defined by 21 CFR 203.3 cyd; over-the-counter drugs; homeopathic drugs; compounded drugs; investigational new drugs; pharmaceuticals remaining in non-empty containers; personal protective equipment contaminated with pharmaceuticals; and clean-up material from spills of pharmaceuticals. This definition does not include dental amalgam or sharps.

**c10d** XPotentially creditable hazardous waste pharmaceuticalY means a prescription hazardous waste pharmaceutical that is all of the following:

cad Has a reasonable expectation to receive manufacturer credit.

cbd Is in original manufacturer packaging, except pharmaceuticals that were subject to a recall.

ccd Is undispensed.

cdd Is unexpired or less than one year past expiration date.

ced The term does not include evaluated hazardous waste pharmaceuticals or nonprescription pharmaceuticals including over-the-counter drugs, homeopathic drugs, and dietary supplements.

**c11d** XReverse distributorY means any person that receives and accumulates prescription pharmaceuticals that are potentially creditable hazardous waste pharmaceuticals for the purpose of facilitating or verifying manufacturer credit. Any person, including forward distributors, third-party logistics providers, and pharmaceutical manufacturers, that processes prescription pharmaceuticals for the facilitation or verification of manufacturer credit is considered a reverse distributor.

**History:** CR 19-082: cr. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.501 Applicability.** **c1d** A healthcare facility that is a very small quantity generator when counting all of its hazardous waste, including both its hazardous waste pharmaceuticals and its non-pharmaceutical hazardous waste, remains subject to s. NR 662.014 and is not subject to this subchapter, except for ss. NR 666.505 and NR 666.507 and the optional provisions under s. NR 666.504.

**c2d** A healthcare facility that is a very small quantity generator when counting all of its hazardous waste, including both its hazardous waste pharmaceuticals and its non-pharmaceutical hazardous waste, has the option of complying with sub. c4d for

the management of its hazardous waste pharmaceuticals as an alternative to complying with s. [NR 662.014](#) and the optional provisions under s. [NR 666.504](#).

**c3d** A healthcare facility or reverse distributor remains subject to all applicable hazardous waste regulations with respect to the management of its non-pharmaceutical hazardous waste.

**c4d** With the exception of healthcare facilities identified in sub. [c1d](#), a healthcare facility is subject to the all of the following in lieu of chs. [NR 662](#) to [665](#):

cad Sections [NR 666.502](#) and [666.505](#) to [666.508](#) of this subchapter with respect to the management of all of the following:

1. Non-creditable hazardous waste pharmaceuticals.
2. Potentially creditable hazardous waste pharmaceuticals if they are not destined for a reverse distributor.

cbd Sections [NR 666.502 c1d](#), [666.503](#), [666.505](#) to [666.507](#), and [666.509](#) with respect to the management of potentially creditable hazardous waste pharmaceuticals that are prescription pharmaceuticals and are destined for a reverse distributor.

**c5d** A reverse distributor is subject to ss. [NR 666.505](#) to [666.510](#) of this subchapter in lieu of chs. [NR 662](#) to [665](#) with respect to the management of hazardous waste pharmaceuticals.

**c6d** Hazardous waste pharmaceuticals generated or managed by entities other than healthcare facilities and reverse distributors, for example pharmaceutical manufacturers and reverse logistics centers, are not subject to this subchapter. Other generators are subject to ch. [NR 662](#) for the generation and accumulation of hazardous wastes, including hazardous waste pharmaceuticals.

**c7d** All of the following are not subject to chs. [NR 660](#) to [673](#), except as specified:

cad Pharmaceuticals that are not solid waste, as defined in s. [NR 661.0002](#), because they are legitimately used or reused ce.g., lawfully donated for their intended purposed or reclaimed.

cbd Over-the-counter pharmaceuticals, dietary supplements, or homeopathic drugs that are not solid wastes, as defined in s. [NR 661.0002](#), because they have a reasonable expectation of being legitimately used or reused ce.g., lawfully redistributed for their intended purposed or reclaimed.

ccd Pharmaceuticals being managed in accordance with a recall strategy that has been approved by the food and drug administration in accordance with [21 CFR part 7](#) subpart C. This subchapter does apply to the management of the recalled hazardous waste pharmaceuticals after the food and drug administration approves the destruction of the recalled items.

cdd Pharmaceuticals being managed in accordance with a recall corrective action plan that has been accepted by the consumer product safety commission in accordance with [16 CFR part 1115](#). This subchapter does apply to the management of the recalled hazardous waste pharmaceuticals after the consumer product safety commission approves the destruction of the recalled items.

ced Pharmaceuticals stored according to a preservation order, or during an investigation or judicial proceeding until after the preservation order, investigation, or judicial proceeding has concluded or a decision is made to discard the pharmaceuticals.

efd Investigational new drugs for which an investigational new drug application is in effect in accordance with the food and drug administration[s regulations in [21 CFR part 312](#). This subchapter does apply to the management of the investigational new drug after the decision is made to discard the investigational new drug or the food and drug administration approves the destruction of the investigational new drug, if the investigational new drug is a hazardous waste.

cgd Household waste pharmaceuticals, including those that have been collected by an authorized collector, as defined by the drug enforcement administration, provided the authorized collector complies with the conditional exemption under s. [NR 666.506 c1d cbd](#) and [c2d](#).

**History:** CR 19-082: cr. Register August 2020 No. 776, eff. 9-1-20; correction in c4d cbd made under s. 13.92 c4d cbd 7., Stats., Register April 2021 No. 784.

## **NR 666.502 Standards for healthcare facilities managing non-creditable hazardous waste pharmaceuticals. c1d**

**NOTIFICATION AND WITHDRAWAL FROM THIS SUBCHAPTER FOR HEALTHCARE FACILITIES MANAGING HAZARDOUS WASTE PHARMACEUTICALS.** cad *Notification.* A healthcare facility shall notify the department, using the site identification form, EPA form 8700-12, that it is a healthcare facility operating under this subchapter. A healthcare facility is not required to fill out box 10.B., waste codes for federally regulated hazardous waste, of the site identification form with respect to its hazardous waste pharmaceuticals. A healthcare facility shall submit a separate notification, using a site identification form, for each site or EPA identification number.

1. A healthcare facility that already has an EPA identification number shall notify the department, using the site identification form EPA form 8700-12, that it is a healthcare facility as part of its next annual report, if it is required to submit one; or if not required to submit an annual report, within 60 calendar days of September 1, 2020, or within 60 calendar days of becoming subject to this subchapter.

2. A healthcare facility that does not have an EPA identification number shall obtain one by notifying the department, using the site identification form EPA form 8700-12, that it is a healthcare facility as part of its next annual report, if it is required to submit one; or if not required to submit an annual report, within 60 calendar days of September 1, 2020, or within 60 calendar days of becoming subject to this subchapter.

3. A healthcare facility shall keep a copy of its notification on file for as long as the healthcare facility is subject to this subchapter.

cbd *Withdrawal.* A healthcare facility that operated under this subchapter but is no longer subject to this subchapter, because it is a very small quantity generator under s. [NR 662.014](#), and elects to withdraw from this subchapter, shall notify the department using the site identification form EPA form 8700-12 that it is no longer operating under this subchapter. A healthcare facility is not required to fill out box 10.B., waste codes for federally regulated hazardous waste, of the site identification form with respect to its hazardous waste pharmaceuticals. A healthcare facility shall submit a separate notification, using a site identification form, for each EPA identification number.

1. A healthcare facility shall submit the site identification form notifying that it is withdrawing from this subchapter before it begins operating under the conditional exemption under s. [NR 662.014](#).

2. A healthcare facility shall keep a copy of its withdrawal on file for 3 years from the date of signature on the notification of its withdrawal.

**c2d TRAINING OF PERSONNEL MANAGING NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS AT HEALTHCARE FACILITIES.** A healthcare facility shall ensure that all personnel that manage non-creditable hazardous waste pharmaceuticals are thoroughly familiar with proper waste handling and emergency procedures relevant to their responsibilities during normal facility operations and emergencies.

**c3d HAZARDOUS WASTE DETERMINATION FOR NON-CREDITABLE PHARMACEUTICALS.** A healthcare facility that generates



a solid waste that is a non-creditable pharmaceutical shall determine whether that pharmaceutical is a hazardous waste pharmaceutical, because it exhibits a characteristic identified in ch. NR 661 subchapter C or is listed in ch. NR 661 subchapter D, in order to determine whether the waste is subject to this subchapter. A healthcare facility may choose to manage its non-hazardous waste pharmaceuticals as non-creditable hazardous waste pharmaceuticals under this subchapter.

**c4d STANDARDS FOR CONTAINERS USED TO ACCUMULATE NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS AT HEALTHCARE FACILITIES.** cad A healthcare facility shall place non-creditable hazardous waste pharmaceuticals in a container that is structurally sound, compatible with its contents, and that lacks evidence of leakage, spillage, or damage that could cause leakage under reasonably foreseeable conditions.

cbd A healthcare facility that manages ignitable or reactive non-creditable hazardous waste pharmaceuticals, or that mixes or commingles incompatible non-creditable hazardous waste pharmaceuticals shall manage the container so that it does not have the potential to do any of the following:

1. Generate extreme heat or pressure, fire or explosion, or violent reaction.
2. Produce uncontrolled toxic mists, fumes, dusts, or gases in sufficient quantities to threaten human health.
3. Produce uncontrolled flammable fumes or gases in sufficient quantities to pose a risk of fire or explosions.
4. Damage the structural integrity of the container of non-creditable hazardous waste pharmaceuticals.
5. Threaten human health or the environment through other like means.

ccd A healthcare facility shall keep containers of non-creditable hazardous waste pharmaceuticals closed and secured in a manner that prevents unauthorized access to its contents.

cdd A healthcare facility may accumulate non-creditable hazardous waste pharmaceuticals and non-hazardous non-creditable waste pharmaceuticals in the same container, except that non-creditable hazardous waste pharmaceuticals prohibited from being combusted because of the dilution prohibition under s. NR 668.03 c3d shall be accumulated in separate containers and labeled with all applicable hazardous waste numbers, or hazardous waste codes.

**c5d LABELING CONTAINERS USED TO ACCUMULATE NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS AT HEALTHCARE FACILITIES.** A healthcare facility shall label or clearly mark each container of non-creditable hazardous waste pharmaceuticals with the phrase XHazardous Waste Pharmaceuticals.Y

**c6d MAXIMUM ACCUMULATION TIME FOR NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS AT HEALTHCARE FACILITIES.** cad A healthcare facility may accumulate non-creditable hazardous waste pharmaceuticals on-site for one year or less without a license or having interim status.

cbd A healthcare facility that accumulates non-creditable hazardous waste pharmaceuticals on-site shall demonstrate the length of time that the non-creditable hazardous waste pharmaceuticals have been accumulating, starting from the date the pharmaceuticals first become a waste. A healthcare facility may make this demonstration by any of the following methods:

1. Marking or labeling the container of non-creditable hazardous waste pharmaceuticals with the date that the non-creditable hazardous waste pharmaceuticals became a waste.
2. Maintaining an inventory system that identifies the date

the non-creditable hazardous waste pharmaceuticals being accumulated first became a waste.

3. Placing the non-creditable hazardous waste pharmaceuticals in a specific area and identifying the earliest date that any of the non-creditable hazardous waste pharmaceuticals in the area became a waste.

**c7d LAND DISPOSAL RESTRICTIONS FOR NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS.** The non-creditable hazardous waste pharmaceuticals generated by a healthcare facility are subject to the land disposal restrictions under ch. NR 668. A healthcare facility that generates non-creditable hazardous waste pharmaceuticals shall comply with the land disposal restrictions in accordance with s. NR 668.07 c1d requirements, except that it is not required to identify the hazardous waste numbers or hazardous waste codes on the land disposal restrictions notification.

**c8d PROCEDURES FOR HEALTHCARE FACILITIES FOR MANAGING REJECTED SHIPMENTS OF NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS.** A healthcare facility that sends a shipment of non-creditable hazardous waste pharmaceuticals to a designated facility with the understanding that the designated facility can accept and manage the waste, and later receives that shipment back as a rejected load in accordance with the manifest discrepancy provisions under s. NR 664.0072 or 665.0072 may accumulate the returned non-creditable hazardous waste pharmaceuticals on-site for up to an additional 90 calendar days provided the rejected or returned shipment is managed in accordance with subs. c4d and c5d. Upon receipt of the returned shipment, the healthcare facility shall do all of the following:

cad Sign one of the following:

1. Item 18c of the original manifest, if the original manifest was used for the returned shipment.
2. Item 20 of the new manifest, if a new manifest was used for the returned shipment.

cbd Provide the transporter a copy of the manifest.

ccd Within 30 calendar days of receipt of the rejected shipment, send a copy of the manifest to the designated facility that returned the shipment to the healthcare facility.

cdd Within 90 calendar days of receipt of the rejected shipment, transport or offer for transport the returned shipment in accordance with the shipping standards under s. NR 666.508 c1d.

**c9d REPORTING BY HEALTHCARE FACILITIES FOR NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS.** cad *Annual reporting by healthcare facilities.* A healthcare facility is not subject to annual reporting requirements under s. NR 662.041 with respect to non-creditable hazardous waste pharmaceuticals managed under this subchapter.

cbd *Exception reporting by healthcare facilities for a missing copy of the manifest.* 1. ZShipments from a healthcare facility to a designated facility.[ For shipments from a healthcare facility to a designated facility, all of the following exception reporting requirements apply:

a. If a healthcare facility does not receive a copy of the manifest with the signature of the owner or operator of the designated facility within 60 calendar days of the date the non-creditable hazardous waste pharmaceuticals were accepted by the initial transporter, the healthcare facility shall submit all of the following to the department:

1d A legible copy of the original manifest, indicating that the healthcare facility has not received confirmation of delivery.

2d A handwritten or typed note on the original manifest itself, or on an attached sheet of paper, stating that the return copy was not received and explaining the efforts taken to locate the



non-creditable hazardous waste pharmaceuticals and the results of those efforts.

2. ZShipments rejected by the designated facility and shipped to an alternate facility.[ For shipments rejected by the designated facility and shipped to an alternate facility, all of the following exception reporting requirements apply:

a. If a healthcare facility does not receive a copy of the manifest for a rejected shipment of the non-creditable hazardous waste pharmaceuticals that is forwarded by the designated facility to an alternate facility using appropriate manifest procedures, with the signature of the owner or operator of the alternate facility, within 60 calendar days of the date the non-creditable hazardous waste was accepted by the initial transporter forwarding the shipment of non-creditable hazardous waste pharmaceuticals from the designated facility to the alternate facility, the healthcare facility shall submit all of the following to the department:

1d A legible copy of the original manifest, indicating that the healthcare facility has not received confirmation of delivery.

2d A handwritten or typed note on the original manifest itself, or on an attached sheet of paper, stating that the return copy was not received and explaining the efforts taken to locate the non-creditable hazardous waste pharmaceuticals and the results of those efforts.

ccd *Additional reports.* The department may require healthcare facilities to furnish additional reports concerning the quantities and disposition of non-creditable hazardous waste pharmaceuticals.

**c10d RECORDKEEPING BY HEALTHCARE FACILITIES FOR NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS.** cad A healthcare facility shall keep a copy of each manifest signed in accordance with s. [NR 662.023 c1d](#) for 3 years or until it receives a signed copy from the designated facility that received the non-creditable hazardous waste pharmaceuticals. This signed copy shall be retained as a record for at least 3 years from the date the waste was accepted by the initial transporter.

cbd A healthcare facility shall keep a copy of each exception report for a period of at least 3 years from the date of the report.

ccd A healthcare facility shall keep records of any test results, waste analyses, or other determinations made to support its hazardous waste determination consistent with s. [NR 662.011 c6d](#), for at least 3 years from the date the waste was last sent to on-site or off-site treatment, storage, or disposal. A healthcare facility that manages all of its non-creditable non-hazardous waste pharmaceuticals as non-creditable hazardous waste pharmaceuticals is not required to keep documentation of hazardous waste determinations.

cdd The periods of retention referred to in this section are extended automatically during the course of any unresolved enforcement action regarding the regulated activity, or as requested by the department.

ced All records shall be readily available upon request by the department.

**c11d RESPONSE TO SPILLS OF NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS AT HEALTHCARE FACILITIES.** A healthcare facility shall immediately contain all spills of non-creditable hazardous waste pharmaceuticals and manage the spill clean-up materials as non-creditable hazardous waste pharmaceuticals in accordance with the requirements of this subchapter.

**c12d ACCEPTING NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS FROM AN OFF-SITE HEALTHCARE FACILITY THAT IS A VERY SMALL QUANTITY GENERATOR.** A healthcare facility may accept non-creditable hazardous waste pharmaceuticals from an off-site healthcare facility that is a very small quan-

ty generator under s. [NR 662.014](#), without a license or without having interim status, provided the receiving healthcare facility meets all of the following:

cad Is under the control of the same person, as defined in s. [NR 660.10 c90d](#), as the very small quantity generator healthcare facility that is sending the non-creditable hazardous waste pharmaceuticals off-site, or has a contractual or other documented business relationship whereby the receiving healthcare facility supplies pharmaceuticals to the very small quantity generator healthcare facility. XControl,Y for the purposes of this section, means the power to direct the policies of the healthcare facility, whether by the ownership of stock, voting rights, or otherwise, except that contractors who operate healthcare facilities on behalf of a different person as defined in s. [NR 660.10](#) may not be deemed to XcontrolY such healthcare facilities.

cbd Is operating under this subchapter for the management of its non-creditable hazardous waste pharmaceuticals.

ccd Manages the non-creditable hazardous waste pharmaceuticals that it receives from off-site in compliance with this subchapter.

cdd Keeps records of the non-creditable hazardous waste pharmaceuticals shipments it receives from off-site for 3 years from the date that the shipment is received.

**History:** CR 19-082: cr. Register August 2020 No. 776, eff. 9-1-20; correction in c6d cbd cintro.d made under s. 35.17, Stats., and renumbering in c8d made under s. 13.92 c4d cbd 2., Stats., Register August 2020 No. 776.

### **NR 666.503 Standards for healthcare facilities managing potentially creditable hazardous waste pharmaceuticals. c1d HAZARDOUS WASTE DETERMINATION FOR POTENTIALLY CREDITABLE PHARMACEUTICALS.**

A healthcare facility that generates a solid waste that is a potentially creditable pharmaceutical shall determine whether the potentially creditable pharmaceutical is a potentially creditable hazardous waste pharmaceutical that is listed in subch. [D of ch. NR 661](#) or exhibits a characteristic identified in subch. [C of ch. NR 661](#). A healthcare facility may choose to manage its potentially creditable non-hazardous waste pharmaceuticals as potentially creditable hazardous waste pharmaceuticals under this subchapter.

**c2d ACCEPTING POTENTIALLY CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS FROM AN OFF-SITE HEALTHCARE FACILITY THAT IS A VERY SMALL QUANTITY GENERATOR.** A healthcare facility may accept potentially creditable hazardous waste pharmaceuticals from an off-site healthcare facility that is a very small quantity generator under s. [NR 662.014](#), without a license or without having interim status, provided the receiving healthcare facility meets all of the following:

cad Is under the control of the same person, as defined in s. [NR 660.10 c90d](#), as the very small quantity generator healthcare facility that is sending the potentially creditable hazardous waste pharmaceuticals off-site or has a contractual or other documented business relationship whereby the receiving healthcare facility supplies pharmaceuticals to the very small quantity generator healthcare facility. XControl,Y for the purposes of this section, means the power to direct the policies of the healthcare facility, whether by the ownership of stock, voting rights, or otherwise, except that contractors who operate healthcare facilities on behalf of a different person as defined in s. [NR 660.10](#) may not be deemed to XcontrolY such healthcare facilities.

cbd Is operating under this subchapter for the management of its potentially creditable hazardous waste pharmaceuticals.

ccd Manages the potentially creditable hazardous waste pharmaceuticals that it receives from off-site in compliance with this subchapter.

cdd Keeps records of the potentially creditable hazardous

waste pharmaceutical shipments it receives from off-site for 3 years from the date that the shipment is received.

**c3d PROHIBITION.** A healthcare facility is prohibited from sending hazardous wastes other than potentially creditable hazardous waste pharmaceuticals to a reverse distributor.

**c4d ANNUAL REPORTING BY HEALTHCARE FACILITIES.** A healthcare facility is not subject to annual reporting requirements under s. NR 662.041 with respect to potentially creditable hazardous waste pharmaceuticals managed under this subchapter.

**c5d RECORDKEEPING BY HEALTHCARE FACILITIES.** A healthcare facility that initiates a shipment of potentially creditable hazardous waste pharmaceuticals to a reverse distributor shall keep all of the following records, paper or electronic, for each shipment of potentially creditable hazardous waste pharmaceuticals for 3 years from the date of shipment:

1. The confirmation of delivery.
2. The shipping papers prepared in accordance with 49 CFR part 172 subpart C, if applicable.

cbd The periods of retention referred to in this section are extended automatically during the course of any unresolved enforcement action regarding the regulated activity, or as requested by the department.

ccd All records shall be readily available upon request by the department.

**c6d RESPONSE TO SPILLS OF POTENTIALLY CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS AT HEALTHCARE FACILITIES.** A healthcare facility shall immediately contain all spills of potentially creditable hazardous waste pharmaceuticals and manage the spill clean-up materials as non-creditable hazardous waste pharmaceuticals in accordance with this subchapter.

**History:** CR 19-082: cr. Register August 2020 No. 776, eff. 9-1-20; correction in c1d made under s. 35.17, Stats., Register August 2020 No. 776.

**NR 666.504 Healthcare facilities that are very small quantity generators for both hazardous waste pharmaceuticals and non-pharmaceutical hazardous waste.**

**c1d POTENTIALLY CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS.** A healthcare facility that is a very small quantity generator for both hazardous waste pharmaceuticals and non-pharmaceutical hazardous waste may send its potentially creditable hazardous waste pharmaceuticals to a reverse distributor.

**c2d OFF-SITE COLLECTION OF HAZARDOUS WASTE PHARMACEUTICALS GENERATED BY A HEALTHCARE FACILITY THAT IS A VERY SMALL QUANTITY GENERATOR.** A healthcare facility that is a very small quantity generator for both hazardous waste pharmaceuticals and non-pharmaceutical hazardous waste may send its hazardous waste pharmaceuticals off-site to another healthcare facility, provided one of the following is met:

cad The receiving healthcare facility meets the conditions specified in ss. NR 666.502 cad and 666.503 c2d, as applicable.

cbd The very small quantity generator healthcare facility meets the conditions specified in s. NR 662.014 c1d ced 8. and the receiving large quantity generator meets the conditions specified in s. NR 662.017 c6d.

**c3d LONG-TERM CARE FACILITIES THAT ARE VERY SMALL QUANTITY GENERATORS.** A long-term care facility that is a very small quantity generator for both hazardous waste pharmaceuticals and non-pharmaceutical hazardous waste may dispose of its hazardous waste pharmaceuticals, excluding contaminated personal protective equipment or clean-up materials, in an on-site collection receptacle of an authorized collector, as defined by the drug enforcement administration, that is registered with the drug enforcement administration provided the contents are collected, stored, transported, destroyed and disposed of in compliance with

all applicable drug enforcement administration regulations for controlled substances.

**c4d LONG-TERM CARE FACILITIES WITH 20 BEDS OR FEWER.** A long-term care facility with 20 beds or fewer is presumed to be a very small quantity generator subject to s. NR 662.014 for both hazardous waste pharmaceuticals and non-pharmaceutical hazardous waste and not subject to this subchapter, except for ss. NR 666.505 and 666.507 and the other optional provisions of this section. The department has the responsibility to demonstrate that a long-term care facility with 20 beds or fewer generates quantities of hazardous waste that are in excess of the very small quantity generator limits as defined in s. NR 660.10 c139d. A long-term care facility with more than 20 beds that operates as a very small quantity generator under s. NR 662.014 shall demonstrate that it generates quantities of hazardous waste that are within the very small quantity generator limits as defined in s. NR 660.10.

**History:** CR 19-082: cr. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.505 Prohibition of sewerage hazardous waste pharmaceuticals.** All healthcare facilities, including very small quantity generators operating under s. NR 662.014 in lieu of this subchapter, and reverse distributors are prohibited from discharging hazardous waste pharmaceuticals to a sewer system that passes through to a publicly-owned treatment works. Healthcare facilities and reverse distributors remain subject to the prohibitions in 40 CFR 403.5 cbd c1d.

**History:** CR 19-082: cr. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.506 Conditional exemptions for hazardous waste pharmaceuticals that are also controlled substances and household waste pharmaceuticals collected in a take-back event or program.** **c1d** CONDITIONAL EXEMPTIONS. Provided the conditions of sub. c2d are met, all of the following are exempt from the requirements under chs. NR 662 to 673:

cad Hazardous waste pharmaceuticals that are also listed on a schedule of controlled substances by the drug enforcement administration in 21 CFR part 1308.

cbd Household waste pharmaceuticals that are collected in a take-back event or program, including those that are collected by an authorized collector, as defined by the drug enforcement administration, registered with the drug enforcement administration that commingles the household waste pharmaceuticals with controlled substances from an ultimate user, as defined by the drug enforcement administration.

**c2d CONDITIONS FOR EXEMPTION.** The hazardous waste pharmaceuticals shall be all of the following:

cad Managed in compliance with the sewer prohibition under s. NR 666.505.

cbd Collected, stored, transported, and disposed of in compliance with all applicable drug enforcement administration regulations for controlled substances.

ccd Destroyed by a method that the drug enforcement administration has publicly deemed in writing to meet its non-retrievable standard of destruction or combusted at one of the following:

1. A permitted large municipal waste combustor, subject to 40 CFR part 62 subpart FFF or applicable state plan for existing large municipal waste combustors, or 40 CFR part 60 subpart Eb for new large municipal waste combustors.

2. A permitted small municipal waste combustor, subject to 40 CFR part 62 subpart JJJ or applicable state plan for existing small municipal waste combustors, or 40 CFR part 60 subpart AAAA for new small municipal waste combustors.

3. A permitted hospital, medical and infectious waste incin-

erator, subject to [40 CFR part 62](#) subpart HHH or applicable state plan for existing hospital, medical and infectious waste incinerators, or [40 CFR part 60](#) subpart Ec for new hospital, medical and infectious waste incinerators.

4. A permitted commercial and industrial solid waste incinerator, subject to [40 CFR part 62](#) subpart III or applicable state plan for existing commercial and industrial solid waste incinerators, or [40 CFR part 60](#) subpart CCCC for new commercial and industrial solid waste incinerators.

5. A permitted hazardous waste combustor subject to [40 CFR part 63](#) subpart EEE.

**History:** CR 19-082; cr. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.507 Residues of hazardous waste pharmaceuticals in empty containers. c1d** STOCK, DISPENSING AND UNIT-DOSE CONTAINERS. A stock bottle, dispensing bottle, vial, or ampule not to exceed 1 liter or 10,000 pills; or a unit-dose container (e.g., a unit-dose packet, cup, wrapper, blister pack, or delivery device) is considered empty and the residues are not regulated as hazardous waste provided the pharmaceuticals have been removed from the stock bottle, dispensing bottle, vial, ampule, or the unit-dose container using the practices commonly employed to remove materials from that type of container.

**c2d** SYRINGES. A syringe is considered empty and the residues are not regulated as hazardous waste under this subchapter provided the contents have been removed by fully depressing the plunger of the syringe. If a syringe is not empty, the syringe shall be placed with its remaining hazardous waste pharmaceuticals into a container that is managed and disposed of as a non-creditable hazardous waste pharmaceutical under this subchapter and any applicable federal, state, and local requirements for sharps containers and medical waste.

**c3d** INTRAVENOUS CIVD BAGS. An IV bag is considered empty and the residues are not regulated as hazardous waste provided the pharmaceuticals in the IV bag have been fully administered to a patient. If an IV bag is not empty, the IV bag shall be placed with its remaining hazardous waste pharmaceuticals into a container that is managed and disposed of as a non-creditable hazardous waste pharmaceutical under this subchapter, unless the IV bag held non-acute hazardous waste pharmaceuticals and is empty as defined in s. [NR 661.0007 c2d cad](#).

**c4d** OTHER CONTAINERS, INCLUDING DELIVERY DEVICES. Hazardous waste pharmaceuticals remaining in all other types of unused, partially administered, or fully administered containers shall be managed as non-creditable hazardous waste pharmaceuticals under this subchapter, unless the container held non-acute hazardous waste pharmaceuticals and is empty as defined in s. [NR 661.0007 c2d cad](#) or *cbd*. Examples of containers and delivery devices containing residues may include inhalers, aerosol cans, nebulizers, tubes of ointments, gels, or creams.

**History:** CR 19-082; cr. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.508 Shipping non-creditable hazardous waste pharmaceuticals from a healthcare facility or evaluated hazardous waste pharmaceuticals from a reverse distributor. c1d** SHIPPING NON-CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS OR EVALUATED HAZARDOUS WASTE PHARMACEUTICALS. A healthcare facility shall ship non-creditable hazardous waste pharmaceuticals and a reverse distributor shall ship evaluated hazardous waste pharmaceuticals off-site to a designated facility, for example a license or interim status treatment, storage, or disposal facility, in compliance with all of the following:

*cad Pretransport.* Before transporting or offering hazardous

waste for transportation off-site, a healthcare facility or reverse distributor shall do all of the following:

1. ZPackaging.[ Package the waste in accordance with the applicable U.S. department of transportation regulations on packaging under [49 CFR parts 173, 178 and 180](#).

2. ZLabeling.[ Label each package in accordance with the applicable U.S. department of transportation regulations on hazardous materials under [49 CFR part 172](#) subpart E.

3. ZMarking.[ a. Mark each package of hazardous waste in accordance with the applicable U.S. department of transportation regulations on hazardous materials under [49 CFR part 172](#) subpart D.

b. Mark each container of 119 gallons or less used in such transportation with the following words and information in accordance with the requirements of [49 CFR 172.304](#):

XHAZARDOUS WASTE—Federal Law Prohibits Improper Disposal. If found, contact the nearest police or public safety authority or the U.S. Environmental Protection Agency.

Healthcare Facility[s] or Reverse distributor[s] Name and Address \_\_\_\_\_.

Healthcare Facility[s] or Reverse distributor[s] EPA Identification Number \_\_\_\_\_.

Manifest Tracking Number \_\_\_\_\_, Y

c. Lab packs that will be incinerated in compliance with s. [NR 668.42 c3d](#) are not required to be marked with EPA hazardous waste numbers, except D004, D005, D006, D007, D008, D010, and D011, where applicable. A nationally recognized electronic system, such as bar coding or radio frequency identification, may be used to identify the EPA hazardous waste numbers.

4. ZPlacarding.[ Placard or offer the initial transporter the appropriate placards according to U.S. department of transportation regulations for hazardous materials under [49 CFR part 172](#), subpart F.

*cbd Manifesting.* A healthcare facility shall comply with the manifest requirements of subch. [B of ch. NR 662](#), except that:

1. A healthcare facility shipping non-creditable hazardous waste pharmaceuticals is not required to list all applicable EPA hazardous waste numbers, or hazardous waste codes, in Item 13 of EPA form 8700-22.

2. A healthcare facility shipping non-creditable hazardous waste pharmaceuticals shall write the word XPHARMSY in Item 13 of EPA form 8700-22.

**Note:** Healthcare facilities may use either PHARMS or PHRM in Item 13 of the manifest per EPA RCRA Online 14919, <https://rcrapublic.epa.gov/rcraonline/>.

**c2d** EXPORTS. A healthcare facility or reverse distributor that exports non-creditable hazardous waste pharmaceuticals or evaluated hazardous waste pharmaceuticals is subject to subch. [H of ch. NR 662](#).

**c3d** IMPORTS. Any person that imports non-creditable hazardous waste pharmaceuticals or evaluated hazardous waste pharmaceuticals is subject to subch. [H of ch. NR 662](#). A healthcare facility or reverse distributor may not accept imported non-creditable hazardous waste pharmaceuticals or evaluated hazardous waste pharmaceuticals unless they have a license or interim status that allows them to accept hazardous waste from off-site.

**History:** CR 19-082; cr. Register August 2020 No. 776, eff. 9-1-20.

**NR 666.509 Shipping potentially creditable hazardous waste pharmaceuticals from a healthcare facility or a reverse distributor to a reverse distributor. c1d** SHIPPING POTENTIALLY CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS. A healthcare facility or a reverse distributor who transports or offers for transport potentially creditable hazardous waste pharmaceuticals off-site to a reverse distributor shall com-



ply with all applicable U.S. department of transportation regulations in 49 CFR parts 171 to 180 for any potentially creditable hazardous waste pharmaceutical that meets the definition of hazardous material in 49 CFR 171.8.

**Note:** For purposes of the department of transportation regulations, a material is considered a hazardous waste if it is subject to the hazardous waste manifest requirements specified in ch. NR 662. Because a potentially creditable hazardous waste pharmaceutical does not require a manifest, it is not considered hazardous waste under the department of transportation regulations.

**c2d DELIVERY CONFIRMATION.** Upon receipt of each shipment of potentially creditable hazardous waste pharmaceuticals, the receiving reverse distributor shall provide confirmation, paper or electronic, to the healthcare facility or reverse distributor that initiated the shipment that the shipment of potentially creditable hazardous waste pharmaceuticals has arrived at its destination and is under the custody and control of the reverse distributor.

**c3d PROCEDURES FOR WHEN DELIVERY CONFIRMATION IS NOT RECEIVED WITHIN 35 CALENDAR DAYS.** If a healthcare facility or reverse distributor initiates a shipment of potentially creditable hazardous waste pharmaceuticals to a reverse distributor and does not receive delivery confirmation within 35 calendar days from the date that the shipment of potentially creditable hazardous waste pharmaceuticals was sent, the healthcare facility or reverse distributor that initiated the shipment shall contact the carrier and the intended recipient, that is the reverse distributor, promptly to report that the delivery confirmation was not received and to determine the status of the potentially creditable hazardous waste pharmaceuticals.

**c4d EXPORTING POTENTIALLY CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS.** A healthcare facility or reverse distributor that sends potentially creditable hazardous waste pharmaceuticals to a foreign destination shall comply with the applicable sections of subch. H of ch. NR 662, except the manifesting requirement under s. NR 662.083 c3d, in addition to subs. c1d to c3d.

**c5d IMPORTING POTENTIALLY CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS.** Any person that imports potentially creditable hazardous waste pharmaceuticals into the United States is subject to subs. c1d to c3d in lieu of subch. H of ch. NR 662. Immediately after the potentially creditable hazardous waste pharmaceuticals enter the United States, they are subject to all applicable requirements of this subchapter.

**History:** CR 19-082; cr. Register August 2020 No. 776, eff. 9-1-20; correction in c1d made under s. 35.17, Stats., Register August 2020 No. 776.

**NR 666.510 Standards for the management of potentially creditable hazardous waste pharmaceuticals and evaluated hazardous waste pharmaceuticals at reverse distributors.** A reverse distributor may accept potentially creditable hazardous waste pharmaceuticals from off-site and accumulate potentially creditable hazardous waste pharmaceuticals or evaluated hazardous waste pharmaceuticals on-site without a hazardous waste permit or without having interim status, provided that the reverse distributor complies with all of the following conditions:

**c1d STANDARDS FOR REVERSE DISTRIBUTORS MANAGING POTENTIALLY CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS AND EVALUATED HAZARDOUS WASTE PHARMACEUTICALS.** *cad Notification.* A reverse distributor shall notify the department using the site identification form EPA form 8700-12, that it is a reverse distributor operating under this subchapter. A reverse distributor shall do one of the following:

1. A reverse distributor that already has an EPA identification number shall notify the department, using the site identification form EPA form 8700-12, that it is a reverse distributor, as de-

finied in s. NR 666.500, within 60 calendar days of September 1, 2020, or within 60 calendar days of becoming subject to this subchapter.

2. A reverse distributor that does not have an EPA identification number shall obtain one by notifying the department, using the site identification form EPA form 8700-12, that it is a reverse distributor, as defined in s. NR 666.500, within 60 calendar days of September 1, 2020, or within 60 calendar days of becoming subject to this subchapter.

*cbd Inventory by the reverse distributor.* A reverse distributor shall maintain a current inventory of all the potentially creditable hazardous waste pharmaceuticals and evaluated hazardous waste pharmaceuticals that are accumulated on-site.

1. A reverse distributor shall inventory each potentially creditable hazardous waste pharmaceutical within 30 calendar days of each waste arriving at the reverse distributor.

2. The inventory shall include the identity, for example name or national drug code, and quantity of each potentially creditable hazardous waste pharmaceutical and evaluated hazardous waste pharmaceutical.

3. If the reverse distributor already meets the inventory requirements of this paragraph because of other regulatory requirements, such as state board of pharmacy regulations, the facility is not required to provide a separate inventory pursuant to this section.

*ccd Evaluation by a reverse distributor that is not a manufacturer.* A reverse distributor who is not a pharmaceutical manufacturer shall evaluate a potentially creditable hazardous waste pharmaceutical within 30 calendar days of the waste arriving at the reverse distributor to establish whether it is destined for another reverse distributor for further evaluation or verification of manufacturer credit or for a permitted or interim status treatment, storage, or disposal facility. A potentially creditable hazardous waste pharmaceutical sent to a reverse distributor that is not a pharmaceutical manufacturer is subject to one of the following:

1. A potentially creditable hazardous waste pharmaceutical that is destined for another reverse distributor is still considered a potentially creditable hazardous waste pharmaceutical and shall be managed in accordance with sub. c2d.

2. A potentially creditable hazardous waste pharmaceutical that is destined for a licensed or interim status treatment, storage, or disposal facility is considered an evaluated hazardous waste pharmaceutical and shall be managed in accordance with sub. c3d.

*cdd Evaluation by a reverse distributor that is a manufacturer.* A reverse distributor that is a pharmaceutical manufacturer shall evaluate a potentially creditable hazardous waste pharmaceutical to verify manufacturer credit within 30 calendar days of the waste arriving at the facility and following the evaluation shall manage the evaluated hazardous waste pharmaceuticals in accordance with sub. c3d.

*ced Maximum accumulation time for hazardous waste pharmaceuticals at a reverse distributor.* 1. A reverse distributor may accumulate potentially creditable hazardous waste pharmaceuticals and evaluated hazardous waste pharmaceuticals on-site for 180 calendar days or less. The 180 calendar days start after the potentially creditable hazardous waste pharmaceutical has been evaluated and applies to all hazardous waste pharmaceuticals accumulated on-site, regardless of whether they are destined for another reverse distributor, such as potentially creditable hazardous waste pharmaceuticals, or a permitted or interim status treatment, storage, or disposal facility, such as evaluated hazardous waste pharmaceuticals.

2. Unexpired pharmaceuticals that are otherwise creditable



but are awaiting their expiration date, by aging in a holding morgue, can be accumulated for up to 180 calendar days after the expiration date, provided that the unexpired pharmaceuticals are managed in accordance with this subsection and the container labeling and management standards specified in sub. [c3d cdd 1.](#) to [6.](#)

*cf* *Security at the reverse distributor facility.* A reverse distributor shall prevent unknowing entry and minimize the possibility for the unauthorized entry into the portion of the facility where potentially creditable hazardous waste pharmaceuticals and evaluated hazardous waste pharmaceuticals are kept. Examples of methods that may be used to prevent unknowing entry and minimize the possibility for unauthorized entry include any of the following:

1. A 24-hour continuous monitoring surveillance system.
2. An artificial barrier such as a fence.
3. A means to control entry, such as keycard access.
4. If the reverse distributor already meets the security requirements of this paragraph because of other regulatory requirements, such as drug enforcement administration or state board of pharmacy regulations, the facility is not required to provide separate security measures pursuant to this section.

*cg* *Contingency plan and emergency procedures at a reverse distributor.* A reverse distributor that accepts potentially creditable hazardous waste pharmaceuticals from off-site shall prepare a contingency plan and comply with the other requirements under subch. [M of ch. NR 662.](#)

*ch* *Closure of a reverse distributor.* When closing an area where a reverse distributor accumulates potentially creditable hazardous waste pharmaceuticals or evaluated hazardous waste pharmaceuticals, the reverse distributor shall comply with s. [NR 662.017 c1d chd 2.](#) and [3.](#)

*ci* *Reporting by a reverse distributor.* 1. ZUnauthorized waste report.[ A reverse distributor shall submit an unauthorized waste report if the reverse distributor receives waste from off-site that it is not authorized to receive, such as non-pharmaceutical hazardous waste, or regulated medical waste. The reverse distributor shall prepare and submit an unauthorized waste report to the department within 45 calendar days after the unauthorized waste arrives at the reverse distributor and shall send a copy of the unauthorized waste report to the healthcare facility or other entity that sent the unauthorized waste. The reverse distributor shall manage the unauthorized waste in accordance with all applicable regulations. The unauthorized waste report shall be signed by the owner or operator of the reverse distributor, or its authorized representative, and contain all of the following information:

- a. The EPA identification number, name, and address of the reverse distributor.
- b. The date the reverse distributor received the unauthorized waste.
- c. The EPA identification number, name, and address of the healthcare facility that shipped the unauthorized waste, if available.
- d. A description and the quantity of each unauthorized waste the reverse distributor received.
- e. The method of treatment, storage, or disposal for each unauthorized waste.
- f. A brief explanation of why the waste was unauthorized, if known.

2. ZAdditional reports.[ The department may require reverse distributors to furnish additional reports concerning the quantities and disposition of potentially creditable hazardous

waste pharmaceuticals and evaluated hazardous waste pharmaceuticals.

*cj* *Recordkeeping by reverse distributors.* The periods of retention referred to in this section are extended automatically during the course of any unresolved enforcement action regarding the regulated activity, or as requested by the department. A reverse distributor shall keep all of the following records, paper or electronic, readily available upon request by an inspector:

1. A copy of its notification on file for as long as the facility is subject to this subchapter.
2. A copy of the delivery confirmation and the shipping papers for each shipment of potentially creditable hazardous waste pharmaceuticals that it receives, and a copy of each unauthorized waste report, for at least 3 years from the date the shipment arrives at the reverse distributor.
3. A copy of its current inventory for as long as the facility is subject to this subchapter.

**c2d** ADDITIONAL STANDARDS FOR REVERSE DISTRIBUTORS MANAGING POTENTIALLY CREDITABLE HAZARDOUS WASTE PHARMACEUTICALS DESTINED FOR ANOTHER REVERSE DISTRIBUTOR. A reverse distributor that does not have a license or interim status shall comply with all of the following conditions, in addition to the requirements specified in sub. [c1d](#), for the management of potentially creditable hazardous waste pharmaceuticals that are destined for another reverse distributor for further evaluation or verification of manufacturer credit:

*ca* A reverse distributor that receives potentially creditable hazardous waste pharmaceuticals from a healthcare facility shall send those potentially creditable hazardous waste pharmaceuticals to another reverse distributor within 180 calendar days after the potentially creditable hazardous waste pharmaceuticals have been evaluated or follow sub. [c3d](#) for evaluated hazardous waste pharmaceuticals.

*cb* A reverse distributor that receives potentially creditable hazardous waste pharmaceuticals from another reverse distributor shall send those potentially creditable hazardous waste pharmaceuticals to a reverse distributor that is a pharmaceutical manufacturer within 180 calendar days after the potentially creditable hazardous waste pharmaceuticals have been evaluated or follow sub. [c3d](#) for evaluated hazardous waste pharmaceuticals.

*cc* A reverse distributor shall ship potentially creditable hazardous waste pharmaceuticals destined for another reverse distributor in accordance with s. [NR 666.509.](#)

*cd* The periods of retention referred to in this paragraph are extended automatically during the course of any unresolved enforcement action regarding the regulated activity, or as requested by the department. A reverse distributor shall keep all of the following records, paper or electronic, readily available upon request by an inspector for each shipment of potentially creditable hazardous waste pharmaceuticals that it initiates to another reverse distributor, for at least 3 years from the date of shipment:

1. The confirmation of delivery.
2. The DOT shipping papers prepared in accordance with [49 CFR part 172](#) subpart C, if applicable

**c3d** ADDITIONAL STANDARDS FOR REVERSE DISTRIBUTORS MANAGING EVALUATED HAZARDOUS WASTE PHARMACEUTICALS. A reverse distributor that does not have a license or interim status shall comply with all of the following conditions, in addition to the requirements of sub. [c1d](#), for the management of evaluated hazardous waste pharmaceuticals:

*ca* *Accumulation area at the reverse distributor.* A reverse distributor shall designate an on-site accumulation area where it will accumulate evaluated hazardous waste pharmaceuticals.

*cb* *Inspections of on-site accumulation area.* A reverse dis-

tributor shall inspect its on-site accumulation area at least once every 7 calendar days, looking at containers for leaks and for deterioration caused by corrosion or other factors, as well as for signs of diversion.

*ccd Personnel training at a reverse distributor.* Personnel at a reverse distributor who handle evaluated hazardous waste pharmaceuticals are subject to the training requirements under s. NR 662.017 c1d cgd.

*cdd Labeling and management of containers at on-site accumulation areas.* A reverse distributor accumulating evaluated hazardous waste pharmaceuticals in containers in an on-site accumulation area shall do all of the following:

1. Label the containers with the words, Xhazardous waste pharmaceuticals.Y
2. Ensure the containers are in good condition and managed to prevent leaks.
3. Use containers that are made of or lined with materials that will not react with, and are otherwise compatible with, the evaluated hazardous waste pharmaceuticals, so that the ability of the container to contain the waste is not impaired.
4. Keep containers closed, if the container is holding liquid or gel evaluated hazardous waste pharmaceuticals. If the liquid or gel evaluated hazardous waste pharmaceuticals are in their original, intact, sealed packaging or repackaged in intact, sealed packaging, they are considered to meet the closed container standard.
5. Manage any container of ignitable or reactive evaluated hazardous waste pharmaceuticals, or any container of commingled incompatible evaluated hazardous waste pharmaceuticals so that the container does not have the potential to do any of the following:
  - a. Generate extreme heat or pressure, fire or explosion, or violent reaction.
  - b. Produce uncontrolled toxic mists, fumes, dusts, or gases in sufficient quantities to threaten human health.
  - c. Produce uncontrolled flammable fumes or gases in sufficient quantities to pose a risk of fire or explosions.
  - d. Damage the structural integrity of the container of hazardous waste pharmaceuticals.
  - e. Through other like means threaten human health or the environment.
6. Accumulate evaluated hazardous waste pharmaceuticals that are prohibited from being combusted because of the dilution prohibition under s. NR 668.03 c3d, for example arsenic trioxide cP012d, in separate containers from other evaluated hazardous waste pharmaceuticals at the reverse distributor.

*ced Hazardous waste numbers.* Prior to shipping evaluated hazardous waste pharmaceuticals off-site, all containers shall be marked with the applicable hazardous waste numbers, or hazardous waste codes. A nationally recognized electronic system, such as bar coding or radio frequency identification, may be used to identify the EPA hazardous waste numbers.

*efd Shipments.* A reverse distributor shall ship evaluated hazardous waste pharmaceuticals that are destined for a permitted or interim status treatment, storage, or disposal facility in accordance with the applicable shipping standards specified in s. NR 666.508 c1d or c2d.

*egd Procedures for a reverse distributor for managing rejected shipments.* A reverse distributor that sends a shipment of evaluated hazardous waste pharmaceuticals to a designated facility with the understanding that the designated facility can accept and manage the waste, and later receives that shipment back as a rejected load in accordance with the manifest discrepancy provi-

sions under s. NR 664.0072 or 665.0072, may accumulate the returned evaluated hazardous waste pharmaceuticals on-site for up to an additional 90 calendar days in the on-site accumulation area provided the rejected or returned shipment is managed in accordance with sub. c1d and this subsection. Upon receipt of the returned shipment, the reverse distributor shall do all of the following:

1. Sign one of the following:
  - a. Item 18c of the original manifest, if the original manifest was used for the returned shipment.
  - b. Item 20 of the new manifest, if a new manifest was used for the returned shipment.
2. Provide the transporter a copy of the manifest.
3. Within 30 calendar days of receipt of the rejected shipment of the evaluated hazardous waste pharmaceuticals, send a copy of the manifest to the designated facility that returned the shipment to the reverse distributor.
4. Within 90 calendar days of receipt of the rejected shipment, transport or offer for transport the returned shipment of evaluated hazardous waste pharmaceuticals in accordance with the applicable shipping standards under s. NR 666.508 c1d or c2d.

*chd Land disposal restrictions.* Evaluated hazardous waste pharmaceuticals are subject to the land disposal restrictions under ch. NR 668. A reverse distributor that accepts potentially creditable hazardous waste pharmaceuticals from off-site shall comply with the land disposal restrictions in accordance with s. NR 668.07 c1d requirements.

*cid Reporting by a reverse distributor for evaluated hazardous waste pharmaceuticals.* 1. ZAnnual reporting by a reverse distributor.[ A reverse distributor that ships evaluated hazardous waste pharmaceuticals off-site shall prepare and submit a single copy of an annual report to the department by March 1 of each year in accordance with s. NR 662.041.

2. ZException reporting by a reverse distributor for a missing copy of the manifest - shipments from a reverse distributor to a designated facility.[ a. A reverse distributor who does not receive a copy of the manifest with the signature of the owner or operator of the designated facility within 35 calendar days of the date the evaluated hazardous waste pharmaceuticals were accepted by the initial transporter, shall contact the transporter or the owner or operator of the designated facility to determine the status of the evaluated hazardous waste pharmaceuticals.

b. A reverse distributor shall submit an exception report to the department if it has not received a copy of the manifest with the signature of the owner or operator of the designated facility within 45 calendar days of the date the evaluated hazardous waste pharmaceutical was accepted by the initial transporter. The exception report shall include all of the following:

1d A legible copy of the manifest for which the reverse distributor does not have confirmation of delivery.

2d A cover letter signed by the reverse distributor, or its authorized representative, explaining the efforts taken to locate the evaluated hazardous waste pharmaceuticals and the results of those efforts.

3. ZException reporting by a reverse distributor for a missing copy of the manifest - shipments rejected by the designated facility and shipped to an alternate facility.[ a. A reverse distributor that does not receive a copy of the manifest with the signature of the owner or operator of the alternate facility within 35 calendar days of the date the evaluated hazardous waste pharmaceuticals were accepted by the initial transporter shall contact the transporter or the owner or operator of the alternate facility to determine the status of the hazardous waste. The 35-day time frame

begins the date the evaluated hazardous waste pharmaceuticals are accepted by the transporter forwarding the hazardous waste shipment from the designated facility to the alternate facility.

b. A reverse distributor shall submit an exception report to the department if it has not received a copy of the manifest with the signature of the owner or operator of the alternate facility within 45 calendar days of the date the evaluated hazardous waste pharmaceuticals were accepted by the initial transporter. The 45-day timeframe begins the date the evaluated hazardous waste pharmaceuticals are accepted by the transporter forwarding the hazardous waste pharmaceutical shipment from the designated facility to the alternate facility. The exception report shall include all of the following:

1d A legible copy of the manifest for which the generator does not have confirmation of delivery.

2d A cover letter signed by the reverse distributor, or its authorized representative, explaining the efforts taken to locate the evaluated hazardous waste pharmaceuticals and the results of those efforts.

cjd *Recordkeeping by a reverse distributor for evaluated hazardous waste pharmaceuticals.* 1. A reverse distributor shall keep a log, written or electronic, of the inspections of the on-site accumulation area, as required under par. *cbd*. This log shall be retained as a record for at least 3 years from the date of the inspection.

2. A reverse distributor shall keep a copy of each manifest signed in accordance with s. *NR 662.023 c1d* for 3 years or until it receives a signed copy from the designated facility that received the evaluated hazardous waste pharmaceutical. This signed copy shall be retained as a record for at least 3 years from the date the evaluated hazardous waste pharmaceutical was accepted by the initial transporter.

3. A reverse distributor shall keep a copy of each annual report for at least 3 years from the due date of the report.

4. A reverse distributor shall keep a copy of each exception report for at least 3 years from the submission of the report.

5. A reverse distributor shall keep records to document personnel training, in accordance with s. *NR 662.017 c1d cgd 4*.

6. All records shall be readily available upon request by an inspector. The periods of retention referred to in this section are extended automatically during the course of any unresolved enforcement action regarding the regulated activity, or as requested by the department.

**c4d** WHEN A REVERSE DISTRIBUTOR IS REQUIRED TO HAVE A LICENSE. A reverse distributor is an operator of a hazardous waste treatment, storage, or disposal facility and is subject to the requirements under chs. *NR 664, 665, and 667* and the license requirements under ch. *NR 670*, if the reverse distributor does any of the following:

cad Does not meet the conditions of this section.

cbd Accepts manifested hazardous waste from off-site.

ccd Treats or disposes of hazardous waste pharmaceuticals on-site.

**History:** *CR 19-082: cr. Register August 2020 No. 776, eff. 9-1-20; correction in c1d ced 2., c2d ccd, c3d cgd cintro.d made under s. 35.17, Stats., Register August 2020 No. 776.*

### Subchapter HH — Household and Very Small Quantity Generator Hazardous Waste Collection Facilities

**NR 666.900 Applicability.** This subchapter establishes minimum design and operating standards for owners or operators of collection facilities that collect or store household hazardous waste or very small quantity generator waste, or both. The owner

or operator of a collection facility is exempt from the hazardous waste storage facility standards and licensing requirements in chs. *NR 664, 665 and 670* if the owner or operator complies with all applicable requirements of this subchapter.

**History:** *CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.*

**NR 666.901 Definitions.** The following definitions apply to this subchapter:

**c1d** XAffected municipalityY means a town, city, village or county in which a collection facility is located, or is proposed to be located.

**c2d** XCollection facilityY means a facility established to collect or store household hazardous waste or very small quantity generator waste, or both.

**c3d** XElementary neutralization unitY means a container or tank used for neutralizing wastes that are hazardous only because they exhibit the corrosivity characteristic defined in s. *NR 661.0022*, or they are listed in subch. *D of ch. NR 661* only for corrosivity.

**c4d** XHousehold hazardous wasteY means a household waste that exhibits a characteristic of hazardous waste or is listed in ch. *NR 661*.

**c5d** XPermanent collection facilityY means a collection facility where household hazardous waste or very small quantity generator waste, or both, is collected or stored for more than 5 consecutive days.

**c6d** XTemporary collection facilityY means a collection facility where household hazardous waste or very small quantity generator waste, or both, is collected or stored for no more than 5 consecutive days.

**History:** *CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 19-082: am. c3d Register August 2020 No. 776, eff. 9-1-20.*

**NR 666.902 Standards for design of permanent collection facilities.** The owner or operator of a permanent collection facility shall construct and maintain the facility according to all of the following minimum design criteria:

**c1d** A collection facility may not be located in any of the following:

cad A flood plain.

cbd A wetland.

ccd A habitat determined by the department to be critical to the continued existence of any threatened or endangered species listed in ch. *NR 27*.

**c2d** The maximum amount of hazardous waste stored may not exceed 240,000 pounds c109,091 kgd.

**c3d** All hazardous waste shall be stored in containers in a building completely enclosed with a floor, walls and roof to prevent exposure to the elements, or in an equivalent manner, if approved by the department.

**c4d** The floor underlying the containers shall be free of cracks and gaps and sufficiently impervious to contain leaks and spills until the released material is detected and removed.

**c5d** The floor shall be sloped or a containment system shall be designed and operated to drain and remove liquids resulting from leaks or spills, unless the containers are elevated or are otherwise prevented from contact with accumulated liquids.

**c6d** The containment system shall have sufficient capacity to contain the volume of the largest container, or 10% of the volume of all containers, whichever is greater. Containers that do not contain free liquids need not be considered in this determination.

**c7d** Spilled or leaked waste shall be removed from the sump or collection area in as timely a manner as is necessary to prevent

overflow of the collection system, or within 24 hours, whichever is less.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: am. c3d Register July 2017 No. 739, eff. 8-1-17.

**NR 666.903 Standards for operation of permanent collection facilities.** An owner or operator of a permanent collection facility shall comply with all of the following:

**c1d NOTIFICATION.** At least 30 days prior to first accepting hazardous waste from off-site, submit the XNotification of Activity for Household and Very Small Quantity Generator Hazardous Waste Collection Facility Y form 4430-020 to the department and to the clerk of the affected municipalities.

**Note:** This is a one-time notification. Collection facilities are not required to re-submit the form unless there is a change in ownership or facility operations. Form 4430-020 may be obtained from the department by E-mail: [DNRWasteMaterials@wisconsin.gov](mailto:DNRWasteMaterials@wisconsin.gov) or phone: c608d 266-2111.

**c2d STORAGE TIME LIMIT.** Store hazardous waste for no longer than one year from the date the waste is received.

**c3d CONTAINER MANAGEMENT.** Manage containers of hazardous waste according to all of the following:

cad Label each container with either the words Xhazardous waste Y or other words that identify the contents of the container.

cbd Clearly mark the accumulation start date on each container.

ccd Store waste in containers that are in good condition and compatible with the waste being stored.

cdd Store containers closed except when adding or removing waste.

ced Open, handle and store containers to prevent ruptures and leaks.

cfid Inspect containers and the areas where they are stored at least weekly for leaks and deterioration caused by corrosion or other factors. Take immediate action to correct problems found during inspections.

cgd Maintain adequate aisle space in the container storage areas to allow for unobstructed movement of personnel, fire protection and spill control equipment in an emergency.

**c4d IGNITABLE, REACTIVE OR INCOMPATIBLE WASTE.** Manage ignitable, reactive or incompatible wastes according to all of the following:

cad Store incompatible wastes in separate containers.

cbd Separate containers of incompatible wastes by means of a dike, berm, wall or other device.

ccd Store and protect ignitable or reactive wastes from sources of ignition or reaction.

cdd Post XNo Smoking Y signs in ignitable and reactive waste storage areas.

**c5d SECURITY.** Control entry of unauthorized persons to the container storage area at all times.

**c6d PREPAREDNESS AND PREVENTION.** Operate the facility to prevent fires or explosions or releases of hazardous waste which could threaten human health or the environment.

**c7d EMERGENCY EQUIPMENT.** Equip the facility with all of the following:

cad An internal communications or alarm system capable of providing immediate emergency instruction cvoice or signal d to facility personnel.

cbd A telephone c immediately available at the scene of operations d or a hand-held 2-way radio, capable of summoning emergency assistance from local police departments, fire departments or state or local emergency response teams.

ccd Portable fire extinguishers, fire control equipment c in-

cluding special extinguishing equipment, such as that using foam, inert gas or dry chemicals d and spill control equipment.

**c8d TESTING AND MAINTENANCE OF EMERGENCY EQUIPMENT.** Test and maintain all facility communications or alarm systems, fire protection equipment and spill control equipment, where required, as necessary to assure its proper operation in time of emergency.

**c9d CONTINGENCY PLAN.** Prepare a contingency plan which describes the actions of facility personnel in response to fires, explosions or any releases of hazardous waste or materials. A spill prevention, control and countermeasures cSPCC d plan or some other emergency or contingency plan may be amended to incorporate the requirements of this subsection. Keep a copy of the contingency plan and all revisions at the facility and submit a copy to all local police departments, fire departments, hospitals and state and local emergency response teams that may be called upon to provide emergency services. Review and immediately amend the plan if the plan fails in an emergency or if changes are made to the design or operation that increase the potential for fires, explosions or releases of hazardous waste or changes the response necessary in an emergency. The plan shall be implemented immediately whenever there is a fire, explosion or release of hazardous waste that could threaten human health or the environment. The plan shall include all of the following:

cad A description of the arrangements agreed to by local police departments, fire departments, hospitals, contractors and state and local emergency response teams to coordinate emergency services.

cbd An up to date list of names, addresses and phone numbers coffice and homed of all persons qualified to act as emergency coordinator. Where more than one person is listed, one shall be named as primary emergency coordinator and others shall be listed in the order in which they will assume responsibility as alternates. The primary and alternate emergency coordinators shall:

1. Either be on the facility premises or available to respond to an emergency by reaching the facility within a short period of time.

2. Be thoroughly familiar with all aspects of the facility [s contingency plan, all operations and activities at the facility, the location and characteristics of waste handled, the location of all records within the facility and the facility layout.

3. Have the authority to commit the resources needed to carry out the contingency plan.

ccd An up to date list of all emergency equipment at the facility, such as fire extinguishing systems, spill control equipment, communications and alarm systems. In addition, the plan shall include the location and a physical description of each item on the list and a brief outline of its capabilities.

cdd A plan to evacuate facility personnel where an evacuation may be necessary. Include the signals to be used to begin evacuation, evacuation routes and alternate evacuation routes c in cases where the primary routes could be blocked by releases of hazardous waste or fires d.

**c10d EMERGENCY COORDINATOR.** Assign at least one employee as emergency coordinator. The emergency coordinator shall be responsible for all of the following:

cad Whenever there is an imminent or actual emergency situation, immediately:

1. Activate internal facility alarms or communication systems, where applicable, to notify all facility personnel.

2. Notify appropriate state or local agencies with designated response roles if their help is needed.

cbd In the event of a fire, explosion or other release:



1. Immediately notify the national response center using their 24-hour toll free number c800d 424-8802 if there is a threat to human health or if a spill has reached surface water. Notification shall include the name and address of the facility owner, date, time and type of incident, quantity and type of hazardous waste involved in the incident, extent of injuries, if any, and estimated quantity and disposition of recovered materials, if any.

2. Notify the division of emergency management at c800d 943-0003, and comply with the remedial action requirements of s. 292.11, Stats., and ch. NR 706.

3. Identify the character, exact source, amount and areal extent of any released materials.

4. Assess possible hazards to human health or the environment that may result from the release, fire or explosion. This assessment shall consider both direct and indirect effects of the release, fire or explosion.

**ccd** Take all reasonable measures necessary to ensure that fires, explosions and releases do not occur, recur or spread to other hazardous waste at the facility.

**cdd** Immediately after an emergency, provide for treating, storing or disposing of recovered waste, contaminated soil or surface water or any other material that results from a release, fire or explosion at the facility.

**Note:** Unless the owner or operator can demonstrate, according to s. NR 661.0003 c3d or c4d, that the recovered material is not a hazardous waste, the owner or operator becomes a generator of hazardous waste and shall manage it according to all applicable requirements of chs. NR 662 and 663 and this subchapter.

**c11d PERSONNEL TRAINING.** Train all facility personnel, either by classroom instruction or on the job training, related to job duties to ensure they are thoroughly familiar with proper waste handling procedures and are able to respond effectively to emergencies. Employees shall not work in unsupervised positions until the training is completed. The training shall:

**cad** Familiarize staff with proper waste handling procedures and emergency equipment and procedures.

**cbd** Be completed within six months of employment.

**ccd** Be reviewed annually for all staff.

**c12d ANNUAL REPORT.** If any hazardous waste is shipped to a licensed or permitted hazardous waste treatment, storage or disposal facility or recycling facility, other than a permanent collection facility, prepare and submit a single copy of an annual report to the department by March 1 of each year. The annual report shall be submitted on department forms and cover generator activities during the previous year.

**Note:** Information on annual reporting is available at: <http://dnr.wi.gov/topic/Waste/AnnualReport.html>.

**c13d RECORDKEEPING.** Retain copies of annual reports and results of any laboratory hazardous waste analyses for a minimum of 3 years.

**c14d BULKING.** If hazardous waste is bulked, prevent the mixing of incompatible wastes by testing or applying knowledge of the waste.

**c15d TREATMENT.** If hazardous waste is treated, it shall only be done by being neutralized in an elementary neutralization unit, or by the addition of absorbent materials to wastes.

**c16d VERY SMALL QUANTITY GENERATOR WASTE.** If hazardous waste is accepted from very small quantity generators, provide a shipment receipt to the very small quantity generator. The shipment receipt shall include the information specified in pars. **cad** to **ccd**, and copies of the receipts shall be retained according to par. **cdd**.

**cad** The generator[s] company name and location, including street address, city and state.

**cbd** The quantity and type of waste.

**ccd** The date the waste was accepted by the collection facility.  
**cdd** Retain a copy of the shipment receipt for a minimum of 3 years from the date the shipment was received.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 16-007: renun. c3d to c17d to c2d to c16d and as renumbered, am. c11d cintro.d, cad, c12d, c13d Register July 2017 No. 739, eff. 8-1-17; correction in c9d cintro.d made under s. 35.17, Stats., Register August 2020 No. 776.

**NR 666.904 Standards for operation of temporary collection facilities.** An owner or operator of a temporary collection facility shall comply with all of the following:

**c1d NOTIFICATION.** At least 30 days prior to first accepting hazardous waste from off-site, submit the XNotification of Activity for Household and Very Small Quantity Generator Hazardous Waste Collection FacilityY form 4430-020 to the department.

**Note:** Form 4430-020 may be obtained from the department by E-mail: [DNR-WasteMaterials@wisconsin.gov](mailto:DNR-WasteMaterials@wisconsin.gov) or phone: c608d 266-2111.

**c2d CONTAINER MANAGEMENT.** Manage containers of hazardous waste according to all of the following:

**cad** Label each container with either the words Xhazardous wasteY or other words that identify the contents of the container.

**cbd** Clearly mark the accumulation starting date on each container.

**ccd** Open, handle and store waste in containers that are in good condition and compatible with the waste being stored.

**cdd** Store containers closed except when adding or removing waste.

**ced** Manage containers to prevent ruptures and leaks.

**c3d IGNITABLE, REACTIVE OR INCOMPATIBLE WASTE.** Manage ignitable, reactive or incompatible wastes according to all of the following:

**cad** Store incompatible wastes in separate containers.

**cbd** Separate containers of incompatible wastes.

**ccd** Store and protect ignitable or reactive wastes from sources of ignition or reaction.

**c4d PREPAREDNESS AND PREVENTION.** Operate the facility to prevent fires or explosions or releases of hazardous waste which could threaten human health or the environment.

**c5d EMERGENCY PROCEDURES.** At all times, ensure that at least one person on the premises is responsible for coordinating all of the following emergency response measures:

**cad** In the event of a fire, call the fire department or attempt to extinguish it using a fire extinguisher.

**cbd** In the event of a spill, contain the flow of hazardous waste to the extent possible, and as soon as is practicable, clean up the hazardous waste and any contaminated materials or soil.

**ccd** In the event of a fire, explosion or other release which could threaten human health or if a spill has reached surface water, immediately notify the national response center, using their 24-hour toll free number c800d424-8802. The notification shall include all of the following information: The name and address of the facility owner, date, time and type of incident, quantity and type of hazardous waste involved in the incident, extent of injuries, if any and estimated quantity and disposition of recovered materials, if any.

**cdd** In the event of a release or discharge, notify the division of emergency management at c800d 943-0003 and comply with the requirements of s. 292.11, Stats., and ch. NR 706.

**c6d PERSONNEL TRAINING.** Ensure that all employees are thoroughly familiar with proper waste handling and emergency procedures relevant to their responsibilities.

**c7d BULKING.** If hazardous waste is bulked, prevent the mixing of incompatible wastes by testing or applying knowledge of the waste.

**c8d TREATMENT.** If hazardous waste is treated, it shall only be done by being neutralized in an elementary neutralization unit, or by the addition of absorbent materials to wastes.

**c9d VERY SMALL QUANTITY GENERATOR WASTE.** If hazardous waste is accepted from very small quantity generators, provide a shipment receipt to the very small quantity generator. The shipment receipt shall include the information specified in pars. **cad** to **ccd**, and copies of the receipts shall be retained by the owner according to par. **cdd**.

**cad** The generator[s] company name and location, including street address, city and state.

**cbd** The quantity and type of waste.

**ccd** The date the waste was accepted by the collection facility.

**cdd** Retain a copy of shipment receipts for a minimum of 3 years from the date the shipment was received.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.905 Transportation requirements.** An owner or operator of a collection facility shall ensure delivery of all hazardous waste to a licensed hazardous waste treatment, storage or disposal facility, legitimate recycling facility or permanent collection facility, according to the following:

**c1d** An owner or operator of a collection facility who offers hazardous waste for transportation to a licensed hazardous waste treatment, storage or disposal facility, or recycling facility, shall:

**cad** Obtain an EPA ID number, using EPA Form 8700-12.

**Note:** EPA instructions and notification form 8700-12 may be obtained from: <https://www.epa.gov/hwgenerators/instructions-and-form-hazardous-waste-generators-transporters-and-treatment-storage-and>.

**cbd** Package the waste in accordance with the applicable U.S. department of transportation regulations on packaging under **49 CFR parts 173, 178 and 179**.

**cd** Label each package in accordance with the applicable U.S. department of transportation regulations on hazardous materials under **49 CFR part 172**.

**cdd** Mark each package of hazardous waste in accordance with the applicable U.S. department of transportation regulations on hazardous materials under **49 CFR part 172**, and mark each container of 119 gallons or less used in the transportation with the following words and information displayed in accordance with the requirements of **49 CFR 172.304**:

XHAZARDOUS WASTE—Federal Law Prohibits Improper Disposal. If found, contact the nearest police or public safety authority or the U.S. Environmental Protection Agency.

Generator[s] Name and Address \_\_\_\_\_.

Generator[s] EPA Identification number \_\_\_\_\_.

Manifest Tracking Number \_\_\_\_\_Y

**ced** Ensure the initial transporter has the appropriate placards according to U.S. DOT regulations for hazardous materials under **49 CFR part 172**, subpart F.

**cf** Use a manifest that consists of at least the number of copies which will provide the collection facility owner or operator, each transporter, the owner or operator of the designated facility, and the department with one copy each for their records and another final, signed copy to be returned to the collection facility owner or operator. Prepare and use a manifest, OMB control number 2050-0039, on EPA form 8700-22, and if necessary, EPA Form 8700]22A, according to the instructions in the appendix to **40 CFR part 262**, and the following:

1. For shipments of hazardous waste outside of Wisconsin, submit a copy of each manifest to the department within 30 days of receiving the signed copy from the designated facility.

2. Keep a copy of each manifest signed by the collection facility owner or operator and the initial transporter for 3 years or

until facility owner or operator receives a signed copy from the designated hazardous waste facility that received the waste. Retain the final, signed copy of the manifest as a record for at least 3 years from the date the waste was accepted by the initial transporter.

**cgd** Meet applicable land disposal restrictions standards in s. **NR 668.07 c1d**.

**c2d** An owner or operator of a collection facility who self-transport hazardous waste off-site to a licensed or permitted hazardous waste treatment, storage or disposal facility, or a recycling facility shall comply with sub. **c1d** and ch. **NR 663**, hazardous waste transportation requirements.

**Note:** Under **49 CFR 171.1 cdd c5d**, governmental employees who self-transport hazardous materials or hazardous waste are exempt from the DOT hazardous materials requirements including packaging, labeling, marking, placarding and manifesting if the transportation is done solely for non-commercial, governmental purposes.

**c3d** An owner or operator of a collection facility may transport hazardous waste, or offer hazardous waste for transport, to a permanent collection facility without using a hazardous waste manifest or obtaining a transportation license for the purpose of bulking or consolidating waste, if the collection facility owner or operator complies with all of the following requirements prior to transporting the hazardous waste:

**cad** Package the waste in accordance with the applicable U.S. department of transportation regulations on packaging under **49 CFR parts 173, 178 and 179**.

**cbd** Label each package in accordance with the applicable U.S. department of transportation regulations on hazardous materials under **49 CFR part 172**.

**ccd** Mark each package of hazardous waste in accordance with the applicable U.S. department of transportation regulations on hazardous materials under **49 CFR part 172**, and mark each container of 119 gallons or less used in the transportation with the following words and information displayed in accordance with the requirements of **49 CFR 172.304**:

XHAZARDOUS WASTE Federal Law Prohibits Improper Disposal. If found, contact the nearest police or public safety authority or the U.S. Environmental Protection Agency.

Generator[s] Name and Address \_\_\_\_\_.

Generator[s] EPA Identification number \_\_\_\_\_.

Manifest Tracking Number \_\_\_\_\_Y

**Note:** Under **49 CFR 171.1 cdd c5d**, governmental employees who self-transport hazardous materials or waste are exempt from the DOT hazardous materials requirements including packaging, labeling, marking, placarding, and manifesting if the transportation is done solely for non-commercial, governmental purposes.

**cdd** Use placards if required by U.S. DOT regulations for hazardous materials under **49 CFR part 172**, subpart F.

**ced** Provide written notification of the waste properties and applicable land disposal restrictions standards to the receiving collection facility.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06; CR 06-102: am. c1d cfd Register March 2007 No. 615, eff. 4-1-07; CR 16-007: cr. cintro.d, am. c1d cintro.d, cdd, cfd cintro.d, c3d ccd Register July 2017 No. 739, eff. 8-1-17.

**NR 666.909 Closure requirements. c1d** Within 5 days of initially accepting hazardous waste, an owner or operator of a temporary collection facility shall close the facility according to all of the following:

**cad** Ensure delivery of all hazardous waste to an off-site licensed or permitted hazardous waste treatment, storage or disposal facility, recycling facility, or to a permanent collection facility.

**cbd** Close the collection facility in a manner that meets all of the following:

1. Minimizes the need for further maintenance.

2. Controls, minimizes or eliminates the escape of hazardous waste, hazardous constituents or contaminated run-off to the ground, surface waters or the atmosphere.

**c2d** An owner or operator of a permanent collection facility that closes for the season shall close the facility according to all of the following:

cad Ensure delivery of all hazardous waste to an off-site licensed or permitted hazardous waste treatment, storage or disposal facility, recycling facility, or another permanent collection facility, within 90 days of the last day of accepting waste.

cbd Close the collection facility in a manner that meets all of the following:

1. Minimizes the need for further maintenance.
2. Controls, minimizes or eliminates the escape of hazardous waste, hazardous constituents or contaminated run-off to the ground, surface waters or the atmosphere.

**c3d** An owner or operator of a permanent collection facility that closes permanently shall close the facility according to all of the following:

cad The standards in sub. **c2d cad** and **cbd**.

cbd All contaminated equipment, structures and soil shall be properly disposed of or decontaminated. By removing all hazardous wastes or hazardous constituents, the owner or operator may become a generator of hazardous waste and shall handle that hazardous waste in accordance with all applicable requirements of ch. **NR 662**.

ccd Within 60 days of completion of closure, submit a report to the department summarizing the activities performed to meet the requirements in pars. **cad** and **cbd**.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.

**NR 666.910 Financial responsibility requirements for permanent collection facilities that store more than 80,000 pounds c36,364 kg.d of hazardous waste. c1d** The owner or operator shall meet all of the following closure cost estimate requirements prior to storing more than 80,000 pounds of hazardous waste at any time:

cad Obtain a detailed written estimate, in current dollars, of the cost of final closure of the collection facility as required in s. **NR 666.909 c2d cad** and **cbd**.

cbd Calculate the closure cost estimate using the cost of hiring

a third party to remove and properly manage the estimated maximum inventory of waste. The quantity of hazardous waste stored at the collection facility shall not exceed the maximum inventory of waste used to calculate the closure cost estimate.

ccd Submit the detailed closure cost estimate to the department with the notification form required under s. **NR 666.903 c1d**.

cdd Adjust the closure cost estimate for inflation within 60 days prior to the anniversary date of the establishment of the financial instrumentcsd, as required in s. **NR 665.0143**, or if any changes are made to the amount of hazardous waste stored. The adjustment may be made by recalculating the closure cost estimate in current dollars, or by using an inflation factor derived from the most recent implicit price deflator for gross domestic product published by the U.S. department of commerce in its *Survey of Current Business*, as specified in pars. **cad** and **cbd**. The inflation factor is the result of dividing the latest published annual deflator by the deflator for the previous year.

1. The first adjustment shall be made by multiplying the closure cost estimate by the inflation factor. The result is the adjusted closure cost estimate.

2. Subsequent adjustments shall be made by multiplying the latest adjusted closure cost estimate by the latest inflation factor.

**c2d** The owner or operator shall meet all of the following financial assurance requirements prior to storing more than 80,000 pounds of hazardous waste:

cad Establish financial assurance for closure of the collection facility, as required in s. **NR 665.0143**.

cbd Submit proof of financial assurance to the department with the notification form required under s. **NR 666.903 c1d**.

**c3d** Within 60 days of receipt of the closure summary report required by s. **NR 666.909 c3d ccd**, the department shall notify the owner or operator of one of the following:

cad Closure is complete and the owner or operator may apply to the department for a release of the proof of financial responsibility.

cbd Additional closure activities are necessary to comply with s. **NR 666.909 c3d**, and proof of financial responsibility shall be maintained.

**History:** CR 05-032: cr. Register July 2006 No. 607, eff. 8-1-06.